GE Fanuc Automation

Computer Numerical Control Products

Series 21i / 210i – Model A for Lathe

Operator's Manual

GFZ-63084EN/01 *April 1997*

Warnings, Cautions, and Notes as Used in this Publication

Warning

Warning notices are used in this publication to emphasize that hazardous voltages, currents, temperatures, or other conditions that could cause personal injury exist in this equipment or may be associated with its use.

In situations where inattention could cause either personal injury or damage to equipment, a Warning notice is used.

Caution

Caution notices are used where equipment might be damaged if care is not taken.

Note

Notes merely call attention to information that is especially significant to understanding and operating the equipment.

This document is based on information available at the time of its publication. While efforts have been made to be accurate, the information contained herein does not purport to cover all details or variations in hardware or software, nor to provide for every possible contingency in connection with installation, operation, or maintenance. Features may be described herein which are not present in all hardware and software systems. GE Fanuc Automation assumes no obligation of notice to holders of this document with respect to changes subsequently made.

GE Fanuc Automation makes no representation or warranty, expressed, implied, or statutory with respect to, and assumes no responsibility for the accuracy, completeness, sufficiency, or usefulness of the information contained herein. No warranties of merchantability or fitness for purpose shall apply.

©Copyright 1997 GE Fanuc Automation North America, Inc.
All Rights Reserved.

SAFETY PRECAUTIONS

This section describes the safety precautions related to the use of CNC units. It is essential that these precautions be observed by users to ensure the safe operation of machines equipped with a CNC unit (all descriptions in this section assume this configuration). Note that some precautions are related only to specific functions, and thus may not be applicable to certain CNC units.
Users must also observe the safety precautions related to the machine, as described in the relevant manual supplied by the machine tool builder. Before attempting to operate the machine or create a program to control the operation of the machine, the operator must become fully familiar with the contents of this manual and relevant manual supplied by the machine tool builder.

Contents

1. DEFINITION OF WARNING, CAUTION, AND NOTE s–2

2. GENERAL WARNINGS AND CAUTIONS s–3

3. WARNINGS AND CAUTIONS RELATED TO PROGRAMMING s–5

4. WARNINGS AND CAUTIONS RELATED TO HANDLING s–7

5. WARNINGS RELATED TO DAILY MAINTENANCE s–9

1 DEFINITION OF WARNING, CAUTION, AND NOTE

This manual includes safety precautions for protecting the user and preventing damage to the machine. Precautions are classified into Warning and Caution according to their bearing on safety. Also, supplementary information is described as a Note. Read the Warning, Caution, and Note thoroughly before attempting to use the machine.

WARNING

Applied when there is a danger of the user being injured or when there is a damage of both the user being injured and the equipment being damaged if the approved procedure is not observed.

CAUTION

Applied when there is a danger of the equipment being damaged, if the approved procedure is not observed.

NOTE

The Note is used to indicate supplementary information other than Warning and Caution.

❍ **Read this manual carefully, and store it in a safe place.**

2 GENERAL WARNINGS AND CAUTIONS

WARNING

1. Never attempt to machine a workpiece without first checking the operation of the machine. Before starting a production run, ensure that the machine is operating correctly by performing a trial run using, for example, the single block, feedrate override, or machine lock function or by operating the machine with neither a tool nor workpiece mounted. Failure to confirm the correct operation of the machine may result in the machine behaving unexpectedly, possibly causing damage to the workpiece and/or machine itself, or injury to the user.

2. Before operating the machine, thoroughly check the entered data.
   Operating the machine with incorrectly specified data may result in the machine behaving unexpectedly, possibly causing damage to the workpiece and/or machine itself, or injury to the user.

3. Ensure that the specified feedrate is appropriate for the intended operation. Generally, for each machine, there is a maximum allowable feedrate. The appropriate feedrate varies with the intended operation. Refer to the manual provided with the machine to determine the maximum allowable feedrate. If a machine is run at other than the correct speed, it may behave unexpectedly, possibly causing damage to the workpiece and/or machine itself, or injury to the user.

4. When using a tool compensation function, thoroughly check the direction and amount of compensation.
   Operating the machine with incorrectly specified data may result in the machine behaving unexpectedly, possibly causing damage to the workpiece and/or machine itself, or injury to the user.

5. The parameters for the CNC and PMC are factory–set. Usually, there is not need to change them. When, however, there is not alternative other than to change a parameter, ensure that you fully understand the function of the parameter before making any change.
   Failure to set a parameter correctly may result in the machine behaving unexpectedly, possibly causing damage to the workpiece and/or machine itself, or injury to the user.

6. Immediately after switching on the power, do not touch any of the keys on the MDI panel until the position display or alarm screen appears on the CNC unit.
   Some of the keys on the MDI panel are dedicated to maintenance or other special operations. Pressing any of these keys may place the CNC unit in other than its normal state. Starting the machine in this state may cause it to behave unexpectedly.

7. The operator’s manual and programming manual supplied with a CNC unit provide an overall description of the machine’s functions, including any optional functions. Note that the optional functions will vary from one machine model to another. Therefore, some functions described in the manuals may not actually be available for a particular model. Check the specification of the machine if in doubt.

WARNING

8. Some functions may have been implemented at the request of the machine–tool builder. When using such functions, refer to the manual supplied by the machine–tool builder for details of their use and any related cautions.

NOTE

Programs, parameters, and macro variables are stored in nonvolatile memory in the CNC unit. Usually, they are retained even if the power is turned off. Such data may be deleted inadvertently, however, or it may prove necessary to delete all data from nonvolatile memory as part of error recovery.
To guard against the occurrence of the above, and assure quick restoration of deleted data, backup all vital data, and keep the backup copy in a safe place.

3 WARNINGS AND CAUTIONS RELATED TO PROGRAMMING

This section covers the major safety precautions related to programming. Before attempting to perform programming, read the supplied operator's manual and programming manual carefully such that you are fully familiar with their contents.

WARNING

1. Coordinate system setting

If a coordinate system is established incorrectly, the machine may behave unexpectedly as a result of the program issuing an otherwise valid move command.
Such an unexpected operation may damage the tool, the machine itself, the workpiece, or cause injury to the user.

2. Positioning by nonlinear interpolation

When performing positioning by nonlinear interpolation (positioning by nonlinear movement between the start and end points), the tool path must be carefully confirmed before performing programming.
Positioning involves rapid traverse. If the tool collides with the workpiece, it may damage the tool, the machine itself, the workpiece, or cause injury to the user.

3. Function involving a rotation axis

When programming polar coordinate interpolation or normal–direction (perpendicular) control, pay careful attention to the speed of the rotation axis. Incorrect programming may result in the rotation axis speed becoming excessively high, such that centrifugal force causes the chuck to lose its grip on the workpiece if the latter is not mounted securely.
Such mishap is likely to damage the tool, the machine itself, the workpiece, or cause injury to the user.

4. Inch/metric conversion

Switching between inch and metric inputs does not convert the measurement units of data such as the workpiece origin offset, parameter, and current position. Before starting the machine, therefore, determine which measurement units are being used. Attempting to perform an operation with invalid data specified may damage the tool, the machine itself, the workpiece, or cause injury to the user.

5. Constant surface speed control

When an axis subject to constant surface speed control approaches the origin of the workpiece coordinate system, the spindle speed may become excessively high. Therefore, it is necessary to specify a maximum allowable speed. Specifying the maximum allowable speed incorrectly may damage the tool, the machine itself, the workpiece, or cause injury to the user.

WARNING

6. Stroke check

After switching on the power, perform a manual reference position return as required. Stroke check is not possible before manual reference position return is performed. Note that when stroke check is disabled, an alarm is not issued even if a stroke limit is exceeded, possibly damaging the tool, the machine itself, the workpiece, or causing injury to the user.

7. Tool post interference check

A tool post interference check is performed based on the tool data specified during automatic operation. If the tool specification does not match the tool actually being used, the interference check cannot be made correctly, possibly damaging the tool or the machine itself, or causing injury to the user.
After switching on the power, or after selecting a tool post manually, always start automatic operation and specify the tool number of the tool to be used.

8. Absolute/incremental mode

If a program created with absolute values is run in incremental mode, or vice versa, the machine may behave unexpectedly.

9. Plane selection

If an incorrect plane is specified for circular interpolation, helical interpolation, or a canned cycle, the machine may behave unexpectedly. Refer to the descriptions of the respective functions for details.

10. Torque limit skip

Before attempting a torque limit skip, apply the torque limit. If a torque limit skip is specified without the torque limit actually being applied, a move command will be executed without performing a skip.

11. Programmable mirror image

Note that programmed operations vary considerably when a programmable mirror image is enabled.

12. Compensation function

If a command based on the machine coordinate system or a reference position return command is issued in compensation function mode, compensation is temporarily canceled, resulting in the unexpected behavior of the machine.
Before issuing any of the above commands, therefore, always cancel compensation function mode.

4 WARNINGS AND CAUTIONS RELATED TO HANDLING

This section presents safety precautions related to the handling of machine tools. Before attempting to operate your machine, read the supplied operator's manual and programming manual carefully, such that you are fully familiar with their contents.

WARNING

1. Manual operation

When operating the machine manually, determine the current position of the tool and workpiece, and ensure that the movement axis, direction, and feedrate have been specified correctly. Incorrect operation of the machine may damage the tool, the machine itself, the workpiece, or cause injury to the operator.

2. Manual reference position return

After switching on the power, perform manual reference position return as required. If the machine is operated without first performing manual reference position return, it may behave unexpectedly. Stroke check is not possible before manual reference position return is performed. An unexpected operation of the machine may damage the tool, the machine itself, the workpiece, or cause injury to the user.

3. Manual numeric command

When issuing a manual numeric command, determine the current position of the tool and workpiece, and ensure that the movement axis, direction, and command have been specified correctly, and that the entered values are valid.
Attempting to operate the machine with an invalid command specified may damage the tool, the machine itself, the workpiece, or cause injury to the operator.

4. Manual handle feed

In manual handle feed, rotating the handle with a large scale factor, such as 100, applied causes the tool and table to move rapidly. Careless handling may damage the tool and/or machine, or cause injury to the user.

5. Disabled override

If override is disabled (according to the specification in a macro variable) during threading, rigid tapping, or other tapping, the speed cannot be predicted, possibly damaging the tool, the machine itself, the workpiece, or causing injury to the operator.

6. Origin/preset operation

Basically, never attempt an origin/preset operation when the machine is operating under the control of a program. Otherwise, the machine may behave unexpectedly, possibly damaging the tool, the machine itself, the tool, or causing injury to the user.

WARNING

7. Workpiece coordinate system shift

Manual intervention, machine lock, or mirror imaging may shift the workpiece coordinate system. Before attempting to operate the machine under the control of a program, confirm the coordinate system carefully.
If the machine is operated under the control of a program without making allowances for any shift in the workpiece coordinate system, the machine may behave unexpectedly, possibly damaging the tool, the machine itself, the workpiece, or causing injury to the operator.

8. Software operator's panel and menu switches

Using the software operator's panel and menu switches, in combination with the MDI panel, it is possible to specify operations not supported by the machine operator's panel, such as mode change, override value change, and jog feed commands.
Note, however, that if the MDI panel keys are operated inadvertently, the machine may behave unexpectedly, possibly damaging the tool, the machine itself, the workpiece, or causing injury to the user.

9. Manual intervention

If manual intervention is performed during programmed operation of the machine, the tool path may vary when the machine is restarted. Before restarting the machine after manual intervention, therefore, confirm the settings of the manual absolute switches, parameters, and absolute/incremental command mode.

10. Feed hold, override, and single block

The feed hold, feedrate override, and single block functions can be disabled using custom macro system variable #3004. Be careful when operating the machine in this case.

11. Dry run

Usually, a dry run is used to confirm the operation of the machine. During a dry run, the machine operates at dry run speed, which differs from the corresponding programmed feedrate. Note that the dry run speed may sometimes be higher than the programmed feed rate.

12. Cutter and tool nose radius compensation in MDI mode

Pay careful attention to a tool path specified by a command in MDI mode, because cutter or tool nose radius compensation is not applied. When a command is entered from the MDI to interrupt in automatic operation in cutter or tool nose radius compensation mode, pay particular attention to the tool path when automatic operation is subsequently resumed. Refer to the descriptions of the corresponding functions for details.

13. Program editing

If the machine is stopped, after which the machining program is edited (modification, insertion, or deletion), the machine may behave unexpectedly if machining is resumed under the control of that program. Basically, do not modify, insert, or delete commands from a machining program while it is in use.

5 WARNINGS RELATED TO DAILY MAINTENANCE

WARNING

1. Memory backup battery replacement

When replacing the memory backup batteries, keep the power to the machine (CNC) turned on, and apply an emergency stop to the machine. Because this work is performed with the power on and the cabinet open, only those personnel who have received approved safety and maintenance training may perform this work.
When replacing the batteries, be careful not to touch the high–voltage circuits (marked ⚠ and fitted with an insulating cover).
Touching the uncovered high–voltage circuits presents an extremely dangerous electric shock hazard.

NOTE

The CNC uses batteries to preserve the contents of its memory, because it must retain data such as programs, offsets, and parameters even while external power is not applied.
If the battery voltage drops, a low battery voltage alarm is displayed on the machine operator's panel or screen.
When a low battery voltage alarm is displayed, replace the batteries within a week. Otherwise, the contents of the CNC's memory will be lost.
Refer to the maintenance section of the operator's manual or programming manual for details of the battery replacement procedure.

WARNING

2. Absolute pulse coder battery replacement

When replacing the memory backup batteries, keep the power to the machine (CNC) turned on, and apply an emergency stop to the machine. Because this work is performed with the power on and the cabinet open, only those personnel who have received approved safety and maintenance training may perform this work.
When replacing the batteries, be careful not to touch the high–voltage circuits (marked ⚠ and fitted with an insulating cover).
Touching the uncovered high–voltage circuits presents an extremely dangerous electric shock hazard.

NOTE

The absolute pulse coder uses batteries to preserve its absolute position.
If the battery voltage drops, a low battery voltage alarm is displayed on the machine operator's panel or screen.
When a low battery voltage alarm is displayed, replace the batteries within a week. Otherwise, the absolute position data held by the pulse coder will be lost.
Refer to the maintenance section of the operator's manual or programming manual for details of the battery replacement procedure.

WARNING

3. Fuse replacement

For some units, the chapter covering daily maintenance in the operator's manual or programming manual describes the fuse replacement procedure.
Before replacing a blown fuse, however, it is necessary to locate and remove the cause of the blown fuse.
For this reason, only those personnel who have received approved safety and maintenance training may perform this work.
When replacing a fuse with the cabinet open, be careful not to touch the high–voltage circuits (marked ⚠ and fitted with an insulating cover).
Touching an uncovered high–voltage circuit presents an extremely dangerous electric shock hazard.

Table of Contents

SAFETY PRECAUTIONS s–1

I. GENERAL

1. GENERAL 3

1.1 GENERAL FLOW OF OPERATION OF CNC MACHINE TOOL 5
1.2 NOTES ON READING THIS MANUAL 7

II. PROGRAMMING

1. GENERAL 11

1.1 TOOL MOVEMENT ALONG WORKPIECE PARTS FIGURE–INTERPOLATION 12
1.2 FEED–FEED FUNCTION 14
1.3 PART DRAWING AND TOOL MOVEMENT 15
1.3.1 Reference Position (Machine–Specific Position) 15
1.3.2 Coordinate System on Part Drawing and Coordinate System Specified by CNC – Coordinate System 16
1.3.3 How to Indicate Command Dimensions for Moving the Tool – Absolute, Incremental Commands 19
1.4 CUTTING SPEED – SPINDLE SPEED FUNCTION 21
1.5 SELECTION OF TOOL USED FOR VARIOUS MACHINING – TOOL FUNCTION 22
1.6 COMMAND FOR MACHINE OPERATIONS – MISCELLANEOUS FUNCTION 22
1.7 PROGRAM CONFIGURATION 23
1.8 COMPENSATION FUNCTION 26
1.9 TOOL MOVEMENT RANGE – STROKE 27

2. CONTROLLED AXES 28

2.1 CONTROLLED AXES 29
2.2 NAMES OF AXES 29
2.3 INCREMENT SYSTEM 30
2.4 MAXIMUM STROKES 31

3. PREPARATORY FUNCTION (G FUNCTION) 32

4. INTERPOLATION FUNCTIONS 36

4.1 POSITIONING (G00) 37
4.2 LINEAR INTERPOLATION (G01) 39
4.3 CIRCULAR INTERPOLATION (G02, G03) 40
4.4 POLAR COORDINATE INTERPOLATION (G12.1, G13.1) 44
4.5 CYLINDRICAL INTERPOLATION (G07.1) 48
4.6 CONSTANT LEAD THREADING (G32) 51
4.7 VARIABLE–LEAD THREAD CUTTING (G34) 55
4.8 CONTINUOUS THREAD CUTTING 56
4.9 MULTIPLE–THREAD CUTTING 57
4.10 SKIP FUNCTION (G31) 59
4.11 MULTISTAGE SKIP 61
4.12 TORQUE LIMIT SKIP (G31 P99) 62

5. FEED FUNCTIONS 64

5.1 GENERAL 65
5.2 RAPID TRAVERSE 66
5.3 CUTTING FEED 67
5.4 DWELL (G04) 69

6. REFERENCE POSITION 70

6.1 REFERENCE POSITION RETURN 71

7. COORDINATE SYSTEM 74

7.1 MACHINE COORDINATE SYSTEM 75
7.2 WORKPIECE COORDINATE SYSTEM 76
7.2.1 Setting a Workpiece Coordinate System 76
7.2.2 Selecting a Workpiece Coordinate System 78
7.2.3 Changing Workpiece Coordinate System 79
7.2.4 Workpiece Coordinate System Preset (G92.1) 81
7.2.5 Workpiece Coordinate System Shift 83
7.3 LOCAL COORDINATE SYSTEM 84
7.4 PLANE SELECTION 86

8. COORDINATE VALUE AND DIMENSION 87

8.1 ABSOLUTE AND INCREMENTAL PROGRAMMING (G90, G91) 88
8.2 INCH/METRIC CONVERSION (G20, G21) 89
8.3 DECIMAL POINT PROGRAMMING 90
8.4 DIAMETER AND RADIUS PROGRAMMING 91

9. SPINDLE SPEED FUNCTION 92

9.1 SPECIFYING THE SPINDLE SPEED WITH A CODE 93
9.2 SPECIFYING THE SPINDLE SPEED VALUE DIRECTLY (S5–DIGIT COMMAND) 93
9.3 CONSTANT SURFACE SPEED CONTROL (G96, G97) 94
9.4 SPINDLE SPEED FLUCTUATION DETECTION FUNCTION (G25, G26) 98
9.5 SPINDLE POSITIONING FUNCTION 101
9.5.1 Spindle Orientation 101
9.5.2 Spindle Positioning 101
9.5.3 Canceling Spindle Positioning 103

10. TOOL FUNCTION (T FUNCTION) 104

10.1 TOOL SELECTION 105
10.2 TOOL LIFE MANAGEMENT 106
10.2.1 Program of Tool Life Data 106
10.2.2 Counting a Tool Life 109
10.2.3 Specifying a Tool Group in a Machining Program 110

11. AUXILIARY FUNCTION 111

11.1 AUXILIARY FUNCTION (M FUNCTION) 112
11.2 MULTIPLE M COMMANDS IN A SINGLE BLOCK 113
11.3 THE SECOND AUXILIARY FUNCTIONS (B CODES) 114

12. PROGRAM CONFIGURATION 115

12.1 PROGRAM COMPONENTS OTHER THAN PROGRAM SECTIONS 117
12.2 PROGRAM SECTION CONFIGURATION 120
12.3 SUBPROGRAM (M98, M99) 126

13. FUNCTIONS TO SIMPLIFY PROGRAMMING 129

13.1 CANNED CYCLE (G90, G92, G94) 130
13.1.1 Outer Diameter / Internal Diameter Cutting Cycle (G90) 130
13.1.2 Thread Cutting Cycle (G92) 132
13.1.3 End Face Turning Cycle (G94) 135
13.1.4 How to Use Canned Cycles (G90, G92, G94) 138
13.2 MULTIPLE REPETITIVE CYCLE (G70 – G76) 140
13.2.1 Stock Removal in Turning (G71) 140
13.2.2 Stock Removal in Facing (G72) 144
13.2.3 Pattern Repeating (G73) 145
13.2.4 Finishing Cycle (G70) 146
13.2.5 End Face Peck Drilling Cycle (G74) 150
13.2.6 Outer Diameter / Internal Diameter Drilling Cycle (G75) 151
13.2.7 Multiple Thread Cutting Cycle (G76) 152
13.2.8 Notes on Multiple Repetitive Cycle (G70 – G76) 156
13.3 CANNED CYCLE FOR DRILLING (G80 – G89) 157
13.3.1 Front Drilling Cycle (G83) / Side Drilling Cycle (G87) 160
13.3.2 Front Tapping Cycle (G84) / Side Tapping Cycle (G88) 163
13.3.3 Front Boring Cycle (G85) / Side Boring Cycle (G89) 165
13.3.4 Canned Cycle for Drilling Cancel (G80) 166
13.3.5 Precautions to be Taken by Operator 167
13.4 CHAMFERING AND CORNER R 168
13.5 MIRROR IMAGE FOR DOUBLE TURRET (G68, G69) 171
13.6 DIRECT DRAWING DIMENSIONS PROGRAMMING 172
13.7 RIGID TAPPING 177
13.7.1 Front Face Rigid Tapping Cycle (G84) / Side Face Rigid Tapping Cycle (G88) 178

14. COMPENSATION FUNCTION 181

14.1 TOOL OFFSET 182
14.1.1 Tool Geometry Offset and Tool Wear Offset 182
14.1.2 T Code for Tool Offset 183
14.1.3 Tool Selection 183
14.1.4 Offset Number 183
14.1.5 Offset 184
14.1.6 G53, G28, G30, and G30.1 Commands When Tool Position Offset is Applied 187
14.2 OVERVIEW OF TOOL NOSE RADIUS COMPENSATION 191
14.2.1 Imaginary Tool Nose 191
14.2.2 Direction of Imaginary Tool Nose 193
14.2.3 Offset Number and Offset Value 194
14.2.4 Work Position and Move Command 196
14.2.5 Notes on Tool Nose Radius Compensation 201

14.3 DETAILS OF TOOL NOSE RADIUS COMPENSATION 204
14.3.1 General 204
14.3.2 Tool Movement in Start–up 206
14.3.3 Tool Movement in Offset Mode 208
14.3.4 Tool Movement in Offset Mode Cancel 221
14.3.5 Interference Check 224
14.3.6 Overcutting by Tool Nose Radius Compensation 229
14.3.7 Correction in Chamfering and Corner Arcs 230
14.3.8 Input Command from MDI 232
14.3.9 General Precautions for Offset Operations 233
14.3.10 G53, G28, G30, and G30.1 Commands in Tool–tip Radius Compensation Mode 234
14.4 TOOL COMPENSATION VALUES, NUMBER OF COMPENSATION VALUES, AND ENTERING VALUES FROM THE PROGRAM (G10) 243
14.4.1 Tool Compensation and Number of Tool Compensation 243
14.4.2 Changing of Tool Offset Value (Programmable Data Input) (G10) 245
14.5 AUTOMATIC TOOL OFFSET (G36, G37) 246

15. CUSTOM MACRO 249

15.1 VARIABLES 250
15.2 SYSTEM VARIABLES 254
15.3 ARITHMETIC AND LOGIC OPERATION 260
15.4 MACRO STATEMENTS AND NC STATEMENTS 265
15.5 BRANCH AND REPETITION 266
15.5.1 Unconditional Branch (GOTO Statement) 266
15.5.2 Conditional Branch (IF Statement) 267
15.5.3 Repetition (While Statement) 268
15.6 MACRO CALL 271
15.6.1 Simple Call (G65) 272
15.6.2 Modal Call (G66) 276
15.6.3 Macro Call Using G Code 278
15.6.4 Macro Call Using an M Code 279
15.6.5 Subprogram Call Using an M Code 280
15.6.6 Subprogram Calls Using a T Code 281
15.6.7 Sample Program 282
15.7 PROCESSING MACRO STATEMENTS 284
15.8 REGISTERING CUSTOM MACRO PROGRAMS 286
15.9 LIMITATIONS 287
15.10 EXTERNAL OUTPUT COMMANDS 288
15.11 INTERRUPTION TYPE CUSTOM MACRO 292
15.11.1 Specification Method 293
15.11.2 Details of Functions 294

16. PROGRAMMABLE PARAMETER ENTRY (G10) 301

17. MEMORY OPERATION BY Series 10/11 TAPE FORMAT 304

17.1 ADDRESSES AND SPECIFIABLE VALUE RANGE FOR Series 10/11 TAPE FORMAT 305
17.2 EQUAL–LEAD THREADING 306
17.3 SUBPROGRAM CALLING 307
17.4 CANNED CYCLE 308
17.5 MULTIPLE REPETITIVE CANNED TURNING CYCLE 309
17.6 CANNED DRILLING CYCLE FORMATS 311

18. FUNCTIONS FOR HIGH SPEED CUTTING 315

18.1 REMOTE BUFFER 316
18.2 HIGH–SPEED REMOTE BUFFER A (G05) 317
18.3 DISTRIBUTION PROCESSING TERMINATION MONITORING FUNCTION FOR THE HIGH–SPEED MACHINING COMMAND (G05) 319

19. AXIS CONTROL FUNCTION 320

19.1 POLYGONAL TURNING 321
19.2 ROTARY AXIS ROLL–OVER 326
19.3 SIMPLE SYNCHRONIZATION CONTROL 327
19.4 B–AXIS CONTROL (G100, G101, G102, G103, G110) 329
19.5 ANGULAR AXIS CONTROL / ARBITRARY ANGULAR AXIS CONTROL 339

20. PATTERN DATA INPUT FUNCTION 341

20.1 DISPLAYING THE PATTERN MENU 342
20.2 PATTERN DATA DISPLAY 346
20.3 CHARACTERS AND CODES TO BE USED FOR THE PATTERN DATA INPUT FUNCTION 350

III. OPERATION

1. GENERAL 355

1.1 MANUAL OPERATION 356
1.2 TOOL MOVEMENT BY PROGRAMMING – AUTOMATIC OPERATION 358
1.3 AUTOMATIC OPERATION 359
1.4 TESTING A PROGRAM 361
1.4.1 Check by Running the Machine 361
1.4.2 How to View the Position Display Change without Running the Machine 362
1.5 EDITING A PART PROGRAM 363
1.6 DISPLAYING AND SETTING DATA 364
1.7 DISPLAY 367
1.7.1 Program Display 367
1.7.2 Current Position Display 368
1.7.3 Alarm Display 368
1.7.4 Parts Count Display, Run Time Display 369
1.7.5 Graphic Display (See Section III–12) 370
1.8 DATA OUTPUT 371

2. OPERATIONAL DEVICES 372

2.1 SETTING AND DISPLAY UNITS 373
2.1.1 CNC Control Unit with 7.2″/8.4″ LCD 374
2.1.2 CNC Control Unit with 9.5″/10.4″ LCD 374
2.1.3 Separate–Type Small MDI Unit 375
2.1.4 Separate–Type Standard MDI Unit (Horizontal Type) 376
2.1.5 Separate–Type Standard MDI Unit (Vertical Type) 377
2.1.6 Separate–Type Standard MDI Unit (Vertical Type) (for 210*i*) 378

2.2 EXPLANATION OF THE KEYBOARD 379
2.3 FUNCTION KEYS AND SOFT KEYS 381
2.3.1 General Screen Operations 381
2.3.2 Function Keys 382
2.3.3 Soft Keys 383
2.3.4 Key Input and Input Buffer 399
2.3.5 Warning Messages 400
2.3.6 Soft Key Configuration 401
2.4 EXTERNAL I/O DEVICES 402
2.4.1 FANUC Handy File 404
2.4.2 FANUC Floppy Cassette 404
2.4.3 FANUC FA Card 405
2.4.4 FANUC PPR 405
2.4.5 Portable Tape Reader 406
2.5 POWER ON/OFF 407
2.5.1 Turning on the Power 407
2.5.2 Screen Displayed at Power–on 408
2.5.3 Power Disconnection 409

3. MANUAL OPERATION 410

3.1 MANUAL REFERENCE POSITION RETURN 411
3.2 JOG FEED 413
3.3 INCREMENTAL FEED 415
3.4 MANUAL HANDLE FEED 416
3.5 MANUAL ABSOLUTE ON AND OFF 419

4. AUTOMATIC OPERATION 424

4.1 MEMORY OPERATION 425
4.2 MDI OPERATION 428
4.3 PROGRAM RESTART 432
4.4 SCHEDULING FUNCTION 440
4.5 SUBPROGRAM CALL FUNCTION (M198) 445
4.6 MANUAL HANDLE INTERRUPTION 447
4.7 MIRROR IMAGE 450
4.8 MANUAL INTERVENTION AND RETURN 452
4.9 DNC OPERATION 454

5. TEST OPERATION 457

5.1 MACHINE LOCK AND AUXILIARY FUNCTION LOCK 458
5.2 FEEDRATE OVERRIDE 460
5.3 RAPID TRAVERSE OVERRIDE 461
5.4 DRY RUN 462
5.5 SINGLE BLOCK 463

6. SAFETY FUNCTIONS 466

6.1 EMERGENCY STOP 467
6.2 OVERTRAVEL 468
6.3 STROKE CHECK 469
6.4 CHUCK AND TAILSTOCK BARRIERS 473

7. ALARM AND SELF–DIAGNOSIS FUNCTIONS 480

7.1 ALARM DISPLAY 481
7.2 ALARM HISTORY DISPLAY 483
7.3 CHECKING BY SELF–DIAGNOSTIC SCREEN 484

8. DATA INPUT/OUTPUT 487

8.1 FILES 488
8.2 FILE SEARCH 490
8.3 FILE DELETION 492
8.4 PROGRAM INPUT/OUTPUT 493
8.4.1 Inputting a Program 493
8.4.2 Outputting a Program 496
8.5 OFFSET DATA INPUT AND OUTPUT 498
8.5.1 Inputting Offset Data 498
8.5.2 Outputting Offset Data 499
8.6 INPUTTING AND OUTPUTTING PARAMETERS AND PITCH ERROR COMPENSATION DATA 500
8.6.1 Inputting Parameters 500
8.6.2 Outputting Parameters 501
8.6.3 Inputting Pitch Error Compensation Data 502
8.6.4 Outputting Pitch Error Compensation Data 503
8.7 INPUTTING/OUTPUTTING CUSTOM MACRO COMMON VARIABLES 504
8.7.1 Inputting Custom Macro Common Variables 504
8.7.2 Outputting Custom Macro Common Variable 505
8.8 DISPLAYING DIRECTORY OF FLOPPY DISK 506
8.8.1 Displaying the Directory 507
8.8.2 Reading Files 510
8.8.3 Outputting Programs 511
8.8.4 Deleting Files 512
8.9 OUTPUTTING A PROGRAM LIST FOR A SPECIFIED GROUP 514
8.10 DATA INPUT/OUTPUT ON THE ALL IO SCREEN 515
8.10.1 Setting Input/Output–Related Parameters 516
8.10.2 Inputting and Outputting Programs 517
8.10.3 Inputting and Outputting Parameters 521
8.10.4 Inputting and Outputting Offset Data 523
8.10.5 Outputting Custom Macro Common Variables 525
8.10.6 Inputting and Outputting Floppy Files 526
8.10.7 Memory Card Input/Output 531
8.11 DATA INPUT/OUTPUT USING A MEMORY CARD 540

9. EDITING PROGRAMS 552

9.1 INSERTING, ALTERING AND DELETING A WORD 553
9.1.1 Word Search 554
9.1.2 Heading a Program 556
9.1.3 Inserting a Word 557
9.1.4 Altering a Word 558
9.1.5 Deleting a Word 559

9.2 DELETING BLOCKS 560
9.2.1 Deleting a Block 560
9.2.2 Deleting Multiple Blocks 561
9.3 PROGRAM NUMBER SEARCH 562
9.4 SEQUENCE NUMBER SEARCH 563
9.5 DELETING PROGRAMS 565
9.5.1 Deleting One Program 565
9.5.2 Deleting All Programs 565
9.5.3 Deleting More Than One Program by Specifying a Range 566
9.6 EXTENDED PART PROGRAM EDITING FUNCTION 567
9.6.1 Copying an Entire Program 568
9.6.2 Copying Part of a Program 569
9.6.3 Moving Part of a Program 570
9.6.4 Merging a Program 571
9.6.5 Supplementary Explanation for Copying, Moving and Merging 572
9.6.6 Replacement of Words and Addresses 574
9.7 EDITING OF CUSTOM MACROS 576
9.8 BACKGROUND EDITING 577
9.9 PASSWORD FUNCTION 578

10. CREATING PROGRAMS 580

10.1 CREATING PROGRAMS USING THE MDI PANEL 581
10.2 AUTOMATIC INSERTION OF SEQUENCE NUMBERS 582
10.3 CREATING PROGRAMS IN TEACH IN MODE (PLAYBACK) 584

11. SETTING AND DISPLAYING DATA 587

11.1 SCREENS DISPLAYED BY FUNCTION KEY [POS] 595
11.1.1 Position Display in the Workpiece Coordinate System 595
11.1.2 Position Display in the Relative Coordinate System 596
11.1.3 Overall Position Display 598
11.1.4 Presetting the Workpiece Coordinate System 599
11.1.5 Actual Feedrate Display 600
11.1.6 Display of Run Time and Parts Count 602
11.1.7 Operating Monitor Display 603
11.2 SCREENS DISPLAYED BY FUNCTION KEY [PROG]
(IN MEMORY MODE OR MDI MODE) 605
11.2.1 Program Contents Display 606
11.2.2 Current Block Display Screen 607
11.2.3 Next Block Display Screen 608
11.2.4 Program Check Screen 609
11.2.5 Program Screen for MDI Operation 611
11.2.6 Displaying the B–axis Operation State 612
11.3 SCREENS DISPLAYED BY FUNCTION KEY [PROG] (IN THE EDIT MODE) 613
11.3.1 Displaying Memory Used and a List of Programs 614
11.3.2 Displaying a Program List for a Specified Group 617

11.4 SCREENS DISPLAYED BY FUNCTION KEY [OFFSET SETTING] 620
11.4.1 Setting and Displaying the Tool Offset Value 621
11.4.2 Direct Input of Tool Offset Value 624
11.4.3 Direct Input of Tool Offset Measured B 626
11.4.4 Counter Input of Offset value 628
11.4.5 Setting the Workpiece Coordinate System Shifting Amount 629
11.4.6 Y Axis Offset 631
11.4.7 Displaying and Entering Setting Data 634
11.4.8 Sequence Number Comparison and Stop 636
11.4.9 Displaying and Setting Run Time, Parts Count, and Time 638
11.4.10 Displaying and Setting the Workpiece Origin Offset Value 640
11.4.11 Direct Input of Measured Workpiece Origin Offsets 641
11.4.12 Displaying and Setting Custom Macro Common Variables 643
11.4.13 Displaying and Setting the Software Operator’s Panel 644
11.4.14 Displaying and Setting Tool Life Management Data 646
11.4.15 Setting and Displaying B–axis Tool Compensation 649
11.5 SCREENS DISPLAYED BY FUNCTION KEY [SYSTEM] 651
11.5.1 Displaying and Setting Parameters 652
11.5.2 Displaying and Setting Pitch Error Compensation Data 654
11.6 DISPLAYING THE PROGRAM NUMBER, SEQUENCE NUMBER, AND STATUS, AND WARNING MESSAGES FOR DATA SETTING OR INPUT/OUTPUT OPERATION 656
11.6.1 Displaying the Program Number and Sequence Number 656
11.6.2 Displaying the Status and Warning for Data Setting or Input/Output Operation 657
11.7 SCREENS DISPLAYED BY FUNCTION KEY [MESSAGE] 659
11.7.1 External Operator Message History Display 659
11.8 CLEARING THE SCREEN 661
11.8.1 Erase CRT Screen Display 661
11.8.2 Automatic Erase Screen Display 662

12. GRAPHICS FUNCTION 663

12.1 GRAPHICS DISPLAY 664

13. HELP FUNCTION 669

IV. MAINTENANCE

1. METHOD OF REPLACING BATTERY 677

1.1 REPLACING THE ALKALINE DRY CELLS (SIZE D) 680
1.2 USE OF ALKALINE DRY CELLS (SIZE D) 681
1.3 BATTERY FOR SEPARATE ABSOLUTE PULSE CODERS 682

APPENDIX

A. TAPE CODE LIST 685

B. LIST OF FUNCTIONS AND TAPE FORMAT 688

C. RANGE OF COMMAND VALUE 692

D. NOMOGRAPHS 695

D.1 INCORRECT THREADED LENGTH 696
D.2 SIMPLE CALCULATION OF INCORRECT THREAD LENGTH 698
D.3 TOOL PATH AT CORNER 700
D.4 RADIUS DIRECTION ERROR AT CIRCLE CUTTING 703

E. STATUS WHEN TURNING POWER ON, WHEN CLEAR AND WHEN RESET 704

F. CHARACTER–TO–CODES CORRESPONDENCE TABLE 706

G. ALARM LIST 707

H. OPERATION OF PORTABLE TAPE READER 729

I. GENERAL

1 GENERAL

About this manual

This manual consists of the following parts:

I. GENERAL
Describes chapter organization, applicable models, related manuals, and notes for reading this manual.

II. PROGRAMMING
Describes each function: Format used to program functions in the NC language, characteristics, and restrictions. When a program is created through conversational automatic programming function, refer to the manual for the conversational automatic programming function (Table1).

III. OPERATION
Describes the manual operation and automatic operation of a machine, procedures for inputting and outputting data, and procedures for editing a program.

IV. MAINTENANCE
Describes procedures for replacing batteries.

V. APPENDIX
Lists tape codes, valid data ranges, and error codes.

Some functions described in this manual may not be applied to some products. For detail, refer to the DESCRIPTIONS manual (B–63002EN).

This manual does not describe parameters in detail. For details on parameters mentioned in this manual, refer to the manual for parameters (B–63090EN).

This manual describes all optional functions. Look up the options incorporated into your system in the manual written by the machine tool builder.
The models covered by this manual, and their abbreviations are:

Product name	Abbreviations	
FANUC Series 21*i*–TA	21*i*–TA	Series 21*i*
FANUC Series 210*i*–TA	210*i*–TA	Series 210*i*

Special symbols

This manual uses the following symbols:

IP_ : Indicates a combination of axes such as X__ Y__ Z (used in PROGRAMMING.).
; : Indicates the end of a block. It actually corresponds to the ISO code LF or EIA code CR.

Related manuals

The table below lists manuals related to MODEL A of Series 21*i* and Series 210*i*.
In the table, this manual is marked with an asterisk (*).

Table 1 Related Manuals

Manual name	Specification number	
DESCRIPTIONS	B–63002EN	
CONNECTION MANUAL (Hardware)	B–63083EN	
CONNECTION MANUAL (Function)	B–63003EN–1	
OPERATOR'S MANUAL for Lathe	B–63084EN	*
OPERATOR'S MANUAL for Machining Center	B–63094EN	
MAINTENANCE MANUAL	B–63085EN	
PARAMETER MANUAL	B–63090EN	
PROGRAMMING MANUAL (Macro Compiler / Macro Executer)	B–61803E–1	
FAPT MACRO COMPILER PROGRAMMING MANUAL	B–66102E	
FANUC Symbolic CAP T Basic Module V1 OPERATOR'S MANUAL	B–62824EN	
FANUC Symbolic CAP T C/Y axis Module V1 OPERATOR'S MANUAL	B–62824EN–1	
FANUC Symbolic CAP M Basic Module V1 OPERATOR'S MANUAL	B–62984EN	

1.1 GENERAL FLOW OF OPERATION OF CNC MACHINE TOOL

When machining the part using the CNC machine tool, first prepare the program, then operate the CNC machine by using the program.

1) First, prepare the program from a part drawing to operate the CNC machine tool.
   How to prepare the program is described in the Chapter II. PROGRAMMING.

2) The program is to be read into the CNC system. Then, mount the workpieces and tools on the machine, and operate the tools according to the programming. Finally, execute the machining actually.
   How to operate the CNC system is described in the Chapter III. OPERATION.



Before the actual programming, make the machining plan for how to machine the part.
Machining plan
1. Determination of workpieces machining range
2. Method of mounting workpieces on the machine tool
3. Machining sequence in every cutting process
4. Cutting tools and cutting conditions
Decide the cutting method in every cutting process.

Cutting process / Cutting procedure	1 End face cutting	2 Outer diameter cutting	3 Grooving
1. Cutting method : Rough Semi Finish			
2. Cutting tools			
3. Cutting conditions : Feedrate Cutting depth			
4. Tool path			



Prepare the program of the tool path and cutting condition according to the workpiece figure, for each cutting.

1.2 NOTES ON READING THIS MANUAL

NOTE

1 The function of an CNC machine tool system depends not only on the CNC, but on the combination of the machine tool, its magnetic cabinet, the servo system, the CNC, the operator's panels, etc. It is too difficult to describe the function, programming, and operation relating to all combinations. This manual generally describes these from the stand–point of the CNC. So, for details on a particular CNC machine tool, refer to the manual issued by the machine tool builder, which should take precedence over this manual.

2 Headings are placed in the left margin so that the reader can easily access necessary information. When locating the necessary information, the reader can save time by searching though these headings.

3 Machining programs, parameters, variables, etc. are stored in the CNC unit internal non–volatile memory. In general, these contents are not lost by the switching ON/OFF of the power. However, it is possible that a state can occur where precious data stored in the non–volatile memory has to be deleted, because of deletions from a maloperation, or by a failure restoration. In order to restore rapidly when this kind of mishap occurs, it is recommended that you create a copy of the various kinds of data beforehand.

4 This manual describes as many reasonable variations in equipment usage as possible. It cannot address every combination of features, options and commands that should not be attempted.
If a particular combination of operations is not described, it should not be attempted.

II. PROGRAMMING

1 GENERAL

1.1 TOOL MOVEMENT ALONG WORKPIECE PARTS FIGURE– INTERPOLATION

Explanations

The tool moves along straight lines and arcs constituting the workpiece parts figure (See II–4).

- **Tool movement along a straight line**



Fig.1.1 (a) Tool movement along the straight line which is parallel to Z–axis



Fig.1.1 (b) Tool movement along the taper line

- **Tool movement along an arc**



Fig. 1.1 (c) Tool movement along an arc

The term interpolation refers to an operation in which the tool moves along a straight line or arc in the way described above.
Symbols of the programmed commands G01, G02, ... are called the preparatory function and specify the type of interpolation conducted in the control unit.



Fig. 1.1 (d) Interpolation function

NOTE
Some machines move tables instead of tools but this manual assumes that tools are moved against workpieces.

- **Thread cutting**

Threads can be cut by moving the tool in synchronization with spindle rotation. In a program, specify the thread cutting function by G32.



Fig. 1.1 (e) Straight thread cutting



Fig. 1.1 (f) Taper thread cutting

1.2 FEED– FEED FUNCTION

Movement of the tool at a specified speed for cutting a workpiece is called the feed.



Fig. 1.2 (a) Feed function

Feedrates can be specified by using actual numerics.
For example, the following command can be used to feed the tool 2 mm while the workpiece makes one turn :

F2.0

The function of deciding the feed rate is called the feed function (See II–5).

1.3 PART DRAWING AND TOOL MOVEMENT

1.3.1 Reference Position (Machine–Specific Position)

A CNC machine tool is provided with a fixed position. Normally, tool change and programming of absolute zero point as described later are performed at this position. This position is called the reference position.



Fig. 1.3.1 (a) Reference position

Explanations

The tool can be moved to the reference position in two ways:

1. Manual reference position return (See III–3.1)
   Reference position return is performed by manual button operation.

2. Automatic reference position return (See II–6)
   In general, manual reference position return is performed first after the power is turned on. In order to move the tool to the reference position for tool change thereafter, the function of automatic reference position return is used.

1.3.2 Coordinate System on Part Drawing and Coordinate System Specified by CNC – Coordinate System



Fig. 1.3.2 (a) Coordinate system

Explanations

- **Coordinate system**

The following two coordinate systems are specified at different locations: (See II–7)

1. Coordinate system on part drawing
   The coordinate system is written on the part drawing. As the program data, the coordinate values on this coordinate system are used.

2. Coordinate system specified by the CNC
   The coordinate system is prepared on the actual machine tool. This can be achieved by programming the distance from the current position of the tool to the zero point of the coordinate system to be set.



Fig. 1.3.2 (b) Coordinate system specified by the CNC

The tool moves on the coordinate system specified by the CNC in accordance with the command program generated with respect to the coordinate system on the part drawing, and cuts a workpiece into a shape on the drawing.
Therefore, in order to correctly cut the workpiece as specified on the drawing, the two coordinate systems must be set at the same position.

- **Methods of setting the two coordinate systems in the same position**

The following method is usually used to define two coordinate systems at the same location.

1. When coordinate zero point is set at chuck face



Fig. 1.3.2 (c) Coordinates and dimensions on part drawing



Fig. 1.3.2 (d) Coordinate system on lathe as specified by CNC (made to coincide with the coordinate system on part drawing)

2. When coordinate zero point is set at work end face.



Fig. 1.3.2 (e) Coordinates and dimensions on part drawing



Fig. 1.3.2 (f) Coordinate system on lathe as specified by CNC (made to coincide with the coordinate system on part drawing)

1.3.3 How to Indicate Command Dimensions for Moving the Tool – Absolute, Incremental Commands

Explanations

Methods of command for moving the tool can be indicated by absolute or incremental designation (See II–8.1).

- **Absolute command**

The tool moves to a point at “the distance from zero point of the coordinate system” that is to the position of the coordinate values.



Fig. 1.3.3 (a) Absolute command

- **Incremental command**

Specify the distance from the previous tool position to the next tool position.



Fig. 1.3.3 (b) Incremental command

- **Diameter programming / radius programming**

Dimensions of the X axis can be set in diameter or in radius. Diameter programming or radius programming is employed independently in each machine.

1. Diameter programming
   In diameter programming, specify the diameter value indicated on the drawing as the value of the X axis.



Fig. 1.3.3 (c) Diameter programming

2. Radius programming
   In radius programming, specify the distance from the center of the workpiece, i.e. the radius value as the value of the X axis.



Fig. 1.3.3 (d) Radius programming

1.4 CUTTING SPEED – SPINDLE SPEED FUNCTION

The speed of the tool with respect to the workpiece when the workpiece is cut is called the cutting speed.
As for the CNC, the cutting speed can be specified by the spindle speed in rpm unit.



Fig. 1.4 Cutting speed

Examples

<When a workpiece 200 mm in diameter should be machined at a cutting speed of 300 m/min. >

The spindle speed is approximately 478 rpm, which is obtained from $N=1000v/\pi D$. Hence the following command is required:

S478 ;

Commands related to the spindle speed are called the spindle speed function (See II–9).
The cutting speed v (m/min) can also be specified directly by the speed value. Even when the workpiece diameter is changed, the CNC changes the spindle speed so that the cutting speed remains constant.
This function is called the constant surface speed control function (See II–9.3).

1.5 SELECTION OF TOOL USED FOR VARIOUS MACHINING – TOOL FUNCTION

When drilling, tapping, boring, milling or the like, is performed, it is necessary to select a suitable tool. When a number is assigned to each tool and the number is specified in the program, the corresponding tool is selected.



Fig. 1.5 Tool used for various machining

Examples

<When No.01 is assigned to a roughing tool>

When the tool is stored at location 01 of the tool post, the tool can be selected by specifying **T0101**.
This is called the tool function (See II–10).

1.6 COMMAND FOR MACHINE OPERATIONS – MISCELLANEOUS FUNCTION

When machining is actually started, it is necessary to rotate the spindle, and feed coolant. For this purpose, on–off operations of spindle motor and coolant valve should be controlled (See II–11).



Fig. 1.6 Command for machine operations

The function of specifying the on–off operations of the components of the machine is called the miscellaneous function. In general, the function is specified by an M code.
For example, when M03 is specified, the spindle is rotated clockwise at the specified spindle speed.

1.7 PROGRAM CONFIGURATION

A group of commands given to the CNC for operating the machine is called the program. By specifying the commands, the tool is moved along a straight line or an arc, or the spindle motor is turned on and off.
In the program, specify the commands in the sequence of actual tool movements.



Fig. 1.7 (a) Program configuration

A group of commands at each step of the sequence is called the block. The program consists of a group of blocks for a series of machining. The number for discriminating each block is called the sequence number, and the number for discriminating each program is called the program number (See II–12).

Explanations

The block and the program have the following configurations.

- **Block**



Fig. 1.7 (b) Block configuration

A block begins with a sequence number that identifies that block and ends with an end–of–block code.
This manual indicates the end–of–block code by ; (LF in the ISO code and CR in the EIA code).

- **Program**



Fig. 1.7 (c) Program configuration

Normally, a program number is specified after the end–of–block (;) code at the beginning of the program, and a program end code (M02 or M30) is specified at the end of the program.

- **Main program and subprogram**

When machining of the same pattern appears at many portions of a program, a program for the pattern is created. This is called the subprogram. On the other hand, the original program is called the main program. When a subprogram execution command appears during execution of the main program, commands of the subprogram are executed. When execution of the subprogram is finished, the sequence returns to the main program.



1.8 COMPENSATION FUNCTION

Explanations

- **Machining using the end of cutter – Tool length compensation function**

Usually, several tools are used for machining one workpiece. The tools have different tool length. It is very troublesome to change the program in accordance with the tools.
Therefore, the length of each tool used should be measured in advance. By setting the difference between the length of the standard tool and the length of each tool in the CNC (data display and setting : see III–11), machining can be performed without altering the program even when the tool is changed. This function is called tool length compensation.



Fig. 1.8 Tool offset

1.9 TOOL MOVEMENT RANGE – STROKE

Limit switches are installed at the ends of each axis on the machine to prevent tools from moving beyond the ends. The range in which tools can move is called the stroke. Besides the stroke limits, data in memory can be used to define an area which tools cannot enter.



Besides strokes defined with limit switches, the operator can define an area which the tool cannot enter using a program or data in memory. This function is called stroke check.

2 CONTROLLED AXES

2.1 CONTROLLED AXES

Item	21*i*–TA 210*i*–TA
Number of basic controlled axes	2 axes
Controlled axis expansion (total)	Max. 4 axes (Included in Cs axis)
Number of basic simultaneously controlled axes	2 axes
Simultaneously controlled axis expansion (total)	Max. 4 axes

NOTE
The number of simultaneously controllable axes for manual operation (jog feed, incremental feed, or manual handle feed) is 1 or 3 (1 when bit 0 (JAX) of parameter 1002 is set to 0 and 3 when it is set to 1).

2.2 NAMES OF AXES

The names of two basic axes are always X and Z; the names of additional axes can be optionally selected from A, B, C, U, V, W, and Y by using parameter No.1020.
Each axis name is determined according to parameter No. 1020. If the parameter specifies 0 or anything other than the nine letters, the axis name defaults to a number from 1 to 4.

Limitations

- **Default axis name**

When a default axis name (1 to 4) is used, the system cannot operate in MEM or MDI mode.

- **Duplicate axis name**

If the parameter specifies an axis name more than once, only the first axis to be assigned that axis name becomes operable.

NOTE
1 When G code system A is used, the letters U, V, and W cannot be used as an axis name (hence, the maximum of six controlled axes), because these letters are used as incremental commands for X, Y, and Z. To use the letters U, V, and W as axis names, the G code system must be B or C. Likewise, letter H is used as an incremental command for C, thus incremental commands cannot be used if A or B is used as an axis name.
2 In G76 (multiple–thread cutting), the A address in a block specifies the tool nose angle instead of a command for axis A.
If C or A is used as an axis name, C or A cannot be used as an angle command for a straight line in chamfering or direct drawing dimension programming. Therefore, C and A should be used according to bit 4 (CCR) of parameter No. 3405.

2.3 INCREMENT SYSTEM

The increment system consists of the least input increment (for input) and least command increment (for output). The least input increment is the least increment for programming the travel distance. The least command increment is the least increment for moving the tool on the machine. Both increments are represented in mm, inches, or degrees.
The increment system is classified into IS–B and IS–C (Tables 2.3(a) and 2.3(b)). Select IS–B or IS–C using bit 1 (ISC) of parameter 1004. When the IS–C increment system is selected, it is applied to all axes and the 1/10 increment system option is required.

Table 2.3 (a) Increment system IS–B

		Least input increment	Least command increment
Metric system machine	**mm input**	0.001mm(Diameter)	0.0005mm
		0.001mm(Radius)	0.001mm
		0.001deg	0.001deg
	inch input	0.0001inch(Diameter)	0.0005mm
		0.0001inch(Radius)	0.001mm
		0.001deg	0.001deg
Inch machine system	**mm input**	0.001mm(Diameter)	0.00005inch
		0.001mm(Radius)	0.0001inch
		0.001deg	0.001deg
	inch input	0.0001inch(Diameter)	0.00005inch
		0.0001inch(Radius)	0.0001inch
		0.001deg	0.001deg

Table 2.3 (b) Increment system IS–C

		Least input increment	Least command increment
Metric system machine	**mm input**	0.0001mm(Diameter)	0.00005mm
		0.0001mm(Radius)	0.0001mm
		0.0001deg	0.0001deg
	inch input	0.00001inch(Diameter)	0.00005mm
		0.00001inch(Radius)	0.0001mm
		0.0001deg	0.0001deg
Inch machine system	**mm input**	0.0001mm(Diameter)	0.000005inch
		0.0001mm(Radius)	0.00001inch
		0.0001deg	0.0001deg
	inch input	0.00001inch(Diameter)	0.000005inch
		0.00001inch(Radius)	0.00001inch
		0.0001deg	0.0001deg

2.4 MAXIMUM STROKES

The maximum stroke controlled by this CNC is shown in the table below:
Maximum stroke=Least command increment ± 99999999

Table 2.4 Maximum strokes

Increment system		Maximum strokes
IS–B	Metric machine system	± 99999.999 mm ± 99999.999 deg
	Inch machine system	± 9999.9999 inch ± 99999.999 deg
IS–C	Metric machine system	± 9999.9999 mm ± 9999.9999 deg
	Inch machine system	± 999.99999 inch ± 9999.9999 deg

NOTE
1 The unit in the table is a diameter value with diameter programming and a radius value in radius programming.
2 A command exceeding the maximum stroke cannot be specified.
3 The actual stroke depends on the machine tool.

3 PREPARATORY FUNCTION (G FUNCTION)

A number following address G determines the meaning of the command for the concerned block.
G codes are divided into the following two types.

Type	Meaning
One–shot G code	The G code is effective only in the block in which it is specified
Modal G code	The G code is effective until another G code of the same group is specified.

(Example)
G01 and G00 are modal G codes.

```
G01X_;
   Z_;
   X_;   } G01 is effective in this range
G00Z_;
```

There are three G code systems : A,B, and C (Table 3). Select a G code system using bits 6 (GSB) and 7 (GSC) of parameter 3401. Generally, this manual describes the use of G code system A, except when the described item can use only G code system B or C. ln such cases, the use of G code system B or C is described.

Explanations

1. If the CNC enters the clear state (see bit 6 (CLR) of parameter 3402) when the power is turned on or the CNC is reset, the modal G codes change as follows.
   (1) G codes marked with ◤ in Table 3 are enabled.
   (2) When the system is cleared due to power–on or reset, whichever specified, either G20 or G21, remains effective.
   (3) Bit 7 of parameter No. 3402 can be used to specify whether G22 or G23 is selected upon power–on. Resetting the CNC to the clear state does not affect the selection of G22 or G23.
   (4) Setting bit 0 (G01) of parameter 3402 determines which code, either G00 or G01, is effective.
   (5) Setting bit 3 (G91) of parameter 3402 determines which code, either G90 or G91, is effective.
2. G codes of group 00 except G10 and G11 are single–shot G codes.
3. P/S larm (No.010) is displayed when a G code not listed in the G code list is specified or a G code without a corresponding option is specified.
4. G codes of different groups can be specified in the same block.
   If G codes of the same group are specified in the same block, the G code specified last is valid.
5. If a G code of group 01 is specified in a canned cycle, the canned cycle is canceled in the same way as when a G80 command is specified. G codes of group 01 are not affected by G codes for specifying a canned cycle.
6. When G code system A is used for a canned cycle, only the initial level is provided at the return point.
7. G codes are displayed for each group number.

Table 3 G code list (1/2)

G code			Group	Function
A	B	C		
G00	G00	G00	01	Positioning (Rapid traverse)
G01	G01	G01		Linear interpolation (Cutting feed)
G02	G02	G02		Circular interpolation CW or Helical interpolation CW
G03	G03	G03		Circular interpolation CCW or Helical interpolation CCW
G04	G04	G04	00	Dwell
G05	G05	G05		High speed cycle cutting
G07	G07	G07	00	Hypothetical axis interpolation
G07.1 (G107)	G07.1 (G107)	G07.1 (G107)	00	Cylindrical interpolation
G10	G10	G10		Programmable data input
G11	G11	G11		Programmable data input cancel
G12.1 (G112)	G12.1 (G112)	G12.1 (G112)	21	Polar coordinate interpolation mode
G13.1 (G113)	G13.1 (G113)	G13.1 (G113)		Polar coordinate interpolation cancel mode
G17	G17	G17	16	XpYp plane selection
G18	G18	G18		ZpXp plane selection
G19	G19	G19		YpZp plane selection
G20	G20	G70	06	Input in inch
G21	G21	G71		Input in mm
G22	G22	G22	09	Stored stroke check function on
G23	G23	G23		Stored stroke check function off
G25	G25	G25	08	Spindle speed fluctuation detection off
G26	G26	G26		Spindle speed fluctuation detection on
G27	G27	G27	00	Reference position return check
G28	G28	G28		Return to reference position
G30	G30	G30		2nd, 3rd and 4th reference position return
G31	G31	G31		Skip function
G32	G33	G33	01	Thread cutting
G34	G34	G34		Variable–lead thread cutting
G36	G36	G36	00	Automatic tool compensation X
G37	G37	G37		Automatic tool compensation Z
G40	G40	G40	07	Tool nose radius compensation cancel
G41	G41	G41		Tool nose radius compensation left
G42	G42	G42		Tool nose radius compensation right
G50	G92	G92	00	Coordinate system setting or max. spindle speed setting
G50.3	G92.1	G92.1		Workpiece coordinate system preset
G50.2 (G250)	G50.2 (G250)	G50.2 (G250)	20	Polygonal turning cancel
G51.2 (G251)	G51.2 (G251)	G51.2 (G251)		Polygonal turning

Table 3 G code list (2/2)

G code			Group	Function
A	**B**	**C**		
G52	G52	G52	00	Local coordinate system setting
G53	G53	G53		Machine coordinate system setting
G54	G54	G54	14	Workpiece coordinate system 1 selection
G55	G55	G55		Workpiece coordinate system 2 selection
G56	G56	G56		Workpiece coordinate system 3 selection
G57	G57	G57		Workpiece coordinate system 4 selection
G58	G58	G58		Workpiece coordinate system 5 selection
G59	G59	G59		Workpiece coordinate system 6 selection
G65	G65	G65	00	Macro calling
G66	G66	G66	12	Macro modal call
G67	G67	G67		Macro modal call cancel
G68	G68	G68	04	Mirror image for double turrets ON or balance cut mode
G69	G69	G69		Mirror image for double turrets OFF or balance cut mode cancel
G70	G70	G72	00	Finishing cycle
G71	G71	G73		Stock removal in turning
G72	G72	G74		Stock removal in facing
G73	G73	G75		Pattern repeating
G74	G74	G76		End face peck drilling
G75	G75	G77		Outer diameter/internal diameter drilling
G76	G76	G78		Multiple threading cycle
G80	G80	G80	10	Canned cycle for drilling cancel
G83	G83	G83		Cycle for face drilling
G84	G84	G84		Cycle for face tapping
G86	G86	G86		Cycle for face boring
G87	G87	G87		Cycle for side drilling
G88	G88	G88		Cycle for side tapping
G89	G89	G89		Cycle for side boring
G90	G77	G20	01	Outer diameter/internal diameter cutting cycle
G92	G78	G21		Thread cutting cycle
G94	G79	G24		Endface turning cycle
G96	G96	G96	02	Constant surface speed control
G97	G97	G97		Constant surface speed control cancel
G98	G94	G94	05	Per minute feed
G99	G95	G95		Per revolution feed
–	G90	G90	03	Absolute programming
–	G91	G91		Incremental programming
–	G98	G98	11	Return to initial level (See **Explanations 6**)
–	G99	G99		Return to R point level (See **Explanations 6**)

4 INTERPOLATION FUNCTIONS

4.1 POSITIONING (G00)

The G00 command moves a tool to the position in the workpiece system specified with an absolute or an incremental command at a rapid traverse rate.
In the absolute command, coordinate value of the end point is programmed.
In the incremental command the distance the tool moves is programmed.

Format

G00IP_;

IP_: For an absolute command, the coordinates of an end position, and for an incremental command, the distance the tool moves.

Explanations

Either of the following tool paths can be selected according to bit 1 (LRP) of parameter No. 1401.

- **Nonlinear interpolation positioning**
  The tool is positioned with the rapid traverse rate for each axis separately. The tool path is normally straight.
- **Linear interpolation positioning**
  The tool path is the same as in linear interpolation (G01). The tool is positioned within the shortest possible time at a speed that is not more than the rapid traverse rate for each axis.



The rapid traverse rate in the G00 command is set to the parameter No.1420 for each axis independently by the machine tool builder. In the positioning mode actuated by G00, the tool is accelerated to a predetermined speed at the start of a block and is decelerated at the end of a block. Execution proceeds to the next block after confirming the in–position.
“In–position” means that the feed motor is within the specified range.
This range is determined by the machine tool builder by setting to parameter No.1826.

Examples



< Radius programming >
G00X40.0Z56.0 ; (Absolute command)
or
G00U–60.0W–30.5;(Incremental command)

Restrictions

The rapid traverse rate cannot be specified in the address F.
Even if linear interpolation positioning is specified, nonlinear interpolation positioning is used in the following cases. Therefore, be careful to ensure that the tool does not foul the workpiece.

- G28 specifying positioning between the reference and intermediate positions.
- G53

4.2 LINEAR INTERPOLATION (G01)

Tools can move along a line.

Format

G01 IP_F_;

IP_: **For an absolute command, the coordinates of an end point , and for an incremental command, the distance the tool moves.**

F_: **Speed of tool feed (Feedrate)**

Explanations

A tools move along a line to the specified position at the feedrate specified in F.
The feedrate specified in F is effective until a new value is specified. It need not be specified for each block.
The feedrate commanded by the F code is measured along the tool path.
If the F code is not commanded, the feedrate is regarded as zero.
For feed–per–minute mode under 2–axis simultaneous control, the feedrate for a movement along each axis as follows :

G01$\alpha\underline{\alpha}\beta\underline{\beta}$ $\boldsymbol{F\underline{f}}$ **;**

Feed rate of α axis direction : $F\alpha = \frac{\alpha}{L} \times f$

Feed rate of β axis direction : $F_\beta = \frac{\beta}{L} \times f$

$L = \sqrt{\alpha^2 + \beta^2}$

Examples

- **Linear interpolation**

< Diameter programming >
G01X40.0Z20.1F20 ; (Absolute command)
or
G01U20.0W–25.9F20 ; (Incremental command)



4.3 CIRCULAR INTERPOLATION (G02, G03)

The command below will move a tool along a circular arc.

Format

Arc in the XpYp plane

G17 { **G02** / **G03** } **Xp_Yp_** { **I_J_** / **R_** } **F_**

Arc in the ZpXp plane

G18 { **G02** / **G03** } **Xp_Zp_** { **I_K_** / **R_** } F_

Arc in the YpZp plane

G19 { **G02** / **G03** } **Yp_Zp_** { J_K_ / **R_** } F_

Table.4.3 Description of the command format

Command	Description
G17	Specification of arc on XpYp plane
G18	Specification of arc on ZpXp plane
G19	Specification of arc on YpZp plane
G02	Circular Interpolation Clockwise direction (CW)
G03	Circular Interpolation Counterclockwise direction (CCW)
$X_{p_}$	Command values of X axis or its parallel axis (set by parameter No. 1022)
$Y_{p_}$	Command values of Y axis or its parallel axis (set by parameter No. 1022)
$Z_{p_}$	Command values of Z axis or its parallel axis (set by parameter No. 1022)
I_	X_p axis distance from the start point to the center of an arc with sign, radius value
J_	Y_p axis distance from the start point to the center of an arc with sign, radius value
k_	Z_p axis distance from the start point to the center of an arc with sign, radius value
R_	Arc radius with no sign (always with radius value)
F_	Feedrate along the arc

NOTE
The U–, V–, and W–axes (parallel with the basic axis) can be used with G–codes B and C.

Explanations

- **Direction of the circular interpolation**

"Clockwise"(G02) and "counterclockwise"(G03) on the X_pY_p plane (Z_pX_p plane or Y_pZ_p plane) are defined when the X_pY_p plane is viewed in the positive–to–negative direction of the Z_p axis (Y_p axis or X_p axis, respectively) in the Cartesian coordinate system. See the figure below.



- **Distance moved on an arc**

The end point of an arc is specified by address Xp, Yp or Zp, and is expressed as an absolute or incremental value according to G90 or G91. For the incremental value, the distance of the end point which is viewed from the start point of the arc is specified.

- **Distance from the start point to the center of arc**

The arc center is specified by addresses I, J, and K for the Xp, Yp, and Zp axes, respectively. The numerical value following I, J, or K, however, is a vector component in which the arc center is seen from the start point, and is always specified as an incremental value irrespective of G90 and G91, as shown below.
I, J, and K must be signed according to the direction.



I0,J0, and K0 can be omitted.
If the difference between the radius at the start point and that at the end point exceeds the value in a parameter (No.3410), an P/S alarm (No.020) occurs.

- **Full–circle programming**

When X_p, Y_p , and Z_p are omitted (the end point is the same as the start point) and the center is specified with I, J, and K, a 360° arc (circle) is specified.

- **Arc radius**

The distance between an arc and the center of a circle that contains the arc can be specified using the radius, R, of the circle instead of I, J, and K. In this case, one arc is less than 180°, and the other is more than 180° are considered. An arc with a sector angle of 180°or wider cannot be specified. If Xp, Yp, and Zp are all omitted, if the end point is located at the same position as the start point and when R is used, an arc of 0°is programmed
G02R ; (The cutter does not move.)

For arc (1) (less than 180°)
G02 W60.0 U10.0 R50.0 F300.0 ;
For arc (2) (greater than 180°)
An arc with a sector angle of 180° or wider cannot be specified within a single block.



- **Feedrate**

The feedrate in circular interpolation is equal to the feed rate specified by the F code, and the feedrate along the arc (the tangential feedrate of the arc) is controlled to be the specified feedrate.
The error between the specified feedrate and the actual tool feedrate is ±2% or less. However, this feed rate is measured along the arc after the tool nose radius compensation is applied

Restrictions

- **Simultaneously specifying R with I, J, and K**

If I, J, K, and R addresses are specified simultaneously, the arc specified by address R takes precedence and the other are ignored.

- **Specifying an axis that is not contained in the specified plane**

If an axis not contained in the specified plane is commanded, an alarm is displayed.
For example, when a ZX plane is specified in G–code B or C, specifying the X–axis or U–axis (parallel to the X–axis) causes P/S alarm No. 028 to be generated.

- **Difference in the radius between the start and end points**

If the difference in the radius between the start and end points of the arc exceeds the value specified in parameter No. 3410, P/S alarm No. 020 is generated.
If the end point is not on the arc, the tool moves in a straight line along one of the axes after reaching the end point.

- **Specifying a semicircle with R**

If an arc having a central angle approaching 180 is specified with R, the calculation of the center coordinates may produce an error. In such a case, specify the center of the arc with I, J, and K.

Examples

- **Command of circular interpolation X, Z**

G02X_Z_I_K_F_;



(Absolute programming)

G03X_Z_I_K_F_;



(Absolute programming)

G02X_Z_R_F_;



(Absolute programming)



(Diameter programming)
G02X50.0Z30.0I25.0F0.3; or
G02U20.0W–020.0I25.0F0.3; or
G02X50.0Z30.0R25.0F0.3 or
G02U20.0W–20.0R25.F0.3;

4.4 POLAR COORDINATE INTERPOLATION (G12.1, G13.1)

Polar coordinate interpolation is a function that exercises contour control in converting a command programmed in a Cartesian coordinate system to the movement of a linear axis (movement of a tool) and the movement of a rotary axis (rotation of a workpiece). This method is useful in cutting a front surface and grinding a cam shaft on a lathe.

Format

- **Specify G12.1 and G13.1 in Separate Blocks.**

G12.1 ; Starts polar coordinate interpolation mode (enables polar coordinate interpolation)

Specify linear or circular interpolation using coordinates in a Cartesian coordinate system consisting of a linear axis and rotary axis (virtual axis).

G13.1 ; Polar coordinate interpolation mode is cancelled (for not performing polar coordinate interpolation)

G112 and G113 can be used in place of G12.1 and G13.1, respectively.

Explanations

- **Polar coordinate interpolation plane**

G12.1 starts the polar coordinate interpolation mode and selects a polar coordinate interpolation plane (Fig. 4.5 (a)). Polar coordinate interpolation is performed on this plane.



Fig4.5 (a) Polar coordinate interpolation plane.

When the power is turned on or the system is reset, polar coordinate interpolation is canceled (G13.1).
The linear and rotation axes for polar coordinate interpolation must be set in parameters (No. 5460 and 5461) beforehand.

CAUTION

The plane used before G12.1 is specified (plane selected by G17, G18, or G19) is canceled. It is restored when G13.1 (canceling polar coordinate interpolation) is specified.
When the system is reset, polar coordinate interpolation is canceled and the plane specified by G17, G18, or G19 is used.

- **Distance moved and feedrate for polar coordinate interpolation**

  The unit for coordinates on the hypothetical axis is the same as the unit for the linear axis (mm/inch)

  The unit for the feedrate is mm/min or inch/min

In the polar coordinate interpolation mode, program commands are specified with Cartesian coordinates on the polar coordinate interpolation plane. The axis address for the rotation axis is used as the axis address for the second axis (virtual axis) in the plane. Whether a diameter or radius is specified for the first axis in the plane is the same as for the rotation axis regardless of the specification for the first axis in the plane. The virtual axis is at coordinate 0 immediately after G12.1 is specified. Polar interpolation is started assuming the angle of 0 for the position of the tool when G12.1 is specified.
Specify the feedrate as a speed (relative speed between the workpiece and tool) tangential to the polar coordinate interpolation plane (Cartesian coordinate system) using F.

- **G codes which can be specified in the polar coordinate interpolation mode**

G01 ..... Linear interpolation
G02, G03 ..... Circular interpolation
G04 ..... Dwell
G40, G41, G42 .... Tool nose radius compensation
(Polar coordinate interpolation is applied to the path after cutter compensation.)
G65, G66, G67 .... Custom macro command
G98, G99 ..... Feed per minute, feed per revolution

- **Circular interpolation in the polar coordinate plane**

The addresses for specifying the radius of an arc for circular interpolation (G02 or G03) in the polar coordinate interpolation plane depend on the first axis in the plane (linear axis).

- I and J in the Xp–Yp plane when the linear axis is the X–axis or an axis parallel to the X–axis.
- J and K in the Yp–Zp plane when the linear axis is Y–axis or an axis parallel to the Y–axis.
- K and I in the Zp–Xp plane when the linear axis is the Z–axis or an axis parallel to the Z–axis.

The radius of an arc can be specified also with an R command.

NOTE
The U–, V–, and W–axes (parallel with the basic axis) can be used with G–codes B and C.

- **Movement along axes not in the polar coordinate interpolation plane in the polar coordinate interpolation mode**

The tool moves along such axes normally, independent of polar coordinate interpolation.

- **Current position display in the polar coordinate interpolation mode**

Actual coordinates are displayed. However, the remaining distance to move in a block is displayed based on the coordinates in the polar coordinate interpolation plane (Cartesian coordinates).

Restrictions

- **Coordinate system for the polar coordinate interpolation**

  Before G12.1 is specified, a workpiece coordinate system) where the center of the rotary axis is the origin of the coordinate system must be set. In the G12.1 mode, the coordinate system must not be changed (G92, G52, G53, relative coordinate reset, G54 through G59, etc.).

- **Tool nose radius compensation command**

  The polar coordinate interpolation mode cannot be started or terminated (G12.1 or G13.1) in the tool nose radius compensation mode (G41 or G42). G12.1 or G13.1 must be specified in the tool nose radius compensation canceled mode (G40).

- **Program restart**

  For a block in the G12.1 mode, the program cannot be restarted.

- **Cutting feedrate for the rotation axis**

  Polar coordinate interpolation converts the tool movement for a figure programmed in a Cartesian coordinate system to the tool movement in the rotation axis (C–axis) and the linear axis (X–axis). When the tool moves closer to the center of the workpiece, the C–axis component of the feedrate becomes larger and may exceed the maximum cutting feedrate for the C–axis (set in parameter (No. 1422)), causing an alarm (see the figure below). To prevent the C–axis component from exceeding the maximum cutting feedrate for the C–axis, reduce the feedrate specified with address F or create a program so that the tool (center of the tool when tool nose radius compensation is applied) does not move close to the center of the workpiece.

WARNING



Consider lines L1, L2, and L3. ΔX is the distance the tool moves per time unit at the feedrate specified with address F in the Cartesian coordinate system. As the tool moves from L1 to L2 to L3, the angle at which the tool moves per time unit corresponding to ΔX in the Cartesian coordinate system increases fromθ1 toθ 2 to θ3.
In other words, the C–axis component of the feedrate becomes larger as the tool moves closer to the center of the workpiece. The C component of the feedrate may exceed the maximum cutting feedrate for the C–axis because the tool movement in the Cartesian coordinate system has been converted to the tool movement for the C–axis and the X–axis.

L : Distance (in mm) between the tool center and workpiece center when the tool center is the nearest to the workpiece center
R :Maximum cutting feedrate (deg/min) of the C axis
Then, a speed specifiable with address F in polar coordinate interpolation can be given by the formula below. Specify a speed allowed by the formula. The formula provides a theoretical value; in practice, a value slightly smaller than a theoretical value may need to be used due to a calculation error.

$$F < L \times R \times \frac{\pi}{180} \text{(mm/min)}$$

- **Diameter and radius programming**

  Even when diameter programming is used for the linear axis (X–axis), radius programming is applied to the rotary axis (C–axis).

Examples

Example of Polar Coordinate Interpolation Program Based on X Axis (Linear Axis) and C Axis (Rotary Axis)



X axis is by diameter programming, C axis is by radius programming.

```
O0001 ;
     ¦
N010 T0101
     ¦
N0100 G00 X120.0 C0 Z _ ;          Positioning to start position
N0200 G12.1 ;                      Start of polar coordinate interpolation
N0201 G42 G01 X40.0 F _ ;
N0202 C10.0 ;
N0203 G03 X20.0 C20.0 R10.0 ;
N0204 G01 X–40.0 ;                 Geometry program
N0205 C–10.0 ;                     (program based on cartesian coordinates on
N0206 G03 X–20.0 C–20.0 I10.0 J0 ; X–C' plane)
N0207 G01 X40.0 ;
N0208 C0 ;
N0209 G40 X120.0 ;
N0210 G13.1 ;                      Cancellation of polar coordinate interpolation
N0300 Z __ ;
N0400 X __C __ ;
     ¦
N0900M30 ;
```

4.5 CYLINDRICAL INTERPOLATION (G07.1)

The amount of travel of a rotary axis specified by an angle is once internally converted to a distance of a linear axis along the outer surface so that linear interpolation or circular interpolation can be performed with another axis. After interpolation, such a distance is converted back to the amount of travel of the rotary axis.
The cylindrical interpolation function allows the side of a cylinder to be developed for programming. So programs such as a program for cylindrical cam grooving can be created very easily.

Format

```
G07.1 IP r ; Starts the cylindrical interpolation mode
      :          (enables cylindrical interpolation).
      :
      :
G07.1 IP 0 ; The cylindrical interpolation mode is cancelled.

    IP : An address for the rotation axis
     r : The radius of the cylinder

Specify G07.1 IP r ; and G07.1 IP 0; in separate blocks.
G107 can be used instead of G07.1.
```

Explanations

- **Plane selection (G17, G18, G19)**

Use parameter No. 1002 to specify whether the rotation axis is the X–, Y–, or Z–axis, or an axis parallel to one of these axes. Specify the G code to select a plane for which the rotation axis is the specified linear axis.
For example, when the rotation axis is an axis parallel to the X–axis, G17 must specify an Xp–Yp plane, which is a plane defined by the rotation axis and the Y–axis or an axis parallel to the Y–axis.
Only one rotation axis can be set for cylindrical interpolation.

NOTE
The U–, V–, and W–axes (parallel with the basic axis) can be used with G–codes B and C.

- **Feedrate**

A feedrate specified in the cylindrical interpolation mode is a speed on the developed cylindrical surface.

- **Circular interpolation (G02,G03)**

In the cylindrical interpolation mode, circular interpolation is possible with the rotation axis and another linear axis. Radius R is used in commands in the same way as described in Section 4.4.
The unit for a radius is not degrees but millimeters (for metric input) or inches (for inch input).

< Example Circular interpolation between the Z axis and C axis >

For the C axis of parameter No. 1022, 5 (axis parallel with the X axis) is to be set. In this case, the command for circular interpolation is

```
G18 Z__C__;
G02 (G03) Z__C__R__;
```

For the C axis of parameter No. 1022, 6 (axis parallel with the Y axis) may be specified instead. In this case, however, the command for circular interpolation is

```
G19 C__Z__;
G02 (G03) Z__C__R__;
```

- **Cutter compensation**

To perform cutter compensation in the cylindrical interpolation mode, cancel any ongoing cutter compensation mode before entering the cylindrical interpolation mode. Then, start and terminate cutter compensation within the cylindrical interpolation mode.

- **Cylindrical interpolation accuracy**

In the cylindrical interpolation mode, the amount of travel of a rotary axis specified by an angle is once internally converted to a distance of a linear axis on the outer surface so that linear interpolation or circular interpolation can be performed with another axis. After interpolation, such a distance is converted back to an angle. For this conversion, the amount of travel is rounded to a least input increment.
So when the radius of a cylinder is small, the actual amount of travel can differ from a specified amount of travel. Note, however, that such an error is not accumulative.
If manual operation is performed in the cylindrical interpolation mode with manual absolute on, an error can occur for the reason described above.

$$\text{The actual amount of travel} = \left[\frac{\text{MOTION REV}}{2\times 2\pi R} \left[\times \text{Specified value} \times \frac{2\times 2\pi R}{\text{MOTION REV}} \right] \right]$$

MOTION REV : The amount of travel per rotation of the rotation axis (Setting value of parameter No. 1260)

R : Workpiece radius

$\left[\ \right]$:Rounded to the least input increment

Restrictions

- **Arc radius specification in the cylindrical interpolation mode**

In the cylindrical interpolation mode, an arc radius cannot be specified with word address I, J, or K.

- **Circular interpolation and tool nose radius compensation**

If the cylindrical interpolation mode is started when tool nose radius compensation is already applied, circular interpolation is not correctly performed in the cylindrical interpolation mode.

- **Positioning**

  In the cylindrical interpolation mode, positioning operations (including those that produce rapid traverse cycles such as G28, G80 through G89) cannot be specified. Before positioning can be specified, the cylindrical interpolation mode must be cancelled. Cylindrical interpolation (G07.1) cannot be performed in the positioning mode (G00).

- **Coordinate system setting**

  In the cylindrical interpolation mode, a workpiece coordinate system G50 cannot be specified.

- **Cylindrical interpolation mode setting**

  In the cylindrical interpolation mode, the cylindrical interpolation mode cannot be reset. The cylindrical interpolation mode must be cancelled before the cylindrical interpolation mode can be reset.

- **Canned cycle for drilling during cylindrical interpolation mode**

  Canned cycles for drilling, G81 to G89, cannot be specified during cylindrical interpolation mode.

Examples

Example of a Cylindrical Interpolation Program

```
O0001 (CYLINDRICAL INTERPOLATION );
N01 G00 Z100.0 C0 ;
N02 G01 G18 W0 H0 ;
N03 G07.1 H57299 ;
N04 G01 G42 Z120.0 D01 F250 ;
N05 C30.0 ;
N06 G02 Z90.0 C60.0 R30.0 ;
N07 G01 Z70.0 ;
N08 G03 Z60.0 C70.0 R10.0 ;
N09 G01 C150.0 ;
N10 G03 Z70.0 C190.0 R75.0 ;
N11 G01 Z110.0 C230.0 ;
N12 G02 Z120.0 C270.0 R75.0 ;
N13 G01 C360.0 ;
N14 G40 Z100.0 ;
N15 G07.1 C0 ;
N16 M30 ;
```





4.6 CONSTANT LEAD THREADING (G32)

Tapered screws and scroll threads in addition to equal lead straight threads can be cut by using a G32 command.
The spindle speed is read from the position coder on the spindle in real time and converted to a cutting feedrate for feed–per minute mode, which is used to move the tool.



Fig. 4.6 (a) Straight thread



Fig. 4.6 (b) Tapered screw



Fig. 4.6 (c) Scroll thread

Format

G32IP_F_;

IP_: End point
F_: Lead of the long axis (always radius programming)



Fig. 4.6 (d) Example of thread cutting

Explanations

In general, thread cutting is repeated along the same tool path in rough cutting through finish cutting for a screw. Since thread cutting starts when the position coder mounted on the spindle outputs a 1–turn signal, threading is started at a fixed point and the tool path on the workpiece is unchanged for repeated thread cutting. Note that the spindle speed must remain constant from rough cutting through finish cutting. If not, incorrect thread lead will occur.



Fig. 4.6 (e) LZ and LX of a tapered thread

In general, the lag of the servo system, etc. will produce somewhat incorrect leads at the starting and ending points of a thread cut. To compensate for this, a threading length somewhat longer than required should be specified.
Table 4.6 lists the ranges for specifying the thread lead.

Table. 4.6 Ranges of lead sizes that can be specified

	Least command increment
mm input	0.0001 to 500.0000mm
Inch input	0.000001 inch to 9.999999inch

Explanations

1. Straight thread cutting



The following values are used in programming :
Thread lead :4mm
δ_1=3mm
δ_2=1.5mm
Depth of cut :1mm (cut twice)
(Metric input, Diameter programming)

```
G00   U–62.0 ;
G32   W–74.5 F4.0 ;
G00   U62.0  ;
  W74.5  ;
  U–64.0 ;
  (For the second cut, cut 1mm more)
G32   W–74.5  ;
G00   U64.0  ;
  W74.5  ;
```

2. Tapered thread cutting



The following values are used in programming :
Thread lead : 3.5mm in the direction of the Z axis
δ_1=2mm
δ_2=1mm
Cutting depth in the X axis direction is 1mm
(Cut twice)
(Metric input, Diameter programming)

```
G00   X 12.0 Z72.0 ;
G32   X 41.0 Z29.0 F3.5 ;
G00   X 50.0 ;
  Z 72.0 ;
  X 10.0 ;
  (Cut 1mm more for the second cut)
G32   X 39.0 Z29.0  ;
G00   X 50.0  ;
  Z 72.0  ;
```

WARNING

1 Feedrate override is effective (fixed at 100%) during thread cutting.
2 it is very dangerous to stop feeding the thread cutter without stopping the spindle. This will suddenly increase the cutting depth. Thus, the feed hold function is ineffective while thread cutting. If the feed hold button is pressed during thread cutting, the tool will stop after a block not specifying thread cutting is executed as if the SINGLE BLOCK button were pushed. However, the feed hold lamp (SPL lamp) lights when the FEED HOLD button on the machine control panel is pushed. Then, when the tool stops, the lamp is turned off (Single Block stop status).
3 When the FEED HOLD button is held down, or is pressed again in the first block that does not specify thread cutting immediately after a thread cutting block, the tool stops at the block that does not specify thread cutting.
4 When thread cutting is executed in the single block status, the tool stops after execution of the first block not specifying thread cutting.
5 When the mode was changed from automatic operation to manual operation during thread cutting, the tool stops at the first block not specifying thread cutting as when the feed hold button is pushed as mentioned in Note 3.
However, when the mode is changed from one automatic operation mode to another, the tool stops after execution of the block not specifying thread cutting as for the single block mode in Note 4.
6 When the previous block was a thread cutting block, cutting will start immediately without waiting for detection of the 1–turn signal even if the present block is a thread cutting block.

```
G32Z _ F_ ;
Z _;     (A 1–turn signal is not detected before this block.)
G32 ;   (Regarded as threading block.)
Z_ F_ ; (One turn signal is also not detected.)
```

7 Because the constant surface speed control is effective during scroll thread or tapered screw cutting and the spindle speed changes, the correct thread lead may not be cut. Therefore, do not use the constant surface speed control during thread cutting. Instead, use G97.
8 A movement block preceding the thread cutting block must not specify chamfering or corner R.
9 A thread cutting block must not specifying chamfering or corner R.
10 The spindle speed override function is disabled during thread cutting. The spindle speed is fixed at 100%.
11 Thread cycle retract function is ineffective to G32.

4.7 VARIABLE–LEAD THREAD CUTTING (G34)

Specifying an increment or a decrement value for a lead per screw revolution enables variable–lead thread cutting to be performed.



Fig. 4.7 Variable–lead screw

Format

G34 IP_F_K_;

IP : End point
F : Lead in longitudinal axis direction at the start point
K : Increment and decrement of lead per spindle revolution

Explanations

Address other than K are the same as in straight/taper thread cutting with G32.
Table 4.7 lists a range of values that can be specified as K.

Table 4.7 Range of valid K values

Metric input	±0.0001 to ±500.0000 mm/rev
Inch input	±0.000001 to ±9.999999 inch/rev

P/S alarm (No. 14) is produced, for example, when K such that the value in Table 4.7 is exceeded is directed, the maximum value of lead is exceeded as a result of increase or decrease by K or the lead has a negative value.

WARNING
The “Thread Cutting Cycle Retract” is not effective for G34.

Examples

Lead at the start point: 8.0 mm
Lead increment: 0.3 mm/rev

G34 Z–72.0 F8.0 K0.3 ;

4.8 CONTINUOUS THREAD CUTTING

This function for continuous thread cutting is such that fractional pulses output to a joint between move blocks are overlapped with the next move for pulse processing and output (block overlap) .
Therefore, discontinuous machining sections caused by the interruption of move during continuously block machining are eliminated, thus making it possible to continuously direct the block for thread cutting instructions.

Explanations

Since the system is controlled in such a manner that the synchronism with the spindle does not deviate in the joint between blocks wherever possible, it is possible to performed special thread cutting operation in which the lead and shape change midway.

Fig. 4.8 Continuous thread cutting

Even when the same section is repeated for thread cutting while changing the depth of cut, this system allows a correct machining without impairing the threads.

NOTE
1 Block overlap is effective even for G01 command, producing a more excellent finishing surface.
2 When extreme micro blocks continue, no block overlap may function.

4.9 MULTIPLE–THREAD CUTTING

Using the Q address to specify an angle between the one–spindle–rotation signal and the start of threading shifts the threading start angle, making it possible to produce multiple–thread screws with ease.



Multiple–thread screws.

Format

(constant–lead threading)

G32 IP_ F_ Q_ ;
G32 IP_ Q_ ;

IP_ : End point
F_ : Lead in longitudinal direction
Q_ : Threading start angle

Explanations

- **Available thread cutting commands**

G32: Constant–lead thread cutting
G34: Variable–lead thread cutting
G76: Multiple–thread cutting cycle
G92: Thread cutting cycle

Limitations

- **Start angle**

The start angle is not a continuous–state (modal) value. It must be specified each time it is used. If a value is not specified, 0 is assumed.

- **Start angle increment**

The start angle (Q) increment is 0.001 degrees. Note that no decimal point can be specified.
Example:
For a shift angle of 180 degrees, specify Q180000.
Q180.000 cannot be specified, because it contains a decimal point.

- **Specifiable start angle range**

A start angle (Q) of between 0 and 360000 (in 0.001–degree units) can be specified. If a value greater than 360000 (360 degrees) is specified, it is rounded down to 360000 (360 degrees).

- **Multiple–thread cutting (G76)**

For the G76 multiple–thread cutting command, always use the FS15 tape format.

Examples

Program for producing double–threaded screws (with start angles of 0 and 180 degrees)

```
G00   X40.0 ;
G32   W–38.0 F4.0 Q0 ;
G00   X72.0 ;
  W38.0 ;
  X40.0 ;
G32   W–38.0 F4.0 Q180000
;
G00   X72.0 ;
  W38.0 ;
```

4.10 SKIP FUNCTION (G31)

Linear interpolation can be commanded by specifying axial move following the G31 command, like G01. If an external skip signal is input during the execution of this command, execution of the command is interrupted and the next block is executed.
The skip function is used when the end of machining is not programmed but specified with a signal from the machine, for example, in grinding. It is used also for measuring the dimensions of a workpiece.
For details of how to use this function, refer to the manual supplied by the machine tool builder.

Format

G31 IP_ ;

G31: One–shot G code (If is effective only in the block in which it is specified)

Explanations

The coordinate values when the skip signal is turned on can be used in a custom macro because they are stored in the custom macro system variable #5061 to #5068, as follows:

#5061 X axis coordinate value
#5062 Z axis coordinate value
#5063 3rd axis coordinate value
:
:
#5068 8th axis coordinate value

WARNING

To increase the precision of the tool position when the skip signal is input, feedrate override, dry run, and automatic acceleration/deceleration is disabled for the skip function when the feedrate is specified as a feed per minute value. To enable these functions, set bit 7 (SKF) of parameter No. 6200 to 1. If the feedrate is specified as a feed per rotation value, feedrate override, dry run, and automatic acceleration/deceleration are enabled for the skip function, regardless of the setting of the SKF bit.

NOTE

1 If G31 command is issued while tool nose radius compensation is applied, an P/S alarm of No.035 is displayed. Cancel the cutter compensation with the G40 command before the G31 command is specified.
2 For the high–speed skip option, executing G31 during feed–per–rotation mode causes P/S alarm (No.211) to be generated.

Examples

- **The next block to G31 is an incremental command**



Fig.4.10(a) The next block is an incremental command

- **The next block to G31 is an absolute command for 1 axis**



Fig.4.10(b) The next block is an absolute command for 1 axis

- **The next block to G31 is an absolute command for 2 axes**



Fig 4.10(c) The next block is an absolute command for 2 axes

4.11 MULTISTAGE SKIP

In a block specifying P1 to P4 after G31, the multistage skip function stores coordinates in a custom macro variable when a skip signal (4–point or 8–point ; 8–point when a high–speed skip signal is used) is turned on. Parameters No. 6202 to No. 6205 can be used to select a 4–point or 8–point (when a high–speed skip signal is used) skip signal. One skip signal can be set to match multiple Pn or Qn (n=1,2,3,4) as well as to match a Pn or Qn on a one–to–one basis. Parameters DS1 to DS8 (No. 6206 #0A#7) can be used for dwell.
A skip signal from equipment such as a fixed–dimension size measuring instrument can be used to skip programs being executed.
In plunge grinding, for example, a series of operations from rough machining to spark–out can be performed automatically by applying a skip signal each time rough machining, semi–fine machining, fine–machining, or spark–out operation is completed.

Format

Move command

G31 IP __ F __ P __ ;

IP_ : End point
F_ : Feedrate
P_ : P1–P4

Dwell

G04 X (U, P)__ (Q__) ;

X(U, P)_ : Dwell time
Q_ : Q1 – Q4

Explanations

Multistage skip is caused by specifying P1, P2, P3, or P4 in a G31 block. For an explanation of selecting (P1, P2, P3, or P4), refer to the manual supplied by the machine tool builder.
Specifying Q1, Q2, Q3, or Q4 in G04 (dwell command) enables dwell skip in a similar way to specifying G31. A skip may occur even if Q is not specified. For an explanation of selecting (Q1, Q2, Q3, or Q4), refer to the manual supplied by the machine tool builder.

- **Correspondence to skip signals**

Parameter Nos. 6202 to 6205 can be used to specify whether the 4–point or 8–point skip signal is used (when a high–speed skip signal is used). Specification is not limited to one–to–one correspondence. It is possible to specify that one skip signal correspond to two or more Pn's or Qn's (n=1, 2, 3, 4). Also, bits 0 (DS1) to 7 (DS8) of parameter No. 6206 can be used to specify dwell.

CAUTION
Dwell is not skipped when Qn is not specified and parameters DS1–DS8 (No. 6206#0–#7) are not set.

4.12 TORQUE LIMIT SKIP (G31 P99)

With the motor torque limited (for example, by a torque limit command, issued through the PMC window), a move command following G31 P99 (or G31 P98) can cause the same type of cutting feed as with G01 (linear interpolation).
With the issue of a signal indicating a torque limit has been reached (because of pressure being applied or for some other reason), a skip occurs.
For details of how to use this function, refer to the manuals supplied by the machine tool builder.

Format

G31 P99 IP_ F_ ;

G31 P98 IP_ F_ ;

G31: One–shot G code (G code effective only in the block in which it is issued)

Explanations

- **G31 P99**

If the motor torque limit is reached, or a SKIP signal is received during execution of G31 P99, the current move command is aborted, and the next block is executed.

- **G31 P98**

If the motor torque limit is reached during execution of G31 P98, the current move command is aborted, and the next block is executed. The SKIP signal <X0004#7/Tool post 2 X0013#7> does not affect G31 P98. Entering a SKIP signal during the execution of G31 P98 does not cause a skip.

- **Torque limit command**

If a torque limit is not specified before the execution of G31 P99/98, the move command continues; no skip occurs even if a torque limit is reached.

- **Custom macro system variable**

When G31 P99/98 is specified, the custom macro variables hold the coordinates at the end of a skip. (See Section 4.9.)
If a SKIP signal causes a skip with G31 P99, the custom macro system variables hold the coordinates based on the machine coordinate system when it stops, rather than those when the SKIP signal is entered.

Limitations

- **Axis command**

Only one axis can be controlled in each block with G31 P98/99.
If two or more axes are specified to be controlled in such blocks, or no axis command is issued, P/S alarm No. 015 is generated.

- **Degree of servo error**

When a signal indicating that a torque limit has been reached is input during execution of G31 P99/98, and the degree of servo error exceeds 32767, P/S alarm No. 244 is generated.

- **High–speed skip**

With G31 P99, a SKIP signal can cause a skip, but not a high–speed skip.

- **Simplified synchronization and slanted axis control**

  G31 P99/98 cannot be used for axes subject to simplified synchronization or the X–axis or Z–axis when under slanted axis control.

- **Speed control**

  Bit 7 (SKF) of parameter No. 6200 must be set to disable dry run, override, and auto acceleration or deceleration for G31 skip commands.

- **Consecutive commands**

  Do not use G31 P99/98 in consecutive blocks.

WARNING

Always specify a torque limit before a G31 P99/98 command. Otherwise, G31 P99/98 allows move commands to be executed without causing a skip.

NOTE

If G31 is issued with tool nose radius compensation specified, P/S alarm No. 035 is generated. Therefore, before issuing G31, execute G40 to cancel tool nose radius compensation.

Examples

```
O0001 ;
  :
  :
  M□□ ;          <-- The PMC specifies the torque limit through the window.
  :
  :
  G31 P99 X200. F100 ;   <-- Torque limit skip command
  :
  G01 X100. F500 ;       <-- Move command for which a torque limit is applied
  :
  :
  MΔΔ ;
  :              <-- Torque limit canceled by the PMC
  :
  M30 ;
  :
  %
```

5 FEED FUNCTIONS

5.1 GENERAL

The feed functions control the feedrate of the tool. The following two feed functions are available:

- **Feed functions**

1. Rapid traverse
   When the positioning command (G00) is specified, the tool moves at!a rapid traverse feedrate set in the CNC (parameter No. 1420).
2. Cutting feed
   The tool moves at a programmed cutting feedrate.

- **Override**

Override can be applied to a rapid traverse rate or cutting feedrate using the switch on the machine operator's panel.

- **Automatic acceleration/ deceleration**

To prevent a mechanical shock, acceleration/deceleration is automatically applied when the tool starts and ends its movement (Fig. 5.1 (a)).



Fig. 5.1 (a) Automatic acceleration/deceleration (example)

- **Tool path in a cutting feed**

If the direction of movement changes between specified blocks during cutting feed, a rounded–corner path may result (Fig. 5.1 (b)).



Fig. 5.1 (b) Example of tool path between two blocks

In circular interpolation, a radial error occurs (Fig. 5.1(c)).



Fig. 5.1 (c) Example of radial error in circular interpolation

The rounded–corner path shown in Fig. 5.1(b) and the error shown in Fig. 5.1(c) depend on the feedrate. So, the feedrate needs to be controlled for the tool to move as programmed.

5.2 RAPID TRAVERSE

Format

G00 IP_ ;

G00 : G code (group 01) for positioning (rapid traverse)
IP_ ; Dimension word for the end point

Explanations

The positioning command (G00) positions the tool by rapid traverse. In rapid traverse, the next block is executed after the specified feedrate becomes 0 and the servo motor reaches a certain range set by the machine tool builder (in–position check).
A rapid traverse rate is set for each axis by parameter No. 1420, so no rapid traverse feedrate need be programmed.
The following overrides can be applied to a rapid traverse rate with the switch on the machine operator's panel:F0, 25, 50, 100%
F0: Allows a fixed feedrate to be set for each axis by parameter No. 1421.
For detailed information, refer to the appropriate manual of the machine tool builder.

5.3 CUTTING FEED

Feedrate of linear interpolation (G01), circular interpolation (G02, G03), etc. are commanded with numbers after the F code.
In cutting feed, the next block is executed so that the feedrate change from the previous block is minimized.
Two modes of specification are available:

1. Feed per minute (G98)
   After F, specify the amount of feed of the tool per minute.
2. Feed per revolution (G99)
   After F, specify the amount of feed of the tool per spindle revolution.

Format

Feed per minute
G98 ; G code (group 05) for feed per minute
F_ ; Feedrate command (mm/min or inch/min)

Feed per revolution
G99 ; G code (group 05) for feed per revolution
F_ ; Feedrate command (mm/rev or inch/rev)

Explanations

• Tangential speed constant control

Cutting feed is controlled so that the tangential feedrate is always set at a specified feedrate.



Fig. 5.3 (a) Tangential feedrate (F)

• Feed per minute (G98)

After specifying G98 (in the feed per minute mode), the amount of feed of the tool per minute is to be directly specified by setting a number after F. G98 is a modal code. Once a G98 is specified, it is valid until G99 (feed per revolution) is specified. At power–on, the feed per revolution mode is set.
An override from 0% to 254% (in 1% steps) can be applied to feed per minute with the switch on the machine operator's panel. For detailed information, see the appropriate manual of the machine tool builder.



Fig. 5.3 (b) Feed per minute

WARNING
No override can be used for some commands such as for threading.

- **Feed per revolution (G99)**

After specifying G99 (in the feed per revolution mode), the amount of feed of the tool per spindle revolution is to be directly specified by setting a number after F. G99 is a modal code. Once a G99 is specified, it is valid until G98 (feed per minute) is specified.
An override from 0% to 254% (in 1% steps) can be applied to feed per revolution with the switch on the machine operator's panel. For detailed information, see the appropriate manual of the machine tool builder.

If bit 0 (NPC) of parameter No. 1402 has been set to 1, feed–per–rotation commands can be specified even when a position coder is not being used. (The CNC converts feed–per–rotation commands to feed–per–minute commands.)



Fig. 5.3 (c) Feed per revolution

CAUTION
When the speed of the spindle is low, feedrate fluctuation may occur. The slower the spindle rotates, the more frequently feedrate fluctuation occurs.

- **Cutting feedrate clamp**

A common upper limit can be set on the cutting feedrate along each axis with parameter No. 1422. If an actual cutting feedrate (with an override applied) exceeds a specified upper limit, it is clamped to the upper limit.

NOTE
An upper limit is set in mm/min or inch/min. CNC calculation may involve a feedrate error of ±2% with respect to a specified value. However, this is not true for acceleration/deceleration. To be more specific, this error is calculated with respect to a measurement on the time the tool takes to move 500 mm or more during the steady state:

- **Reference**

See Appendix C for a range of feedrates that can be specified.

5.4 DWELL (G04)

Format

Dwell G04 X_ ; or G04 U_ ; or G04 P_ ;
X_ : Specify a time (decimal point permitted)
U_ : Specify a time (decimal point permitted)
P_ : Specify a time (decimal point not permitted)

Explanations

By specifying a dwell, the execution of the next block is delayed by the specified time.
Bit 1 (DWL) of parameter No. 3405 can specify dwell for each rotation in feed per rotation mode (G99).

Table 5.4 (a)
Command value range of the dwell time (Command by X)

Increment system	Command value range	Dwell time unit
IS–B	0.001 to 99999.999	s or rev
IS–C	0.0001 to 9999.9999	

Table 5.4 (b)
Command value range of the dwell time (Command by P)

Increment system	Command value range	Dwell time unit
IS–B	1 to 99999999	0.001 s or rev
IS–C	1 to 99999999	0.0001 s or rev

6 REFERENCE POSITION

A CNC machine tool has a special position where, generally, the tool is exchanged or the coordinate system is set, as described later. This position is referred to as a reference position.

6.1 REFERENCE POSITION RETURN

- **Reference position**

The reference position is a fixed position on a machine tool to which the tool can easily be moved by the reference position return function.
For example, the reference position is used as a position at which tools are automatically changed. Up to four reference positions can be specified by setting coordinates in the machine coordinate system in parameters (No. 1240 to 1243).



Fig. 6.1 (a) Machine zero point and reference positions

- **Reference position return**

Tools are automatically moved to the reference position via an intermediate position along a specified axis. When reference position return is completed, the lamp for indicating the completion of return goes on.



Fig. 6.2 (b) Reference position return

- **Reference position return check**

The reference position return check (G27) is the function which checks whether the tool has correctly returned to the reference position as specified in the program. If the tool has correctly returned to the reference position along a specified axis, the lamp for the axis goes on.

Format

- **Reference position return**

G28 IP _ ; Reference position return

G30 P2 IP _ ; 2nd reference position return (P2 can be omitted.)

G30 P3 IP _ ; 3rd reference position return

G30 P4 IP _ ; 4th reference position return

IP : Command specifying the intermediate position
(Absolute/incremental command)

- **Reference position return check**

G27 IP _ ;

IP : Command specifying the reference position
(Absolute/incremental command)

Explanations

- **Reference position return (G28)**

Positioning to the intermediate or reference positions are performed at the rapid traverse rate of each axis.
Therefore, for safety, the tool nose radius compensation, and tool offset should be cancelled before executing this command.

- **2nd, 3rd, and 4th reference position return (G30)**

In a system without an absolute–position detector, the first, third, and fourth reference position return functions can be used only after the reference position return (G28) or manual reference position return (see III–3.1) is made. The G30 command is generally used when the automatic tool changer (ATC) position differs from the reference position.

- **Reference position return check (G27)**

G27 command positions the tool at rapid traverse rate. If the tool reaches the reference position, the reference position return lamp lights up.
However, if the position reached by the tool is not the reference position, an alarm (No. 092) is displayed.

Restrictions

- **Status the machine lock being turned on**

The lamp for indicating the completion of return does not go on when the machine lock is turned on, even when the tool has automatically returned to the reference position. In this case, it is not checked whether the tool has returned to the reference position even when a G27 command is specified.

- **First return to the reference position after the power has been turned on (without an absolute position detector)**

When the G28 command is specified when manual return to the reference position has not been performed after the power has been turned on, the movement from the intermediate point is the same as in manual return to the reference position.
In this case, the tool moves in the direction for reference position return specified in parameter ZMIx (bit 5 of No. 1006). Therefore the specified intermediate position must be a position to which reference position return is possible.

- **Reference position return check in an offset mode**

In an offset mode, the position to be reached by the tool with the G27 command is the position obtained by adding the offset value. Therefore, if the position with the offset value added is not the reference position, the lamp does not light up, but an alarm is displayed instead. Usually, cancel offsets before G27 is commanded.

- **Lighting the lamp when the programmed position does not coincide with the reference position**

When the machine tool is an inch system with metric input, the reference position return lamp may also light up even if the programmed position is shifted from the reference position by least input increment. This is because the least input increment of the machine is smaller than its least command increment.

Reference

- **Manual reference position return**

See III–3.1.

7 COORDINATE SYSTEM

By teaching the CNC a desired tool position, the tool can be moved to the position. Such a tool position is represented by coordinates in a coordinate system. Coordinates are specified using program axes.
When two program axes, the X–axis and Z–axis, are used, coordinates are specified as follows:

X_Z_

This command is referred to as a dimension word.



Fig. 7 Tool position specified by XαZβ

Coordinates are specified in one of following three coordinate systems:

(1) Machine coordinate system
(2) Workpiece coordinate system
(3) Local coordinate system

The number of the axes of a coordinate system varies from one machine to another. So, in this manual, a dimension word is represented as **IP_**.

7.1 MACHINE COORDINATE SYSTEM

The point that is specific to a machine and serves as the reference of the machine is referred to as the machine zero point. A machine tool builder sets a machine zero point for each machine.
A coordinate system with a machine zero point set as its origin is referred to as a machine coordinate system.
A machine coordinate system is set by performing manual reference position return after power–on (see III–3.1). A machine coordinate system, once set, remains unchanged until the power is turned off.

Format

```
G53 IP _ ;
    IP _; Absolute dimension word
```

Explanations

- **Selecting a machine coordinate system (G53)**

When a position has been specified as a set of machine coordinates, the tool moves to that position by means of rapid traverse. G53, used for selecting the machine coordinate system, is a one–shot G code. Any commands based on the selected machine coordinate system are thus effective only in the block containing G53. The G53 command must be specified using absolute values. If incremental values are specified, the G53 command is ignored. When the tool is to be moved to a machine–specific position such as a tool change position, program the movement in a machine coordinate system based on G53.

Restrictions

- **Cancel of the compensation function**

When the G53 command is specified, cancel the tool nose radius compensation and tool offset.

- **G53 specification immediately after power–on**

Since the machine coordinate system must be set before the G53 command is specified, at least one manual reference position return or automatic reference position return by the G28 command must be performed after the power is turned on. This is not necessary when an absolute–position detector is attached.

Reference

When manual reference position return is performed after power–on, a machine coordinate system is set so that the reference position is at the coordinate values of (α, β) set using parameter No.1240.



7.2 WORKPIECE COORDINATE SYSTEM

A coordinate system used for machining a workpiece is referred to as a workpiece coordinate system. A workpiece coordinate system is to be set with the NC beforehand (**setting a workpiece coordinate system**).
A machining program sets a workpiece coordinate system (**selecting a workpiece coordinate system**).
A set workpiece coordinate system can be changed by shifting its origin (**changing a workpiece coordinate system**).

7.2.1 Setting a Workpiece Coordinate System

A workpiece coordinate system can be set using one of three methods:

(1) Method using G50

A workpiece coordinate system is set by specifying a value after G50 in the program.

(2) Automatic setting

If bit 0 of parameter No. 1201 is set beforehand, a workpiece coordinate system is automatically set when manual reference position return is performed (see Part III–3.1.).

This function is, however, disabled when the workpiece coordinate system option is being used.

(3) Input using the MDI panel

Six workpiece coordinate systems can be set beforehand using the MDI panel (see Part III–3.1.).
When an absolute command is used, a workpiece coordinate system must be established in any of the ways described above.

Format

- **Setting a workpiece coordinate system by G50**

```
G50 IP_
```

Explanations

A workpiece coordinate system is set so that a point on the tool, such as the tool tip, is at specified coordinates. If IP is an incremental command value, the work coordinate system is defined so that the current tool position coincides with the result of adding the specified incremental value to the coordinates of the previous tool position. If a coordinate system is set using G50 during offset, a coordinate system in which the position before offset matches the position specified in G50 is set.

Examples

Example 1

Setting the coordinate system by the
G50X128.7Z375.1; command (Diameter designation)



Example 2

Base point

Setting the coordinate system by the
G50X1200.0Z700.0; command (Diameter designation)



7.2.2 Selecting a Workpiece Coordinate System

The user can choose from set workpiece coordinate systems as described below. (For information about the methods of setting, see Subsec. II–7.2.1.)

(1) G50 or automatic workpiece coordinate system setting

Once a workpiece coordinate system is selected, absolute commands work with the workpiece coordinate system.

(2) Choosing from six workpiece coordinate systems set using the MDI

By specifying a G code from G54 to G59, one of the workpiece coordinate systems 1 to 6 can be selected.

G54 Workpiece coordinate system 1
G55 Workpiece coordinate system 2
G56 Workpiece coordinate system 3
G57 Workpiece coordinate system 4
G58 Workpiece coordinate system 5
G59 Workpiece coordinate system 6

Workpiece coordinate system 1 to 6 are established after reference position return after the power is turned on. When the power is turned on, G54 coordinate system is selected.

When bit 2 (G50) of parameter No. 1202 is set to 1, executing the G50 command results in the issue of P/S alarm No. 10. This is designed to prevent the user from confusing coordinate systems.

Examples



Fig. 7.2.2

7.2.3 Changing Workpiece Coordinate System

The six workpiece coordinate systems specified with G54 to G59 can be changed by changing an external workpiece zero point offset value or workpiece zero point offset value.
Three methods are available to change an external workpiece zero point offset value or workpiece zero point offset value.

(1) Inputting from the MDI panel (see III–11.4.10)

(2) Programming by G10 or G50

(3) Using the external data input function
An external workpiece origin offset can be changed by using a signal input to the CNC. For details, refer to the relevant manual supplied by the machine tool builder.



Fig. 7.2.3 Changing an external workpiece zero point offset value or workpiece zero point offset value

Format

- **Changing by G10**

G10 L2 Pp IP _;

p=0 : External workpiece zero point offset value

p=1 to 6 : Workpiece zero point offset value correspond to workpiece coordinate system 1 to 6

IP : For an absolute command (G90), workpiece zero point offset for each axis.
For an incremental command (G91), value to be added to the set workpiece zero point offset for each axis (the sum is set as the new offset).

- **Changing by G50**

G50 IP _;

Explanations

- **Changing by G10**

With the G10 command, each workpiece coordinate system can be changed separately.

- **Changing by G50**

By specifying G50IP_;, a workpiece coordinate system (selected with a code from G54 to G59) is shifted to set a new workpiece coordinate system so that the current tool position matches the specified coordinates (IP_).
If IP is an incremental command value, the work coordinate system is defined so that the current tool position coincides with the result of adding the specified incremental value to the coordinates of the previous tool position. (Coordinate system shift)
Then, the amount of coordinate system shift is added to all the workpiece zero point offset values. This means that all the workpiece coordinate systems are shifted by the same amount.

Examples



If G50X100Z100; is commanded when the tool is positioned at (200, 160) in G54 mode, workpiece coordinate system 1 (X' – Z') shifted by vector A is created.

<G54 Workpiece coordinate system>



X' – Z' New workpiece coordinate system
X – Z Original workpiece coordinate system
A : Offset value created by G50
B : Workpiece zero point offset value in G54
C : Workpiece zero point offset value in G55

Suppose that a G54 workpiece coordinate system is specified. Then, a G55 workpiece coordinate system where the black circle on the tool (figure at the left) is at (600.0,12000.0) can be set with the following command if the relative relationship between the G54 workpiece coordinate system and G55 workpiece coordinate system is set correctly:G50X600.0Z1200.0;Also, suppose that pallets are loaded at two different positions. If the relative relationship of the coordinate systems of the pallets at the two positions is correctly set by handling the coordinate systems as the G54 workpiece coordinate system and G55 workpiece coordinate system, a coordinate system shift with G50 in one pallet causes the same coordinate system shift in the other pallet. This means that workpieces on two pallets can be machined with the same program just by specifying G54 or G55.

7.2.4 Workpiece Coordinate System Preset (G92.1)

The workpiece coordinate system preset function presets a workpiece coordinate system shifted by manual intervention to the pre–shift workpiece coordinate system. The latter system is displaced from the machine zero point by a workpiece zero point offset value.
There are two methods for using the workpiece coordinate system preset function. One method uses a programmed command (G92.1). The other uses MDI operations on the absolute position display screen, relative position display screen, and overall position display screen (III – 11.1.4).

Format

G92.1 IP 0 ; (**G50.3 P0 ;** for G code system A)

IP 0 ; Specifies axis addresses subject to the workpiece coordinate system preset operation. Axes that are not specified are not subject to the preset operation.

Explanations

When manual reference position return operation is performed in the reset state, a workpiece coordinate system is shifted by the workpiece zero point offset value from the machine coordinate system zero point. Suppose that the manual reference position return operation is performed when a workpiece coordinate system is selected with G54. In this case, a workpiece coordinate system is automatically set which has its zero point displaced from the machine zero point by the G54 workpiece zero point offset value; the distance from the zero point of the workpiece coordinate system to the reference position represents the current position in the workpiece coordinate system.



If an absolute position detector is provided, the workpiece coordinate system automatically set at power–up has its zero point displaced from the machine zero point by the G54 workpiece zero point offset value. The machine position at the time of power–up is read from the absolute position detector and the current position in the workpiece coordinate system is set by subtracting the G54 workpiece zero point offset value from this machine position. The workpiece coordinate system set by these operations is shifted from the machine coordinate system using the commands and operations listed next page.

(a) Manual intervention performed when the manual absolute signal is off
(b) Move command executed in the machine lock state
(c) Movement by handle interrupt
(d) Operation using the mirror image function
(e) Setting the local coordinate system using G52, or shifting the workpiece coordinate system using G92

In the case of (a) above, the workpiece coordinate system is shifted by the amount of movement during manual intervention.



In the operation above, a workpiece coordinate system once shifted can be preset using G code specification or MDI operation to a workpiece coordinate system displaced by a workpiece zero point offset value from the machine zero point. This is the same as when manual reference position return operation is performed on a workpiece coordinate system that has been shifted. In this example, such G code specification or MDI operation has the effect of returning workpiece coordinate system zero point WZn to the original zero point WZo, and the distance from WZo to Pn is used to represent the current position in the workpiece coordinate system.

Bit 3 (PPD) of parameter No. 3104 specifies whether to preset relative coordinates (RELATIVE) as well as absolute coordinates.

When no workpiece coordinate system option (G54 to G59) is selected, the workpiece coordinate system is preset to the coordinate system set by automatic workpiece coordinate system setting. When automatic workpiece coordinate system setting is not selected, the workpiece coordinate system is preset with its zero point placed at the reference position.

Restrictions

- **Cutter compensation, tool length compensation, tool offset**

  When using the workpiece coordinate system preset function, cancel compensation modes: cutter compensation, tool length compensation, and tool offset. If the function is executed without cancelling these modes, compensation vectors are temporarily cancelled.

- **Program restart**

  The workpiece coordinate system preset function is not executed during program restart.

- **Prohibited modes**

  Do not use the workpiece coordinate system preset function when the scaling, coordinate system rotation, programmable image, or drawing copy mode is set.

7.2.5 Workpiece Coordinate System Shift

When the coordinate system actually set by the G50 command or the automatic system setting deviates from the programmed work system, the set coordinate system can be shifted (see III–3.1).
Set the desired shift amount in the work coordinate system shift memory.

Explanations



Fig. 7.2.5 Workpiece coordinate system shift

See Section 11.4.5 of Part III for how to specify the distance the work coordinate system is shifted.

7.3 LOCAL COORDINATE SYSTEM

When a program is created in a workpiece coordinate system, a child workpiece coordinate system may be set for easier programming. Such a child coordinate system is referred to as a local coordinate system.

Format

G52 IP _; Setting the local coordinate system

.....

G52 IP 0 ; Canceling of the local coordinate system

IP _ : Origin of the local coordinate system

Explanations

By specifying G52IP_;, a local coordinate system can be set in all the workpiece coordinate systems (G54 to G59). The origin of each local coordinate system is set at the position specified by IP_ in the workpiece coordinate system.

Once a local coordinate system is established, the coordinates in the local coordinate system are used in an axis shift command. The local coordinate system can be changed by specifying the G52 command with the zero point of a new local coordinate system in the workpiece coordinate system.

To cancel the local coordinate system and specify the coordinate value in the workpiece coordinate system, match the zero point of the local coordinate system with that of the workpiece coordinate system.



Fig. 7.3 Setting the local coordinate system

WARNING

1 The local coordinate system setting does not change the workpiece and machine coordinate systems.
2 When G50 is used to define a work coordinate system, if coordinates are not specified for all axes of a local coordinate system, the local coordinate system remains unchanged.
  If coordinates are specified for any axis of a local coordinate system, the local coordinate system is canceled.
3 G52 cancels the offset temporarily in tool nose radius compensation.
4 Command a move command immediately after the G52 block in the absolute mode.
5 Whether the local coordinate system is canceled upon reset depends on the specified parameters. The local coordinate system is canceled upon reset when bit 6 (CLR) of parameter No. 3402 or bit 3 (RLC) of parameter No. 1202 is set to 1.
6 Whether manual reference position return cancels the local coordinate system depends on the setting of ZCL (bit 2 of parameter No. 1201).

7.4 PLANE SELECTION

Select the planes for circular interpolation, tool nose radius compensation, coordinate system rotation, and drilling by G–code.
The following table lists G–codes and the planes selected by them.

Explanations

Table 7.4 Plane selected by G code

G code	Selected plane	Xp	Yp	Zp
G17	Xp Yp plane	X–axis or an axis parallel to it	Y–axis or an axis parallel to it	Z–axis or an axis parallel to it
G18	Zp Xp plane			
G19	Yp Zp plane			

Xp, Yp, Zp are determined by the axis address appeared in the block in which G17, G18 or G19 is commanded.
When an axis address is omitted in G17, G18 or G19 block, it is assumed that the addresses of basic three axes are omitted.
Parameter No. 1022 specifies whether each axis is a basic axis (X–axis, Y–axis, or Z–axis) or an axis parallel to a basic axis.
The plane is unchanged in the block in which G17, G18 or G19 is not commanded.
When the power is turned on, G18 (ZX plane) is selected .
The movement instruction is irrelevant to the plane selection.

NOTE
1 U–, V–, and W–axes (parallel to a basic axis) can be used with G–codes B and C.
2 Direct drawing dimension programming, chamfering, corner R, multiple repetitive canned cycle, and simple canned cycle are enabled only for the ZX plane.
Specifying these functions for other planes causes P/S alarm No. 212 to be generated.

Examples

Plane selection when the X–axis is parallel with the U–axis.

```
G17X_Y_;  XY plane,
G17U_Y_;  UY plane
G18X_Z_;  ZX plane
   X_Y_;  Plane is unchanged (ZX plane)
G17 ;     XY plane
G18 ;     ZX plane
G17 U_ ;  UY plane
G18Y_ ;   ZX plane, Y axis moves regardless without any
          relation to the plane.
```

8 COORDINATE VALUE AND DIMENSION

This chapter contains the following topics.

8.1 ABSOLUTE AND INCREMENTAL PROGRAMMING (G90, G91)
8.2 INCH/METRIC CONVERSION (G20, G21)
8.3 DECIMAL POINT PROGRAMMING
8.4 DIAMETER AND RADIUS PROGRAMMING

8.1 ABSOLUTE AND INCREMENTAL PROGRAMMING (G90, G91)

There are two ways to command travels of the tool; the absolute command, and the incremental command. In the absolute command, coordinate value of the end position is programmed; in the incremental command, move distance of the position itself is programmed. G90 and G91 are used to command absolute or incremental command, respectively.
Absolute programming or incremental programming is used depending on the command used. See following tables.

G code system	A	B or C
Command method	Address word	G90, G91

Format

- **G code system A**

	Absolute command	Incremental command
X axis move command	X	U
Z axis move command	Z	W
Y axis move command	Y	V
C axis move command	C	H

- **G code system B or C**

Absolute command **G90 IP_ ;**
Incremental command **G91 IP_ ;**

Examples

- **Tool movement from point P to point Q (diameter programming is used for the X–axis)**

	G code system A	G code system B or C
Absolute command	X400.0 Z50.0 ;	G90 X400.0 Z50.0 ;
Incremental command	U200.0 W–400.0 ;	G91 X200.0 Z–400.0 ;



NOTE
1 Absolute and incremental commands can be used together in a block.
In the above example, the following command can be specified :
X400.0 W–400.0 ;
2 When both X and U or W and Z are used together in a block, the one specified later is effective.
3 Incremental commands cannot be used when names of the axes are A and B during G code system A is selected.

8.2 INCH/METRIC CONVERSION (G20, G21)

Either inch or metric input can be selected by G code.

Format

G20 ;	**Inch input**
G21 ;	**mm input**

This G code must be specified in an independent block before setting the coordinate system at the beginning of the program. After the G code for inch/metric conversion is specified, the unit of input data is switched to the least inch or metric input increment of increment system IS–B or IS–C (Section II–2.3). The unit of data input for degrees remains unchanged. The unit systems for the following values are changed after inch/metric conversion:

– Feedrate commanded by F code
– Positional command
– Work zero point offset value
– Tool compensation value
– Unit of scale for manual pulse generator
– Movement distance in incremental feed
– Some parameters

When the power is turned on, the G code is the same as that held before the power was turned off.

WARNING
1 G20 and G21 must not be switched during a program.
2 When switching inch input (G20) to metric input (G21) and vice versa, the tool compensation value must be re–set according to the least input increment.
However, when bit 0 (OIM) of parameter 5006 is 1, tool compensation values are automatically converted and need not be re–set.

CAUTION
Movement from the intermediate point is the same as that for manual reference position return. The direction in which the tool moves from the intermediate point is the same as the reference position return direction, as specified with bit 5 (ZMI) of parameter No. 1006.

NOTE
1 When the least input increment and the least command increment systems are different, the maximum error is half of the least command increment. This error is not accumulated.
2 The inch and metric input can also be switched using setting of data setting (III–11.4.7).

8.3 DECIMAL POINT PROGRAMMING

Numerical values can be entered with a decimal point. A decimal point can be used when entering a distance, time, or speed. Decimal points can be specified with the following addresses:
X, Y, Z, U, V, W, A, B, C, I, J, K, R, and F.

Explanations

There are two types of decimal point notation: calculator–type notation and standard notation.
When calculator–type decimal notation is used, a value without decimal point is considered to be specified in millimeters. When standard decimal notation is used, such a value is considered to be specified in least input increments. Select either calculator–type or standard decimal notation by using the DPI bit (bit 0 of parameter 3401).Values can be specified both with and without decimal point in a single program.

Examples

Program command	Pocket calculator type decimal point programming	Standard type decimal point programming
X1000 Command value without decimal point	1000mm Unit : mm	1mm Unit : Least input increment (0.001 mm)
X1000.0 Command value with decimal point	1000mm Unit : mm	1000mm Unit : mm

WARNING

In a single block, specify a G code before entering a value. The position of decimal point may depend on the command.

Examples:

G20; Input in inches

X1.0 G04; X1.0 is considered to be a distance and processed as X10000. This command is equivalent to G04 X10000. The tool dwells for 10 seconds.

G04 X1.0; Equivalent to G04 X1000. The tool dwells for one second.

NOTE

1 Fractions less than the least input increment are truncated.

Examples:

X1.23456; Truncated to X1.234 when the least input increment is 0.001 mm.
Processed as X1.2345 when the least input increment is 0.0001 inch.

2 When more than eight digits are specified, an alarm occurs. If a value is entered with a decimal point, the number of digits is also checked after the value is converted to an integer according to the least input increment.

Examples:

X1.23456789; P/S alarm 003 occurs because more than eight digits are specified.

X123456.7; If the least input increment is 0.001 mm, the value is converted to integer 123456700. Because the integer has more than eight digits, an P/S alarm 003 occurs.

8.4 DIAMETER AND RADIUS PROGRAMMING

Since the work cross section is usually circular in CNC lathe control programming, its dimensions can be specified in two ways :

Diameter and Radius

When the diameter is specified, it is called diameter programming and when the radius is specified, it is called radius programming.



Explanations

- **Notes on diameter programming/radius programming for each command**

Radius programming or diameter programming can be specified by parameter DIA (No.1006#3). When using diameter programming, note the conditions listed in the table 8.4.

Table 8.4 Notes on specifying diameter value

Item	Notes
X axis command	Specified with a diameter value
Incremental command	Specified with a diameter value In the above figure, specifies D2 minus D1 for tool path B to A.
Coordinate system setting (G50)	Specifies a coordinate value with a diameter value
Component of tool offset value	Parameter (No.5004#1) determines either diameter or radius value
Parameters in canned cycle, such as cutting depth along X axis. (R)	Specifies a radius value
Radius designation in circular interpolation (R, I, K, and etc.)	Specifies a radius value
Feedrate along axis	Specifies change of radius/rev. or change of radius/min.
Display of axis position	Displayed as diameter value

9 SPINDLE SPEED FUNCTION

The spindle speed can be controlled by specifying a value following address S.
In addition, the spindle can be rotated by a specified angle.
This chapter contains the following topics.

9.1 SPECIFYING THE SPINDLE SPEED WITH A CODE

9.2 SPECIFYING THE SPINDLE SPEED VALUE DIRECTLY (S5–DIGIT COMMAND)

9.3 CONSTANT SURFACE SPEED CONTROL (G96, G97)

9.4 SPINDLE SPEED FLUCTUATION DETECTION FUNCTION (G25, G26)

9.5 SPINDLE POSITIONING FUNCTION

9.1 SPECIFYING THE SPINDLE SPEED WITH A CODE

Specifying a value following address S sends code and strobe signals to the machine. On the machine, the signals are used to control the spindle speed. A block can contain only one S code. Refer to the appropriate manual provided by the machine tool builder for details such as the number of digits in an S code or the execution order when a move command and an S code command are in the same block.

9.2 SPECIFYING THE SPINDLE SPEED VALUE DIRECTLY (S5–DIGIT COMMAND)

The spindle speed can be specified directly by address S followed by a five–digit value (rpm). The unit for specifying the spindle speed may vary depending on the machine tool builder. Refer to the appropriate manual provided by the machine tool builder for details.

9.3 CONSTANT SURFACE SPEED CONTROL (G96, G97)

Specify the surface speed (relative speed between the tool and workpiece) following S. The spindle is rotated so that the surface speed is constant regardless of the position of the tool.

Format

- **Constant surface speed control command**

G96 S○○○○○ ;

↑Surface speed (m/min or feet/min)

Note : This surface speed unit may change according to machine tool builder's specification.

- **Constant surface speed control cancel command**

G97 S○○○○○ ;

↑Spindle speed (rpm)

Note : This surface speed unit may change according to machine tool builder's specification.

- **Clamp of maximum spindle speed**

G50 S_ ; The maximum spindle speed (rpm) follows S.

Explanations

- **Constant surface speed control command (G96)**

G96 (constant surface speed control command) is a modal G code. After a G96 command is specified, the program enters the constant surface speed control mode (G96 mode) and specified S values are assumed as a surface speed. A G96 command must specify the axis along which constant surface speed control is applied. A G97 command cancels the G96 mode.When constant surface speed control is applied, a spindle speed higher than the value specified in G50S_; (maximum spindle speed) is clamped at the maximum spindle speed. When the power is turned on, the maximum spindle speed is not yet set and the speed is not clamped.S (surface speed) commands in the G96 mode are assumed as S = 0 (the surface speed is 0) until M03 (rotating the spindle in the positive direction) or M04 (rotating the spindle in the negative direction) appears in the program.



Fig. 9.3 (a) Relation between workpiece radius, spindle speed and surface speed

- **Setting the workpiece coordinate system for constant surface speed control**

To execute the constant surface speed control, it is necessary to set the work coordinate system , Z axis, (axis to which the constant surface speed control applies) becomes zero.



Fig. 9.3 (b) Example of the workpiece coordinate system for constant surface speed control

- **Surface speed specified in the G96 mode**



Restrictions

- **Constant surface speed control for threading**

The constant surface speed control is also effective during threading. Accordingly, it is recommended that the constant surface speed control be invalidated with G97 command before starting the scroll threading and taper threading, because the response problem in the servo system may not be considered when the spindle speed changes.

- **Constant surface speed control for rapid traverse (G00)**

In a rapid traverse block specified by G00, the constant surface speed control is not made by calculating the surface speed to a transient change of the tool position, but is made by calculating the surface speed based on the position at the end point of the rapid traverse block, on the condition that cutting is not executed at rapid traverse.



Example

```
N8  G00 X1000.0Z1400.0 ;
N9  T33;
N11 X400.0Z1050.0;
N12 G50S3000 ; (Designation of max. spindle speed)
N13 G96S200 ; (Surface speed 200m/min)
N14 G01 Z 700.0F1000 ;
N15 X600.0Z 400.0;
N16 Z … ;
```

The CNC calculates the spindle speed which is proportional to the specified surface speed at the position of the programmed coordinate value on the X axis. This is not the value calculated according to the X axis coordinate after offset when offset is valid. At the end point N15 in the example above, the speed at 600 dia. (Which is not the turret center but the tool nose) is 200 m/min. If X axis coordinate value is negative, the CNC uses the absolute value.

9.4 SPINDLE SPEED FLUCTUATION DETECTION FUNCTION (G25, G26)

With this function, an overheat alarm (No. 704) is raised when the spindle speed deviates from the specified speed due to machine conditions.
This function is useful, for example, for preventing the seizure of the guide bushing.

Format

G26 enables spindle speed fluctuation detection.
G25 disables spindle speed fluctuation detection.

G26 Pp Qq Rr ;	**Spindle fluctuation detection on**
G25 ;	**Spindle fluctuation detection off**

p : Time (in ms) from the issue of a new spindle rotation command (S command) to the start of checking whether the actual spindle speed is so fast that an overheat can occur.
When a specified speed is reached within the time period of P, spindle speed is checked at that time.

q : Tolerance (%) of a specified spindle speed

$$q = \frac{1\text{–}actual\ spindle\ speed}{specified\ spindle\ speed} \times 100$$

If a specified spindle speed lies within this range, it is regarded as having reached the specified value. Then, an actual spindle speed is checked.

r : Spindle speed fluctuation (%) at which the actual spindle speed is so fast that an overheat can occur

$$r = \frac{1\text{–}speed\ that\ can\ cause\ overheat}{specified\ spindle\ speed} \times 100$$

G26 enables the spindle speed fluctuation detection function, and G25 disables the spindle speed fluctuation detection.
Even if G25 is specified, p, q, and r are not cleared.

Explanations

The fluctuation of the spindle speed is detected as follows:

1. When an alarm is issued after a specified spindle speed is reached



2. When an alarm is issued before a specified spindle speed is reached



Specified speed :
(Speed specified by address S and five–digit value) × (spindle override)

Actual speed : Speed detected with a position coder

p : Time elapses since the specified speed changes until a check starts.

q : (Percentage tolerance for a check to start) × (specified speed)

r : (Percentage fluctuation detected as an alarm condition) × (specified speed)

d : Fluctuation detected as an alarm (specified in parameter 4913)

An alarm is issued when the difference between the specified speed and the actual speed exceeds both r and d.

NOTE

1 When an alarm is issued in automatic operation, a single block stop occurs. The spindle overheat alarm is indicated on the CRT screen, and the alarm signal “SPAL” is output (set to 1 for the presence of an alarm). This signal is cleared by resetting.
2 Even when reset operation is performed after an alarm occurs, the alarm is issued again unless the cause of the alarm is corrected.
3 No check is made during spindle stop state (*SSTP = 0).
4 By setting the parameter (No. 4913), an allowable range of speed fluctuations can be set which suppresses the occurrence of an alarm. However, an alarm is issued one second later if the actual speed is found to be 0 rpm.
5 The values of p, q, and r specified in the G26 block are set in the following parameters. If the specification of p, q, or r is omitted, the value set in the corresponding parameter is referenced.
   p : Parameter No. 4914
   q : Parameter No. 4911
   r : Parameter No. 4912
6 Bit 0 (FLR) of parameter No. 4900 can be used to specify 0.1% as the units of the specified q and r values.

9.5 SPINDLE POSITIONING FUNCTION

In turning, the spindle connected to the spindle motor is rotated at a certain speed to rotate the workpiece mounted on the spindle. The spindle positioning function turns the spindle connected to the spindle motor by a certain angle to position the workpiece mounted on the spindle at a certain angle. The spindle is positioned about the C–axis.
The spindle positioning function involves the following three operations:

1. Canceling the spindle rotation mode and entering the spindle positioning mode (spindle orientation)
2. Positioning the spindle in the spindle positioning mode
3. Canceling the spindle positioning mode, and entering the spindle rotation mode

9.5.1 Spindle Orientation

When spindle positioning is first performed after the spindle motor is used for normal spindle operation, or when spindle positioning is interrupted, the spindle orientation is required.
Orientation permits the spindle to stop at a predetermined position.
Orientation is directed by the M code set in parameter No. 4960. The direction of orientation can be set with a parameter. For the analog spindle, the direction is set in ZMIx (bit 5 of parameter 1006).
For the serial spindle, it is set in RETRN (bit 5 of parameter 4005).

9.5.2 Spindle Positioning

The spindle can be positioned with an arbitrary angle or semi–fixed angle.

- **Positioning with a semi–fixed angle specified by an M code**

Address M is followed by a 2–digit numeric. The specifiable value may be one of the six values from Mα to M(α+5). Value α must be set in parameter No. 4962 beforehand. The positioning angles corresponding to Mα to M(α+5) are listed below. Value β must be set in parameter No. 4963 beforehand.

M–code	Positioning angle	(Ex.)β=30°
Mα	β	30°
M(α+1)	2β	60°
M(α+2)	3β	90°
M(α+3)	4β	120°
M(α+4)	5β	150°
M(α+5)	6β	180°

Specify the command with incremental values. The direction of rotation can be specified in parameter IDM (bit 1 of parameter 4950).

- **Positioning with a given angle specified by address C or H**

Specify the position using address C or H followed by a signed numeric value or numeric values. Addresses C and H must be specified in the G00 mode.
(Example) C–1000
H4500
The end point must be specified with a distance from the program reference position (in absolute mode) using address C. Alternatively, the end point must also be specified with a distance from the start point to the end point (in incremental mode) using address H.
A numeric with the decimal point can be entered.
The value must be specified in degrees.
(Example) C35.0=C35 degrees

- **Program reference position**

The position to which the spindle is oriented is assumed as the program reference position. The program reference position can be changed by setting of a coordinate system (G50) or automatic setting of a coordinate system (#OZPR of parameter 1202).

- **Feedrate for positioning**



Command format		G code A		G code B and C	
		Address used	Command A–B in the above figure	Address used and G code	Command A–B in the above figure
Absolute command	Specify the end point with a distance from the program reference position.	C	C180.0 ;	G90,C	G90C180.0;
Incremental command	Specify a distance from the start point to the end point.	H	H90.0 ;	G91,C	G90C90.0 ;

- **Feedrate during positioning**

The feedrate during positioning equals the rapid traverse speed specified in parameter No. 1420. Linear acceleration/deceleration is performed. For the specified speed, an override of 100%, 50%, 25%, and F0 (parameter No. 1421) can be applied.

- **Speed during orientation**

The tool moves at the rapid traverse speed set in parameter No.1420 until a sufficient speed for orientation is attained. After the speed for orientation has been attained, orientation is performed at the speed set in parameter No.1425.

9.5.3 Canceling Spindle Positioning

When modes are to be switched from spindle positioning to normal spindle rotation, the M code set in parameter No. 4961 is specified.

WARNING
1 Feed hold, dry run, machine lock, and auxiliary function lock cannot be performed during spindle positioning.
2 Parameter No. 4962 must always be set even when positioning with a semi–fixed angle specified in an M–code is not performed. If the parameter is not set, M–codes from the M00 to M05 do not function properly.

NOTE
1 Specify spindle positioning alone in a block. A move command for the X or Z axis cannot be specified within the same block.
2 When emergency stop is applied during spindle positioning, spindle positioning stops. To resume it, restart with the orientation step.
3 The serial spindle Cs–axis contour control function and the spindle positioning function cannot be used at a time. If both options are specified, the spindle positioning function has priority.
4 The spindle positioning axis is indicated in pulses in the machine coordinate system.

10 TOOL FUNCTION (T FUNCTION)

Two tool functions are available. One is the tool selection function, and the other is the tool life management function.

10.1 TOOL SELECTION

By specifying a 2–digit/4–digit numerical value following address T, a code signal and a strobe signal are transmitted to the machine tool. This is mainly used to select tools on the machine.
One T code can be commanded in a block. Refer to the machine tool builder's manual for the number of digits commandable with address T and the correspondence between the T codes and machine operations.
When a move command and a T code are specified in the same block, the commands are executed in one of the following two ways:

1. Simultaneous execution of the move command and T function commands.
2. Executing T function commands upon completion of move command execution.

The selection of either sequence depends on the machine tool builder's specifications. Refer to the machine tool builder's manual for details.

1.Last one digit of T–code designates the offset number.



2.Last two digits of T–code designate the offset number.

Explanations

The value after the T code indicates the desired tool. Part of the values is also used as the offset number indicating the compensation amount for tool offset.
Refer to the machine tool builder's manual for correspondence between the T–code and the tool and the number of digit to specify tool selection.
Example(T2+2)
N1G00X1000Z1400
N2T0313; (Select Tool No. 3 and Offset value No.13)
N3X400Z1050;
Some machines use a 1–digit value to specify tool selection.

10.2 TOOL LIFE MANAGEMENT

Tools are classified into some groups. For each group, a tool life (time or frequency of use) is specified. Each time a tool is used, the time for which the tool is used is accumulated. When the tool life has been reached, the next tool previously determined in the same group is used. This function is called the tool life management function.
With 2–path control, tool life management is performed for each tool post separately. So tool life management data is also set for each tool post.

10.2.1 Program of Tool Life Data

Format

Tools used sequentially in each group and their tool life are registered in the CNC as following program format of table 10.2.1(a).

Table10.2.1(a) Program format of life management

Tape format	Meaning
O_ _ _ _ ; G10L3; P_ _ _ L_ _ _ _ ; T_ _ _ _ ; T_ _ _ _ ; ⋮ P_ _ _ L_ _ _ _ ; T_ _ _ _ ; T_ _ _ _ ; ⋮ G11; M02(M30);	Program number Start of setting tool life data P___ :Group number (1 to 128) L___ :Tool life (1 to 9999) (1) (2) T:____ Tool number Tools are selected from (n) (1)to (2) to ... to (n). Data for the next group End of setting tool life data End of program

For the method of registering tool life data in CNC, refer to Subsec. III–11.4.14.

Explanations

- **Specification by duration or number of times the tool has been used**

A tool life is specified either as the time of use (in minutes) or the frequency of use, which depends on the parameter setting parameter No. 6800#2(LTM) .
Up to 4300 minutes in time or 9999 times in frequency can be specified for a tool life.

- **Maximum number of groups and tools**

The number of groups to be registered and the number of tools registered per group can be combined in three ways. One of the three combinations is set by a parameter No.6800#0,#1(Each GS1 and GS2).

Table 10.2.1(b) The max. number of groups and tools that can be registered

GS2 (No.6800#1)	GS1 (No.6800#0)	The Max. number of groups and tools without optional function of 128 tool pairs	
		Number of group	Number of tool
0	0	16	16
0	1	32	8
1	0	64	4
1	1	16	16

In each of the cases listed above, the maximum number of tools which can be registered is 512 or 256 depending, respectively, on whether the option for 128 tool life control groups is used or not. When the option is not used, set the parameters as follows: For up to 16 groups, with up to 16 tools in each group, set GS1 = 0 and GS2 = 0. For up to 32 groups, with up to 8 tools in each group, set GS1 = 0 and GS2 = 1. To change the combination, change the parameter, then set program is executed with the old tool group combination set in the NC. Whenever the parameter is changed, be sure to reexecute the group setting program.

- **A T code for registering tools**

The same tool number may appear anywhere any times in the program of tool life data.
A T code for registering tools can usually consist of up to four digits. When the option for 128 tool life control groups is used, however, it can consist of up to six digits.



When using the tool life control function, do not use tool position offset parameters LD1 and LGN (bits 0 and 1 of parameter No. 5002).

Example



Explanations

The group numbers specified in P need not be serial. They need not be assigned to all groups, either. When using two or more offset numbers for the same tool in the same process, set as follows;

Tape format	Meaning
P004L0500; T0101; T0105; T0108; T0206; T0203; T0202; T0209; T0304; T0309; P005L1200; T0405;	The tools in group 4 are used from (1) to (2) to (3). (1) Each tool is used 500 times (or for 500 minutes). (2) When this group is specified three times in one process, the offset numbers are selected in the following orders: Tools (1): 01→05→08 (3) Tools (2): 06→03→02→09 Tools (3): 04→09

10.2.2 Counting a Tool Life

Explanation

- **When a tool life is specified as the time of use (in minutes)**

Between TΔΔ99(ΔΔ=Tool group number)and TΔΔ88 in a machining program, the time for which the tool is used in the cutting mode is counted at intervals of 4 seconds. The time taken for single–block stoppage, feed hold, rapid traverse, dwelling, and FIN wait is ignored.
Up to 4300 minutes can be specified for a life.

- **When a tool life is specified as the frequency of use**

Counting is performed for each process that is initiated by the cycle start of a machining program and ended when the NC is reset by the M02 or M03 command. The counters for tool groups used in a process are incremented by one. Even when the same group is specified more than once in one process, the counter is incremented only by one. Up to 9999 can be set for a tool life.
Counting of a tool life is performed for each group. The life counter contents are not erased even when the power of CNC is cut off.
When a life is specified as the frequency of use, apply an external reset (ERS) signal to the CNC when M02 or M30 is executed.

10.2.3 Specifying a Tool Group in a Machining Program

In machining programs, T codes are used to specify tool groups as follows:

Tape format	Meaning
⋮	
T△△99;	Ends the tool used by now, and starts to use the tool of the △△group. ”99” distinguishes this specification from ordinary specification.
⋮	
T△△88;	Cancels the offset of the tool of the group. ”88” distin–guishes this specification from ordinary specification.
⋮	
M02(M300);	Ends the machining program.

Explanations

Tape format	Meaning
T0199;	Ends the previous tool, and starts to use the tool of the 01 group.
⋮	
T0188;	Cancels the offset of the tool of the 01 group.
⋮	
T0508;	Ends the tool of the 01 group. Selects tool number 05 and offset number 08.
⋮	
T0500;	Cancels the offset of tool number 05.
⋮	
T0299;	Ends tool number 05, and starts to use the tool of the 02 group.
⋮	
T0199;	Ends the tool of the 02 group, and starts to use the tool of the 01 group. If more than one offset number is specified for the tool, the second offset number is selected. Otherwise, the previous offset number is used.
⋮	

11 AUXILIARY FUNCTION

There are two types of auxiliary functions ; miscellaneous function (M code) for specifying spindle start, spindle stop program end, and so on, and secondary auxiliary function (B code) .
When a move command and miscellaneous function are specified in the same block, the commands are executed in one of the following two ways:

i) Simultaneous execution of the move command and miscellaneous function commands.

ii) Executing miscellaneous function commands upon completion of move command execution.

The selection of either sequence depends on the machine tool builder's specification. Refer to the manual issued by the machine tool builder for details.

11.1 AUXILIARY FUNCTION (M FUNCTION)

When address M followed by a number is specified, a code signal and strobe signal are transmitted. These signals are used for turning on/off the power to the machine.
In general, only one M code is valid in a block but up to three M codes can be specified in a block (although some machines may not allow that). The correspondence between M codes and functions is up to the machine tool builder.
All M codes are processed in the machine except for M98, M99,M198, M codes for calling a subprogram (parameters Nos. 6071 to 6079), and M codes for calling a custom macro (parameters Nos. 6080 to 6089). Refer to the appropriate manual issued by the machine tool builder.

Explanations

The following M codes have special meanings.

- **M02,M03 (End of program)**

This indicates the end of the main program
Automatic operation is stopped and the CNC unit is reset. This differs with the machine tool builder. After a block specifying the end of the program is executed,control returns to the start of the program. Bit 5 of parameter No.3404 (M02) or bit 4 of parameter No.3404 (M03)can be used to disable M02 or M03 from returning control to the start of the program.

- **M00 (Program stop)**

Automatic operation is stopped after a block containing M00 is executed. When the program is stopped, all existing modal information remains unchanged. The automatic operation can be restarted by actuating the cycle operation. This differs with the machine tool builder.

- **M01 (Optional stop)**

Similarly to M00, automatic operation is stopped after a block containing M01 is executed. This code is only effective when the Optional Stop switch on the machine operator's panel has been pressed.

- **M98 (Calling of subprogram)**

This code is used to call a subprogram. The code and strobe signals are not sent. See the subprogram section II–13.3 for details .

- **M99 (End of subprogram)**

This code indicates the end of a subprogram.
M99 execution returns control to the main program. No code or strobe signal is sent. See the subprogram section II–13.3 for details.

- **M198 (Calling a subprogram)**

This code is used to call a subprogram of a file in the external input/output function. See the description of the subprogram call function (III–4.5) for details.

NOTE
A block immediately after an M00, M01, M02, or M03 block is not buffered. Similarly, ten M codes which do not buffer can be set by parameters (Nos. 3411 to 3421). Refer to the machine tool builder's instruction manual for these M codes.

11.2 MULTIPLE M COMMANDS IN A SINGLE BLOCK

So far, one block has been able to contain only one M code. Up to three M codes can be specified in a single block when bit 7 (M3B) of parameter No. 3404 is set to 1.
Up to three M codes specified in a block are simultaneously output to the machine. This means that compared with the conventional method of a single M command in a single block, a shorter cycle time can be realized in machining.

Explanations

CNC allows up to three M codes to be specified in one block. However, some M codes cannot be specified at the same time due to mechanical operation restrictions. For detailed information about the mechanical operation restrictions on simultaneous specification of multiple M codes in one block, refer to the manual of each machine tool builder.
M00, M01, M02, M30, M98, M99, or M198 must not be specified together with another M code.
Some M codes other than M00, M01, M02, M30, M98, M99, and M198 cannot be specified together with other M codes; each of those M codes must be specified in a single block.
Such M codes include these which direct the CNC to perform internal operations in addition to sending the M codes themselves to the machine. To be specified, such M codes are M codes for calling program numbers 9001 to 9009 and M codes for disabling advance reading (buffering) of subsequent blocks. Meanwhile, multiple of M codes that direct the CNC only to send the M codes themselves (without performing internal operations) can be specified in a single block.

Examples

One M command in a single block	Multiple M commands in a single block
M40 ; M50 ; M60 ; G28G91X0Z0 ; : : :	M40M50M60 ; G28G91X0Z0 ; : : : : :

11.3 THE SECOND AUXILIARY FUNCTIONS (B CODES)

Indexing of the table is performed by address B and a following 8–digit number. The relationship between B codes and the corresponding indexing differs between machine tool builders.
Refer to the manual issued by the machine tool builder for details.

Explanations

- **Command range**

0 to 99999999

- **Command method**

1. The decimal point can be used for input.
   Command Output value
   B10. 10000
   B10 10
2. It is possible to change over the scale factor of B output, 1000 or 1 when the decimal point input is omitted, using the parameter DPI (No.3401#0).
   Command Output value
   When DPI is 1: B1 1000
   When DPI is 0: B1 1
3. It is possible to change over the scale factor of B output 1000 or 10000 when the decimal point input is omitted in the inch input system, using the parameter AUX (No.3405#0) When DPI=1.
   Command Output value
   When AUX is 1: B1 10000
   When AUX is 0: B1 1000

Restrictions

When this functions is used, the B address specifying an axis movement disabled.

12 PROGRAM CONFIGURATION

General

● Main program and subprogram

There are two program types, main program and subprogram. Normally, the CNC operates according to the main program. However, when a command calling a subprogram is encountered in the main program, control is passed to the subprogram. When a command specifying a return to the main program is encountered in a subprogram, control is returned to the main program.



Fig. 12(a) Main program and subprogram

The CNC memory can hold up to 400 main programs and subprograms (63 as standard). A main program can be selected from the stored main programs to operate the machine. See Chapter III–10 for the methods of registering and selecting programs.

● Program components

A program consists of the following components:

Table 12 Program components

Components	Descriptions
Tape start	Symbol indicating the start of a program file
Leader section	Used for the title of a program file, etc.
Program start	Symbol indicating the start of a program
Program section	Commands for machining
Comment section	Comments or directions for the operator
Tape end	Symbol indicating the end of a program file



Fig. 12(b) Program configuration (Example of using ISO code)

● Program section configuration

A program section consists of several blocks. A program section starts with a program number and ends with a program end code.

Program section configuration	**Program section (Example of using ISO code)**
Program number	O0001 ;
Block 1	N1 G91 G00 X120.0 Y80.0 ;
Block 2	N2 G43 Z–32.0 H01 ;
:	:
Block n	Nn Z0 ;
Program end	M30 ;

A block contains information necessary for machining, such as a move command or coolant on/off command.Specifying a value following a slash (/) at the start of a block disables the execution of some blocks (see “optional block skip” in Section II–12.2).

12.1 PROGRAM COMPONENTS OTHER THAN PROGRAM SECTIONS

This section describes program components other than program sections. See Section II–12.2 for a program section.



Fig. 12.1 Program configuration (Example of using ISO code)

Explanations

- **Tape start**

The tape start indicates the start of a file that contains CNC programs. The mark is not required when programs are entered using SYSTEM P or ordinary personal computers. The mark is not displayed on the display screen. However, if the file is output,the mark is automatically output at the start of the file.

Table 12.1(a) Code of a tape start

Name	ISO code	EIA code	Notation in this manual
Tape start	%	ER	%

- **Leader section**

Data entered before the programs in a file constitutes a leader section. When machining is started, the label skip state is usually set by turning on the power or resetting the system. In the label skip state, all information is ignored until the first end–of–block code is read. When a file is read into the CNC unit from an I/O device, leader sections are skipped by the label skip function.
A leader section generally contains information such as a file header. When a leader section is skipped, even a TV parity check is not made. So a leader section can contain any codes except the EOB code.

- **Program start**

The program start code is to be entered immediately after a leader section, that is, immediately before a program section. This code indicates the start of a program, and is always required to disable the label skip function. With SYSTEM P or ordinary personal computers, this code can be entered by pressing the return key.

Table 12.1(b) Code of a program start

Name	ISO code	EIA code	Notation in this manual
Program start	LF	CR	;

NOTE
If one file contains multiple programs, the EOB code for label skip operation must not appear before a second or subsequent program number. However, an program start is required at the start of a program if the preceding program ends with %.

- **Comment section**

Any information enclosed by the control–out and control–in codes is regarded as a comment and skipped by the CNC. The user can enter a header, comments, directions to the operator, etc. There is no limit on the length of a comment section.

Table 12.1(c) Codes of a control–in and a control–out

Name	ISO code	EIA code	Notation in this manual	Meaning
Control–out	(	2–4–5	(	Start of comment section
Control–in	)	2–4–7	)	End of comment section

When a program is read into memory for memory operation, comment sections, if any, are not ignored but are also read into memory. Note, however, that codes other than those listed in the code table in Appendix F are ignored, and thus are not read into memory. When the program in this memory is output to an external input/output device (see Section III–8), any comments are also output.
When a program is displayed on the screen, its comment sections are also displayed. However, those codes that were ignored when read into memory are not outputted or displayed.
During memory operation or DNC operation, all comment sections are ignored.
The TV check function can be used for a comment section by setting parameter CTV (bit 1 of No. 0100).

CAUTION
If a long comment section appears in the middle of a program section, a move along an axis may be suspended for a long time because of such a comment section. So a comment section should be placed where movement suspension may occur or no movement is involved.

NOTE
1 If only a control–in code is read with no matching control–out code, the read control–in code is ignored.
2 The EOB code cannot be used in a comment.

● Tape end

A tape end is to be placed at the end of a file containing NC programs. If programs are entered using the automatic programming system, the mark need not be entered. The mark is not displayed on the CRT display screen. However, when a file is output, the mark is automatically output at the end of the file.
If an attempt is made to execute % when M02 or M03 is not placed at the end of the program, the P/S alarm (No. 5010) is occurred.

Table 12.1(d) Code of a tape end

Name	ISO code	EIA code	Notation in this manual
Tape end	%	ER	%

12.2 PROGRAM SECTION CONFIGURATION

This section describes elements of a program section. See Section II–12.1 for program components other than program sections.



Fig. 12.2 (a) Program configuration

- **Program number**

A program number consisting of address O followed by a four–digit number is assigned to each program at the beginning registered in memory to identify the program.
When the 8–digit program number option is used, however, specify eight digits for the program number (see Section II.12.4).
In ISO code, the colon (:) can be used instead of O.
When no program number is specified at the start of a program, the sequence number (N....) at the start of the program is regarded as its program number. If a five–digit sequence number is used, the lower four digits are registered as a program number. If the lower four digits are all 0, the program number registered immediately before added to 1 is registered as a program number. Note, however, that N0 cannot be used for a program number.
If there is no program number or sequence number at the start of a program, a program number must be specified using the MDI panel when the program is stored in memory (See Section 8.4 or 10.1 in Part III.).

NOTE
Program numbers 8000 to 9999 may be used by machine tool builders, and the user may not be able to use these numbers.

● Sequence number and block

A program consists of several commands. One command unit is called a block. One block is separated from another with an EOB of end of block code.

Table 12.2(a) EOB code

Name	ISO code	EIA code	Notation in this manual
End of block (EOB)	LF	CR	;

At the head of a block, a sequence number consisting of address N followed by a number not longer than five digits (1 to 99999) can be placed. Sequence numbers can be specified in a random order, and any numbers can be skipped. Sequence numbers may be specified for all blocks or only for desired blocks of the program. In general, however, it is convenient to assign sequence numbers in ascending order in phase with the machining steps (for example, when a new tool is used by tool replacement, and machining proceeds to a new surface with table indexing.)

N300 X200.0 Z300.0 ; A sequence number is underlined.

Fig. 12.2(b) Sequence number and block (example)

NOTE
N0 must not be used for the reason of file compatibility with other CNC systems.
Program number 0 cannot be used. So 0 must not be used for a sequence number regarded as a program number.

● TV check (Vertical parity check along tape)

A parity check is made for a block on input tape vertically. If the number of characters in one block (starting with the code immediately after an EOB and ending with the next EOB) is odd, an P/S alarm (No.002) is output. No TV check is made only for those parts that are skipped by the label skip function. Bit 1 (CTV) of parameter No. 0100 can be used to specify whether the characters constituting comments, enclosed in "(" and ")", are counted when obtaining the number of characters for TV check. The TV check function can be enabled or disabled by setting on the MDI unit (See subsec. 11.4.7 in Part III.).

- **Block configuration (word and address)**

A block consists of one or more words. A word consists of an address followed by a number some digits long. (The plus sign (+) or minus sign (–) may be prefixed to a number.)

Word = Address + number (Example : X–1000)

For an address, one of the letters (A to Z) is used ; an address defines the meaning of a number that follows the address. Table 12.2 (b) indicates the usable addresses and their meanings.

The same address may have different meanings, depending on the preparatory function specification.

Table 12.2(b) Major functions and addresses

Function	Address	Meaning
Program number	O (1)	Program number
Sequence number	N	Sequence number
Preparatory function	G	Specifies a motion mode (linear, arc, etc.)
Dimension word	X, Y, Z, U, V, W, A, B, C	Coordinate axis move command
	I, J, K	Coordinate of the arc center
	R	Arc radius
Feed function	F	Rate of feed per minute, Rate of feed per revolution
Spindle speed function	S	Spindle speed
Tool function	T	Tool number
Auxiliary function	M	On/off control on the machine tool
	B	Table indexing, etc.
Dwell	P, X, U	Dwell time
Program number designation	P	Subprogram number
Number of repetitions	P	Number of subprogram repetitions
Parameter	P, Q	Canned cycle parameter

NOTE
In ISO code, the colon (:) can also be used as the address of a program number.



Fig. 12.2 (c) 1 block (example)

- **Major addresses and ranges of command values**

Major addresses and the ranges of values specified for the addresses are shown below. Note that these figures represent limits on the CNC side, which are totally different from limits on the machine tool side. For example, the CNC allows a tool to traverse up to about 100 m (in millimeter input) along the X axis.
However, an actual stroke along the X axis may be limited to 2 m for a specific machine tool.
Similarly, the CNC may be able to control a cutting federate of up to 240 m/min, but the machine tool may not allow more than 3 m/min. When developing a program, the user should carefully read the manuals of the machine tool as well as this manual to be familiar with the restrictions on programming.

Table 12.2(c) Major addresses and ranges of command values

Function		Address	Input in mm	Input in inch
Program number		O (1)	1–9999	1–9999
Sequence number		N	1–99999	1–99999
Preparatory function		G	0–99	0–99
Dimension word	Increment system IS–B	X, Y, Z, U, V, W, A, B, C, I, J, K, R,	–99999.999 to +99999.999	–9999.9999 to +9999.9999
	Increment system IS–C		–9999.9999 to +9999.9999	–999.99999 to +999.99999
Feed per minute	Increment system IS–B	F	1 to 240000 mm/min	0.01 to 9600.00 inch/min
	Increment system IS–C		1 to 100000 mm/min	0.01 to 4000.00 inch/min
Feed per revolution		F	0.01 to 500.00 mm/rev	0.0001 to 9.9999 inch/rev
Spindle speed function		S	0 to 20000	0 to 20000
Tool function		T	0 to 99999999	0 to 99999999
Auxiliary function		M	0 to 99999999	0 to 99999999
		B	0 to 99999999	0 to 99999999
Dwell	Increment system IS–B	P, X, U	0 to 99999.999s	0 to 99999.999s
	Increment system IS–C		0 to 9999.9999s	0 to 9999.9999s
Designation of a program number		P	1 to 9999	1 to 9999
Number of repetitions		P	1 to 9999	1 to 9999

NOTE
In ISO code, the colon (:) can also be used as the address of a program number.

- **Optional block skip**

When a slash followed by a number (/n (n=1 to 9)) is specified at the head of a block, and optional block skip switch n on the machine operator panel is set to on, the information contained in the block for which /n corresponding to switch number n is specified is ignored in tape operation or memory operation.
When optional block skip switch n is set to off, the information contained in the block for which /n is specified is valid. This means that the operator can determine whether to skip the block containing /n.
Number 1 for /1 can be omitted. However, when two or more optional block skip switches are used for one block, number 1 for /1 cannot be omitted.

Example)

(Incorrect) (Correct)
//3 G00X10.0; /1/3 G00X10.0;

This function is ignored when programs are loaded into memory. Blocks containing /n are also stored in memory, regardless of how the optional block skip switch is set.
Programs held in memory can be output, regardless of how the optional block skip switches are set.
Optional block skip is effective even during sequence number search operation.
Depending on the machine tool, all optional block skip switches (1 to 9) may not be usable. Refer to manuals of the machine tool builder to find which switches are usable.

WARNING

1 ***Position of a slash***
A slash (/) must be specified at the head of a block. If a slash is placed elsewhere, the information from the slash to immediately before the EOB code is ignored.

2 ***Disabling an optional block skip switch***
Optional block skip operation is processed when blocks are read from memory or tape into a buffer. Even if a switch is set to on after blocks are read into a buffer, the blocks already read are not ignored.

NOTE

TV and TH check
When an optional block skip switch is on. TH and TV checks are made for the skipped portions in the same way as when the optional block skip switch is off.

- **Program end**

The end of a program is indicated by punching one of the following codes at the end of the program:

Table 12.2(d) Code of a program end

Code	Meaning usage
M02	For main program
M30	
M99	For subprogram

If one of the program end codes is executed in program execution, the CNC terminates the execution of the program, and the reset state is set. When the subprogram end code is executed, control returns to the program that called the subprogram.

WARNING
A block containing an optional block skip code such as /M02 ; , /M30 ; , or /M99 ; is not regarded as the end of a program, if the optional block skip switch on the machine operator's panel is set to on.
(See item "Optional block skip".)

12.3 SUBPROGRAM (M98, M99)

If a program contains a fixed sequence or frequently repeated pattern, such a sequence or pattern can be stored as a subprogram in memory to simplify the program.
A subprogram can be called from the main program.
A called subprogram can also call another subprogram.

Format

- **Subprogram configuration**

One subprogram

O □□□□ ; **Subprogram number (or the colon (:) optionally in the case of ISO)**

M99 ; Program end

M99 need not constitute a separate block as indicated below.
Example) **X100.0 Y100.0 M99 ;**

- **Subprogram call (M98)**

M98 P ○○○○ ○○○○ ;

Number of times the subprogram is called repeatedly **Subprogram number**

When no repetition data is specified, the subprogram is called just once.

Explanations

When the main program calls a subprogram, it is regarded as a one–level subprogram call. Thus, subprogram calls can be nested up to four levels as shown below.



A single call command can repeatedly call a subprogram up to 9999 times.
For compatibility with automatic programming systems, in the first block, Nxxxx can be used instead of a subprogram number that follows O (or :). A sequence number after N is registered as a subprogram number.

Reference item

See Chapter 10 in Part III for the method of registering a subprogram.

NOTE
1 The M98 and M99 signals are not output to the machine tool.
2 If the subprogram number specified by address P cannot be found, an alarm (No. 078) is output.

Examples

☆ **M98 P51002 ;**

This command specifies “Call the subprogram (number 1002) five times in succession.” A subprogram call command (M98P_) can be specified in the same block as a move command.

☆ **X1000.0 M98 P1200 ;**

This example calls the subprogram (number 1200) after an X movement.

☆ Execution sequence of subprograms called from a main program



A subprogram can call another subprogram in the same way as a main program calls a subprogram.

Special Usage

- **Specifying the sequence number for the return destination in the main program**

If P is used to specify a sequence number when a subprogram is terminated, control does not return to the block after the calling block, but returns to the block with the sequence number specified by P. Note, however, that P is ignored if the main program is operating in a mode other than memory operation mode.
This method consumes a much longer time than the normal return method to return to the main program.



- **Using M99 in the main program**

If M99 is executed in a main program, control returns to the start of the main program. For example, M99 can be executed by placing /M99 ; at an appropriate location of the main program and setting the optional block skip function to off when executing the main program. When M99 is executed, control returns to the start of the main program, then execution is repeated starting at the head of the main program.
Execution is repeated while the optional block skip function is set to off. If the optional block skip function is set to on, the /M99 ; block is skipped ; control is passed to the next block for continued execution.
If/M99Pn ; is specified, control returns not to the start of the main program, but to sequence number n. In this case, a longer time is required to return to sequence number n.

- **Using a subprogram only**

A subprogram can be executed just like a main program by searching for the start of the subprogram with the MDI.
(See Section 9.4 in Part III for information about search operation.)
In this case, if a block containing M99 is executed, control returns to the start of the subprogram for repeated execution. If a block containing M99Pn is executed, control returns to the block with sequence number n in the subprogram for repeated execution. To terminate this program, a block containing /M02 ; or /M30 ; must be placed at an appropriate location, and the optional block switch must be set to off ; this switch is to be set to on first.



13 FUNCTIONS TO SIMPLIFY PROGRAMMING

General

This chapter explains the following items:

13.1 CANNED CYCLE (G90, G92, G94)
13.2 MULTIPLE REPETITIVE CYCLE (G70 to G76)
13.3 CANNED CYCLE FOR DRILLING (G80 to G89)
13.4 CHAMFERING AND CORNER R
13.5 MIRROR IMAGE FOR DOUBLE TURRET (G68, G69)
13.6 DIRECT DRAWING DIMENSIONS PROGRAMMING
13.7 RIGID TAPPING

NOTE
Explanatory diagrams in this chapter uses diameter programming in X axis.
In radius programming, changes U/2 with U and X/2 with X.

13.1 CANNED CYCLE (G90, G92, G94)

There are three canned cycles : the outer diameter/internal diameter cutting canned cycle (G90), the thread cutting canned cycle (G92), and the end face turning canned cycle (G94).

13.1.1 Outer Diameter / Internal Diameter Cutting Cycle (G90)

- **Straight cutting cycle**



Fig. 13.1.1(a) Straight cutting cycle

In incremental programming, the sign of the numbers following address U and W depends on the direction of paths 1 and 2. In the cycle of 14. 1 1 (a), the signs of U and W are negative.
In single block mode, operations 1, 2, 3 and 4 are performed by pressing the cycle start button once.

- **Taper cutting cycle**



Fig. 13.1.1(b) Taper cutting cycle

- **Signs of numbers specified in the taper cutting cycle**

In incremental programming, the relationship between the signs of the numbers following address U, W, and R, and the tool paths are as follows:

1. U < 0, W < 0, R < 0



2. U > 0, W < 0, R > 0



3. U < 0, W < 0, R > 0 at | R | ≦ | U/2 |



4. U > 0, W < 0, R<0 at | R | ≦ | U/2 |



13.1.2 Thread Cutting Cycle (G92)



Fig. 13.1.2(a) Straight thread cutting

In incremental programming, the sign of numbers following addresses U and W depends on the direction of paths 1 and 2. That is , if the direction of path 1 is the negative along the X axis, the value of U is negative.
The range of thread leads, limitation of spindle speed, etc. are the same as in G32 (thread cutting). Thread chamfering can be performed in this thread cutting cycle. A signal from the machine tool, initiates thread chamfering. The chamfering distance is specified in a range from 0.1L to 12.7L in 0.1L increments by parameter (No. 5130). (In the above expression, L is the thread lead.)
In the single block mode, operations 1, 2, 3, and 4 are performed by pressing cycle start button once.

WARNING

Notes on this thread cutting are the same as in thread cutting in G32. However, a stop by feed hold is as follows ; Stop after completion of path 3 of thread cutting cycle.

CAUTION

The tool retreats while chamfering and returns to the start point on the X axis then the Z axis, as soon as the feed hold status is entered during thread cutting (motion 2) when the “Thread Cutting Cycle retract” option is used.



Another feed hold cannot be made during retreat. The chamfered amount is the same as that at the end point.

- **Taper thread cutting cycle**



Fig. 13.1.2 (b) Taper thread cutting cycle

13.1.3 End Face Turning Cycle (G94)

- **Face cutting cycle**



Fig. 13.1.3 (a) Face cutting cycle

In incremental programming, the sign of numbers following addresses U and W depends on the direction of paths 1 and 2. That is, if the direction of the path is in the negative direction of the Z axis, the value of W is negative.
In single block mode, operations 1, 2, 3, and 4 are performed by pressing the cycle start button once.

- **Taper face cutting cycle**



Fig. 13.1.3 (b)

- **Signs of numbers specified in the taper cutting cycle**

In incremental programming, the relationship between the signs of the numbers following address U, W, and R, and the tool paths are as follows:

1. U < 0, W < 0, R < 0	**2. U > 0, W < 0, R < 0**
	
3. U < 0, W < 0, R > 0 at | R | ≦ | W |	**4. U > 0, W < 0, R<0 at | R | ≦ | W |**
	

NOTE

1 Since data values of X (U), Z (W) and R during canned cycle are modal, if X (U), Z (W), or R is not newly commanded, the previously specified data is effective. Thus, when the Z axis movement amount does not vary as in the example below, a canned cycle can be repeated only by specifying the movement commands for the X–axis.

However, these data are cleared, if a one–shot G code expect for G04 (dwell) or a G code in the group 01 except for G90, G92, G94 is commanded.

(Example)



The cycle in the above figure is executed by the following program.

```
N030    G90 U–8.0 W–66.0 F0.4 ;
N031    U–16.0 ;
N032    U–24.0 ;
N033    U–32.0 ;
```

2 The following two applications can be performed.

(1) If an EOB or zero movement commands are specified for the block following that specified with a canned cycle, the same canned cycle is repeated.

(2) If the M, S, T function is commanded during the canned cycle mode, both the canned cycle and M, S, or T function can be performed simultaneously. If this is inconvenient, cancel the canned cycle once as in the program examples below (specify G00 or G01) and execute the M, S, or T command. After the execution of M, S, or T terminates, command the canned cycle again.

```
(Example)
N003 T0101 ;
  :
  :
N010    G90 X20.0 Z10.0 F0.2 ;
N011    G00 T0202 ;
N012    G90 X20.5 Z10.0 ;
```

13.1.4 How to Use Canned Cycles (G90, G92, G94)

An appropriate canned cycle is selected according to the shape of the material and the shape of the product.

- **Straight cutting cycle (G90)**



- **Taper cutting cycle (G90)**



- **Face cutting cycle (G94)**



- **Face taper cutting cycle (G94)**



13.2 MULTIPLE REPETITIVE CYCLE (G70 – G76)

This option canned cycles to make CNC programming easy. For instance, the data of the finish work shape describes the tool path for rough machining. And also, a canned cycles for the thread cutting is available.

13.2.1 Stock Removal in Turning (G71)

There are two types of stock removals in turning : Type I and II.

- **Type I**

If a finished shape of A to A' to B is given by a program as in the figure below, the specified area is removed by Δd (depth of cut), with finishing allowance Δu/2 and Δw left.



G71 U (Δd) R (e) ;
G71 P (ns) Q (nf) U (Δu) W (Δw) F (f) S (s) T (t)

N (ns)·····
·····
F____
S____
T____
N (nf)·····;

The move command between A and B is specified in the blocks from sequence number ns to nf.

Δd : Depth of cut (radius designation)
Designate without sign. The cutting direction depends on the direction AA'. This designation is modal and is not changed until the other value is designated. Also this value can be specified by the parameter (No. 5132), and the parameter is changed by the program command.

e : Escaping amount
This designation is modal and is not changed until the other value is designated. Also this value can be specified by the parameter (No. 5133), and the parameter is changed by the program command.

ns : Sequence number of the first block for the program of finishing shape.

nf : Sequence number of the last block for the program of finishing shape.

Δu : Distance and direction of finishing allowance in X direction (diameter / radius designation).

Δw : Distance and direction of finishing allowance in Z direction.

f,s,t : Any F , S, or T function contained in blocks ns to nf in the cycle is ignored, and the F, S, or T function in this G71 block is effective.

Fig. 13.2.1 (a) Cutting path in stock removal in turning (Type I)

NOTE

1 While both Δd and Δu, are specified by address U, the meanings of them are determined by the presence of addresses P and Q.

2 The cycle machining is performed by G71 command with P and Q specification.
F, S, and T functions which are specified in the move command between points A and B are ineffective and those specified in G71 block or the previous block are effective.

When an option of constant surface speed control is selected, G96 or G97 command specified in the move command between points A and B are ineffective, and that specified in G71 block or the previous block is effective.
The following four cutting patterns are considered. All of these cutting cycles are made paralleled to Z axis and the sign of Δu and Δw are as follows:



The tool path between A and A' is specified in the block with sequence number "ns" including G00 or G01, and in this block, a move command in the Z axis cannot be specified. The tool path between A' and B must be steadily increasing or decreasing pattern in both X and Z axis. When the tool path between A and A' is programmed by G00/G01, cutting along AA' is performed in G00/G01 mode respectively.

3 The subprogram cannot be called from the block between sequence number "ns" and "nf".

- **Type** II

Type II differs from type I in the following : The profile need not show monotone increase or monotone decrease along the X axis, and it may have up to 10 concaves (pockets).



Fig. 13.2.1 (b) Number of pockets in stock removal in turning (Type II)

Note that, however, the profile must have monotone decrease or increase along the Z axis. The following profile cannot be machined:



Fig. 13.2.1 (c) Figure which cannot be machined in stock removal in turning (Type II)

The first cut portion need not be vertical ; any profile is permitted if monotone change is shown along the Z axis.



Fig. 13.2.1 (d) Figure which can be machined (Monotonic change) in stock removal in turning (Type II)

After turning, a clearance is provided by cutting along the workpiece profile.



Fig. 13.2.1 (e) Chamfering in stock removal in turning (Type II)

The clearance e (specified in R) to be provided after cutting can also be set in parameter No. 5133.
A sample cutting path is given below:



Fig. 13.2.1 (f) Cutting path in stock removal in facing

The offset of the tool tip radius is not added to finishing allowances Δu and Δw. In turning, the offset of the tool tip radius is assumed to be zero.
W=0 must be specified ; otherwise, the tool tip may cut into one wall side.
For the first block of a repetitive portion, two axes X(U) and Z (W) must be specified. When Z motion is not performed, W0 is also specified.

- **Distinction between type I and type II**

When only one axis is specified in the first block of a repetitive portion
-- Type I
When two axes are specified in the first block of a repetitive portion
-- Type II
When the first block does not include Z motion and type IIis to be used, W0 must be specified.
(Example)

TYPEI	TYPEII
G71 V10.0 R5.0 ;	G71 V10.0 R5.0 ;
G71 P100 Q200....;	G71 P100 Q200.....;
N100X (U)___;	N100X (U)___ Z(W)___;
:	:
:	:
N200.....;	N200.....;

13.2.2 Stock Removal in Facing (G72)

As shown in the figure below, this cycle is the same as G71 except that cutting is made by a operation parallel to X axis.



G72 W(Δd) R(e) ;
G72 P(ns) Q(nf) U(Δu) W(Δw) F(f) S(s) T(t) ;
The meanings of Δd, e, ns, nf, Δu,Δw, f, s, and t are the same as those in G71.

Fig. 13.2.2 (a) Cutting path in stock removal in facing

- **Signs of specified numbers**

The following four cutting patterns are considered. All of these cutting cycles are made parallel to X axis and the sign of Δu and Δw are as follows :



Fig. 13.2.2 (b)
Signs of numbers specified with u and w in stock removal in facing

The tool path between A and A' is specified in the block with sequence number "ns" including G00 or G01, and in this block, a move command in the X axis cannot be specified. The tool path between A' and B must be steadily increasing and decreasing pattern in both X and Z axes. Whether the cutting along AA' is G00 or G01 mode is determined by the command between A and A', as described in item 13.2.1.

13.2.3 Pattern Repeating (G73)

This function permits cutting a fixed pattern repeatedly, with a pattern being displaced bit by bit. By this cutting cycle, it is possible to efficiently cut work whose rough shape has already been made by a rough machining, forging or casting method, etc.



The pattern commanded in the program should be as follows.

A→A'→B

G73 U (△i) W (△k) R (d) ;

G73 P (ns) Q (nf) U (△u) W (△w) F (f) S (s) T (t) ;

N (ns)·····
·····
F____
S____
T____
N (nf)·····;

The move command between A and B is specified in the blocks from sequence number ns to nf.

Δi : Distance and direction of relief in the X axis direction (Radius designation). This designation is modal and is not changed until the other value is designated. Also this value can be specified by the parameter No. 5135, and the parameter is changed by the program command.

Δk : Distance and direction of relief in the Z axis direction. This designation is modal and is not changed until the other value is designated. Also this value can be specified by the parameter No. 5136, and the parameter is changed by the program command.

d : The number of division. This value is the same as the repetitive count for rough cutting. This designation is modal and is not changed until the other value is designated. Also, this value can be specified by the parameter No. 5137, and the parameter is changed by the program command.

ns : Sequence number of the first block for the program of finishing shape.

nf : Sequence number of the last block for the program of finishing shape.

Δu : Distance and direction of finishing allowance in X direction (diameter/radius designation)

Δw : Distance and direction of finishing allowance in Z direction

f,s,t : Any F, S, and T function contained in the blocks between sequence number "ns" and "nf" are ignored, and the F, S, and T functions in this G73 block are effective.

Fig. 13.2.3 Cutting path in pattern repeating

NOTE
1 While the values Δi and Δk, or Δu and Δw are specified by address U and W respectively, the meanings of them are determined by the presence of addresses P and Q in G73 block. When P and Q are not specified in a same block, addresses U and W indicates Δi and Δk respectively. When P and Q are specified in a same block, addreses U and W indicates Δu and Δw respectively.
2 The cycle machining is performed by G73 command with P and Q specification.
The four cutting patterns are considered. Take care of the sign of Δu, Δw, Δk, and Δi.
When the machining cycle is terminated, the tool returns to point A.

13.2.4 Finishing Cycle (G70)

After rough cutting by G71, G72 or G73, the following command permits finishing.

Format

G70P (ns) Q (nf) ;

(ns) : Sequence number of the first block for the program of finishing shape.

(nf) : Sequence number of the last block for the program of finishing shape.

NOTE
1 F, S, and T functions specified in the block G71, G72, G73 are not effective but those specified between sequence numbers “ns” and “nf” are effective in G70.
2 When the cycle machining by G70 is terminated, the tool is returned to the start point and the next block is read.
3 In blocks between “ns” and “nf” referred in G70 through G73, the subprogram cannot be called.

Examples

Stock Removal in Turning (G71) (Type I)



(Diameter designation, metric input)

```
N010 G50 X200.0 Z220.0 ;
N011 G00 X160.0 Z180.0 ;
N012 G71 U7.0 R1.0 ;
N013 G71 P014 Q020 U4.0 W2.0 F0.3 S550 ;
N014 G00 X40.0 F0.15 S700 ;
N015 G01 W–40.0;
N016    X60.0 W–30.0 ;
N017    W–20.0 ;
N018    X100.0 W–10.0 ;
N019    W–20.0 ;
N020    X140.0 W–20.0 ;
N021 G70 P014 Q020 ;
```

Stock Removal In Facing (G72)



(Diameter designation, metric input)

```
N010  G50 X220.0 Z190.0 ;
N011  G00 X176.0 Z132.0 ;
N012  G72 W7.0 R1.0 ;
N013  G72 P014 Q019 U4.0 W2.0 F0.3 S550 ;
N014  G00 Z58.0 S700 ;
N015  G01 X120.0 W12.0 F0.15 ;
N016     W10.0 ;
N017     X80.0 W10.0 ;
N018     W20.0 ;
N019     X36.0 W22.0 ;
N020  G70 P014 Q019 ;
```

Pattern Repeating (G73)



(Diameter designation, metric input)

```
N010 G50 X260.0 Z220.0 ;
N011 G00 X220.0 Z160.0 ;
N012 G73 U14.0 W14.0 R3 ;
N013 G73 P014 Q019 U4.0 W2.0 F0.3 S0180 ;
N014 G00 X80.0 W–40.0 ;
N015 G01 W–20.0 F0.15 S0600 ;
N017 W–20.0 S0400 ;
N018 G02 X160.0 W–20.0 R20.0 ;
N019 G01 X180.0 W–10.0 S0280 ;
N020 G70 P014 Q019 ;
```

13.2.5 End Face Peck Drilling Cycle (G74)

The following program generates the cutting path shown in Fig. 13.2.5. Chip breaking is possible in this cycle as shown below. If X (U) and Pare omitted, operation only in the Z axis results, to be used for drilling.



G74R (e) ;

G74X(U)_ Z(W)_ P(Δi) Q(Δk) R(Δd) F (f) ;

e : Return amount
This designation is modal and is not changed until the other value is designated. Also this value can be specified by the parameter No. 5139, and the parameter is changed by the program command.
X : X component of point B
U : Incremental amount from A to B
Z : Z component of point C
W : Increment amount from A to C
Δi : Movement amount in X direction (without sign)
Δk : Depth of cut in Z direction (without sign)
Δd : Relief amount of the tool at the cutting bottom. The sign of Δd is always plus (+). However, if address X (U) and Δi are omitted, the relief direction can be specified by the desired sign.
f : Feed rate

Fig. 13.2.5 Cutting path in end face peek drilling cycle

NOTE
1 While both e and Δd are specified by address R, the meanings of them are determined by the present of address X (U). When X(U) is specified, Δd is used.
2 The cycle machining is performed by G74 command with X (U) specification.

13.2.6 Outer Diameter / Internal Diameter Drilling Cycle (G75)

The following program generates the cutting path shown in Fig. 13.2.6. This is equivalent to G74 except that X is replaced by Z. Chip breaking is possible in this cycle, and grooving in X axis and peck drilling in X axis (in this case, Z, W, and Q are omitted) are possible.



Fig. 13.2.6 Cutting path in outer diameter/internal diameter drilling cycle

Both G74 and G75 are used for grooving and drilling, and permit the tool to relief automatically. Four symmetrical patterns are considered, respectively.

13.2.7 Multiple Thread Cutting Cycle (G76)

The thread cutting cycle as shown in Fig.13.2.7 is programmed by the G76 command.



Fig. 13.2.7 Cutting path in multiple thread cutting cycle



G76P (m) (r) (a) Q (Δd min) R(d);
G76X (u) _ Z(W) _ R(i) P(k) Q(Δd) F(L) ;

m ; Repetitive count in finishing (1 to 99)
This designation is modal and is not changed until the other value is designated. Also this value can be specified by the parameter No. 5142, and the parameter is changed by the program command.

r : Chamfering amount
When the thread lead is expressed by L, the value of L can be set from 0.0L to 9.9L in 0.1L increment (2–digit number from 00 to 90).
This designation is modal and is not changed until the other value is designated. Also this value can be specified by the parameter No. 5130, and the parameter is changed by the program command.

a : Angle of tool tip
One of six kinds of angle, 80°, 60°, 55°, 30°, 29°, and 0°, can be selected, and specified by 2–digit number.
This designation is modal and is not changed until the other value is designated. Also this value can be specified by the parameter No. 5143, and the parameter is changed by the program command.

m, r, and a are specified by address P at the same time.

(Example)
When m=2, r=1.2L, a=60°, specify as shown below (L is lead of thread).

P $\frac{02}{m}$ $\frac{12}{r}$ $\frac{60}{a}$

Δdmin : Minimum cutting depth (specified by the radius value)
When the cutting depth of one cycle operation (Δd – Δd –1) becomes smaller than this limit, the cutting depth is clamped at this value. This designation is modal and is not changed until the other value is designated. Also this value can be specified by parameter No. 5140, and the parameter is changed by the program command.

d : Finishing allowance
This designation is modal and is not changed until the other value is designated. Also this value can be specified by parameter No. 5141, and the parameter is changed by the program command.

i : Difference of thread radius If i = 0, ordinary straight thread cutting can be made.

k : Height of thread
This value is specified by the radius value.

Δd : Depth of cut in 1st cut (radius value)

L : Lead of thread (same as G32).

Fig. 13.2.7 (b) Detail of cutting

- **Thread cutting cycle retract**

When feed hold is applied during threading in the multiple thread cutting cycle (G76), the tool quickly retracts in the same way as in chamfering performed at the end of the thread cutting cycle. The tool goes back to the start point of the cycle. When cycle start is triggered, the multiple thread cutting cycle resumes.
Without this retraction function, when feed hold is applied during threading, the tool goes back to the start point of the cycle after threading is completed.
See notes in 13.1.2.

NOTE
1 The meanings of the data specified by address P, Q, and R determined by the presence of X (U) and X (W).
2 The cycle machining is performed by G76 command with X (U) and Z (W) specification.
By using this cycle , one edge cutting is performed and the load on the tool tip is reduced.
Making the cutting depth Δd for the first path, and Δdn for the nth path, cutting amount per one cycle is held constant.
Four symmetrical patterns are considered corresponding to the sign of each address.
The internal thread cutting is available. In the above figure, the feed rate between C and D is specified by address F, and in the other path, at rapid traverse. The sign of incremental dimensions for the above figure is as follows:
U, W : minus (determined by the direction of the tool path AC and CD.)
R : minus (determined by the direction of the tool path AC.)
P : plus (always)
Q : plus (always)
3 Notes on thread cutting are the same as those on G32 thread cutting and G92 thread cutting cycle.
4 The designation of chamfering is also effective for G92 thread cutting cycle.
5 The tool returns to the cycle start point at that time (cutting depth Δdn) as soon as the feed hold status is entered during thread cutting when the “Thread Cutting Cycle retract” option is used.

Examples

Multiple repetitive cycle (G76)



G76 P011060 Q100 R200 ;
G76 X60640 Z25000 P3680 Q1800 F6.0 ;

- **Staggered thread cutting**

Specifying P2 can perform staggered thread cutting with a constant depth of cut.
Example: G76 X60640 Z25000 K3680 D1800 F6.0 A60 P2;
For staggered thread cutting, always use the FS15 tape format (see Section 18.5).
If the depth of cut in one cycle is less than dmin (specified in parameter No. 5140), the depth of cut is clamped at Δdmin.



Staggered thread cutting with a constant depth of cut

13.2.8 Notes on Multiple Repetitive Cycle (G70 – G76)

1. In the blocks where the multiple repetitive cycle are commanded, the addresses P, Q, X, Z, U, W, and R should be specified correctly for each block.
2. In the block which is specified by address P of G71, G72 or G73, G00 or G01 group should be commanded. If it is not commanded, P/S alarm No.65 is generated.
3. In MDI mode, G70, G71, G72, or G73 cannot be commanded. If it is commanded, P/S alarm No. 67 is generated. G74, G75, and G76 can be commanded in MDI mode.
4. In the blocks in which G70, G71, G72, or G73 are commanded and between the sequence number specified by P and Q, M98 (subprogram call) and M99 (subprogram end) cannot be commanded.
5. In the blocks between the sequence number specified by P and Q, the following commands cannot be specified.
   ·One shot G code except for G04 (dwell)
   ·01 group G code except for G00, G01, G02, and G03
   ·06 group G code
   ·M98 / M99
6. While a multiple repetitive cycle (G70AG76) is being executed, it is possible to stop the cycle and to perform manual operation. But, when the cycle operation is restarted, the tool should be returned to the position where the cycle operation is stopped.
   If the cycle operation is restarted without returning to the stop position, the movement in manual operation is added to the absolute value, and the tool path is shifted by the movement amount in manual operation.
7. When G70, G71, G72, or G73 is executed, the sequence number specified by address P and Q should not be specified twice or more in the same program.
8. Do not program so that the final movement command of the finishing shape block group designated with P and Q for G70, G71, G72, and G73 finishes with chamfering or corner rounding. If it is specified,P/S alarm No. 69 is generated.

9 G74, G75, and G76 also do not support the input of a decimal point for P or Q. The least input increments are used as the units in which the amount of travel and depth of cut are specified.

10 When #1 = 2500 is executed using a custom macro, 2500.000 is assigned to #1. In such a case, P#1 is equivalent to P2500.

11 Tool nose radius compensation cannot be applied to G71, G72, G73, G74, G75, G76, or G78.

13.3 CANNED CYCLE FOR DRILLING (G80 – G89)

The canned cycle for drilling simplifies the program normally by directing the machining operation commanded with a few blocks, using one block including G code.
This canned cycle conforms to JIS B 6314.
Following is the canned cycle table.

Table 13.3(a) Canned cycles

G code	Drilling axis	Hole machining operation (– direction)	Operation in the bottom hole position	Retraction operation (+ direction)	Applications
G80	____	_____	_____	___	Cancel
G83	Z axis	Cutting feed / intermittent	Dwell	Rapid traverse	Front drilling cycle
G84	Z axis	Cutting feed	Dwell→spindle CCW	Cutting feed	Front tapping cycle
G85	Z axis	Cutting feed	_____	Cutting feed	Front boring cycle
G87	X axis	Cutting feed / intermittent	Dwell	Rapid traverse	Side drilling cycle
G88	X axis	Cutting feed	Dwell→Spindle CCW	Cutting feed	Side tapping cycle
G89	X axis	Cutting feed	Dwell	Cutting feed	Side boring cycle

In general, the drilling cycle consists of the following six operation sequences.

Operation 1 Positioning of X (Z) and C axis
Operation 2 Rapid traverse up to point R level
Operation 3 Hole machining
Operation 4 Operation at the bottom of a hole
Operation 5 Retraction to point R level
Operation 6 Rapid traverse up to the initial point



Fig. 13.3 Drilling cycle operation sequence

Explanations

• Positioning axis and drilling axis

A drilling G code specifies positioning axes and a drilling axis as shown below. The C–axis and X– or Z–axis are used as positioning axes. The X– or Z–axis, which is not used as a positioning axis, is used as a drilling axis.
Although canned cycles include tapping and boring cycles as well as drilling cycles, in this chapter, only the term drilling will be used to refer to operations implemented with canned cycles.

Table13.1(b) Positioning axis and drilling axis

G code	Positioning plane	Drilling axis
G83, G84, G85	X axis, C axis	Z axis
G87, G88, G89	Z axis, C axis	X axis

G83 and G87, G84 and G88, and G85 and G89 have the same function respectively except for axes specified as positioning axes and a drilling axis.

• Drilling mode

G83AG85 / G87A89 are modal G codes and remain in effect until canceled. When in effect, the current state is the drilling mode.
Once drilling data is specified in the drilling mode, the data is retained until modified or canceled.
Specify all necessary drilling data at the beginning of canned cycles; when canned cycles are being performed, specify data modifications only.

• Return point level G98/G99

In G code system A, the tool returns to the initial level from the bottom of a hole. In G code system B or C, specifying G98 returns the tool to the initial level from the bottom of a hole and specifying G99 returns the tool to the point–R level from the bottom of a hole.
The following illustrates how the tool moves when G98 or G99 is specified. Generally, G99 is used for the first drilling operation and G98 is used for the last drilling operation.
The initial level does not change even when drilling is performed in the G99 mode.



- **Number of repeats**

To repeat drilling for equally–spaced holes, specify the number of repeats in K_.
K is effective only within the block where it is specified.
Specify the first hole position in incremental mode.
If it is specified in absolute mode, drilling is repeated at the same position.

Number of repeats K	The maximum command value = 9999

If K0 is specified, drilling data is stored, but drilling is not performed.

- **M code used for C–axis clamp/unclamp**

When an M code specified in parameter No.5110 for C–axis clamp / unclamp is coded in a program, the CNC issues the M code for C–axis clamp after the tool is positioned and before the tool is fed in rapid traverse to the point–R level. The CNC also issues the M code for C–axis unclamp after the tool retracts to the point–R level. The tool dwells for the time specified in parameter No. 5111.

- **Cancel**

To cancel a canned cycle, use G80 or a group 01 G code.

Group 01 G codes
G00 : Positioning (rapid traverse)
G01 : Linear interpolation
G02 : Circular interpolation (CW)
G03 : Circular interpolation (CCW)

- **Symbols in figures**

Subsequent sections explain the individual canned cycles. Figures in these explanations use the following symbols:

	Positioning (rapid traverse G00)
	Cutting feed (linear interpolation G01)
	Manual feed
P1	Dwell specified in the program
P1	Dwell specified in parameter No.5111
Mα	Issuing the M code for C–axis clamp
	(The value of α is specified with parameter No. 5110.)
M (α+1)	Issuing the M code for C–axis unclamp

CAUTION
In each canned cycle,
R_ (distance between the initial level and point R) is always handled as a radius.
Z_ or X_ (distance between point R and the bottom of the hole) is, however, handled either as a diameter or radius, depending on the specification.

13.3.1 Front Drilling Cycle (G83) / Side Drilling Cycle (G87)

The peck drilling cycle or high–speed peck drilling cycle is used depending on the setting in RTR, bit 2 of parameter No. 5101. If depth of cut for each drilling is not specified, the normal drilling cycle is used.

- **High–speed peck drilling cycle (G83, G87) (parameter RTR (No. 5101#2) =0)**

This cycle performs high–speed peck drilling. The drill repeats the cycle of drilling at the cutting feedrate and retracting the specified retraction distance intermittently to the bottom of a hole. The drill draws cutting chips out of the hole when it retracts.

Format

G83 X(U)_ C(H)_ Z(W)_ R_ Q_ P_ F_ M_ ;
or
G87 Z(W)_ C(H)_ X(U)_ R_ Q_ P_ F_ M_ ;

X_ C_ or Z_ C_ : Hole position data
Z_ or X_ : The distance from point R to the bottom of the hole
R_ : The distance from the initial level to point R level
Q_ : Depth of cut for each cutting feed
P_ : Dwell time at the bottom of a hole
F_ : Cutting feedrate
K_ : Number of repeats (When it is needed)
M_ : M code for C–axis clamp (When it is needed.)

G83 or G87 (G98 mode)



G83 or G87 (G99 mode)



Mα : M code for C−axis clamp
M(α+1) : M code for C−axis unclamp
P1 : Dwell specified in the program
P2 : Dwell specified in parameter No. 5111
d : Retraction distance specified in parameter No. 5114

- **Peck drilling cycle (G83, G87) (parameter No. 5101#2 =1)**

Format

G83 X(U)_ C(H)_ Z(W)_ R_ Q_ P_ F_ M_ K_ ;
or
G87 Z(W)_ C(H)_ X(U)_ R_ Q_ P_ F_ M_ K_ ;

X_ C_ or Z_ C_ : Hole position data
Z_ or X_ : The distance from point R to the bottom of the hole
R_ : The distance from the initial level to point R level
Q_ : Depth of cut for each cutting feed
P_ : Dwell time at the bottom of a hole
F_ : Cutting feedrate
K_ : Number of repeats (When it is needed.)
M_ : M code for C–axis clamp (When it is needed.)

G83 or G87 (G98 mode)	G83 or G87 (G99 mode)
	

Mα : M code for C−axis clamp
M(α+1) : M code for C−axis unclamp
P1 : Dwell specified in the program
P2 : Dwell specified in parameter No.5111
d : Retraction distance specified in parameter No. 5114

Examples

```
M51 ;                          Setting C–axis index mode ON
M3 S2000 ;                     Rotating the drill
G00 X50.0 C0.0 ;               Positioning the drill along the X– and C–axes
G83 Z–40.0 R–5.0 Q5000 F5.0 M31 ; Drilling hole 1
C90.0 M31 ;                    Drilling hole 2
C180.0 M31 ;                   Drilling hole 3
C270.0 M31 ;                   Drilling hole 4
G80 M05 ;                      Canceling the drilling cycle and stopping drill rotation
M50 ;                          Setting C–axis index mode off
```

● Drilling cycle (G83 or G87)

If depth of cut is not specified for each drilling, the normal drilling cycle is used. The tool is then retracted from the bottom of the hole in rapid traverse.

Format

G83 X(U)_ C(H)_ Z(W)_ R_ P_ F_ M_ K_ ;
or
G87 Z(W)_ C(H)_ X(U)_ R_ P_ F_ M_ K_ ;

X_ C_ or Z_ C_ : Hole position data
Z_ or X_ : The distance from point R to the bottom of the hole
R_ : The distance from the initial level to point R level
P_ : Dwell time at the bottom of a hole
F_ : Cutting feedrate
K_ : Number of repeats (When it is needed.)
M_ : M code for C–axis clamp (When it is needed.)

G83 or G87 (G98 mode)	G83 or G87 (G99 mode)
	

Mα : M code for C−axis clamp
M(α+1) : M code for C−axis unclamp
P1 : Dwell specified in the program
P2 : Dwell specified in parameter No. 5111

Examples

```
M51 ;                    Setting C–axis index mode ON
M3 S2000 ;               Rotating the drill
G00 X50.0 C0.0 ;         Positioning the drill along the X– and C–axes
G83 Z–40.0 R–5.0 P500 F5.0 M31 ;  Drilling hole 1
C90.0 M31 ;              Drilling hole 2
C180.0 M31 ;             Drilling hole 3
C270.0 M31 ;             Drilling hole 4
G80 M05 ;                Canceling the drilling cycle and stopping drill rotation
M50 ;                    Setting C–axis index mode off
```

13.3.2 Front Tapping Cycle (G84) / Side Tapping Cycle (G88)

This cycle performs tapping.
In this tapping cycle, when the bottom of the hole has been reached, the spindle is rotated in the reverse direction.

Format

G84 X(U)_ C(H)_ Z(W)_ R_ P_ F_ M_ K_ ;
or
G88 Z(W)_ C(H)_ X(U)_ R_ P_ F_ M_ K_ ;

X_ C_ or Z_ C_ : Hole position data
Z_ or X_ : The distance from point R to the bottom of the hole
R_ : The distance from the initial level to point R level
P_ : Dwell time at the bottom of a hole
F_ : Cutting feedrate
K_ : Number of repeats (When it is needed.)
M_ : M code for C–axis clamp (when it is needed.)



Explanations

Tapping is performed by rotating the spindle clockwise. When the bottom of the hole has been reached, the spindle is rotated in the reverse direction for retraction. This operation creates threads.
Feedrate overrides are ignored during tapping. A feed hold does not stop the machine until the return operation is completed.

NOTE

Bit 6 (M5T) of parameter No. 5101 specifies whether the spindle stop command (M05) is issued before the direction in which the spindle rotates is specified with M03 or M04. For details, refer to the operator's manual created by the machine tool builder.

Examples

```
M51 ;                  Setting C–axis index mode ON
M3 S2000 ;             Rotating the drill
G00 X50.0 C0.0 ;       Positioning the drill along the X– and C– axes
G83 Z–40.0 R–5.0 P500 F5.0 M31 ;  Drilling hole 1
C90.0 M31 ;            Drilling hole 2
C180.0 M31 ;           Drilling hole 3
C270.0 M31 ;           Drilling hole 4
G80 M05 ;              Canceling the drilling cycle and stopping drill rotation
M50 ;                  Setting C–axis index mode off
```

13.3.3 Front Boring Cycle (G85) / Side Boring Cycle (G89)

This cycle is used to bore a hole.

Format

G85 X(U)_ C(H)_ Z(W)_ R_ P_ F_ K_ M_ ;
or
G89 Z(W)_ C(H)_ X(U)_ R_ P_ F_ K_ M_ ;

X_ C_ or Z_ C_ : Hole position data
Z_ or X_ : The distance from point R to the bottom of the hole
R_ : The distance from the initial level to point R level
P_ : Dwell time at the bottom of a hole
F_ : Cutting feedrate
K_ : Number of repeats (When it is needed.)
M_ : M code for C–axis clamp (When it is needed.)



Explanations

After positioning, rapid traverse is performed to point R.
Drilling is performed from point R to point Z.
After the tool reaches point Z, it returns to point R at a feedrate twice the cutting feedrate.

Examples

```
M51 ;                  Setting C–axis index mode ON
M3 S2000 ;             Rotating the drill
G00 X50.0 C0.0 ;       Positioning the drill along the X– and C–axes
G83 Z–40.0 R–5.0 P500 F5.0 M31 ;  Drilling hole 1
C90.0 M31 ;            Drilling hole 2
C180.0 M31 ;           Drilling hole 3
C270.0 M31 ;           Drilling hole 4
G80 M05 ;              Canceling the drilling cycle and stopping drill rotation
M50 ;                  Setting C–axis index mode off
```

13.3.4 Canned Cycle for Drilling Cancel (G80)

G80 cancels canned cycle.

Format

```
G80 ;
```

Explanations

Canned cycle for drilling is canceled to perform normal operation. Point R and point Z are cleared. Other drilling data is also canceled (cleared).

Examples

```
M51 ;                  Setting C–axis index mode ON
M3 S2000 ;             Rotating the drill
G00 X50.0 C0.0 ;       Positioning the drill along the X– and C–axes.
G83 Z–40.0 R–5.0 P500 F5.0 M31 ;  Drilling hole 1
C90.0 M31 ;            Drilling hole 2
C180.0 M31 ;           Drilling hole 3
C270.0 M31 ;           Drilling hole 4
G80 M05 ;              Canceling the drilling cycle and stopping drill rotation
M50 ;                  Setting C–axis index mode off
```

13.3.5 Precautions to be Taken by Operator

- **Reset and emergency stop**

  Even when the controller is stopped by resetting or emergency stop in the course of drilling cycle, the drilling mode and drilling data are saved ; with this mind, therefore, restart operation.

- **Single block**

  When drilling cycle is performed with a single block, the operation stops at the end points of operations 1, 2, 6 in Fig. 13.3 (a).
  Consequently, it follows that operation is started up 3 times to drill one hole. The operation stops at the end points of operations 1, 2 with the feed hold lamp ON. The operation stops in the feed hold conditions at the end point of operation 6 if the repeat remains, and it stops in stop conditions in other cases.

- **Feed hold**

  When “Feed Hold” is applied between operations 3 and 5 by G84/G88, the feed hold lamp lights up immediately if the feed hold is applied again to operation 6.

- **Override**

  During operation with G84 and G88, the feedrate override is 100%.

13.4 CHAMFERING AND CORNER R

A chamfer or corner can be inserted between two blocks which intersect at a right angle as follows :

- **Chamfering**
  Z → X

Format	Tool movement
G01 Z(W) _ I (C) ±i ; Specifies movement to point b with an absolute or incremental command in the figure on the right.	

Fig. 13.5(a) Chamfering (Z→X)

- **Chamfering**
  X → Z

Format	Tool movement
G01 X(U) _ K (C) ±k ; Specifies movement to point b with an absolute or incremental command in the figure on the right.	

Fig. 13.5(b) Chamfering (X→Z)

- **Corner R**
  Z → X

Format	Tool movement
G01 Z(W) _ R ±r ; Specifies movement to point b with an absolute or incremental command in the figure on the right.	

Fig. 13.5(c) Corner R (Z→X)

- **Corner R**
  X → Z

Format	Tool movement
G01 X(U) _ R ±r ; Specifies movement to point b with an absolute or incremental command in the figure on the right.	

Fig. 13.5(d) Corner R (X→Z)

Explanations

The movement for chamfering or corner R must be a single movement along the X or Z axis in G01 mode. The next block must be a single movement along the X or Z axis perpendicular to the former block.
I or K, and R always specify a radius value.
Note that the start point for a command specified in a block following a chamfering or corner–R block is not point c but point b shown in Figs. 13.5 (a) to (d). In incremental programming, specify a distance from point b.

Examples



NOTE

1 The following commands cause an alarm.
   1) One of I, K, or R is commanded when X and Z axes are specified by G01.
      (P/S alarm No. 054)
   2) Move amount of X or Z is less than chamfering value and corner R value in the block where chamfering and corner R are specified. (P/S alarm No. 055)
   3) Next block to the block where chamfering and corner R were specified, has not G01 command. (P/S alarm No. 051, 052)
   4) If more than one of I, K, and R are specified in G01, P/S alarm No. 053 is issued.
2 During chamfering, a single block stops at point c in Fig. 13.5 (a) and (b), not at point d. During corner R machining, a single block stops at points c and d in Fig. 13.5 (c) and (d).
3 Chamfering and corner R cannot be applied to a thread cutting block.
4 C can be used instead of I or K as an address for chamfering on the system which does not use C as an axis name. To use C for an address for chamfering, fix parameter CCR No. 3405#4 to 1.
5 If both C and R are specified with G01 in a block, the address specified last is valid.
6 Neither chamfering nor corner–R machining can be specified in direct drawing dimension programming.

13.5 MIRROR IMAGE FOR DOUBLE TURRET (G68, G69)

Format

G68 : Double turret mirror image on
G69 : Mirror image cancel

Explanations

Mirror image can be applied to X–axis with G code.
When G68 is designated, the coordinate system is shifted to the mating turret side, and the X–axis sign is reversed from the programmed command to perform symmetrical cutting. To use this function, set the distance between the two turrets to a parameter (No. 1290).

Examples

- **Double turret programming**



X40.0 Z180.0 T0101 ;	Position turret A at (**1**)
G68 ;	Shift the coordinate system by the distance A to B (120mm), and turn mirror image on.
X80.0 Z120.0 T0202 ;	Position turret B at (**2**)
G69 ;	Shift the coordinate system by the distance B to A, and turn mirror image cancel.
X120.0 Z60.0 T0101 ;	Position turret A at (**3**)

13.6 DIRECT DRAWING DIMENSIONS PROGRAMMING

Angles of straight lines, chamfering value, corner rounding values, and other dimensional values on machining drawings can be programmed by directly inputting these values. In addition, the chamfering and corner rounding can be inserted between straight lines having an optional angle. This programming is only valid in memory operation mode.

Format

Table 13.7 Commands table

	Commands	Movement of tool
1	$X_2_$ ($Z_2_$), $A_$;	
2	,$A_1_$; $X_3_$ $Z_3_$, $A_2_$;	
3	$X_2_$ $Z_2_$, $R_1_$; $X_3_$ $Z_3_$; or ,$A_1_$, $R_1_$; $X_3_$ $Z_3_$, $A_2_$;	
4	$X_2_$ $Z_2_$, $C_1_$; $X_3_$ $Z_3_$; or ,$A_1_$, $C_1_$; $X_3_$ $Z_3_$, $A_2_$;	

	Commands	Movement of tool
5	$X_2_\ Z_2_\ , R_1_\ ;$ $X_3_\ Z_3_\ , R_2_\ ;$ $X_4_\ Z_4_\ ;$ or $,A_1_, R_1_\ ;$ $X_3_\ Z_3_, A_2_, R_2_\ ;$ $X_4_\ Z_4_\ ;$	
6	$X_2_\ Z_2_\ , C_1_\ ;$ $X_3_\ Z_3_\ , C_2_\ ;$ $X_4_\ Z_4_\ ;$ or $,A_1_, C_1_\ ;$ $X_3_\ Z_3_, A_2_, C_2_\ ;$ $X_4_\ Z_4_\ ;$	
7	$X_2_\ Z_2_\ , R_1_\ ;$ $X_3_\ Z_3_\ , C_2_\ ;$ $X_4_\ Z_4_\ ;$ or $,A_1_, R_1_\ ;$ $X_3_\ Z_3_, A_2_, C_2_\ ;$ $X_4_\ Z_4_\ ;$	
8	$X_2_\ Z_2_\ , C_1_\ ;$ $X_3_\ Z_3_\ , R_2_\ ;$ $X_4_\ Z_4_\ ;$ or $,A_1_, C_1_\ ;$ $X_3_\ Z_3_, A_2_, R_2_\ ;$ $X_4_\ Z_4_\ ;$	

Explanations

A program for machining along the curve shown in Fig. 13.7 (a) is as follows :



Fig. 13.7 Machining drawing (example)

For command a straight line, specify one or two out of X, Z, and A.
If only one is specified, the straight line must be primarily defined by a command in the next block.
To command the degree of a straight line or the value of chamfering or corner R, command with a comma (,) as follows :

, A_
, C_
, R_

By specifying 1 to parameter CCR No. 3405#4 on the system which does not use A or C as an axis name, the degree of a straight line or the value of chamfering or corner R can be commanded without a comma (,) as follows :

A_
C_
R_

NOTE

1 The following G codes are not applicable to the same block as commanded by direct input of drawing dimensions or between blocks of direct input of drawing dimensions which define sequential figures.
   1) G codes (other than G04) in group 00.
   2) G02, G03, G90, G92, and G94 in group 01.
2 Corner rounding cannot be inserted into a threading block.
3 Chamfering and corner R using the direct input of drawing dimensions cannot be used simultaneously with the chamfering and corner R described in Section 13.5. (The option for chamfering and corner R and that for the direct input of drawing dimensions cannot be selected simultaneously.)
4 When the end point of the previous block is determined in the next block according to sequential commands of direct input of drawing dimensions, the single block stop is not done, but the feed hold stop is done at the end point of the previous block.
5 The angle allowance in calculating the point of intersection in the program below is ±1°.
   (Because the travel distance to be obtained in this calculation is too large.)
   1) X_ , A_ ; (If a value within 0°±1°or 180°±1°is specified for the angle instruction, the P/S alarm No.057 occurs.)
   2) Z_ , A_ ; (If a value within 90°±1°or 270°±1°is specified for the angle instruction, the P/S alarm No. 057 occurs.)
6 An alarm occurs if the angle made by the 2 lines is within ±1°when calculating the point of intersection.
7 Chamfering or corner % is ignored if the angle made by the 2 lines is within ±1°.
8 Both a dimensional command (absolute programming) and angle instruction must be specified in the block following a block in which only the angle instruction is specified.
   (Example)

```
N1 X_, A_, R_ ;
N2, A_ ;
N3 X_ Z_, A_ ;
```

   (In addition to the dimentional command, angle instruction must be specified in block No. 3.)

Examples



(Diameter specification, metric input)

```
N001 G50 X0.0 Z0.0 ;
N002 G01 X60.0, A90.0, C1.0 F80 ;
N003 Z–30.0, A180.0, R6.0 ;
N004 X100.0, A90.0 ;
N005 ,A170.0, R20.0 ;
N006 X300.0 Z–180.0, A112.0, R15.0 ;
N007 Z–230.0, A180.0 ;
     :
     :
```

13.7 RIGID TAPPING

Front face tapping cycles (G84) and side face tapping cycles (G88) can be performed either in conventional mode or rigid mode.

In conventional mode, the spindle is rotated or stopped, in synchronization with the motion along the tapping axis according to miscellaneous functions M03 (spindle CW rotation), M04 (spindle CCW rotation), and M05 (spindle stop).

In rigid mode, the spindle motor is controlled in the same way as a control motor, by the application of compensation to both motion along the tapping axis and that of the spindle.

For rigid tapping, each turn of the spindle corresponds to a certain amount of feed (screw lead) along the spindle axis. This also applies to acceleration/deceleration. This means that rigid tapping does not demand the use of float tappers as in the case of conventional tapping, thus enabling high–speed, high–precision tapping.

When the system is equipped with the optional multispindle control function, the second spindle can be used for rigid tapping.

13.7.1 Front Face Rigid Tapping Cycle (G84) / Side Face Rigid Tapping Cycle (G88)

Controlling the spindle motor in the same way as a servo motor in rigid mode enables high–speed tapping.

Format

G84 X(U)_ C(H)_ Z(W)_ R_ P_ F_ M_ K_ ;
or
G88 Z(W)_ C(H)_ X(U)_ R_ P_ F_ M_ K_ ;

X_ C_ or Z_ C_ : Hole position data
Z_ or X_ : The distance from point R to the bottom of the hole
R_ : The distance from the initial level to point R level
P_ : Dwell time at the bottom of a hole
F_ : Cutting feedrate
K_ : Number of repeats (When it is needed.)
M_ : M code for C–axis clamp (when it is needed.)

G84 or G88 (G98 mode)



G84 or G88 (G99 mode)



Explanations

Once positioning for the X–axis (G84) or Z–axis (G88) has been completed, the spindle is moved, by rapid traverse, to point R. Tapping is performed from point R to point Z, after which the spindle stops and observes a dwell time. Then, the spindle starts reverse rotation, retracts to point R, stops rotating, then moves to the initial level by rapid traverse. During tapping, the feedrate override and spindle override are assumed to be 100%. For retraction (operation 5), however, a fixed override of up to 200% can be applied by setting parameter No. 5211 (RGOVR) and bit 4 (DOV) of parameter No. 5200.

- **Rigid mode**

Rigid mode can be specified by applying any of the following methods:

- Specifying M29S***** before a tapping block
- Specifying M29S***** within a tapping block
- Handling G84 or G88 as a G code for rigid tapping (Set bit 0 (G84) of parameter No. 5200 to 1.)

- **Screw lead**

In feed per minute mode, the feedrate divided by the spindle speed is equal to the screw lead. In feed per rotation mode, the feedrate is equal to the screw lead.

Limitations

- **S commands**

When a value exceeding the maximum rotation speed for the gear being used is specified, P/S alarm No. 200 is issued. For an analog spindle, when a command is specified such that more than 4095 pulses are generated during 8 ms (detection unit), P/S alarm No. 202 is issued. For a serial spindle, when a command is specified such that more than 32767 pulses are generated during 8 ms (detection unit), P/S alarm No. 202 is issued.

<Example>

For a built–in motor equipped with a detector having a resolution of 4095 pulses per rotation, the maximum spindle speed during rigid tapping is as follows:

For an analog spindle

(4095×1000÷8×60)÷4095 = 7500 (rpm)

For a serial spindle

(32767×1000÷8×60)÷4095 = 60012 (rpm) [Note: Ideal value]

- **F commands**

Specifying a value larger than the upper limit for cutting feed will cause P/S alarm No. 201 to be issued.

- **M29**

Specifying an S command or axis movement between M29 and M84 will cause P/S alarm No. 203 to be issued. Specifying M29 during a tapping cycle will cause P/S alarm No. 204 to be issued.

- **Rigid tapping command M code**

The M code used to specify rigid tapping mode is usually set in parameter No. 5210. To set a value of more than 255, however, use parameter No. 5212.

- **Maximum position deviation during movement along the tapping axis**

The maximum position deviation during movement along the tapping axis in rigid tapping mode is usually set in parameter No. 5310. Use parameter No. 5314, however, when setting a value of more than 32767, for example, according to the resolution of the detector being used.

- **R**

The value of R must be specified in a block which performs drilling. If the value is specified in a block which does not perform drilling, it is not stored as modal data.

- **Cancellation**

G00 to G03 (G codes in group 01) must not be specified in a block containing G84 or G88. If specified, G84 or G88 in that block is canceled.

- **Tool position offset**

Any tool position offset is ignored in canned cycle mode.

- **Units for F**

	Metric input	Inch input	Remark
G98	1 mm/min	0.01inch/min	Decimal point allowed
G99	0.01mm/rev	0.0001inch/rev	Decimal point allowed

Examples

Tapping axis feedrate: 1000 mm/min
Spindle speed: 1000 rpm
Screw lead: 1.0 mm

<Programming for feed per minute>

G98 ;	Command for feed per minute
G00 X100.0 ;	Positioning
M29 S1000 ;	Command for specifying rigid mode
G84 Z–100.0 R–20.0 F1000 ;	Rigid tapping

<Programming for feed per rotation>

G99 ;	Command for feed per rotation
G00 X100.0 ;	Positioning
M29 S1000 ;	Command for specifying rigid mode
G84 Z–100.0 R–20.0 F1.0 ;	Rigid tapping

14 COMPENSATION FUNCTION

This chapter describes the following compensation functions:

14.1 TOOL OFFSET

14.2 OVERVIEW OF TOOL NOSE RADIUS COMPENSATION

14.3 DETAILS OF TOOL NOSE RADIUS COMPENSATION

14.4 TOOL COMPENSATION VALUES, NUMBER OF COMPENSATION VALUES, AND ENTERING VALUES FROM THE PROGRAM (G10)

14.5 AUTOMATIC TOOL OFFSET (G36, G37)

14.1 TOOL OFFSET

Tool offset is used to compensate for the difference when the tool actually used differs from the imagined tool used in programming (usually, standard tool).



Fig. 14.1 Tool offset

In this unit, there is no G code to specify tool offset.
The tool offset is specified by T code.

14.1.1 Tool Geometry Offset and Tool Wear Offset

Tool geometry offset and tool wear offset are possible to divide the tool offset to the tool geometry offset for compensating the tool shape or tool mounting position and the tool wear offset for compensating the tool nose wear.
Total value of tool geometry offset value and tool wear offset value is set as the tool wear offset value without option.

NOTE
Tool geometry offset and tool wear offset are optioned.



Fig. 14.1.1(a) Difference the tool geometry offset from tool wear offset

Fig. 14.1.1(b) Not difference the tool geometry offset from tool wear offset

14.1.2 T Code for Tool Offset

There are two methods for specifying a T code as shown in Table 14.1.2(a) and Table 14.1.2(b).

Format

- **Lower digit of T code specifies geometry and wear offset number**

Table 14.1.2(a)

Kind of T code	Meaning of T code	Parameter setting for specifying of offset No.	
2–digit command	T ○ ○ Tool wear and tool geometry offset number Tool selection	When LD1, bit 0 of parameter No.5002, is set to 1, a tool wear offset number is specified with the last digit of a T code.	When LGN, bit 1 of parameter No.5002, is set to 0, the tool geometry offset number and tool wear offset number specified for a certain tool are the same.
4–digit command	T ○○ ○○ Tool wear and tool geometry offset number Tool selection	When LD1, bit 0 of parameter No.5002, is set to 0, a tool wear offset number is specified with the last two digits of a T code.	

- **Lower digit of T code specifies wear offset number and higher digit number specifies tool selection number and geometry offset number**

Table 14.1.2(b)

Kind of T code	Meaning of T code	Parameter setting for specifying of offset No.	
2–digit command	T ○ ○ Tool wear offset number Tool selection and tool geometry offset number	When LD1, bit 0 of parameter No.5002, is set to 1, a tool wear offset number is specified with the last digit of a T code.	When LGN, bit 1 of parameter No.5002, is set to 0, the tool geometry offset number and tool wear offset number specified for a certain tool are the same.
4–digit command	T ○○ ○○ Tool wear offset number Tool selection and tool geometry offset number	When LD1, bit 0 of parameter No.5002, is set to 0, a tool wear offset number is specified with the last two digits of a T code.	

14.1.3 Tool Selection

Tool selection is made by specifying the T code corresponding to the tool number. Refer to the machine tool builder's manual for the relationship between the tool selection number and the tool.

14.1.4 Offset Number

Tool offset number has two meanings.
It is specifies the offset distance corresponding to the number that is selected to begin the offset function. A tool offset number of 0 or 00 indicates that the offset amount is 0 and the offset is cancelled.

14.1.5 Offset

There are two types of offset. One is tool wear offset and the other is tool geometry offset.

Explanations

- **Tool wear offset**

The tool path is offset by the X, Y, and Z wear offset values for the programmed path. The offset distance corresponding to the number specified by the T code is added to or subtracted from the and position of each programmed block.



Fig. 14.1.5(a) Movement of offset (1)

- **Offset vector**

In Fig. 14.1.5(a), the vector with offset X, Y, and Z is called the offset vector. Compensation is the same as the offset vector.

- **Offset cancel**

Offset is cancelled when T code offset number 0 or 00 is selected. At the end of the cancelled block, the offset vector becomes 0.

N1 X50.0 Z100.0 T0202 ; Creates the offset vector corresponding to offset number 02

N2 X200.0 ;

N3 X100.0 Z250.0 T0200 ; Specifying offset number 00 deletes the offset vector.



Fig. 14.1.5(b) Movement of offset (2)

When the power is first turned on , and the reset key on the MDI units is pushed or the reset signal is input to the CNC from the machine tool, the offset is cancelled.
Parameter LVK (No.5003#6) can be set so that offset will not be cancelled by pressing the reset key or by reset input.

- **Only T code**

When only a T code is specified in a block, the tool is moved by the wear offset value without a move command. The movement is performed at rapid traverse rate in the G00 mode . It is performed at feedrate in other modes.
When a T code with offset number 0 or 00is specified by itself, movement is performed to cancel the offset.

WARNING
When G50 X_Z_T_ ; is specified
Tool is not moved.
The coordinate system in which the coordinate value of the tool position is (X,Z) is set. The tool position is obtained by subtracting the wear offset value corresponding to the offset number specified in the T code.

- **Tool geometry offset**

With the tool geometry offset, the work coordinate system is shifted by the X, Y, and Z geometry offset amounts. Namely, the offset amount corresponding to the number designated with the code is added to or subtracted from the current position.



Fig. 14.1.5(c) Movement of tool geometry offset

NOTE
As well as wear offset, the tool can be compensated by parameter setting LGT(No.5002#4) to add or subtract the programmed end point of each block.

- **Offset cancel**

Specifying offset number 0, 00, or 0000 cancels offset.

NOTE
When LGC, bit 5 of parameter No.5002, is set to 0, specifying offset number 0 or 00 does not cancel offset.

Examples

1. When a tool geometry offset number and tool wear offset number are specified with the last two digits of a T code
   (when LGN, bit 1 of parameter No.5002, is set 0),
   N1 X50.0 Z100.0 T0202 ; Specifies offset number 02
   N2 Z200.0 ;
   N3 X100.0 Z250.0 T0200 ; Cancels offset



NOTE
When LGC, bit 5 of parameter No.5002, is set to 0, specifying offset number 0 does not cancel tool geometry offset.

2. Assume that geometry offset is not cancelled with offset No.0
   (Set the parameter (No.5002#1).)
   N1 X50.0 Z100.0 T0202 ; Tool selection number (specified tool geometry offset number 02)
   N2 Z200.0 ;
   N3 X100.0 Z250.0 T0000 ; Cancels offset



14.1.6 G53, G28, G30, and G30.1 Commands When Tool Position Offset is Applied

This section describes the following operations when tool position offset is applied: G53, G28, G30, and G30.1 commands, manual reference position return, and the canceling of tool position offset with a T00 command.

Explanations

- **Reference position return (G28) and G53 command when tool position offset is applied**

Executing reference position return (G28) or a G53 command when tool position offset is applied does not cancel the tool position offset vector. The absolute position display is as follows, however, according to the setting of bit 4 (LGT) of parameter No. 5002.

LGT = 0 (Tool geometry compensation is based on shift of the coordinate system.)

		Tool position offset (without option)	Tool geometry compensation	Tool wear compensation
Absolute position coordinate display	Block for reference position return or G53 command	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.	The shift is reflected. Coordinates shifted according to the tool geometry compensation are displayed.	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.
	Next block	The vector is reflected.	Coordinates shifted according to the tool geometry compensation are displayed.	The vector is reflected.

LGT = 1 (Tool geometry compensation is based on tool movement.)

		Tool position offset (without option)	Tool geometry compensation	Tool wear compensation
Absolute position coordinate display	Block for reference position return or G53 command	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.
	Next block	The vector is reflected.	The vector is reflected.	The vector is reflected.

NOTE
Bit 6 (DAL) of parameter No. 3104 is set to 0 (the actual positions to which the tool position offset is applied are displayed in the absolute position display).

- **Manual reference position return when tool position offset is applied**

Executing manual reference position return when tool position offset is applied does not cancel the tool position offset vector. The absolute position display is as follows, however, according to the setting of bit 4 (LGT) of parameter No. 5002.

LGT = 0 (Tool geometry compensation is based on shift of the coordinate system.)

		Tool position offset (without option)	Tool geometry compensation	Tool wear compensation
Absolute position coordinate display	Upon manual reference position return	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.	The shift is reflected. Coordinates shifted according to tool geometry compensation are displayed.	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.
	Next block	The vector is reflected.	Coordinates shifted according to tool geometry compensation are displayed.	The vector is reflected.

LGT = 1 (Tool geometry compensation is based on tool movement.)

		Tool position offset (without option)	Tool geometry compensation	Tool wear compensation
Absolute position coordinate display	Upon manual reference position return	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.	The vector is not reflected. The coordinates are displayed as if the offset had been temporarily canceled.
	Next block	The vector is reflected.	The vector is reflected.	The vector is reflected.

NOTE

Bit 6 (DAL) of parameter No. 3104 is set to 0 (the actual positions to which the tool position offset is applied are displayed in the absolute position display).

- **Canceling tool position offset with T00**

Whether specifying T00 alone, while tool position offset is applied, cancels the offset depends on the settings of the following parameters:

When the tool geometry/wear compensation option is selected

LGN = 0

LGN (No.5002#1)	LGT (No.5002#4)	LGC (No.5002#5)	
The geometry offset number is: 0: Same as the wear offset number 1: Same as the tool selection number	Geometry compensation is applied: 0: Based on shift of the coordinate system 1: Based on movement of the tool	The geometry offset is: 0: Not canceled with T00 1: Canceled with T00	Result
LGT=0	LGT=0	LGC=0 LGC=1	Not canceled Canceled
		LWM (No.5002#6) Tool position offset is applied: 0: By means of T code 1: By means of movement along axis	
	LGT=1	LWM=0 LWM=1	Canceled Not canceled

NOTE
1 When LGT=0, LWM is unrelated.
2 When LGT=1, LGC is unrelated, even when LGN = 0.

LGN = 1

LGN (No.5002#1)	LGT (No.5002#4)	LGC (No.5002#5)	
The geometry offset number is: 0: Same as the wear offset number 1: Same as the tool selection number	Geometry compensation is applied: 0: Based on shift of the coordinate system 1: Based on movement of the tool	The geometry offset is: 0: Not canceled with T00 1: Canceled with T00	Result
LGT=0	LGT=0	LGC is unrelated.	Canceled
		LWM (No.5002#6) Tool position offset is applied: 0: By means of T code 1: By means of movement along axis	
	LGT=1	LWM=0 LWM=1	Canceled Not canceled

NOTE
1 When LGT = 0, LWM is unrelated.
2 When LGT = 1, LGC is unrelated.

When the tool geometry/wear compensation option is not selected

<table>
<tr><th>LGN (No.5002#1)</th><th>LGT (No.5002#4)</th><th>LGC (No.5002#5)</th><th></th></tr>
<tr><td>The geometry offset number is:
0: Same as the wear offset number
1: Same as the tool selection number</td><td>Geometry compensation is applied:
0: Based on shift of the coordinate system
1: Based on movement of the tool</td><td>The geometry offset is:
0: Not canceled with T00
1: Canceled with T00</td><td>Result</td></tr>
<tr><td rowspan="4">LGN is unrelated.

The tool position offset number always uses the low–order digits.</td><td rowspan="4">LGT is unrelated.

Tool position offset is always applied based on the movement of the tool.</td><td>LGC is unrelated.</td><td rowspan="3"></td></tr>
<tr><td>LWM (No.5002#6)</td></tr>
<tr><td>Tool position offset is applied:
0: By means of T code
1: By means of movement along axis</td></tr>
<tr><td>LWM=0
LWM=1</td><td>Canceled
Not canceled</td></tr>
</table>

14.2 OVERVIEW OF TOOL NOSE RADIUS COMPENSATION

It is difficult to produce the compensation necessary to form accurate parts when using only the tool offset function due to tool nose roundness in taper cutting or circular cutting. The tool nose radius compensation function compensates automatically for the above errors.



Fig 14.2 Tool path of tool nose radius compensation

14.2.1 Imaginary Tool Nose

The tool nose at position A in following figure does not actually exist.
The imaginary tool nose is required because it is usually more difficult to set the actual tool nose radius center to the start position than the imaginary tool nose (Note).
Also when imaginary tool nose is used, the tool nose radius need not be considered in programming.
The position relationship when the tool is set to the start position is shown in the following figure.



Fig. 14.2.1(a) Tool nose radius center and imaginary tool nose

CAUTION

In a machine with reference positions, a standard position like the turret center can be placed over the start position. The distance from this standard position to the nose radius center or the imaginary tool nose is set as the tool offset value.

Setting the distance from the standard position to the tool nose radius center as the offset value is the same as placing the tool nose radius center over the start position, while setting the distance from the standard position to the imaginary tool nose is the same as placing the imaginary tool nose over the standard position. To set the offset value, it is usually easier to measure the distance from the standard position to the imaginary tool nose than from the standard position to the tool nose radius center.



Fig 14.2.1(b) Tool offset value when the turret center is placed over the start position



Fig 14.2.1(c) Tool path when programming using the tool nose center



Fig 14.2.1(d) Tool path when programming using the imaginary tool nose

14.2.2 Direction of Imaginary Tool Nose

The direction of the imaginary tool nose viewed from the tool nose center is determined by the direction of the tool during cutting, so it must be set in advance as well as offset values.
The direction of the imaginary tool nose can be selected from the eight specifications shown in the Fig. 14.2.2 below together with their corresponding codes.
This Fig 14.2.2 illustrates the relation between the tool and the start position. The following apply when the tool geometry offset and tool wear offset option are selected.



Fig. 14.2.2 Direction of imaginary tool nose

Imaginary tool nose numbers 0 and 9 are used when the tool nose center coincides with the start position. Set imaginary tool nose number to address OFT for each offset number.
Bit 7 (WNP) of parameter No. 5002 is used to determine whether the tool geometry offset number or the tool wear offset number specifies the direction of the virtual tool nose for tool nose radius compensation.



Limitations

- **Plane selection**

Virtual tool nose directions 1 to 8 can be used only in the G18 (Z–X) plane. For virtual tool nose 0 or 9, compensation is applied in both the G17 and G19 planes.

14.2.3 Offset Number and Offset Value

Explanations

- **Offset number and offset value**



This value is set from the MDI according to the offset number.
When the options of tool geometry compensation and tool wear compensation are selected, offset values become as follows :

Table 14.2.3(a) Offset number and offset value

Offset number	OFX (Offset value on X axis)	OFZ (Offset value on Z axis)	OFR (Tool nose radius compensation value)	OFT (Direction of imaginary tool nose)	OFY (Offset value on Y axis)
01	0.040	0.020	0.20	1	0.030
02	0.060	0.030	0.25	2	0.040
:	:	:	:	:	:
98	0.050	0.015	0.12	6	0.025
99	0.030	0.025	0.24	3	0.035

When the options of tool geometry compensation and tool wear compensation are selected, the offset values become as follows :

Table 14.2.3(b) Tool geometry offset

Geometry offset number	OFGX (X–axis geometry offset amount)	OFGZ (Z–axis geometry offset amount)	OFGR (Tool nose radius geometry offset value)	OFT (Imaginary tool nose direction)	OFGY (Y–axis geometry offset amount)
G01	10.040	50.020	0	1	70.020
G02	20.060	30.030	0	2	90.030
G03	0	0	0.20	6	0
G04	:	:	:	:	:
G05	:	:	:	:	:
:	:	:	:	:	:

Table 14.2.3(c) Tool wear offset

Wear offset number	OFGX (X–axis wear offset amount)	OFGZ (Z–axis wear offset amount)	OFGR (Tool nose radius wear offset value)	OFT (Imaginary tool nose direction)	OFGY (Y–axis wear offset amount)
W01	0.040	0.020	0	1	0.010
W02	0.060	0.030	0	2	0.020
W03	0	0	0.20	6	0
W04	:	:	:	:	:
W05	:	:	:	:	:
:	:	:	:	:	:

- **Tool nose radius compensation**

In this case, the tool nose radius compensation value is the sum of the geometry or the wear offset value.

OFR=OFGR+OFWR

- **Imaginary tool nose direction**

The imaginary tool nose direction may be set for either the geometry offset or the wear offset.
However, the last designated direction later is effective.

- **Command of offset value**

A offset number is specified with the same T code as that used for tool offset. For details, see Subsec. II–14.1.2.

NOTE

When the geometry offset number is made common to the tool selection by the parameter LGT(No.5002#1)setting and a T code for which the geometry offset and wear offset number differ from each other is designated, the imaginary tool nose direction specified by the geometry offset number is valid.

Example) T0102
$OFR=RFGR_{01}+OFWR_{02}$
$OFT=OFT_{01}$

- **Setting range of offset value**

The range of the offset value is an follows :

Increment system	metric system	Inch system
IS–B	0 to ±999.999 mm	0 to ±99.9999 inch
IS–C	0 to ±999.9999 mm	0 to ±99.99999 inch

The offset value corresponding to the offset number 0 is always 0.
No offset value can be set to offset number 0.

14.2.4 Work Position and Move Command

In tool nose radius compensation, the position of the workpiece with respect to the tool must be specified.

G code	Workpiece position	Tool path
G40	(Cancel)	Moving along the programmed path
G41	Right side	Moving on the left side the programmed path
G42	Left side	Moving on the right side the programmed path

The tool is offset to the opposite side of the workpiece.



The workpiece position can be changed by setting the coordinate system as shown below.



G40, G41, and, G42 are modal.
Don’t specify G41 while in the G41 mode. If you do, compensation will not work properly.
Don’t specify G42 while in the G42 mode for the same reason.
G41 or G42 mode blocks in which G41 or G42 are not specified are expressed by (G41) or (G42) respectively.

- **Tool movement when the workpiece position does not change**

When the tool is moving, the tool nose maintains contact with the workpiece.



- **Tool movement when the workpiece position changes**

The workpiece position against the toll changes at the corner of the programmed path as shown in the following figure.



Although the workpiece does not exist on the right side of the programmed path in the above case. the existence of the workpiece is assumed in the movement from A to B. The workpiece position must not be changed in the block next to the start–up block. In the above example, if the block specifying motion from A to B were the start–up block, the tool path would not be the same as the one shown.

- **Start–up**

The block in which the mode changes to G41 or G42 from G40 is called the start–up block.

G40 _ ;

G41 _ ; (Start–up block)

Transient tool movements for offset are performed in the start–up block. In the block after the start–up block, the tool nose center is positioned Vertically to the programmed path of that block at the start position.



- **Offset cancel**

The block in which the mode changes to G40 from G41 or G42 is called the offset cancel block.

G41 _ ;

G40 _ ; (Offset cancel block)

The tool nose center moves to a position vertical to the programmed path in the block before the cancel block. The tool is positioned at the end position in the offset cancel block (G40) as shown below.



- **Specification of G41/G42 in G41/G42 mode**

When is specified again in G41/G42 mode , the tool nose center is positioned vertical to the programmed path of the preceding block at the end position of the preceding block.



In the block that first specifies G41/G42, the above positioning of the tool nose center is not performed.

- **Tool movement when the moving direction of the tool in a block which includes a G40 command is different from the direction of the workpiece**

When you wish to retract the tool in the direction specified by X(U) and Z(W) cancelling the tool nose radius compensation at the end of machining the first block in the figure below, specify the following :

G40 X(U) _ Z(W) _ I _ K _ ;



The workpiece position specified by addresses I and K is the same as that in the preceding block. If I and/or K is specified with G40 in the cancel mode, the I and/or K is ignored.

G40 X_ Z_ I_ K_ ;	Tool nose radius compensation
G40 G02 X_ Z_ I_ K_ ;	Circular interpolation

G40 G01 X_ Z_ ;
G40 G01 X_ Z_ I_ K_ ; Offset cancel mode (I and k are ineffective.)
The numeral s followed I and K should always be specified as radius values.

Examples



(G40 mode)
1.G42 G00 X60.0 ;
2.G01 X120.0 W–150.0 F10 ;
3.G40 G00 X300.0 W150.0 I40.0 K–30.0 ;

14.2.5 Notes on Tool Nose Radius Compensation

Explanations

- **Tool movement when two or more blocks without a move command should not be programmed consecutively**

1.M05 ;	M code output
2.S210 ;	S code output
3.G04 X1000 ;	Dwell
4.G01 U0 ;	Feed distance of zero
5.G98 ;	G code only
6.G10 P01 X10.0 Z20.0 R0.5 Q2 ;	Offset change

If two or more of the above blocks are specified consecutively, the tool nose center comes to a position vertical to the programmed path of the preceding block at the end of the preceding block. However, if the no movement commands is **4** above, the above tool motion is attained only with one block.



- **Tool nose radius compensation with G90 or G94**

Tool nose radius compensation with G90 (outer diameter/internal diameter cutting cycle) or G94 (end face turning cycle) is as follows, :

1. Motion for imaginary tool nose numbers
For each path in the cycle, the tool nose center path is generally parallel to the programmed path.



2. Direction of the offset

The offset direction is indicated in the figure below regardless of the G41/G42 mode.



- **Tool nose radius compensation with G71 to G76 or G78**

When one of following cycles is specified, the cycle deviates by a tool nose radius compensation vector. During the cycle, no intersection calculation is performed.

G71 (Stock removal in turning or traverse grinding cycle)
G72 (Stock removal in facing or traverse direct constant–dimension grinding cycle)
G73 (Pattern repeating or Oscillation grinding cycle)
G74 (End face peck drilling)
G75 (Outer diameter/internal diameter drilling)
G76 (Multiple threading cycle)
G78 (Threading cycle)

- **Tool nose radius compensation when chamfering is performed**

Movement after after compensation is shown below.



- **Tool nose radius compensation when a corner arc is inserted**

Movement after compensation is shown below.



- **Tool nose radius compensation when the block is specified from the MDI**

In this case, tool nose radius compensation is not performed.

14.3 DETAILS OF TOOL NOSE RADIUS COMPENSATION

This section provides a detailed explanation of the movement of the tool for tool nose radius compensation outlined in Section 14.2.
This section consists of the following subsections:

14.3.1 General
14.3.2 Tool Movement in Start–up
14.3.3 Tool Movement in Offset Mode
14.3.4 Tool Movement in Offset Mode Cancel
14.3.5 Interference Check
14.3.6 Overcutting by Tool Nose Radius Compensation
14.3.7 Correction in Chamfering and Corner Arcs
14.3.8 Input Command from MDI
14.3.9 General Precautions for Offset Operations
14.3.10 G53, G28, G30, and G30.1 Commands in Tool–tip Radius Compensation Mode

14.3.1 General

- **Tool nose radius center offset vector**

The tool nose radius center offset vector is a two dimensional vector equal to the offset value specified in a T code, and the is calculated in the CNC. Its dimension changes block by block according to tool movement.
This offset vector (simply called vector herein after) is internally crated by the control unit as required for proper offsetting and to calculate a tool path with exact offset (by tool nose radius) from the programmed path. This vector is deleted by resetting.
The vector always accompanies the tool as the tool advances.
Proper understanding of vector is essential to accurate programming. Read the description below on how vectors are created carefully.

- **G40, G41, G42**

G40, G41 or G42 is used to delete or generate vectors.
These codes are used together with G00, G01, G02, G03 or G33 to specify a mode for tool motion (Offsetting).

G code	Function	Workpiece position
G40	Tool nose radius compensation cancel	Neither
G41	Left offset along tool path	Right
G42	Right offset along tool path	Left

G41 and G42 specify an off mode, while G40 specifies cancellation of the offset.

- **Cancel mode**

The system enters the cancel mode immediately after the power is turned on, when the RESET button on the MDI is pushed or a program is forced to end by executing M02 or M30. (the system may not enter the cancel mode depending on the machine tool.) In the cancel mode, the vector is set to zero, and the path of the center of tool nose coincides with the programmed, path. A program must end in cancel mode. If it ends in the offset mode, the tool cannot be positioned at the end point, and the tool stops at a location the vector length away from the end point.

● Start–up

When a block which satisfies all the following conditions is executed in cancel mode, the system enters the offset mode. Control during this operation is called start–up.

- G41 or G42 is contained in the block, or has been specified to set the system enters the offset mode. Control during this operation is called start–up.
- The offset number for tool nose radius compensation is not 00.
- X or Z moves is specified in the block and the move distance is not zero.

A circular command (G02 or G03) is not allowed in start–up.
If specified, P/S alarm (PS34) will occur. Two blocks are read in during start– up. The first block is executed, and the second block is entered into the tool nose radius compensation buffer. In the single block mode, two blocks are read and the first block is executed, then the machine stops. In subsequent operations, two blocks are read in advance, so the CNC has the block currently being executed, and the next two blocks.

● Inner side and outer side

When an angle of intersection created by tool paths specified with move commands for two blocks is over 180°, it is referred to as “inner side.” When the angle is between 0° and 180°, it is referred to as “outer side.”



● Meaning of symbols

The following symbols are used in subsequent figures:
– ***S*** indicates a position at which a single block is executed once.
– ***SS*** indicates a position at which a single block is executed twice.
– ***SSS*** indicates a position at which a single block is executed three times.
– ***L*** indicates that the tool moves along a straight line.
– ***C*** indicates that the tool moves along an arc.
– ***r*** indicates the tool nose radius compensation value.
– An intersection is a position at which the programmed paths of two blocks intersect with each other after they are shifted by ***r***.
– indicates ○ the center of the tool nose radius.

14.3.2 Tool Movement in Start–up

When the offset cancel mode is changed to offset mode, the tool moves as illustrated below (start–up):

Explanations

- **Tool movement around an inner side of a corner (180° ≦ α)**



- **Tool movement around the outside of a corner at an obtuse angle (90° ≦ α<180°)**



- **Tool movement around the outside of an acute angle (α<90°)**



- **Tool movement around the outside linear→linear at an acute angle less than 1 degree (α<1°)**



- **A block without tool movement specified at start–up**

If the command is specified at start–up, the offset vector is not created.

```
G91 G40 … ;
      :
N6 U100.0 W100.0 ;
N7 G41 U0 ;
N8 U–100.0 ;
N9 U–100.0 W100.0 ;
```



NOTE
For the definition of blocks that do not move the tool, see Subsec. II–14.3.3.

14.3.3 Tool Movement in Offset Mode

In the offset mode, the tool moves as illustrated below:

Explanations

- **Tool movement around the inside of a corner (180° ≦ α)**



- **Tool movement around the inside (α<1°) with an abnormally long vector, linear → linear**



Also in case of arc to straight line, straight line to arc and arc to arc, the reader should infer in the same procedure.

- **Tool movement around the outside corner at an obtuse angle (90° ≦ α<180°)**



- **Tool movement around the outside corner at an acute angle (α<90°)**



- **When it is exceptional**

  - End position for the arc is not on the arc

If the end of a line leading to an arc is programmed as the end of the arc by mistake as illustrated below, the system assumes that tool nose radius compensation has been executed with respect to an imaginary circle that has the same center as the arc and passes the specified end position. Based on this assumption, the system creates a vector and carries out compensation. The resulting tool nose radius center path is different from that created by applying tool nose radius compensation to the programmed path in which the line leading to the arc is considered straight.



The same description applies to tool movement between two circular paths.

- There is no inner intersection

If the tool nose radius compensation value is sufficiently small, the two circular Tool nose radius center paths made after compensation intersect at a position (P). Intersection P may not occur if an excessively large value is specified for tool nose radius compensation. When this is predicted, P/S alarm (No.33) occurs at the end of the previous block and the tool is stopped. In the example shown below, Tool nose radius center paths along arcs A and B intersect at P when a sufficiently small value is specified for tool nose radius compensation. If an excessively large value is specified, this intersection does not occur.



- The center of the arc is identical with the start position or the end position

If the center of the arc is identical with the start position or end point, P/S alarm (No. 038) is displayed, and the tool will stop at the end position of the preceding block.



● Change in the offset direction in the offset mode

The offset direction is decided by G codes (G41 and G42) for tool nose radius and the sign of tool nose radius compensation value as follows.

Sign of offset value / G code	+	–
G41	Left side offset	Right side offset
G42	Right side offset	Left side offset

The offset direction can be changed in the offset mode. If the offset direction is changed in a block, a vector is generated at the intersection of the tool nose radius center path of that block and the tool nose radius center path of a preceding block. However, the change is not available in the start–up block and the block following it.

- Tool nose radius center path with an intersection



- Tool nose radius center path without an intersection

When changing the offset direction in block A to block B using G41 and G42, if intersection with the offset path is not required, the vector normal to block B is created at the start point of block B.



- **Temporary tool nose radius compensation cancel**

If the following command is specified in the offset mode, the offset mode is temporarily canceled then automatically restored. The offset mode can be canceled and started as described in Subsections II–14.3.2 and II–14.3.4.

- Specifying G28 (automatic return to the reference position) in the offset mode

If G28 is specified in the offset mode, the offset mode is canceled at an intermediate position. If the vector still remains after the tool is returned to the reference position, the components of the vector are reset to zero with respect to each axis along which reference position return has been made.



- Tool nose radius compensation G code in the offset mode

The offset vector can be set to form a right angle to the moving direction in the previous block, irrespective of machining inner or outer side, by commanding the tool nose radius compensation G code (G41, G42) in the offset mode, independently. If this code is specified in a circular command, correct circular motion will not be obtained.
When the direction of offset is expected to be changed by the command of tool nose radius compensation G code (G41, G42), refer to ”Change in the offset direction in the offset mode” in Subsec.14.3.3.



- **Command cancelling the offset vector temporality**

During offset mode, if G50 is commanded,the offset vector is temporarily cancelled and thereafter offset mode is automatically restored.
In this case, without movement of offset cancel, the tool moves directly from the intersecting point to the commanded point where offset vector is canceled. Also when restored to offset mode, the tool moves directly to the intersecting point.

- **Workpiece coordinate system setting (G50)**




```
(G41)
N5 G91 G01 U700.0 W300.0 ;
N6 U600.0 W–300.0 ;
N7 G50 X200.0 Z100.0 ;
N8 G01 X800.0 Z400.0 ;
```

- **Canned cycles (G90, G92, G94) and Multiple repetitive cycles (G71 to G76)**

See Sections II–14.1 (G90, G92, G94) and II–14.2 (G70 to G76) for the tool nose radius compensation is related canned cycles.




```
(G42)
N5 G01 U500.0 W600.0 ;
N6 W–800.0 ;
N7 G90 U–600.0 Z–800.0 I–300.0 ;
N8 U1200.0 W500.0 ;
```

- **A block without tool movement**

The following blocks have no tool movement. In these blocks, the tool will not move even if tool nose radius compensation is effected.

1. M05 ; M code output
2. S21 ; S code output
3. G04 X10.0 ; Dwell
4. G10 P01 X10 Z20 R10.0 ; tool nose radius compen–sation value setting
5. (G17) Z200.0 ; Move command not included in the offset plane.
6. G98 ; G code only
7. X0 ; Move distance is zero.

} Commands **1** to **6** are of no movement.

- A block without tool movement specified in offset mode

When a single block without tool movement is commanded in the offset mode, the vector and Tool nose radius center path are the same as those when the block is not commanded. This block is executed at the single block stop point.



However, when the move distance is zero, even if the block is commanded singly, tool motion becomes the same as that when more than one block of without tool movement are commanded, which will be described subsequently.



- **Corner movement**

When two or more vectors are produced at the end of a block, the tool moves linearly from one vector to another. This movement is called the corner movement.
If these vectors almost coincide with each other, the corner movement isn't performed and the latter vector is ignored.



If $\Delta Vx \leqq \Delta Vlimit$ and $\Delta Vy \leqq \Delta Vlimit$, the latter vector is ignored. The $\Delta Vlimit$ is set in advance by parameter (No. 5010).
If these vectors do not coincide, a move is generated to turn around the corner. This move belongs to the latter block.



- **Interruption of manual operation**

For manual operation during the tool nose radius compensation, refer to Section III–3.5, " Manual Absolute ON and OFF."

14.3.4 Tool Movement in Offset Mode Cancel

Explanations

- **Tool movement around an inside corner (180° ≦ α)**



- **Tool movement around an outside corner at an obtuse angle (90° ≦ α<180°)**



- **Tool movement around an outside corner at an acute angle (α<90°)**



- **Tool movement around the outside linear→linear at an acute angle less than 1 degree (α<1°)**



- **A block without tool movement specified together with offset cancel**

When a block without tool movement is commanded together with an offset cancel, a vector whose length is equal to the offset value is produced in a normal direction to tool motion in the earlier block, the vector is cancelled in the next move command.



- **Block containing G40 and I_J_K_**

  - The previous block contains G41 or G42

If a G41 or G42 block precedes a block in which G40 and I_, J_, K_ are specified, the system assumes that the path is programmed as a path from the end position determined by the former block to a vector determined by (I,J), (I,K), or (J,K). The direction of compensation in the former block is inherited.



In this case, note that the CNC obtains an intersection of the tool path irrespective of whether inner or outer side machining is specified



When an intersection is not obtainable, the tool comes to the normal position to the previous block at the end of the previous block.



14.3.5 Interference Check

Tool overcutting is called interference. The interference check function checks for tool overcutting in advance. However, all interference cannot be checked by this function. The interference check is performed even if overcutting does not occur.

Explanations

- **Criteria for detecting interference**

(1) The direction of the tool nose radius path is different from that of the programmed path (from 90 degrees to 270 degrees between these paths).



(2) In addition to the condition (1), the angle between the start point and end point on the Tool nose radius center path is quite different from that between the start point and end point on the programmed path in circular machining(more than 180 degrees).



(G41)
N5 G01 U200.0 W800.0 T1 ;
N6 G02 U–160.0 W320.0 I–800.0 K–200.0 T2 ;
N7 G01 U–500.0 W200.0 ;
(Tool compensation value corresponding to T1 : r_1 = 200.0)
(Tool compensation value corresponding to T2 : r_2 = 600.0)

In the above example, the arc in block N6 is placed in the one quadrant. But after tool nose radius compensation, the arc is placed in the four quadrants.

- **Correction of interference in advance**

(1) Removal of the vector causing the interference
When tool nose radius compensation is performed for blocks A, B and C and vectors V_1, V_2, V_3 and V_4 between blocks A and B, and V_5, V_6, V_7 and V_8 between B and C are produced, the nearest vectors are checked first. If interference occurs, they are ignored. But if the vectors to be ignored due to interference are the last vectors at the corner, they cannot be ignored.

Check between vectors V_4 and V_5
Interference V_4 and V_5 are ignored.
Check between V_3 and V_6
Interference V_3 and V_6 are ignored
Check between V_2 and V_7
Interference V_2 and V_7 are Ignored
Check between V_1 and V_8
Interference V_1 and V_8 are cannot be ignored

If while checking, a vector without interference is detected, subsequent vectors are not checked. If block B is a circular movement, a linear movement is produced if the vectors are interfered.

(Example 1) The tool moves linearly from V_1 to V_8



(Example 2) The tool moves linearly from V_1, V_2, V_7, to V_8



(2) If the interference occurs after correction (1), the tool is stopped with an alarm.
If the interference occurs after correction (1) or if there are only one pair of vectors from the beginning of checking and the vectors interfere, the P/S alarm (No.41) is displayed and the tool is stopped immediately after execution of the preceding block. If the block is executed by the single block operation, the tool is stopped at the end of the block.



After ignoring vectors V_2 and V_5 because of interference, interference also occurs between vectors V_1 and V_6. The alarm is displayed and the tool is stopped.

- **When interference is assumed although actual interference does not occur**

(1) Depression which is smaller than the tool nose radius compensation value



There is no actual interference, but since the direction programmed in block B is opposite to that of the path after tool nose radius compensation the tool stops and an P/S alarm(No.041) is displayed.

(2) Groove which is smaller than the tool nose radius compensation value



Like (1) , the direction is reverse in block B.

14.3.6 Overcutting by Tool Nose Radius Compensation

Explanations

- **Machining an inside corner at a radius smaller than the tool nose radius**

When the radius of a corner is smaller than the cutter radius, because the inner offsetting of the cutter will result in overcuttings, an alarm is displayed and the CNC stops at the start of the block. In single block operation, the overcutting is generated because the tool is stopped after the block execution.



- **Machining a groove smaller than the tool nose radius**

Since the tool nose radius compensation forces the path of the center of the tool to move in the reverse of the programmed direction, overcutting will result. In this case an alarm is displayed and the CNC stops at the start of the block.



- **Machining a step smaller than the tool nose radius**

When machining of the step is commanded by circular machining in the case of a program containing a step smaller than the tool nose radius, the path of the center of tool with the ordinary offset becomes reverse to the programmed direction. In this case, the first vector is ignored, and the tool moves linearly to the second vector position. The single block operation is stopped at this point. If the machining is not in the single block mode, the cycle operation is continued. If the step is of linear, no alarm will be generated and cut correctly. However uncut part will remain.



14.3.7 Correction in Chamfering and Corner Arcs

In chamfering or corner arcs, tool nose radius compensation only be performed when an ordinary intersection exists at the corner.
In offset cancel mode, a start–up block or when exchanging the offset direction, compensation cannot be performed, an P/S alarm (No.39) is displayed and the tool is stopped.
In inner chamfering or inner corner arcs, if the chamfering value or corner arc value is smaller than the tool nose radius value, the tool is stopped with an P/S alarm (No.39) since overcutting will occur.



The valid inclination angle of the programmed path in the blocks before and after the corner is 1 degree or less so that the P/S alarm (No.52, 54) generated by the calculating error of tool nose radius compensation does not occur.



- **When machining area remains or an alarm is generated**

The following example shows a machining area which cannot be cut sufficiently.



In inner chamfering, if the portion of the programmed path that is not a part of the chamfering (in the above figure ℓ_1 or ℓ_2) is in following range, insufficiently cut are will exist.
$0 \leqq \ell_1$ or $\ell_2 < r \cdot \tan 22.5°$ (r : too nose radius)
Enlarged view on the remaining machining area



Although the tool should be positioned at **2** in the above figure, the tool is positioned at **1** (the tool nose is tangent to line L).
Thus, area **3** is not machined.
P/S alarm No.52 or 55 is displayed in the following cases :



In outer chamfering with an offset, a limit is imposed on the programmed path. The path during chamfering coincides with the intersection points P_1 or P_2 without chamfering, therefore, outer chamfering is limited. In the figure above, the end point of the tool center path with chamfering coincides with the intersection point (P2) of the next block without chamfering. If the chamfering value is more than the limit value specified, P/S alarm No.52 or 55 will be displayed.

14.3.8 Input Command from MDI

Tool nose radius compensation is not performed for commands input from the MDI.
However, when automatic operation using absolute commands is temporarily stopped by the single block function, MDI operation is performed, then automatic operation starts again, the tool path is as follows :
In this case, the vectors at the start position of the next block are translated and the other vectors are produced by the next two blocks. Therefore, from next block but one, tool nose radius compensation is accurately performed.



When position P_A, P_B, and P_C are programmed in an absolute command, tool is stopped by the single block function after executing the block from P_A to P_B and the tool is moved by MDI operation. Vectors V_{B1} and V_{B2} are translated to V_{B1}' and V_{B2}' and offset vectors are recalculated for the vectors V_{C1} and V_{C2} between block P_B–P_C and P_C–P_D.
However, since vector V_{B2} is not calculated again, compensation is accurately performed from position P_C.

14.3.9 General Precautions for Offset Operations

- **Changing the offset value**

In general, the offset value is changed in cancel mode, or when changing tools. If the offset value is changed in offset mode, the vector at the end point of the block is calculated for the new offset value.



When some vectors are produced between blocks N6 and N7, the vector at the end point of the present blocks is calculated using the offset value of the block N6.

- **The polarity of the offset amount and the tool nose center path**

When a negative offset value is specified, the program is executed for the figure which is created by exchanging G41 for G42 or G42 for G41 in the process sheet.
A tool machining an inner profile will machine the occur profile, and tool machining the outer profile will machine the inner profile.
An example is shown below. In general, CNC machining is programmed assuming a positive offset value. When a program specifies a tool path as shown in **1**, the tool will move as shown in **2** if a negative offset is specified. The tool in **2** will move as shown in **1** when the sign of the offset value is reserved.



WARNING

When the sign of the offset value is reversed, the offset vector of the tool nose is reversed but the imaginary tool nose direction does not change.
Therefore, do not reverse the sign of the offset value when starting the machining meeting the imaginary tool nose to the start point.

14.3.10 G53, G28, G30, and G30.1 Commands in Tool–tip Radius Compensation Mode

- When a G53 command is executed in tool–tip radius compensation mode, the tool–tip radius compensation vector is automatically canceled before positioning, that vector being automatically restored by a subsequent move command. The format for restoring the tool–tip radius compensation vector is the FS16 type when bit 2 (CCN) of parameter No. 5003 is set to 0, or the FS15 type when the bit is set to 1.
- When a G28, G30, or G30.1 command is executed in tool–tip radius compensation mode, the tool–tip radius compensation vector is automatically canceled before automatic reference position return, that vector being automatically restored by a subsequent move command. The timing and format for canceling and restoring the tool–tip radius compensation vector are the FS15 type when bit 2 (CCN) of parameter No. 5003 is set to 1, or the FS16 type when the bit is set to 0.

Explanations

- **G53 command in tool–tip radius compensation mode**

When a G53 command is executed in tool–tip radius compensation mode, a vector having a length equal to the offset is created, at the end of the preceding block, perpendicular to the direction in which the tool moves. When the tool moves to a specified position according to the G53 command, the offset vector is canceled. When the tool moves according to the next command, the offset vector is automatically restored.
The format for restoring the tool–tip radius compensation vector is the start–up type when bit 2 (CCN) of parameter No. 5003 is set to 0, or the intersection vector type (FS15 type) when the bit is set to 1.

- G53 command in offset mode

❑ When bit 2 (CCN) of parameter No. 5003 is set to 0



❑ When bit 2 (CCN) of parameter No. 5003 is set to 1



- Incremental G53 command in offset mode

❑ When bit 2 (CCN) of parameter No. 5003 is set to 0



❑ When bit 2 (CCN) of parameter No. 5003 is set to 1



- G53 command specifying no movement in offset mode

❑ When bit 2 (CCN) of parameter No. 5003 is set to 0



❑ When bit 2 (CCN) of parameter No. 5003 is set to 1



WARNING

1 When a G53 command is executed in tool–tip radius compensation mode when all–axis machine lock is applied, positioning is not performed for those axes to which machine lock is applied and the offset vector is not canceled. When bit 2 (CCN) of parameter No. 5003 is set to 0 or each–axis machine lock is applied, the offset vector is canceled.

Example 1)
When bit 2 (CCN) of parameter No. 5003 is set to 0 and all–axis machine lock is applied



Example 2)
When bit 2 (CCN) of parameter No. 5003 is set to 1 and all–axis machine lock is applied

[FS15 type]



Example 3)
When bit 2 (CCN) of parameter No. 5003 is set to 1 and each–axis machine lock is applied

[FS15 type]



WARNING

2 When a compensation axis is specified in a G53 command in tool–tip radius compensation mode, the vectors for other compensation axes are also canceled. This also applies when bit 2 (CCN) of parameter No. 5003 is set to 1. (The FS15 cancels only the vector for the specified axis. Note that the FS15 type cancellation differs from the actual FS15 specification in this point.)

Example)
When bit 2 (CCN) of parameter No. 5003 is set to 0

[FS15 type]



NOTE

1 When an axis not included in the tool–tip radius compensation plane is specified in a G53 command, a vector perpendicular to the direction in which the tool moves is created at the end of the preceding block and the tool does not move. Offset mode is automatically resumed from the next block (in the same way as when two or more blocks specifying no movement are consecutively executed).

Example)
When bit 2 (CCN) of parameter No. 5003 is set to 0



2 When a G53 command is specified as a start–up block, the next block actually becomes the start–up block. When bit 2 (CCN) of parameter No. 5003 is set to 1, however, the next block creates an intersection vector.

Example)
When bit 2 (CCN) of parameter No. 5003 is set to 0



- **G28, G30, G30.1 command in tool–tip radius compensation mode**

When a G28, G30, or G30.1 command is executed in tool–tip radius compensation mode, the operation specified in the command is performed according to the FS15 format if bit 2 (CCN) of parameter No. 5003 is set to 1. An intersection vector is created at the end of the preceding block and a perpendicular vector is created at the intermediate position. The offset vector is canceled when the tool moves from the intermediate position to the reference position. The offset vector is restored as an intersection vector by the next block.

- G28, G30, or G30.1 command in offset mode (with movement to both an intermediate position and reference position performed)

❑ When bit 2 (CCN) of parameter No. 5003 is set to 0



❑ When bit 2 (CCN) of parameter No. 5003 is set to 1



- G28, G30, or G30.1 command in offset mode (with movement to an intermediate position not performed)

❑ When bit 2 (CCN) of parameter No. 5003 is set to 0



❑ When bit 2 (CCN) of parameter No. 5003 is set to 1



- G28, G30, or G30.1 command in offset mode (with movement to a reference position not performed)

❑ When bit 2 (CCN) of parameter No. 5003 is set to 0



Reference position or floating reference position=Intermediate position

❑ When bit 2 (CCN) of parameter No. 5003 is set to 1



Reference position or floating reference position=Intermediate position

- G28, G30, or G30.1 command in offset mode (with no movement)

❑ When bit 2 (CCN) of parameter No. 5003 is set to 0



Reference position or floating reference position=Intermediate position

❑ When bit 2 (CCN) of parameter No. 5003 is set to 1



Reference position or floating reference position=Intermediate position

WARNING

1 When a G28, G30, or G30.1 command is executed when all–axis machine lock is applied, a vector perpendicular to the direction in which the tool moves is created at the intermediate position. In this case, the tool does not move to the reference position and the offset vector is not canceled. When bit 2 (CCN) of parameter No. 5003 is set to 0 or each–axis machine lock is applied, the offset vector is canceled.

Example 1)
When bit 2 (CCN) of parameter No. 5003 is set to 1.

[FS15 type]



Example 2)
When bit 2 (CCN) of parameter No. 5003 is set to 0 and all–axis machine lock is applied

[FS15 type]



2 When a compensation axis is specified in a G28, G30, or G30.1 command in tool–tip radius compensation mode, the vectors for other compensation axes are also canceled. This also applies when bit 2 (CCN) of parameter No. 5003 is set to 1. (The FS15 cancels only the vector for the specified axis. Note that the FS15 type cancellation differs from the actual FS15 specification in this point.)

[FS15 type]



NOTE

1 When an axis not included in the tool–tip radius compensation plane is specified in a G28, G30, or G30.1 command, a vector perpendicular to the direction in which the tool moves is created at the end of the preceding block and the tool does not move. Offset mode is automatically resumed from the next block (in the same way as when two or more blocks specifying no movement are consecutively executed).

Example)
When bit 2 (CCN) of parameter No. 5003 is set to 1.
[FS15 type]



2 When a G28, G30, or G30.1 command is specified as a start–up block, a vector perpendicular to the direction in which the tool moves is created at the intermediate position. The vector is then canceled at the reference position. The next block creates an intersection vector.

Example 1)
When bit 2 (CCN) of parameter No. 5003 is set to 1.
[FS15 type]



14.4 TOOL COMPENSATION VALUES, NUMBER OF COMPENSATION VALUES, AND ENTERING VALUES FROM THE PROGRAM (G10)

Tool compensation values include tool geometry compensation values and tool wear compensation (Fig. 14.4 (a)).
Tool compensation can be specified without differentiating compensation for tool geometry from that for tool wear.



Fig. 14.4 (a) Difference the tool geometry offset from tool wear offset

Fig. 14.4 (b) Not difference the tool geometry offset from tool wear offset

Tool compensation values can be entered into CNC memory from the MDI panel or from a program.
A tool compensation value is selected from the CNC memory when the corresponding code is specified after address T in a program.
The value is used for tool offset or tool nose radius compensation.
See subsec. II–14.1.2 for details.

14.4.1 Tool Compensation and Number of Tool Compensation

- **Valid range of tool compensation values**

Table 14.4.1 shows the valid input range of tool compensation values.

Table 14.4.1 Valid range of tool compensation values

Increment system	Tool compensation value	
	Metric input (mm)	Inch input (inch)
IS–B	–999.999 to +999.999 mm	–99.9999 to +99.9999 inch
IS–C	–999.9999 to +999.9999 mm	–99.99999 to +99.99999 inch

The maximum tool wear compensation can be changed by setting parameter No.5013.

- **Seven–digit tool offset specification**

The number of digits used to specify a tool geometry/wear compensation value can be expanded by selecting the option which enables seven–digit tool offset specification. When this option is used, tool compensation values can be specified using up to seven digits for IS–B and eight digits for IS–C. The valid data range for tool compensation values will thus be as listed in Table 14.4.1(b).

Table 14.4.1(b)

Increment system	Tool compensation value	
	Metric input (mm)	Inch input (inch)
IS–B	0 to ±9999.999 mm	0 to ±999.9999 inch
IS–C	0 to ±9999.9999 mm (0 to ±4000.0000 mm)	0 to ±999.99999 inch (0 to ±160.00000 inch)

NOTE
1 The range enclosed in parentheses applies when automatic inch/metric conversion is enabled (bit 0 (OIM) of parameter No. 5006 is set to 1).
2 The option enabling seven–digit tool offset specification cannot be used for B–axis offsets for B–axis control.

- **Number of tool compensation**

The memory can hold 16, 32, 64, or 99 tool compensation values.

NOTE
With the two–path control, the number of specified tool compensation values equals the number of tool compensations for each tool post.

14.4.2 Changing of Tool Offset Value (Programmable Data Input) (G10)

Offset values can be input by a program using the following command :

Format

G10 P_ X_ Y_ Z_ R_ Q_ ;
or
G10 P_ U_ V_ W_ C_ Q_ ;

P : Offset number
0 : Command of work coordinate system shift value
1–64 : Command of tool wear offset value
Command value is offset number
10000+(1–64) : Command of tool geometry offset value
(1–64) : Offset number
X : Offset value on X axis (absolute)
Y : Offset value on Y axis (absolute)
Z : Offset value on Z axis (absolute)
U : Offset value on X axis (incremental)
V : Offset value on Y axis (incremental)
W: Offset value on Z axis (incremental)
R : Tool nose radius offset value (absolute)
R : Tool nose radius offset value (incremental)
Q : Imaginary tool nose number

In an absolute command, the values specified in addresses X, Y , Z, and R are set as the offset value corresponding to the offset number specified by address P. In an incremental command, the value specified in addresses U, V, W, and C is added to the current offset value corresponding to the offset number.

NOTE
1 Addresses X, Y, Z, U, V, and W can be specified in the same block.
2 Use of this command in a program allows the tool to advance little by little. This command can also be used input offset values one at a time from a program by specifying this command successively instead of inputting these values one at a time from the MDI unit.

14.5 AUTOMATIC TOOL OFFSET (G36, G37)

When a tool is moved to the measurement position by execution of a command given to the CNC, the CNC automatically measures the difference between the current coordinate value and the coordinate value of the command measurement position and uses it as the offset value for the tool. When the tool has been already offset, it is moved to the measurement position with that offset value. If the CNC judges that further offset is needed after calculating the difference between the coordinate values of the measurement position and the commanded coordinate values, the current offset value is further offset.
Refer to the instruction manuals of the machine tool builder for details.

Explanations

- **Coordinate system**

When moving the tool to a position for measurement, the coordinate system must be set in advance. (The work coordinate system for programming is used in common.)

- **Movement to measurement position**

A movement to a measurement position is performed by specifying as follows in the MDI, or MEM mode :

G36 Xx_a ; or **G37 Zz_a ;**

In this case, the measurement position should be x_a or z_a (absolute command).
Execution of this command moves the tool at the rapid traverse rate toward the measurement position, lowers the feedrate halfway, then continues to move it until the approach end signal from the measuring instrument is issued. When the tool tip reaches the measurement position, the measuring instrument outputs the measurement position reach signal to the CNC which stops the tool.

- **Offset**

The current tool offset value is further offset by the difference between the coordinate value (α or β) when the tool has reached the measurement position and the value of x_a or z_a specified in G36Xx_a or G37Zz_a.

Offset value x = Current offset value x+(α–x_a)
Offset value z = Current offset value z+(β–z_a)

x_a : Programmed X–axis measurement point
z_a : Programmed Z–axis measurement point

These offset values can also be altered from the MDI keyboard.

- **Feedrate and alarm**

The tool, when moving from the stating position toward the measurement position predicted by x_a or z_a in G36 or G37, is fed at the rapid traverse rate across area **A**. Then the tool stops at point T (x_a–γ_x or z_a–γ_z) and moves at the measurement feedrate set by parameter (No.6241) across areas **B**, **C**, and **D**. If the approach end signal turns on during movement across area B, alarm is generated. If the approach end signal does not turn on before point V, and tool stops at point V and P/S alarm (No.080) is generated.



Fig. 14.5 (a) Feedrate and alarm

- **G code**

If bit 3 (G36) of parameter No. 3405 has been set to 1, G37.1 and G37.2 are used as the G codes for automatic tool compensation for the X– and Z–axes, respectively.

Examples



G50 X760.0 Z1100.0 ; Programming of absolute zero point (Coordinate system setting)

S01 M03 T0101 ; Specifies tool T1, offset number 1, and spindle revolution

G36 X200.0 ;	Moves to the measurement position If the tool has reached the measurement position at X198.0 ; since the correct measurement position is 200 mm, the offset value is altered by 198.0–200.0=–2.0mm.
G00 X204.0 ;	Refracts a little along the X axis.
G37 Z800.0 ;	Moves to the Z–axis measurement position. If the tool has reached the measurement position at X804.0, the offset value is altered by 804.0–800.0=4.0mm.
T0101 ;	Further offsets by the difference. The new offset value becomes valid when the T code is specified again.

WARNING

1 Measurement speed(Fp), γ, and ε are set as parameters (Fp : No.6241, γ : No.6251, ε : No.6254) by machine tool builder. ε must be positive numbers so that $\gamma > \varepsilon$.
2 Cancel the tool nose radius compensation before G36, G37.
3 When a manual movement is inserted into a movement at a measurement feedrate, return the tool to the position before the inserted manual movement for restart.
4 When using the optional tool nose radius compensation function, the tool offset amount is determined considering the value of tool nose R. Make sure that tool nose radius value is set correctly.
Example) When the tool nose center coincides with the start point.



The tool actually moves from point A to point B, but the tool offset value is determined assuming that the tool moves to point C considering the tool nose radius value.

NOTE

1 When there is no T code command before G36 or G37, P/S alarm No.81 is generated.
2 When a T code is specified in the same block as G36 or G37, P/S alarm No.82 is generated.

15 CUSTOM MACRO

Although subprograms are useful for repeating the same operation, the custom macro function also allows use of variables, arithmetic and logic operations, and conditional branches for easy development of general programs such as pocketing and user–defined canned cycles.A machining program can call a custom macro with a simple command, just like a subprogram.



15.1 VARIABLES

An ordinary machining program specifies a G code and the travel distance directly with a numeric value; examples are G100 and X100.0.
With a custom macro, numeric values can be specified directly or using a variable number. When a variable number is used, the variable value can be changed by a program or using operations on the MDI panel.

```
#1=#2+100 ;
G01 X#1 F0.3 ;
```

Explanation

• Variable representation

When specifying a variable, specify a number sign (#) followed by a variable number. General–purpose programming languages allow a name to be assigned to a variable, but this capability is not available for custom macros.

Example: #1

An expression can be used to specify a variable number. In such a case, the expression must be enclosed in brackets.

Example: #[#1+#2–12]

• Types of variables

Variables are classified into four types by variable number.

Table 15.1 Types of variables

Variable number	Type of variable	Function
#0	Always null	This variable is always null. No value can be assigned to this variable.
#1 – #33	Local variables	Local variables can only be used within a macro to hold data such as the results of operations. When the power is turned off, local variables are initialized to null. When a macro is called, arguments are assigned to local variables.
#100 – #149 (#199) #500 – #531 (#999)	Common variables	Common variables can be shared among different macro programs. When the power is turned off, variables #100 to #149 are initialized to null. Variables #500 to #531 hold data even when the power is turned off. As an option, common variables #150 to #199 and #532 to #999 are also available. However, when these values are using, the length of the tape that can be used for storage decreases by 8.5 m.
#1000 –	System variables	System variables are used to read and write a variety of NC data items such as the current position and tool compensation values.

NOTE
Common variables #150 to #199 and #532 to #999 are optional.

- **Range of variable values**

Local and common variables can have value 0 or a value in the following ranges :
-10^{47} to -10^{-29}
0
$+10^{-29}$ to $+10^{47}$
If the result of calculation turns out to be invalid, an P/S alarm No. 111 is issued.

- **Omission of the decimal point**

When a variable value is defined in a program, the decimal point can be omitted.

Example:
When #1=123; is defined, the actual value of variable #1 is 123.000.

- **Referencing variables**

To reference the value of a variable in a program, specify a word address followed by the variable number. When an expression is used to specify a variable, enclose the expression in brackets.

Example: G01X[#1+#2]F#3;

A referenced variable value is automatically rounded according to the least input increment of the address.

Example:
When G00X#1; is executed on a 1/1000–mm CNC with 12.3456 assigned to variable #1, the actual command is interpreted as G00X12.346;.

To reverse the sign of a referenced variable value, prefix a minus sign (–) to #.

Example: G00X–#1;

When an undefined variable is referenced, the variable is ignored up to an address word.

Example:
When the value of variable #1 is 0, and the value of variable #2 is null, execution of G00X#1Z#2; results in G00X0;.

- **Undefined variable**

When the value of a variable is not defined, such a variable is referred to as a ”null” variable. Variable #0 is always a null variable. It cannot be written to, but it can be read.

(a) Quotation

When an undefined variable is quotated, the address itself is also ignored.

When #1 = < vacant >	When #1 = 0
G90 X100 Y#1 ↓ G90 X100	G90 X100 Y#1 ↓ G90 X100 Y0

(b) Operation

< vacant > is the same as 0 except when replaced by < vacant>

When #1 = < vacant >	When #1 = 0
#2 = #1 ↓ #2 = < vacant >	#2 = #1 ↓ #2 = 0
#2 = #1*5 ↓ #2 = 0	#2 = #1*5 ↓ #2 = 0
#2 = #1+#1 ↓ #2 = 0	#2 = #1 + #1 ↓ #2 = 0

(c) Conditional expressions

< vacant > differs from 0 only for EQ and NE.

When #1 = < vacant >	When #1 = 0
#1 EQ #0 ↓ Established	#1 EQ #0 ↓ Not established
#1 NE 0 ↓ Established	#1 NE 0 ↓ Not established
#1 GE #0 ↓ Established	#1 GE #0 ↓ Established
#1 GT 0 ↓ Not established	#1 GT 0 ↓ Not established

- **Custom macro variables common to tool posts (two–path control)**

With the two–path control, macro variables are provided for each tool post. Specifying parameter Nos.6036 and 6037 allows some of the common variables to be used for all tool posts.

- **Displaying variable values**



- When the value of a variable is blank, the variable is null.
- The mark ******** indicates an overflow (when the absolute value of a variable is greater than 99999999) or an underflow (when the absolute value of a variable is less than 0.0000001).

Limitations

Program numbers, sequence numbers, and optional block skip numbers cannot be referenced using variables.

Example:

Variables cannot be used in the following ways:
O#1;
/#2G00X100.0;
N#3Z200.0;

15.2 SYSTEM VARIABLES

System variables can be used to read and write internal NC data such as tool compensation values and current position data. Note, however, that some system variables can only be read. System variables are essential for automation and general–purpose program development.

Explanations

- **Interface signals**

Signals can be exchanged between the programmable machine controller (PMC) and custom macros.

Table 15.2 (a) System variables for interface signals

Variable number	Function
#1000–#1015 #1032	A 16–bit signal can be sent from the PMC to a custom macro. Variables #1000 to #1015 are used to read a signal bit by bit. Variable #1032 is used to read all 16 bits of a signal at one time.
#1100–#1115 #1132	A 16–bit signal can be sent from a custom macro to the PMC. Variables #1100 to #1115 are used to write a signal bit by bit. Variable #1132 is used to write all 16 bits of a signal at one time.
#1133	Variable #1133 is used to write all 32 bits of a signal at one time from a custom macro to the PMC. Note, that values from –99999999 to +99999999 can be used for #1133.

For detailed information, refer to the connection manual (B–63003EN–1).

- **Tool compensation values**

When the system does not differentiate tool geometry compensation from tool wear compensation, use variable numbers for wear compensation.

Table 15.2 (b) System variables for tool compensation memory C

Compensation number	X axis compensation value		Z axis compensation value		Tool nose radius compensation value		Imaginary tool nose position T	Y axis compensation value	
	Wear	Geometry	Wear	Geometry	Wear	Geometry		Wear	Geometry
1 : 49 : 64	#2001 : : : #2064	#2701 : #2749	#2101 : : : #2164	#2801 : #2849	#2201 : : : #2264	#2901 : : : #2964	#2301 : : : #2364	#2401 : #2449	#2451 : #2499

Table 15.2 (c) System variables for 99 tool compensation values

Compensation number	X axis compensation value		Z axis compensation value		Tool nose radius compensation value		Imaginary tool nose position T	Y axis compensation value	
	Wear	Geometry	Wear	Geometry	Wear	Geometry		Wear	Geometry
1 : : 99	#10001 : : #10099	#15001 : : #15099	#11001 : : #11099	#12001 : : #12099	#12001 : : #12099	#17001 : : #17099	#13001 : : #13099	#14001 : : #14099	#19001 : : #19099

NOTE
System variables #2001 to #2964 can also be used to determine Y–axis wear or geometry compensation values No. 1 to 49, X–axis or Z–axis geometry compensation values No. 1 to 49, and other compensation values No. 1 to 64.

- **Macro alarms**

Table 15.2 (d) System variable for macro alarms

Variable number	Function
#3000	When a value from 0 to 200 is assigned to variable #3000, the CNC stops with an alarm. After an expression, an alarm message not longer than 26 characters can be described. The CRT screen displays alarm numbers by adding 3000 to the value in variable #3000 along with an alarm message.

Example:
#3000=1(TOOL NOT FOUND);
→ The alarm screen displays ”3001 TOOL NOT FOUND.”

- **Time information**

Time information can be read and written.

Table 15.2 (e) System variables for time information

Variable number	Function
#3001	This variable functions as a timer that counts in 1–millisecond increments at all times. When the power is turned on, the value of this variable is reset to 0. When 2147483648 milliseconds is reached, the value of this timer returns to 0.
#3002	This variable functions as a timer that counts in 1–hour increments when the cycle start lamp is on. This timer preserves its value even when the power is turned off. When 9544.371767 hours is reached, the value of this timer returns to 0.
#3011	This variable can be used to read the current date (year/month/day). Year/month/day information is converted to an apparent decimal number. For example, March 28, 1993 is represented as 19930328.
#3012	This variable can be used to read the current time (hours/minutes/seconds). Hours/minutes/seconds information is converted to an apparent decimal number. For example, 34 minutes and 56 seconds after 3 p.m. is represented as 153456.

- **Automatic operation control**

The control state of automatic operation can be changed.

Table 15.2 (f) System variable (#3003) for automatic operation control

#3003	Single block	Completion of an auxiliary function
0	Enabled	To be awaited
1	Disabled	To be awaited
2	Enabled	Not to be awaited
3	Disabled	Not to be awaited

- When the power is turned on, the value of this variable is 0.
- When single block stop is disabled, single block stop operation is not performed even if the single block switch is set to ON.
- When a wait for the completion of auxiliary functions (M, S, and T functions) is not specified, program execution proceeds to the next block before completion of auxiliary functions. Also, distribution completion signal DEN is not output.

Table 15.2 (g) System variable (#3004) for automatic operation control

#3004	Feed hold	Feedrate Override	Exact stop
0	Enabled	Enabled	Enabled
1	Disabled	Enabled	Enabled
2	Enabled	Disabled	Enabled
3	Disabled	Disabled	Enabled
4	Enabled	Enabled	Disabled
5	Disabled	Enabled	Disabled
6	Enabled	Disabled	Disabled
7	Disabled	Disabled	Disabled

- When the power is turned on, the value of this variable is 0.
- When feed hold is disabled:

  (1) When the feed hold button is held down, the machine stops in the single block stop mode. However, single block stop operation is not performed when the single block mode is disabled with variable #3003.

  (2) When the feed hold button is pressed then released, the feed hold lamp comes on, but the machine does not stop; program execution continues and the machine stops at the first block where feed hold is enabled.

- When feedrate override is disabled, an override of 100% is always applied regardless of the setting of the feedrate override switch on the machine operator's panel.
- When exact stop check is disabled, no exact stop check (position check) is made even in blocks including those which do not perform cutting.

- **Settings**

Settings can be read and written. Binary values are converted to decimals.

#3005

	#15	#14	#13	#12	#11	#10	#9	#8
Setting							FCV	

	#7	#6	#5	#4	#3	#2	#1	#0
Setting			SEQ			INI	ISO	TVC

#9 (FCV) : Whether to use the FS15 tape format conversion capability
#5 (SEQ) : Whether to automatically insert sequence numbers
#2 (INI) : Millimeter input or inch input
#1 (ISO) : Whether to use EIA or ISO as the output code
#0 (TVC) : Whether to make a TV check

- **Mirror image**

The mirror–image status for each axis set using an external switch or setting operation can be read through the output signal (mirror–image check signal). The mirror–image status present at that time can be checked. (See Section 4.7 in III.)
The value obtained in binary is converted into decimal notation.

#3007

	#7	#6	#5	#4	#3	#2	#1	#0
Setting	8th axis	7th axis	6th axis	5th axis	4th axis	3th axis	2th axis	1th axis

For each bit, 0 (mirror–image function is disabled) or 1 (mirror–image function is enabled) is indicated.

Example : If #3007 is 3, the mirror–image function is enabled for the first and second axes.

- When the mirror–image function is set for a certain axis by both the mirror–image signal and setting, the signal value and setting value are ORed and then output.
- When mirror–image signals for axes other than the controlled axes are turned on, they are still read into system variable #3007.
- System variable #3007 is a write–protected system variable. If an attempt is made to write data in the variable, P/S 116 alarm ”WRITE PROTECTED VARIABLE” is issued.

- **Number of machined parts**

The number (target number) of parts required and the number (completion number) of machined parts can be read and written.

Table 15.2 (h) System variables for the number of parts required and the number of machined parts

Variable number	Function
#3901	Number of machined parts (completion number)
#3902	Number of required parts (target number)

NOTE
Do not substitute a negative value.

● Modal information

Modal information specified in blocks up to the immediately preceding block can be read.

Table 15.2 (i) System variables for modal information

Variable number	Function	
#4001	G00, G01, G02, G03, G33, G34	(Group 01)
#4002	G96, G97	(Group 02)
#4003		(Group 03)
#4004	G68, G69	(Group 04)
#4005	G98, G99	(Group 05)
#4006	G20, G21	(Group 06)
#4007	G40, G41, G42	(Group 07)
#4008	G25, G26	(Group 08)
#4009	G22, G23	(Group 09)
#4010	G80 – G89	(Group 10)
#4011		(Group 11)
#4012	G66, G67	(Group 12)
#4014	G54–G59	(Group 14)
#4015		(Group 15)
#4016	G17 – G19	(Group 16)
:	:	:
#4022		(Group 22)
#4109	F code	
#4113	M code	
#4114	Sequence number	
#4115	Program number	
#4119	S code	
#4120	T code	

Example:

When #1=#4001; is executed, the resulting value in #1 is 0, 1, 2, 3, or 33.

When a modal information reading system variable corresponding to a G code group which cannot be used is specified, a P/S alarm is issued.

● Current position

Position information cannot be written but can be read.

Table 15.2 (j) System variables for position information

Variable number	Position information	Coordinate system	Tool compensation value	Read operation during movement
#5001–#5008	Block end point	Workpiece coordinate system	Not included	Enabled
#5021–#5028	Current position	Machine coordinate system	Included	Disabled
#5041–#5048	Current position	Workpiece coordinate system		
#5061–#5068	Skip signal position			Enabled
#5081, #5082	Tool offset value			Disabled
#5101–#5108	Deviated servo position			

- The first digit (from 1 to 8) represents an axis number.
- The tool offset value currently used for execution rather than the immediately preceding tool offset value is held in variables #5081 to 5088.
- The tool position where the skip signal is turned on in a G31 (skip function) block is held in variables #5061 to #5068. When the skip signal is not turned on in a G31 block, the end point of the specified block is held in these variables.
- When read during movement is “disabled,” this means that expected values cannot be read due to the buffering (preread) function.

● Workpiece coordinate system compensation values (workpiece zero point offset values)

Workpiece zero point offset values can be read and written.

Table 15.2(k) System variables for workpiece zero point offset values

Variable number	Function
#5201 : #5208	First–axis external workpiece zero point offset value : Eighth–axis external workpiece zero point offset value
#5221 : #5228	First–axis G54 workpiece zero point offset value : Eighth–axis G54 workpiece zero point offset value
#5241 : #5248	First–axis G55 workpiece zero point offset value : Eighth–axis G55 workpiece zero point offset value
#5261 : #5268	First–axis G56 workpiece zero point offset value : Eighth–axis G56 workpiece zero point offset value
#5281 : #5288	First–axis G57 workpiece zero point offset value : Eighth–axis G57 workpiece zero point offset value
#5301 : #5308	First–axis G58 workpiece zero point offset value : Eighth–axis G58 workpiece zero point offset value
#5321 : #5328	First–axis G59 workpiece zero point offset value : Eighth–axis G59 workpiece zero point offset value

NOTE
To use variables #5201 to #5328, the workpiece coordinate system option is necessary.

15.3 ARITHMETIC AND LOGIC OPERATION

The operations listed in Table 15.3(a) can be performed on variables. The expression to the right of the operator can contain constants and/or variables combined by a function or operator. Variables #j and #K in an expression can be replaced with a constant. Variables on the left can also be replaced with an expression.

Table 15.3 (a) Arithmetic and logic operation

Function	Format	Remarks
Definition	#i=#j	
Sum Difference Product Quotient	#i=#j+#k; #i=#j–#k; #i=#j*#k; #i=#j/#k;	
Sine Arc sine Cosine Arc cosine Tangent Arctangent	#i=SIN[#j]; #i=ASIN[#j]; #i=COS[#j]; #i=ACOS[#j]; #i=TAN[#j]; #i=ATAN[#j]/[#k];	An angle is specified in degrees. 90 degrees and 30 minutes is represented as 90.5 degrees.
Square root Absolute value Rounding off Rounding down Rounding up Natural logarithm Exponential function	#i=SQRT[#j]; #i=ABS[#j]; #i=ROUND[#j]; #i=FIX[#j]; #i=FUP[#j]; #i=LN[#j] #i=EXP[#j];	
OR XOR AND	#i=#j OR #k; #i=#j XOR #k; #i=#j AND #k;	A logical operation is performed on binary numbers bit by bit.
Conversion from BCD to BIN Conversion from BIN to BCD	#i=BIN[#j]; #i=BCD[#j];	Used for signal exchange to and from the PMC

Explanations

- **Angle units**

The units of angles used with the SIN, COS, TAN, ASIN, ACOS and ATAN functions are degrees. For example, 90 degrees and 30 minutes is represented as 90.5 degrees.

- **ARCSIN #i = ASIN[#j];**

- The solution ranges are as indicated below:
  When the NAT bit (bit 0 of parameter 6004) is set to 0: 270° to 90°
  When the NAT bit (bit 0 of parameter 6004) is set to 1: –90° to 90°
- When #j is beyond the range of –1 to 1, P/S alarm No. 111 is issued.
- A constant can be used instead of the #j variable.

- **ARCCOS #i = ACOS[#j];**
  - The solution ranges from 180° to 0°.
  - When #j is beyond the range of –1 to 1, P/S alarm No. 111 is issued.
  - A constant can be used instead of the #j variable.

- **ARCTAN #i = ATAN[#j]/[#k];**
  - Specify the lengths of two sides, separated by a slash (/).
  - The solution ranges are as follows:
    When the NAT bit (bit 0 of parameter 6004) is set to 0: 0° to 360°

Example:
When #1 = ATAN[–1]/[–1]; is specified, #1 is 225.0
When the NAT bit (bit 0 of parameter 6004) is set to 1: –180° to 180°

Example:
When #1 = ATAN[–1]/[–1]; is specified, #1 is –135.0.

- A constant can be used instead of the #j variable.

- **Natural logarithm #i = LN[#j];**
  - Note that the relative error may become 10^{-8} or greater.
  - When the antilogarithm (#j) is zero or smaller, P/S alarm No. 111 is issued.
  - A constant can be used instead of the #j variable.

- **Exponential function #i = EXP[#j];**
  - Note that the relative error may become 10^{-8} or greater.
  - When the result of the operation exceeds 3.65×10^{47} (j is about 110), an overflow occurs and P/S alarm No. 111 is issued.
  - A constant can be used instead of the #j variable.

- **ROUND function**
  - When the ROUND function is included in an arithmetic or logic operation command, IF statement, or WHILE statement, the ROUND function rounds off at the first decimal place.

Example:
When #1=ROUND[#2]; is executed where #2 holds 1.2345, the value of variable #1 is 1.0.

- When the ROUND function is used in NC statement addresses, the ROUND function rounds off the specified value according to the least input increment of the address.

Example:
Creation of a drilling program that cuts according to the values of variables #1 and #2, then returns to the original position
Suppose that the increment system is 1/1000 mm, variable #1 holds 1.2345, and variable #2 holds 2.3456. Then,
G00 G91 X–#1; Moves 1.235 mm.
G01 X–#2 F300; Moves 2.346 mm.
G00 X[#1+#2];
Since 1.2345 + 2.3456 = 3.5801, the travel distance is 3.580, which does not return the tool to the original position.
This difference comes from whether addition is performed before or after rounding off. G00X–[ROUND[#1]+ROUND[#2]] must be specified to return the tool to the original position.

- **Rounding up and down to an integer**

With CNC, when the absolute value of the integer produced by an operation on a number is greater than the absolute value of the original number, such an operation is referred to as rounding up to an integer. Conversely, when the absolute value of the integer produced by an operation on a number is less than the absolute value of the original number, such an operation is referred to as rounding down to an integer. Be particularly careful when handling negative numbers.

Example:
Suppose that #1=1.2 and #2=–1.2.
When #3=FUP[#1] is executed, 2.0 is assigned to #3.
When #3=FIX[#1] is executed, 1.0 is assigned to #3.
When #3=FUP[#2] is executed, –2.0 is assigned to #3.
When #3=FIX[#2] is executed, –1.0 is assigned to #3.

- **Abbreviations of arithmetic and logic operation commands**

When a function is specified in a program, the first two characters of the function name can be used to specify the function. (See III–9.7)

Example:
ROUND → RO
FIX → FI

- **Priority of operations**

(1) Functions
(2) Operations such as multiplication and division (*, /, AND, MOD)
(3) Operations such as addition and subtraction (+, –, OR, XOR)



- **Bracket nesting**

Brackets are used to change the order of operations. Brackets can be used to a depth of five levels including the brackets used to enclose a function. When a depth of five levels is exceeded, alarm No. 118 occurs.



Limitations

- **Brackets**

Brackets ([,]) are used to enclose an expression. Note that parentheses are used for comments.

● Operation error

Errors may occur when operations are performed.

Table 15.3 (b) Errors involved in operations

Operation	Average error	Maximum error	Type of error
a = b*c	1.55×10^{-10}	4.66×10^{-10}	Relative error(*1) $\left\lvert \frac{\varepsilon}{b} \right\rvert$
a = b / c	4.66×10^{-10}	1.88×10^{-9}	
$a = \sqrt{b}$	1.24×10^{-9}	3.73×10^{-9}	
a = b + c a = b – c	2.33×10^{-10}	5.32×10^{-10}	(*2) $\mathrm{Min}\left\lvert \frac{\varepsilon}{b} \right\rvert \left\lvert \frac{\varepsilon}{c} \right\rvert$
a = SIN [b] a = COS [b]	5.0×10^{-9}	1.0×10^{-8}	Absolute error(*3) $\lvert \varepsilon \rvert$ degrees
a = ATAN [b] / [c] (*4)	1.8×10^{-6}	3.6×10^{-6}	

NOTE
1 The relative error depends on the result of the operation.
2 Smaller of the two types of errors is used.
3 The absolute error is constant, regardless of the result of the operation.
4 Function TAN performs SIN/COS.

- The precision of variable values is about 8 decimal digits. When very large numbers are handled in an addition or subtraction, the expected results may not be obtained.

Example:

When an attempt is made to assign the following values to variables #1 and #2:
#1=9876543210123.456
#2=9876543277777.777
the values of the variables become:
#1=9876543200000.000
#2=9876543300000.000
In this case, when #3=#2–#1; is calculated, #3=100000.000 results. (The actual result of this calculation is slightly different because it is performed in binary.)

- Also be aware of errors that can result from conditional expressions using EQ, NE, GE, GT, LE, and LT.

Example:

IF[#1 EQ #2] is effected by errors in both #1 and #2, possibly resulting in an incorrect decision.
Therefore, instead find the difference between the two variables with IF[ABS[#1–#2]LT0.001].
Then, assume that the values of the two variables are equal when the difference does not exceed an allowable limit (0.001 in this case).

- Also, be careful when rounding down a value.

Example:

When #2=#1*1000; is calculated where #1=0.002;, the resulting value of variable #2 is not exactly 2 but 1.99999997.
Here, when #3=FIX[#2]; is specified, the resulting value of variable #1 is not 2.0 but 1.0. In this case, round down the value after correcting the error so that the result is greater than the expected number, or round it off as follows:
#3=FIX[#2+0.001]
#3=ROUND[#2]

● Divisor

When a divisor of zero is specified in a division or TAN[90], alarm No. 112 occurs.

15.4 MACRO STATEMENTS AND NC STATEMENTS

The following blocks are referred to as macro statements:

- **Blocks containing an arithmetic or logic operation (=)**
- **Blocks containing a control statement (such as GOTO, DO, END)**
- **Blocks containing a macro call command (such as macro calls by G65, G66, G67, or other G codes, or by M codes)**

Any block other than a macro statement is referred to as an NC statement.

Explanations

- **Differences from NC statements**
  - Even when single block mode is on, the machine does not stop. Note, however, that the machine stops in the single block mode when bit 5 (SBM) of parameter 6000 is 1.
  - Macro blocks are not regarded as blocks that involve no movement in the tool nose radius compensation mode (see Section II–15.7).
- **NC statements that have the same property as macro statements**
  - If a block contains a subprogram call command (M98, a subprogram call using an M code, or a subprogram call using a T code) and does not contain any command address other than O, N, P, or L, that block is equivalent to a macro statement.
  - If a block contains M99 and does not contain any command address other than O, N, P, or L, that block is equivalent to a macro statement.

15.5 BRANCH AND REPETITION

In a program, the flow of control can be changed using the GOTO statement and IF statement. Three types of branch and repetition operations are used:

- Branch and repetition
  - GOTO statement (unconditional branch)
  - IF statement (conditional branch: if ..., then...)
  - WHILE statement (repetition while ...)

15.5.1 Unconditional Branch (GOTO Statement)

A branch to sequence number n occurs. When a sequence number outside of the range 1 to 99999 is specified, P/S alarm No. 128 occurs. A sequence number can also be specified using an expression.

GOTO n ; n: Sequence number (1 to 99999)

Example:

```
GOTO1;
GOTO#10;
```

15.5.2 Conditional Branch (IF Statement)

Specify a conditional expression after IF. IF [<conditional expression>] GOTO n If the specified conditional expression is satisfied, a branch to sequence number n occurs. If the specified condition is not satisfied, the next block is executed.

If the value of variable #1 is greater than 10, a branch to sequence number N2 occurs.



IF[<conditional expression>]THEN

If the specified conditional expression is satisfied, a predetermined macro statement is executed. Only a single macro statement is executed.

If the values of #1 and #2 are the same, 0 is assigned to #3.

```
IF [#1 EQ #2] THEN #3=0;
```

Explanations

- **Conditional expression**

A conditional expression must include an operator inserted between two variables or between a variable and constant, and must be enclosed in brackets ([,]). An expression can be used instead of a variable.

- **Operators**

Operators each consist of two letters and are used to compare two values to determine whether they are equal or one value is smaller or greater than the other value. Note that the inequality sign cannot be used.

Table 15.5.2 Operators

Operator	Meaning
EQ	Equal to(=)
NE	Not equal to(≠)
GT	Greater than(>)
GE	Greater than or equal to(≧)
LT	Less than(<)
LE	Less than or equal to(≦)

Sample program

The sample program below finds the total of numbers 1 to 10.

```
O9500;
 #1=0;Initial value of the variable to hold the sum
 #2=1;Initial value of the variable as an addend
N1 IF[#2 GT 10] GOTO 2;  Branch to N2 when the addend is greater than
10
 #1=#1+#2;  Calculation to find the sum
 #2=#2+1; Next addend
 GOTO 1; Branch to N1
N2 M30;End of program
```

15.5.3 Repetition (WHILE Statement)

Specify a conditional expression after WHILE. While the specified condition is satisfied, the program from DO to END is executed. If the specified condition is not satisfied, program execution proceeds to the block after END.



Explanations

While the specified condition is satisfied, the program from DO to END after WHILE is executed. If the specified condition is not satisfied, program execution proceeds to the block after END. The same format as for the IF statement applies. A number after DO and a number after END are identification numbers for specifying the range of execution. The numbers 1, 2, and 3 can be used. When a number other than 1, 2, and 3 is used, P/S alarm No. 126 occurs.

- **Nesting**

The identification numbers (1 to 3) in a DO–END loop can be used as many times as desired. Note, however, when a program includes crossing repetition loops (overlapped DO ranges), P/S alarm No. 124 occurs.



Limitations

- **Infinite loops**

When DO m is specified without specifying the WHILE statement, an infinite loop ranging from DO to END is produced.

- **Processing time**

When a branch to the sequence number specified in a GOTO statement occurs, the sequence number is searched for. For this reason, processing in the reverse direction takes a longer time than processing in the forward direction. Using the WHILE statement for repetition reduces processing time.

- **Undefined variable**

In a conditional expression that uses EQ or NE, a null value and zero have different effects. In other types of conditional expressions, a null value is regarded as zero.

Sample program

The sample program below finds the total of numbers 1 to 10.

```
O0001;
#1=0;
#2=1;
WHILE[#2 LE 10]DO
1;
#1=#1+#2;
#2=#2+1;
END 1;
M30;
```

15.6 MACRO CALL

A macro program can be called using the following methods:



Restrictions

- **Differences between macro calls and subprogram calls**

Macro call (G65) differs from subprogram call (M98) as described below.

- With G65, an argument (data passed to a macro) can be specified. M98 does not have this capability.
- When an M98 block contains another NC command (for example, G01 X100.0 M98Pp), the subprogram is called after the command is executed. On the other hand, G65 unconditionally calls a macro.
- When an M98 block contains another NC command (for example, G01 X100.0 M98Pp), the machine stops in the single block mode. On the other hand, G65 does not stops the machine.
- With G65, the level of local variables changes. With M98, the level of local variables does not change.

15.6.1 Simple Call (G65)

When G65 is specified, the custom macro specified at address P is called. Data (argument) can be passed to the custom macro program.

G65 P p L ℓ <argument–specification> ;

P : Number of the program to call
ℓ : Repetition count (1 by default)
Argument : Data passed to the macro



Explanations

- **Call**

  - After G65, specify at address P the program number of the custom macro to call.
  - When a number of repetitions is required, specify a number from 1 to 9999 after address L. When L is omitted, 1 is assumed.
  - By using argument specification, values are assigned to corresponding local variables.

- **Argument specification**

Two types of argument specification are available. Argument specification I uses letters other than G, L, O, N, and P once each. Argument specification II uses A, B, and C once each and also uses I, J, and K up to ten times. The type of argument specification is determined automatically according to the letters used.

Argument specification I

Address	Variable number
A	#1
B	#2
C	#3
D	#7
E	#8
F	#9
H	#11

Address	Variable number
I	#4
J	#5
K	#6
M	#13
Q	#17
R	#18
S	#19

Address	Variable number
T	#20
U	#21
V	#22
W	#23
X	#24
Y	#25
Z	#26

- Addresses G, L, N, O, and P cannot be used in arguments.
- Addresses that need not be specified can be omitted. Local variables corresponding to an omitted address are set to null.

Argument specification II

Argument specification II uses A, B, and C once each and uses I, J, and K up to ten times. Argument specification II is used to pass values such as three–dimensional coordinates as arguments.

Address	Variable number
A	#1
B	#2
C	#3
I_1	#4
J_1	#5
K_1	#6
I_2	#7
J_2	#8
K_2	#9
I_3	#10
J_3	#11

Address	Variable number
K_3	#12
I_4	#13
J_4	#14
K_4	#15
I_5	#16
J_5	#17
K_5	#18
I_6	#19
J_6	#20
K_6	#21
I_7	#22

Address	Variable number
J_7	#23
K_7	#24
I_8	#25
J_8	#26
K_8	#27
I_9	#28
J_9	#29
K_9	#30
I_{10}	#31
J_{10}	#32
K_{10}	#33

- Subscripts of I, J, and K for indicating the order of argument specification are not written in the actual program.

Restrictions

- **Format**

  G65 must be specified before any argument.

- **Mixture of argument specifications I and II**

  The CNC internally identifies argument specification I and argument specification II. If a mixture of argument specification I and argument specification II is specified, the type of argument specification specified later takes precedence.

- **Position of the decimal point**

  The units used for argument data passed without a decimal point correspond to the least input increment of each address. The value of an argument passed without a decimal point may vary according to the system configuration of the machine. It is good practice to use decimal points in macro call arguments to maintain program compatibility.

- **Call nesting**

  Calls can be nested to a depth of four levels including simple calls (G65) and modal calls (G66). This does not include subprogram calls (M98).

- **Local variable levels**

  - Local variables from level 0 to 4 are provided for nesting.
  - The level of the main program is 0.
  - Each time a macro is called (with G65 or G66), the local variable level is incremented by one. The values of the local variables at the previous level are saved in the CNC.

- When M99 is executed in a macro program, control returns to the calling program. At that time, the local variable level is decremented by one; the values of the local variables saved when the macro was called are restored.



Sample program (Drill cycle)

Move the tool beforehand along the X– and Z–axes to the position where a drilling cycle starts. Specify Z or W for the depth of a hole, K for the depth of a cut, and F for the cutting feedrate to drill the hole.



- **Calling format**

G65 P9100 { Zz / Ww } Kk Ff ;

Z : Hole depth (absolute specification)
U: Hole depth (incremental specification)
K: Cutting amount per cycle
F : Cutting feedrate

- **Program calling a macro program**

```
O0002;
G50 X100.0 Z200.0 ;
G00 X0 Z102.0 S1000 M03 ;
G65 P9100 Z50.0 K20.0 F0.3 ;
G00 X100.0 Z200.0 M05 ;
M30 ;
```

- **Macro program (called program)**

```
O9100;
#1=0 ; ..... Clear the data for the depth of the current hole.
#2=0 ; ..... Clear the data for the depth of the preceding hole.
IF [#23 NE #0] GOTO 1 ; ..... If incremental programming, specifies the
                             jump to N1.
IF [#26 EQ #0] GOTO 8 ; ..... If neither Z nor W is specified, an error occurs.
#23=#5002−#26 ; ..... Calculates the depth of a hole.
N1 #1=#1+#6 ; ..... Calculates the depth of the current hole.
IF [#1 LE #23] GOTO 2 ; ..... Determines whether the hole to be cut is
  too deep.?
#1=#23 ; ..... Clamps at the depth of the current hole.
N2 G00 W−#2 ; ..... Moves the tool to the depth of the preceding
                    hole at the cutting feedrate.
G01 W− [#1−#2] F#9 ; ..... Drills the hole.
G00 W#1 ; ..... Moves the tool to the drilling start point.
IF [#1 GE #23] GOTO 9 ; ..... Checks whether drilling is completed.
#2=#1 ; ..... Stores the depth of the current hole.
GOTO 1 ;
N9 M99 ;
N8 #3000=1 (NOT Z OR U COMMAND)
```

15.6.2 Modal Call (G66)

Once G66 is issued to specify a modal call a macro is called after a block specifying movement along axes is executed. This continues until G67 is issued to cancel a modal call.

G66 P p L ℓ <argument–specification> ;

P : Number of the program to call
ℓ : Repetition count (1 by default)
Argument : Data passed to the macro

```
O0001 ;                      O9100 ;
    :                            :
G66 P9100 L2 A1.0 B2.0 ;     G00 Z–#1 ;
G00 G90 X100.0 ;             G01 Z–#2 F0.3 ;
X125.0 ;                         :
X150.0 ;                         :
G67 ;                            :
    :                            :
M30 ;                        M99 ;
```

Explanations

- **Call**
  - After G66, specify at address P a program number subject to a modal call.
  - When a number of repetitions is required, a number from 1 to 9999 can be specified at address L.
  - As with a simple call (G65), data passed to a macro program is specified in arguments.
- **Cancellation**

  When a G67 code is specified, modal macro calls are no longer performed in subsequent blocks.
- **Call nesting**

  Calls can be nested to a depth of four levels including simple calls (G65) and modal calls (G66). This does not include subprogram calls (M98).
- **Modal call nesting**

  Modal calls can be nested by specifying another G66 code during a modal call.

Restrictions

- In a G66 block, no macros can be called.
- G66 needs to be specified before any arguments.
- No macros can be called in a block which contains a code such as a miscellaneous function that does not involve movement along an axis.
- Local variables (arguments) can only be set in G66 blocks. Note that local variables are not set each time a modal call is performed.

Sample program

This program makes a groove at a specified position.



- **Calling format**

```
G66 P9110 Uu Ff ;
```

U: Groove depth (incremental specification)
F : Cutting feed of grooving

- **Program that calls a macro program**

```
O0003 ;
G50 X100.0 Z200.0 ;
S1000 M03 ;
G66 P9110 U5.0 F0.5 ;
G00 X60.0 Z80.0 ;
Z50.0 ;
Z30.0 ;
G67 ;
G00 X00.0 Z200.0 M05 ;
M30;
```

- **Macro program (program called)**

```
O9110 ;
G01 U–#21 F#9 ; . . . . . Cuts the workpiece.
G00 U#21 ; . . . . . Retracts the tool.
M99 ;
```

15.6.3 Macro Call Using G Code

By setting a G code number used to call a macro program in a parameter, the macro program can be called in the same way as for a simple call (G65).



Explanations

By setting a G code number from 1 to 9999 used to call a custom macro program (9010 to 9019) in the corresponding parameter (Nos. 6050 to 6059), the macro program can be called in the same way as with G65. For example, when a parameter is set so that macro program O9010 can be called with G81, a user–specific cycle created using a custom macro can be called without modifying the machining program.

- **Correspondence between parameter numbers and program numbers**

Program number	Parameter number
O9010	6050
O9011	6051
O9012	6052
O9013	6053
O9014	6054
O9015	6055
O9016	6056
O9017	6057
O9018	6058
O9019	6059

- **Repetition**

As with a simple call, a number of repetitions from 1 to 9999 can be specified at address L.

- **Argument specification**

As with a simple call, two types of argument specification are available: Argument specification I and argument specification II. The type of argument specification is determined automatically according to the addresses used.

Restrictions

- **Nesting of calls using G codes**

In a program called with a G code, no macros can be called using a G code. A G code in such a program is treated as an ordinary G code. In a program called as a subprogram with an M or T code, no macros can be called using a G code. A G code in such a program is also treated as an ordinary G code.

15.6.4 Macro Call Using an M Code

By setting an M code number used to call a macro program in a parameter, the macro program can be called in the same way as with a simple call (G65).



Explanations

By setting an M code number from 1 to 99999999 used to call a custom macro program (O9020 to O9029) in the corresponding parameter (Nos. 6080 to 6089), the macro program can be called in the same way as with G65.

- **Correspondence between parameter numbers and program numbers**

Program number	Parameter number
O9020	6080
O9021	6081
O9022	6082
O9023	6083
O9024	6084
O9025	6085
O9026	6086
O9027	6087
O9028	6088
O9029	6089

- **Repetition**

As with a simple call, a number of repetitions from 1 to 9999 can be specified at address L.

- **Argument specification**

As with a simple call, two types of argument specification are available: Argument specification I and argument specification II. The type of argument specification is determined automatically according to the addresses used.

Restrictions

– An M code used to call a macro program must be specified at the start of a block.
– In a macro called with a G code or in a program called as a subprogram with an M or T code, no macros can be called using an M code. An M code in such a macro or program is treated as an ordinary M code.

15.6.5 Subprogram Call Using an M Code

By setting an M code number used to call a subprogram (macro program) in a parameter, the macro program can be called in the same way as with a subprogram call (M98).



Explanations

By setting an M code number from 1 to 99999999 used to call a subprogram in a parameter (Nos. 6071 to 6076), the corresponding custom macro program (O9001 to O9006) can be called in the same way as with M98.

- **Correspondence between parameter numbers and program numbers**

Program number	Parameter number
O9001	6071
O9002	6072
O9003	6073
O9004	6074
O9005	6075
O9006	6076
O9007	6077
O9008	6078
O9009	6079

- **Repetition**

As with a simple call, a number of repetitions from 1 to 9999 can be specified at address L.

- **Argument specification**

Argument specification is not allowed.

- **M code**

An M code in a macro program that has been called is treated as an ordinary M code.

Limitations

In a macro called with a G code or in a program called with an M or T code, no subprograms can be called using an M code. An M code in such a macro or program is treated as an ordinary M code.

15.6.6 Subprogram Calls Using a T Code

By enabling subprograms (macro program) to be called with a T code in a parameter, a macro program can be called each time the T code is specified in the machining program.



Explanations

- **Call**

By setting bit 5 (TCS) of parameter No.6001 to 1, the macro program O9000 can be called when a T code is specified in the machining program. A T code specified in a machining program is assigned to common variable #149.

Limitations

In a macro called with a G code or in a program called with an M or T code, no subprograms can be called using a T code. A T code in such a macro or program is treated as an ordinary T code.

15.6.7 Sample Program

By using the subprogram call function that uses M codes, the cumulative usage time of each tool is measured.

Conditions

- The cumulative usage time of each of tool numbers 1 to 5 is measured. The time is not measured for tools whose number is 6 or more.
- The following variables are used to store the tool numbers and measured times:

#501	Cumulative usage time of tool number 1
#502	Cumulative usage time of tool number 2
#503	Cumulative usage time of tool number 3
#504	Cumulative usage time of tool number 4
#505	Cumulative usage time of tool number 5

- Usage time starts being counted when the M03 command is specified and stops when M05 is specified. System variable #3002 is used to measure the time during which the cycle start lamp is on. The time during which the machine is stopped by feed hold and single block stop operation is not counted, but the time used to change tools and pallets is included.

Operation check

- **Parameter setting**

Set 3 in parameter No.6071, and set 05 in parameter No.6072.

- **Variable value setting**

Set 0 in variables #501 to #505.

- **Program that calls a macro program**

```
O0001;
T0100 M06;
M03;
 :
M05; . . . . . Changes #501.
T0200 M06;
M03;
 :
M05; . . . . . Changes #502.
T0300 M06;
M03;
 :
M05; . . . . . Changes #503.
T0400 M06;
M03;
 :
M05; . . . . . Changes #504.
T0500 M06;
M03;
 :
M05; . . . . . Changes #505.
M30;
```

Macro program (program called)

```
O9001(M03); ..... Macro to start counting
  M01;
  IF[FIX[#4120/100] EQ 0]GOTO 9; ..... No tool specified
  IF[FIX[#4120/100] GT 5]GOTO 9; ..... Out–of–range tool number
  #3002=0; ..... Clears the timer.
N9 M03; ..... Rotates the spindle in the forward direction.
  M99;

O9002(M05); ..... Macro to end counting
  M01;
  IF[FIX[#4120/100] EQ 0]GOTO 9; ..... No tool specified
  IF[FIX[#4120/100] GT 5]GOTO 9; ..... Out–of–range tool number
  #[500+FIX[#4120/100]]=#3002+#[500+FIX[#4120/100]];
 ..... Calculates cumulative time.

N9 M05; ..... Stops the spindle.
  M99;
```

15.7 PROCESSING MACRO STATEMENTS

For smooth machining, the CNC prereads the CNC statement to be performed next. This operation is referred to as buffering. In tool nose radius compensation mode (G41, G42), the NC prereads NC statements two or three blocks ahead to find intersections. Macro statements for arithmetic expressions and conditional branches are processed as soon as they are read into the buffer. Blocks containing M00, M01, M02, or M30, blocks containing M codes for which buffering is suppressed by setting parameter(Nos.3411 to 3420), and blocks containing G31 are not preread.

Explanations

- **When the next block is not buffered (M codes that are not buffered, G31, etc.)**



- **Buffering the next block in other than tool nose radius compensation mode (G41, G42) (normally prereading one block)**



When N1 is being executed, the next NC statement (N4) is read into the buffer. The macro statements (N2, N3) between N1 and N4 are processed during execution of N1.

- **Buffering the next block in tool nose radius compensation mode (G41, G42)**



When N1 is being executed, the NC statements in the next two blocks (up to N5) are read into the buffer. The macro statements (N2, N4) between N1 and N5 are processed during execution of N1.

- **When the next block involves no movement in tool nose radius compensation C (G41, G42) mode**



When the NC1 block is being executed, the NC statements in the next two blocks (up to N5) are read into the buffer. Since N5 is a block that involves no movement, an intersection cannot be calculated. In this case, the NC statements in the next three blocks (up to N7) are read. The macro statements (N2, N4, and N6) between N1 and N7 are processed during execution of N1.

15.8 REGISTERING CUSTOM MACRO PROGRAMS

Custom macro programs are similar to subprograms. They can be registered and edited in the same way as subprograms. The storage capacity is determined by the total length of tape used to store both custom macros and subprograms.

15.9 LIMITATIONS

- **MDI operation**

  The macro call command can be specified in MDI mode too. During automatic operation, however, it is impossible to switch to the MDI mode for a macro program call.

- **Sequence number search**

  A custom macro program cannot be searched for a sequence number.

- **Single block**

  Even while a macro program is being executed, blocks can be stopped in the single block mode (except blocks containing macro call commands, arithmetic operation commands, and control commands).
  A block containing a macro call command (G65, G66, or G67) does not stop even when the single block mode is on. Blocks containing arithmetic operation commands and control commands can be stopped in single block mode by setting SBM (bit 5 of parameter 6000) to 1.
  Single block stop operation is used for testing custom macro programs. Note that when a single block stop occurs at a macro statement in tool nose radius compensation mode, the statement is assumed to be a block that does not involve movement, and proper compensation cannot be performed in some cases. (Strictly speaking, the block is regarded as specifying a movement with a travel distance 0.)

- **Optional block skip**

  A / appearing in the middle of an <expression> (enclosed in brackets [ ] on the right–hand side of an arithmetic expression) is regarded as a division operator; it is not regarded as the specifier for an optional block skip code.

- **Operation in EDIT mode**

  By setting NE8 (bit 0 of parameter 3202) and NE9 (bit 4 of parameter 3202) to 1, deletion and editing are disabled for custom macro programs and subprograms with program numbers 8000 to 8999 and 9000 to 9999. Registered custom macro programs and subprograms should be protected from being destroyed by accident. When the entire memory is cleared (by pressing the RESET and DELETE keys at the same time to turn on the power), the contents of memory such as custom macro programs are deleted.

- **Reset**

  With a reset operation, local variables and common variables #100 to #149 are cleared to null values. They can be prevented from being cleared by setting, CLV and CCV (bits 7 and 6 of parameter 6001). System variables #1000 to #1133 are not cleared.
  A reset operation clears any called states of custom macro programs and subprograms, and any DO states, and returns control to the main program.

- **Display of the PROGRAM RESTART screen**

  As with M98, the M and T codes used for subprogram calls are not displayed.

- **Feed hold**

  When a feed hold is enabled during execution of a macro statement, the machine stops after execution of the macro statement. The machine also stops when a reset or alarm occurs.

- **Constant values that can be used in <expression>**

  +0.0000001 to +99999999
  –99999999 to –0.0000001
  The number of significant digits is 8 (decimal). If this range is exceeded, P/S alarm No. 003 occurs.

15.10 EXTERNAL OUTPUT COMMANDS

In addition to the standard custom macro commands, the following macro commands are available. They are referred to as external output commands.

– BPRNT
– DPRNT
– POPEN
– PCLOS

These commands are provided to output variable values and characters through the reader/punch interface.

Explanations

Specify these commands in the following order:

Open command: POPEN
Before specifying a sequence of data output commands, specify this command to establish a connection to an external input/output device.

Data output command: BPRNT or DPRNT
Specify necessary data output.

Close command: PCLOS
When all data output commands have completed, specify PCLOS to release a connection to an external input/output device.

- **Open command POPEN**

POPEN

POPEN establishes a connection to an external input/output device. It must be specified before a sequence of data output commands. The CNC outputs a DC2 control code.

- **Data output command BPRNT**

BPRNT [a #b [c] …]



The BPRNT command outputs characters and variable values in binary.

(i) Specified characters are converted to corresponding ISO codes according to the setting data (ISO) that is output at that time.
Specifiable characters are as follows:
– Letters (A to Z)
– Numbers
– Special characters (*, /, +, –, etc.)
An asterisk (*) is output by a space code.

(ii) All variables are stored with a decimal point. Specify a variable followed by the number of significant decimal places enclosed in brackets. A variable value is treated as 2–word (32–bit) data, including the decimal digits. It is output as binary data starting from the highest byte.

(iii) When specified data has been output, an EOB code is output according to the ISO code settings.

(iv) Null variables are regarded as 0.

Example)

BPRINT [C X#100 [3] Z#101 [3] M#10 [0]]**
Variable value
#100=0.40596
#101=–1638.4
#10=12.34



- **Data output command DPRNT**



The DPRNT command outputs characters and each digit in the value of a variable according to the code set in the settings (ISO).

(i) For an explanation of the DPRNT command, see Items (i), (iii), and (iv) for the BPRNT command.

(ii) When outputting a variable, specify # followed by the variable number, then specify the number of digits in the integer part and the number of decimal places enclosed in brackets.
One code is output for each of the specified number of digits, starting with the highest digit. For each digit, a code is output according to the settings (ISO). The decimal point is also output using a code set in the settings (ISO).
Each variable must be a numeric value consisting of up to eight digits. When high–order digits are zeros, these zeros are not output if PRT (bit1 of parameter 6001) is 1. If PRT(bit 1 of parameter 6001) is 0, a space code is output each time a zero is encountered.
When the number of decimal places is not zero, digits in the decimal part are always output. If the number of decimal places is zero, no decimal point is output. When PRT (bit 1 of parameter 6001) is 0, a space code is output to indicate a positive number instead of +; if PRT(bit 1 of parameter 6001) is 1, no code is output.

Example)

DPRNT [X#2 [53] Z#5 [53] T#30 [20]]
Variable value
#2=128.47398
#5=–91.2
#30=123.456

(1) Parameter PRT(No.6001#1)=0



(2) Parameter PRT(No.6001#1)=1



- **Close command PCLOS**

PCLOS ;
The PCLOS command releases a connection to an external input/output device. Specify this command when all data output commands have terminated. DC4 control code is output from the CNC.

- **Required setting**

Specify the channel use for parameter 020. According to the specification of this parameter, set data items (such as the baud rate) for the reader/punch interface.
I/O channel 0 : Parameters 101, 102 and 103
I/O channel 1 : Parameters 111, 112 and 113
I/O channel 2 : Parameters 121, 122 and 123
Never specify output to the Fanuc Cassette or floppy disks.)
When specifying a DPRNT command to output data, specify whether leading zeros are output as spaces (by setting PRT (bit 1 of parameter 6001) to 1 or 0). To indicate the end of a line of data in ISO code, specify whether to use only an LF (NCR, of bit 3 of parameter 0103 is 0) or an LF and CR (NCR is 1).

NOTE

1 It is not necessary to always specify the open command (POPEN), data output command (BPRNT, DPRNT), and close command (PCLOS) together. Once an open command is specified at the beginning of a program, it does not need to be specified again except after a close command was specified.
2 Be sure to specify open commands and close commands in pairs. Specify the close command at the end of the program. However, do not specify a close command if no open command has been specified.
3 When a reset operation is performed while commands are being output by a data output command, output is stopped and subsequent data is erased. Therefore, when a reset operation is performed by a code such as M30 at the end of a program that performs data output, specify a close command at the end of the program so that processing such as M30 is not performed until all data is output.
4 Abbreviated macro words enclosed in brackets [ ] remains unchanged. However, note that when the characters in brackets are divided and input several times, the second and subsequent abbreviations are converted and input.
5 O can be specified in brackets [ ]. Note that when the characters in brackets [ ] are divided and input several times, O is omitted in the second and subsequent inputs.

15.11 INTERRUPTION TYPE CUSTOM MACRO

When a program is being executed, another program can be called by inputting an interrupt signal (UINT) from the machine. This function is referred to as an interruption type custom macro function. Program an interrupt command in the following format:

Format

M96 P○○○○ ;	Enables custom macro interrupt
M97 ;	Disables custom macro interrupt

Explanations

Use of the interruption type custom macro function allows the user to call a program during execution of an arbitrary block of another program. This allows programs to be operated to match situations which vary from time to time.

(1) When a tool abnormality is detected, processing to handle the abnormality is started by an external signal.

(2) A sequence of machining operations is interrupted by another machining operation without the cancellation of the current operation.

(3) At regular intervals, information on current machining is read.
Listed above are examples like adaptive control applications of the interruption type custom macro function.



Fig 15.11 Interruption type custom macro function

When M96Pxxxx is specified in a program, subsequent program operation can be interrupted by an interrupt signal (UINT) input to execute the program specified by Pxxxx.
When the interrupt signal (UINT, marked by * in Fig. 15.11 is input during execution of the interrupt program or after M97 is specified, it is ignored.

15.11.1 Specification Method

Explanations

- **Interrupt conditions**

A custom macro interrupt is available only during program execution. It is enabled under the following conditions

– When memory operation or MDI operation is selected
– When STL (start lamp) is on
– When a custom macro interrupt is not currently being processed

- **Specification**

Generally, the custom macro interrupt function is used by specifying M96 to enable the interrupt signal (UINT) and M97 to disable the signal.
Once M96 is specified, a custom macro interrupt can be initiated by the input of the interrupt signal (UINT) until M97 is specified or the NC is reset. After M97 is specified or the NC is reset, no custom macro interrupts are initiated even when the interrupt signal (UINT) is input. The interrupt signal (UINT) is ignored until another M96 command is specified.



The interrupt signal (UINT) becomes valid after M96 is specified. Even when the signal is input in M97 mode, it is ignored. When the signal input in M97 mode is kept on until M96 is specified, a custom macro interrupt is initiated as soon as M96 is specified (only when the status–triggered scheme is employed); when the edge–triggered scheme is employed, the custom macro interrupt is not initiated even when M96 is specified.

NOTE
For the status–triggered and edge–triggered schemes, see Item “Custom macro interrupt signal (UINT)” of Subsec. 16.11.2.

15.11.2 Details of Functions

Explanations

- **ubprogram–type interrupt and macro–type interrupt**

There are two types of custom macro interrupts: Subprogram–type interrupts and macro–type interrupts. The interrupt type used is selected by MSB (bit 5 of parameter 6003).

(a) Subprogram–type interrupt
An interrupt program is called as a subprogram. This means that the levels of local variables remain unchanged before and after the interrupt. This interrupt is not included in the nesting level of subprogram calls.

(b) Macro–type interrupt
An interrupt program is called as a custom macro. This means that the levels of local variables change before and after the interrupt. The interrupt is not included in the nesting level of custom macro calls. When a subprogram call or a custom macro call is performed within the interrupt program, this call is included in the nesting level of subprogram calls or custom macro calls. Arguments cannot be passed from the current program even when the custom macro interrupt is a macro–type interrupt.

- **M codes for custom macro interrupt control**

In general, custom macro interrupts are controlled by M96 and M97. However, these M codes, may already being used for other purposes (such as an M function or macro M code call) by some machine tool builders. For this reason, MPR (bit 4 of parameter 6003) is provided to set M codes for custom macro interrupt control.
When specifying this parameter to use the custom macro interrupt control M codes set by parameters, set parameters 6033 and 6034 as follows:
Set the M code to enable custom macro interrupts in parameter 6033, and set the M code to disable custom macro interrupts in parameter 6034.
When specifying that parameter–set M codes are not used, M96 and M97 are used as the custom macro control M codes regardless of the settings of parameters 6033 and 6034.
The M codes used for custom macro interrupt control are processed internally (they are not output to external units). However, in terms of program compatibility, it is undesirable to use M codes other than M96 and M97 to control custom macro interrupts.

- **Custom macro interrupts and NC statements**

When performing a custom macro interrupt, the user may want to interrupt the NC statement being executed, or the user may not want to perform the interrupt until the execution of the current block is completed. MIN (bit 2 of parameter 6003)is used to select whether to perform interrupts even in the middle of a block or to wait until the end of the block.

- **Type I (when an interrupt is performed even in the middle of the block)**

(i) When the interrupt signal (UINT) is input, any movement or dwell being performed is stopped immediately and the interrupt program is executed.

(ii) If there are NC statements in the interrupt program, the command in the interrupted block is lost and the NC statement in the interrupt program is executed. When control is returned to the interrupted program, the program is restarted from the next block after the interrupted block.

(iii) If there are no NC statements in the interrupt program, control is returned to the interrupted program by M99, then the program is restarted from the command in the interrupted block.



- **Type II (when an interrupt is performed at the end of the block)**

(i) If the block being executed is not a block that consists of several cycle operations such as a drilling canned cycle and automatic reference position return (G28), an interrupt is performed as follows:
When an interrupt signal (UINT) is input, macro statements in the interrupt program are executed immediately unless an NC statement is encountered in the interrupt program. NC statements are not executed until the current block is completed.

(ii) If the block being executed consists of several cycle operations, an interrupt is performed as follows:
When the last movement in the cycle operations is started, macro statements in the interrupt program are executed unless an NC statement is encountered. NC statements are executed after all cycle operations are completed.



- **Conditions for enabling and disabling the custom macro interrupt signal**

The interrupt signal becomes valid after execution starts of a block that contains M96 for enabling custom macro interrupts. The signal becomes invalid when execution starts of a block that contains M97.
While an interrupt program is being executed, the interrupt signal becomes invalid. The signal become valid when the execution of the block that immediately follows the interrupted block in the main program is started after control returns from the interrupt program. In type I, if the interrupt program consists of only macro statements, the interrupt signal becomes valid when execution of the interrupted block is started after control returns from the interrupt program.

- **Custom macro interrupt during execution of a block that involves cycle operation**

  - **For type I**

Even when cycle operation is in progress, movement is interrupted, and the interrupt program is executed. If the interrupt program contains no NC statements, the cycle operation is restarted after control is returned to the interrupted program. If there are NC statements, the remaining operations in the interrupted cycle are discarded, and the next block is executed.

  - **For type II**

When the last movement of the cycle operation is started, macro statements in the interrupt program are executed unless an NC statement is encountered. NC statements are executed after cycle operation is completed.

- **Custom macro interrupt signal (UINT)**

There are two schemes for custom macro interrupt signal (UINT) input: The status–triggered scheme and edge– triggered scheme. When the status–triggered scheme is used, the signal is valid when it is on. When the edge triggered scheme is used, the signal becomes valid on the rising edge when it switches from off to on status.
One of the two schemes is selected with TSE (bit 3 of parameter 6003). When the status–triggered scheme is selected by this parameter, a custom macro interrupt is generated if the interrupt signal (UINT) is on at the time the signal becomes valid. By keeping the interrupt signal (UINT) on, the interrupt program can be executed repeatedly.
When the edge–triggered scheme is selected, the interrupt signal (UINT) becomes valid only on its rising edge. Therefore, the interrupt program is executed only momentarily (in cases when the program consists of only macro statements). When the status–triggered scheme is inappropriate, or when a custom macro interrupt is to be performed just once for the entire program (in this case, the interrupt signal may be kept on), the edge–triggered scheme is useful.
Except for the specific applications mentioned above, use of either scheme results in the same effects. The time from signal input until a custom macro interrupt is executed does not vary between the two schemes.



In the above example, an interrupt is executed four times when the status triggered scheme is used; when the edge– triggered scheme is used, the interrupt is executed just once.

- **Return from a custom macro interrupt**

To return control from a custom macro interrupt to the interrupted program, specify M99. A sequence number in the interrupted program can also be specified using address P. If this is specified, the program is searched from the beginning for the specified sequence number. Control is returned to the first sequence number found.
When a custom macro interrupt program is being executed, no interrupts are generated. To enable another interrupt, execute M99. When M99 is specified alone, it is executed before the preceding commands terminate. Therefore, a custom macro interrupt is enabled for the last command of the interrupt program. If this is inconvenient, custom macro interrupts should be controlled by specifying M96 and M97 in the program.
When a custom macro interrupt is being executed, no other custom macro interrupts are generated; when an interrupt is generated, additional interrupts are inhibited automatically. Executing M99 makes it possible for another custom macro interrupt to occur. M99 specified alone in a block is executed before the previous block terminates. In the following example, an interrupt is enabled for the Gxx block of O1234. When the signal is input, O1234 is executed again. O5678 is controlled by M96 and M97. In this case, an interrupt is not enabled for O5678 (enabled after control is returned to O1000).



NOTE

When an M99 block consists only of address O, N, P, L, or M, this block is regarded as belonging to the previous block in the program. Therefore, a single–block stop does not occur for this block. In terms of programming, the following (1) and (2) are basically the same. (The difference is whether G○○ is executed before M99 is recognized.)

(1) G○○ X○○○ ;
M99 ;
(2) G○○ X○○○ M99 ;

● Custom macro interrupt and modal information

A custom macro interrupt is different from a normal program call. It is initiated by an interrupt signal (UINT) during program execution. In general, any modifications of modal information made by the interrupt program should not affect the interrupted program.
For this reason, even when modal information is modified by the interrupt program, the modal information before the interrupt is restored when control is returned to the interrupted program by M99.
When control is returned from the interrupt program to the interrupted program by M99 Pxxxx, modal information can again be controlled by the program. In this case, the new continuous information modified by the interrupt program is passed to the interrupted program. Restoration of the old modal information present before the interrupt is not desirable. This is because after control is returned, some programs may operate differently depending on the modal information present before the interrupt. In this case, the following measures are applicable:

(1) The interrupt program provides modal information to be used after control is returned to the interrupted program.

(2) After control is returned to the interrupted program, modal information is specified again as necessary.



• Modal information when control is returned by M99

The modal information present before the interrupt becomes valid. The new modal information modified by the interrupt program is made invalid.

• Modal information when control is returned by M99 P○○○○

The new modal information modified by the interrupt program remains valid even after control is returned. The old modal information which was valid in the interrupted block can be read using custom macro system variables #4001 to #4120.
Note that when modal information is modified by the interrupt program, system variables #4001 to #4120 are not changed.

- **System variables (position information values) for the interrupt program**

  - The coordinates of point A can be read using system variables #5001 and up until the first NC statement is encountered.
  - The coordinates of point A’ can be read after an NC statement with no move specifications appears.
  - The machine coordinates and workpiece coordinates of point B’ can be read using system variables #5021 and up and #5041 and up.



- **Custom macro interrupt and custom macro modal call**

  When the interrupt signal (UINT) is input and an interrupt program is called, the custom macro modal call is canceled (G67). However, when G66 is specified in the interrupt program, the custom macro modal call becomes valid. When control is returned from the interrupt program by M99, the modal call is restored to the state it was in before the interrupt was generated. When control is returned by M99Pxxxx;, the modal call in the interrupt program remains valid.

- **Custom macro interrupt and program restart**

  When the interrupt signal (UINT) is input while a return operation is being performed in the dry run mode after the search operation for program restart, the interrupt program is called after restart operation terminates for all axes. This means that interrupt type II is used regardless of the parameter setting.

16 PROGRAMMABLE PARAMETER ENTRY (G10)

General

The values of parameters can be entered in a program. This function is used for setting pitch error compensation data when attachments are changed or the maximum cutting feedrate or cutting time constants are changed to meet changing machining conditions.

Format

Format	
G10L50;	Parameter entry mode setting
N_R_;	For parameters other than the axis type
N_P_R_;	For axis type parameters
⋮	
G11;	Parameter entry mode cancel

Meaning of command	
N_:	Parameter No. (4digits) or compensation position No.(0 to 1023) for pitch errors compensation +10,000 (5digit)
R_:	Parameter setting value (Leading zeros can be omitted.)
P_:	Axis No. 1 to 8 (Used for entering axis type parameters)

Explanations

- **Parameter setting value (R_)**

Do not use a decimal point in a value set in a parameter (R_).
a decimal point cannot be used in a custom macro variable for R_ either.

- **Axis No.(P_)**

Specify an axis number (P_) from 1 to 8 (up to eight axes) for an axis type parameter. The control axes are numbered in the order in which they are displayed on the CNC display.
For example, specify P2 for the control axis which is displayed second.

WARNING
1 Do not fail to perform reference point return manually after changing the pitch error compensation data or backlash compensation data. Without this, the machine position can deviate from the correct position.
2 The canned–cycle mode must be cancelled before entering of parameters. When not cancelled, the drilling motion will be activated.

NOTE
Other NC statements cannot be specified while in parameter input mode.

Examples

1. Set bit 2 (SPB) of bit type parameter No. 3404

G10L50 ;	Parameter entry mode
N3404 R 00000100 ;	SBP setting
G11 ;	cancel parameter entry mode

2. Change the values for the Z–axis and C–axis in axis type parameter No.1322 (the coordinates of stored stroke limit 2 in the positive direction for each axis).

G10L50 ;	Parameter entry mode
N1322P3R4500 ;	Modify Z axis
N1322P4R12000 ;	Modify C axis
G11 ;	cancel parameter entry mode

17 MEMORY OPERATION BY Series 10/11 TAPE FORMAT

Programs in the Series 10/11 tape format can be registered in memory for memory operation by setting bit 1 of parameter No. 0001. Registration to memory and memory operation are possible for the functions which use the same tape format as that for the Series 10/11 as well as for the following functions which use a different tape format:

- **Equal–lead threading**
- **Subprogram calling**
- **Canned cycle**
- **Multiple repetitive canned cycle**
- **Canned drilling cycle**

NOTE
Registration to memory and memory operation are possible only for the functions available in this CNC.

17.1 ADDRESSES AND SPECIFIABLE VALUE RANGE FOR Series 10/11 TAPE FORMAT

Some addresses which cannot be used for the this CNC can be used in the Series 10/11 tape format. The specifiable value range for the Series 15 tape format is basically the same as that for the this CNC. Sections II–17.2 to II–17.5 describe the addresses with a different specifiable value range. If a value out of the specifiable value range is specified, an alarm is issued.

17.2 EQUAL–LEAD THREADING

Format

G32IP_F_Q_;
or
G32IP_E_Q_;

IP:Combination of axis addresses
F :Lead along the longitudinal axis
E :Lead along the longitudinal axis
Q :Sight of the threading start angle (ignored if specified)

Explanations

- **Address**

Although the Series 15 allows the operator to specify the number of threads per inch with address E, the Series 15 tape format does not. Addresses E and F are used in the same way for specifying the lead along the longitudinal axis. The thread lead specified with address E is therefore also assumed as a continuous–state value for address F. Address Q for specifying the shift of the threading start angle can be specified but is ignored.

- **Specifiable value range for the thread lead**

Address for thread lead		mm input	inch input
E		0.0001 to 500.0000mm	0.000001 to 9.999999inch
F	Command with a decimal point	0.0001 to 500.0000mm	0.000001 to 9.999999inch
	Command without a decimal point	0.01 to 500.00mm	0.0001 to 9.9999inch

- **Specifiable value range for the feedrate**

Address for feedrate			mm input	inch input
F	Feed per minute	Increment system (IS–B)	1 to 240000 mm/min	0.01 to 9600.00 inch/min
		Increment system (IS–C)	1 to 100000 mm/min	0.01 to 4800.00 inch/min
	Feed per rotation		0.01 to 500.00 mm/rev	0.0001 to 9.9999 inch/rev

WARNING
Specify the feedrate one more time when switching between feed per minute and feed per rotation.

17.3 SUBPROGRAM CALLING

Format

M98P○○○○L○○○○;

P:Subprogram number
L:Repetition count

Explanation

- **Address**

  Address L cannot be used in this CNC tape format but can be used in the Series 15 tape format.

- **Subprogram number**

  The specifiable value range is the same as that for this CNC (1 to 9999). If a value of more than four digits is specified, the last four digits are assumed as the subprogram number.

- **Repetition count**

  The repetition count L can be specified in the range from 1 to 9999. If no repetition count is specified, 1 is assumed.

17.4 CANNED CYCLE

Format

Outer / inner surface turning cycle (straight cutting cycle)
G90X_Z_F_;

Outer / inner surface turning cycle (taper cutting cycle)
G90X_Z_I_F_;
I:Length of the taper section along the X–axis (radius)

Threading cycle (straight threading cycle)
G92X_Z_F_Q_;
F:Thread lead
Q:Shift of the threading start angle (ignored if specified)

Threading cycle (taper threading cycle)
G92X_Z_I_F_;
I:Length of the taper section along the X–axis (radius)

End surface turning cycle (front taper cutting cycle)
G94X_Z_F_;

End surface turning cycle (front taper cutting cycle)
G94X_Z_K_F_;
K:Length of the taper section along the Z–axis

- **Address**

Addresses I and K cannot be used for a canned cycle in this CNC tape format but can be used in the Series 15 tape format. Address Q can be specified in the Series 15 format but is ignored.

- **Specifiable value range for the feedrate**

Same as that for equal–lead threading in section II–17.2. See section II–17.2.

17.5 MULTIPLE REPETITIVE CANNED TURNING CYCLE

Format

Outer / inner surface turning cycle

G71P_Q_U_W_I_K_D_F_S_T_;

I : Length and direction of cutting allowance for finishing the rough machining cycle along the X–axis (ignored if specified)
K : Length and direction of cutting allowance for finishing the rough machining cycle along the Z–axis (ignored if specified)
D : Depth of cut

End surface rough machining cycle

G72P_Q_U_W_I_K_D_F_S_T_;

I : Length and direction of cutting allowance for finishing the rough machining cycle along the X–axis (ignored if specified)
K : Length and direction of cutting allowance for finishing the rough machining cycle along the Z–axis (ignored if specified)
D : Depth of cut

Closed–loop turning cycle

G73P_Q_U_W_I_K_D_F_S_T_;

I : Length and direction of clearance along the X–axis (radius)
K : Length and direction of clearance along the Z–axis
D : Number of divisions

End surface cutting–off cycle

G74X_Z_I_K_F_D_;
or
G74U_W_I_K_F_D_;

I : Distance to be traveled along the X–axis
K : Depth of cut along the Z–axis
D : Clearance of the tool at the end of the cutting path

Outer / inner surface cutting–off cycle

G75X_Z_I_K_F_D_;
or
G75U_W_I_K_F_D_;

I : Distance to be traveled along the X–axis
K : Depth of cut along the Z–axis
D : Clearance of the tool at the end of the cutting path

Multiple repetitive threading cycle

G76X_Z_I_K_D_F_A_P_Q_;

I : Difference of radiuses at threads
K : Height of thread crest (radius)
D : Depth of the first cut (radius)
A : Angle of the tool tip (angle of ridges)
P : Method of cutting

- **Addresses and specifiable value range**

If the following addresses are specified in the Series 15 tape format, they are ignored.

- I and K for the outer/inner surface rough machining cycle (G71)
- I and K for the end surface rough machining cycle (G72)

Address P for specifying the method of cutting for the multiple repetitive threading cycle (G76) is always P1 (constant depth of cut with a single edge) regardless of the command value for P. A value of between 0 and 120 degrees can be specified for tool tip angle A. If other values are specified, P/S alarm 062 is issued.
Address D (cutting depth and retraction distance) can be specified with a value between –99999999 and 99999999, in the minimum input increment, even when calculator–like decimal point input is specified (when bit 0 (DPI) of parameter No. 3401 is set to 1). When address D contains a decimal point, P/S alarm No. 007 is issued.

The specifiable value range for the feedrate is the same as that for equal–lead threading. See section II–17.2.

17.6 CANNED DRILLING CYCLE FORMATS

Format

Drilling cycle
G81X_C_Z_F_L_ ; or G82X_C_Z_R_F_L_ ;
R : Distance from the initial level to the R position
P : Dwell time at the bottom of the hole
F : Cutting feedrate
L : Number of repetitions

Peck drilling cycle
G81X_C_Z_R_Q_P_F_L_ ;
R : Distance from the initial level to the R position
Q : Depth of cut in each cycle
P : Dwell time at the bottom of the hole
F : Cutting feedrate
L : Number of repetitions

High–speed peck drilling cycle
G83.1X_C_Z_R_Q_P_F_L_ ;
R : Distance from the initial level to the R position
Q : Depth of cut in each cycle
P : Dwell time at the bottom of the hole
F : Cutting feedrate
L : Number of repetitions

Tapping
G84X_C_Z_R_P_F_L_ ;
R : Distance from the initial level to the R position
P : Dwell time at the bottom of the hole
F : Cutting feedrate
L : Number of repetitions

Rigid tapping
G84.2X_C_Z_R_P_F_L_S_ ;
R : Distance from the initial level to the R position
P : Dwell time at the bottom of the hole
F : Cutting feedrate
L : Number of repetitions
S : Spindle speed

Boring cycle
G85X_C_Z_R_F_L_ ; or G89X_C_Z_R_P_F_L_ ;
R : Distance from the initial level to the R position
P : Dwell time at the bottom of the hole
F : Cutting feedrate
L : Number of repetitions

Cancel
G80 ;

Explanations

- **Address**

For this CNC tape format, the address used to specify the number of repetitions is K. For the Series 15 tape format, it is L.

● G code

Some G codes are valid only for this CNC tape format or Series 15 tape format. Specifying an invalid G code results in P/S alarm No. 10 being generated.

G codes valid only for the Series 15 tape format	G81, G82, G83.1, G84.2
G codes valid only for the Series 16/18/160/180 tape format	G87, G88

● Positioning plane and drilling axis

For this CNC tape format, the positioning plane and drilling axis are determined according to the G code for the canned cycle used.
For the Series 15 tape format, the positioning plane and drilling axis are determined according to G17/G19.
The drilling axis is the basic axis (Z–axis or X–axis) that does not lie in the positioning plane.

G code	Positioning plane	Drilling axis
G17	XY plane	Z–axis
G19	YZ plane	X–axis

Resetting bit 1 (FXY) of parameter No. 5101 enables fixing of the drilling axis to the Z–axis.

● Details of data specifying machining

Data for the canned cycle is specified as follows:



Setting	Address	Explanation
Drilling mode	G□□	Canned drilling cycle G code
Hole position data	X/U (Z/W) C/H	Incremental or absolute value used to specify the hole position
Drilling mode	Z/W (X/U)	Incremental or absolute value used to specify the distance from the R position to the bottom of the hole
	R	Incremental value used to specify the distance from the initial level to the R position, or absolute value used to specify the R position. Which to use depends on bit 6 of parameter No. 5102 and the G code system being used.
	Q	Incremental value used to specify the depth of cut in each G83 or G83.1 cycle with radius programming.
	P	Dwell time at the bottom of the hole. The relationship between the dwell time and the specified value is the same as that for G04.
	F	Cutting feedrate
Number of repetitions	L	Number of repetitions for a sequence of cutting operations. If L is not specified, it is assumed to be 1.

- **Specifying the R position**

The R position is specified as an incremental value for the distance between the initial level to the R position. For the Series 15 tape format, the parameter and the G code system used determine whether an incremental or absolute value is to be used to specify the distance between the initial level and the R position.
If bit 6(RAB) of parameter No. 5102 is 0, an incremental value is always used. If it is 1, the type of value used depends on the G code system used. When G code system A is used, an absolute value is used. When G code system B or C is used, an absolute value is used in G90 mode, and an incremental value is used in G91 mode.

<table>
<tr><th colspan="4">Series 15 tape format</th><th>Series 16/18/160/180 tape format</th></tr>
<tr><td colspan="3">Bit 6 of parameter No. 5102 = 1</td><td>Bit 6 of parameter No. 5102 = 0</td><td rowspan="5">Incremental</td></tr>
<tr><td colspan="3">G code system</td><td rowspan="4">Incremental</td></tr>
<tr><td>A</td><td colspan="2">B, C</td></tr>
<tr><td rowspan="2">Absolute</td><td>G90</td><td>G91</td></tr>
<tr><td>Absolute</td><td>Incremental</td></tr>
</table>

- **Details of the canned cycle**

The correspondence between the G codes and this CNC tape format or Series 15 tape format is listed below. This list also provides notes on dwell during a canned cycle.

No. G□□ (Use) This CNC command format

1. **G81 (Drilling cycle) G83 (G87) P0 <Q not specified>**
   No dwelling
2. **G82 (Drilling cycle) G83 (G87) P <Q not specified>**
   The tool always dwells at the bottom of the hole.
3. **G83 (Peck drilling cycle) G83 (G87) <Type B>**
   If the block contains a P command, the tool dwells at the bottom of the hole.
4. **G83.1 (Peck drilling cycle) G83 (G87) <Type A>**
   If the block contains a P command, the tool dwells at the bottom of the hole.
   Note) Either type A or B is selected according to bit 2 (RTR) of parameter No. 5101.
5. **G84 (Tapping) G84 (G88)I**
   f the block contains a P command, the tool dwells after it reaches the bottom of the hole and after it is retracted to the R position.
6. **G84.2 (Rigid tapping) M29 S_ G84 (G88)**
   If the block contains a P command, the tool dwells before the spindle starts rotating in reverse at the bottom of the hole and before it starts rotating in the normal direction at the R position.
7. **G85 (Boring cycle) G85 (G89) P0**
   No dwelling
8. **G89 (Boring cycle) G85 (G89) P_**
   The tool always dwells at the bottom of the hole.

- **Clearance d for G83 and G83.1**

Parameter No. 5114 determines clearance d for G83 and G83.1.

- **Dwell with G83 and G83.1**

For Series 15–T, G83 or G83.1 does not cause the tool to dwell. For the Series 15 tape format, the tool dwells at the bottom of the hole only if the block contains a P address.

- **Dwelling with G84 and G84.2**

In Series 15–T, G84/G84.2 causes the tool to dwell before the spindle starts rotating in either the normal or reverse direction, according to the corresponding parameter setting. For the Series 15 tape format, when the block contains a P address, the tool dwells at the bottom of the hole and at the R position before the spindle starts rotating either in the normal or reverse direction.

- **Rigid tapping**

For the Series 15 tape format, rigid tapping can be specified by using the methods listed below:

Format	Condition (parameter), comment
G84.2 X_ Z_ R_ ...S**** ;	Setting (F10/F11) = 1
S**** ; G84.2 X_ Z_ R_ .... ;	
M29 S**** ; G84 X_ Z_ R_ .... ;	* Common to Series 16 format
M29 S**** G84 X_ Z_ R_ .... ;	
G84 X_ Z_ R_ .... S**** ;	G84 is made a G code for rigid tapping. Bit 0 (G84) of parameter No. 5200 = 1 * Common to Series 16 format
S**** ; G84 X_ Z_ R_ .... ;	

- **Diameter or radius programming**

Specifying 1 for bit 7 (RDI) of parameter No. 5102 causes the canned cycle R command diameter or radius programming mode in the Series 15 tape format to match the diameter or radius programming mode for the drilling axis.

- **Disabling the Series 15 format**

Specifying bit 3 (F16) of parameter No. 5102 disables the Series 15 tape format. This applies only to the canned drilling cycle. However, the number of repetitions must be specified by using the L address.

CAUTION
Setting bit 3 (F16) of parameter No. 5102 to 1 overrides bits 6 (RAB) and 7 (RDI) of parameter No. 5102; both settings are assumed to be 0.

Limitations

- **C–axis as the drilling axis**

It is impossible to use the C–axis (the third axis) as a drilling axis. So, specifying G18 (ZX plane) generates P/S alarm No. 28 (plane selection command error).

- **Clamping the C–axis**

For the Series 15 tape format, it is impossible to specify an M code for clamping the C–axis.

18 FUNCTIONS FOR HIGH SPEED CUTTING

18.1 REMOTE BUFFER

The remote buffer function enables a large amount of data to be supplied to the CNC continuously and at high speed, by connecting a host computer or input/output device via a serial interface.



Using a remote buffer for online connection to the host computer enables high–speed, highly reliable DNC operation.
Remote buffers include high–speed remote buffer A, which enables high–speed machining using binary data.
For details of the remote buffer specifications, refer to the Supplement for Remote Buffer Description (B–61802E–1).

18.2 HIGH–SPEED REMOTE BUFFER A (G05)

After a block containing only G05 is specified in normal NC format, operation can be performed by specifying movement data in the format described below. Once zero has been specified as the amount of travel for each axis, normal NC command format is restored.



Format

- Turning binary input operation on: G05;
- Turning binary input operation off: 0 for amount of travel for each axis
- Data format for binary input operation



Data for binary input operation is specified in a format where the amount of travel per unit time (2 bytes) for each axis is specified sequentially from the first axis to the Nth axis, after which a check byte (1 byte) follows (the data length for a single block is [2 x N + 1] bytes).

All data is represented in binary.

Explanations

- **Selecting the unit time**

The unit time (ms) can be specified using bits 4, 5, and 6 (IT0, IT1, and IT2) of parameter No. 7501.

- **Data for amount of travel**

Specify the amount of travel for each axis in the following units (specify a twos complement for a negative amount).

Increment system	IS–B	IS–C	Units
Millimeter machine	0.001	0.0001	mm
Inch machine	0.0001	0.00001	inch

The format of each data word is as follows. Use the bits indicated by * to specify the amount of travel per unit time.

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
*	*	*	*	*	*	*	0	*	*	*	*	*	*	*	0

Example: When the amount of travel per unit time is 700 um (millimeter machine, IS–B)

15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
0	0	0	0	1	0	1	0	0	1	1	1	1	0	0	0

- **Check byte**

The check byte shall indicate the sum of the [2 × N] bytes, not including the check byte, in byte units, with any overflow exceeding eight bits discarded.

- **Transfer rate**

The CNC outputs data of [2 × N + 1] bytes (N: number of axes) from the remote buffer every unit time, specified with the parameters. To ensure that the CNC can continue machining without stopping halfway, the minimum transfer baud rate between the host and remote buffer is as follows:

$$(2 \times N + 1) \times \frac{11}{T} \times 1000 \qquad (T: \text{ unit time})$$

- **Tool–nose R compensation**

If G05 is specified in tool–nose R compensation mode, a P/S alarm (No. 178) is issued.

- **Feed hold and interlock**

Feed hold and interlock are valid in binary input operation mode.

- **Mirror image**

Mirror image (programmable mirror image or setting image) cannot be turned on or off in G05 mode.

- **Acceleration/deceleration type**

Exponential acceleration/deceleration (with the time constant specified with parameter No. 1622) in cutting feed mode is used at the start and end of movement in binary input operation mode.

Limitations

- **Modal command**

In binary input operation mode, only linear interpolation based on the specified data format is executed (equivalent to an incremental command for linear interpolation).

- **Invalid functions**

Single block stop, feedrate override, and maximum cutting feedrate clamp are invalid in binary input operation mode. The program restart function cannot be used. Miscellaneous functions are also invalid.

- **Registration in memory**

A program cannot be registered in memory in binary input operation mode.

18.3 DISTRIBUTION PROCESSING TERMINATION MONITORING FUNCTION FOR THE HIGH–SPEED MACHINING COMMAND (G05)

During high–speed machining, the distribution processing status is monitored. When distribution processing terminates, P/S alarm No. 000 and P/S alarm No. 179 are issued upon completion of the high–speed machining command (according to the setting of ITPDL (bit 7 of parameter No. 7501)).

These P/S alarms can be canceled only by turning off the CNC power.

Explanations

- **High–speed machining command**

High–speed machining using the high–speed remote buffer A function, high–speed remote buffer B function, and high–speed cycle function based on the G05 command

- **Distribution processing termination**

Failure to perform normal distribution processing because distribution processing required for high–speed machining exceeded the CNC processing capacity, or because distribution data sent from the host was delayed for some reason while the high–speed remote buffer A or G function was being used

Number	Message	Contents
000	PLEASE TURN OFF POWER	During high–speed machining, distribution processing was terminated. Related parameters: Remote buffer transfer baud rate (parameter No. 133) Number of controlled axes in high–speed machining (parameter No. 7150) High–speed axis selection during high–speed machining (bit 0 of parameter No. 7510)
179	PARAM. (NO. 7510) SETTING ERROR	

19 AXIS CONTROL FUNCTION

19.1 POLYGONAL TURNING

Polygonal turning means machining a polygonal figure by rotating the workpiece and tool at a certain ratio.



Fig. 19.1 (a) Polygonal turning

By changing conditions which are rotation ratio of workpiece and tool and number of cutters,the machining figure can be changed to a square or hexagon. The Machining time can be reduced as compared with polygonal figure machining using C and X axes of the polar coordinate. The machined figure however, is not exactly polygonal. Generally, polygonal turning is used for the heads of square and/or hexagon bolts or hexagon nuts.



Fig. 19.1 (b) Hexagon bolt

Format

G51.2(G251)	**P_Q_;**	
	P,Q:	**Rotation ratio of spindle and Y axis** **Specify range**:**Intefer 1 to 9 for both P and Q** **When Q is a positive value, Y axis makes positive rotation.** **When Q is a negative value, Y axis makes negative rotation.**

Explanations

Tool rotation for polygonal turning is controlled by CNC controlled axis. This rotary axis of tool is called Y axis in the following description.
The Y axis is controlled by G51.2 command, so that the rotation speeds of the workpiece mounted on the spindle (previously specified by S–command) and the tool becomt the specified ratio.
(Example) Rotation ratio of workpiece (spindle) to Y axis is 1:2, and the Y axis makes positive rotation.
G51.2P1Q2;
When simultaneous start is specified by G51.2, the one–rotation signal sent from the position codes set on the spindle is detected. After this detection. the Y axis rotation is controoled according to the rotation ratio (P:Q) while synchronizing with the spindle speed. Namely, the Y axis rotation is controlled so that the spindle and Y axis stand in a relation of P:Q. This relation will be maintained until the plygonal turning cancel command is executed (G50.2 or reset operation). The direction of Y axis rotation is determined by the code
Q and not affected by the direction of the lposition coder rotation.
Synchronixation of the spindle and Y axis is canceled by the following commnad:
G50.2(G250);
When G50.2 is specified, synchronization of the spindle and Y axis is canceled and the Y axis stops.
This synchronization is also canceledd in the following casset:

i) Power off

ii) Emergency stop

iii) Servo alarm

iv) Reset (external reset signal ERS, reset/rewind ignal RRW, and RESET key on the MDI panel)

v) Occurrence of P/S alarm Nos. 217 to 221

Example

G00X100. 0Z20.0 S1000.0M03 ; Workpiece rotation speed 1000rmp
G51.2P1 Q2 ; Tool rotation start (tool rotation speed 2000rpm)
G01X80.0 F10.0 ; X axis infeed
G04X2. ;
G00X100.0 ; X axis escape
G50.2 ; Tool rotation stop
M05 ; Spindle stop Specify **G50.2** and **G51.2** always in a single block.

- **Principle of Polygonal Turning**

The principle of polygonal turning is explained below. In the figure below the radius of tool and workpiece are A and B, and the angular speeds of tool and workpiece are aand b. The origin of XY cartesian coordinates is assumed to be the center of the workpiece.
Simplifying the explanation, consider that the tool center exists at the position
Po (A,0) on the workpiece periphery, and the tool nose starts from position Pto(A–B, 0).



In this case, the tool nose position Pt (Xt,Yt) after time t is expressed by equation 1:



$Xt=A\cos \alpha t-B\cos(\beta-\alpha)t$
(Equation 1)
$Yt=A\sin \alpha t+B\sin(\beta-\alpha)t$
Assuming that the rotation ration of workpiece to tool is 1:2, namely, $\beta=2\alpha$,
equation 1 is modified as follows

$Xt=A\cos \alpha t-B\cos \alpha t=(A-B)\cos \alpha t$
(Equation 2)
$Xt=A\sin \alpha t+B\sin \alpha t=(A+B)\sin \alpha t$
Equation 2 indicates that the tool nose path draws an ellipse with longer diameter A+B and shorter diameter A–B.
Then consider the case when one tool is set at 180° symmetrical positions, for atotal of two. It is seen that a square can be machined with these tools as shown below.



If three tools are set at every 120°, the machining figure will be a hexagon as shown below.



WARNING

1 The starting point of the threading process becomes inconsistent when performed during synchronous operation.
Cancel the synchronizing by executing G50.2 when threading.

2 The following signals become either valid or invalid in relation to the Y axis in synchronous operation.
Valid signals in relation to Y axis:
machine lock
servo off
Invalid signals in relation to Y axis:
feed hold
interlock
ovrride
dry run
(During a dry run, however, there is no wait for a revolution signal in the G51.2 block.)

NOTE

1 The Y axis, unlike the other controlled axes, cannot be specifiied a move command as Y—. That is, an axis move command is unnecessary for the Y axis. Because, when G51.2 (polygonal turning mode) is specified, it is only necessary to control the Y axis so that the tool rotates at a certain ratio to the spindle rotation speed.
However, only the reference point return command (G28V0;) can be specified since the Y axis rotation is stopped at the unstable position when G50.2 (polygonal turning mode cancel command) is specified. If the tool rotation start position is unstable , a problem may occur, for example, when the same figure is machined with a finishing tool after once machined with a roughing tool.
Specification of G28V0; for Y axis is equal to the orientation command for the spindle. In the other axes, unlike the manual reference point return, G28 usually makes reference point return without detecting the deceleration limit. However, with G28V0; , for the Y axis, reference point return is executed by detecting the deceleration limit, like manual reference point return.
To machine a workpiece into the same figure as the previous one, the tool and the spindle must be in the same position as the previous time when the tool starts rotating. The tool is set start rotation when the one–rotation signal of the position coder set on the spindle is detected.

2 The Y axis used to control tool rotation for polygonal turning uses the 4th axis. However, by setting parameters, (No.7610) the 3rd axis may also be used. In this case, that axis must be named C axis.

3 Among the position display of the Y axis, the display for the machine coordinate value (MECHINE) will change from a range of 0 to the parameter setting (the amount of movement per revolution) as the Y axis moves.
Absolute or relative coordinate values are not renewed.

4 An absolute position detector cannot be set on the Y axis.

5 Manual continuous feed or handle feed is invalid when the Y axis is in synchronous operation.

6 The Y axis in synchronous operation is not included in the number of axis controlled simultaneously.

19.2 ROTARY AXIS ROLL–OVER

The roll–over function prevents coordinates for the rotation axis from overflowing. The roll–over function is enabled by setting bit 0 of parameter 1008 to 1.

Explanations

For an incremental command, the tool moves the angle specified in the command. For an absolute command, the coordinates after the tool has moved are values set in parameter No. 1260, and rounded by the angle corresponding to one rotation. The tool moves in the direction in which the final coordinates are closest when bit 1 (ROAx)of parameter No. 1008 is set to 0. Displayed values for relative coordinates are also rounded by the angle corresponding to one rotation when bit 2 (ROAx) of parameter No. 1008 is set to 1

Examples

Assume that axis C is the rotating axis and that the amount of movement per rotation is 360.000 (parameter No. 1260 = 360000). When the following program is executed using the roll–over function of the rotating axis, the axis moves as shown below.

C0 ;	**Sequence number**	**Actual movement value**	**Absolute coordinate value after movement end**
N1 C–150.0 ;	N1	–150	210
N2 C540.0 ;	N2	–30	180
N3 C–620.0 ;	N3	–80	100
N4 H380.0 ;	N4	+380	120
N5 H–840.0 ;	N5	–840	0



19.3 SIMPLE SYNCHRONIZATION CONTROL

The simple synchronization control function allows synchronous and normal operations on two specified axes to be switched, according to an input signal from the machine.
For a machine with two tool posts that can be independently driven with different controlled axes, this function enables the operations described below.
This section describes the operations of a machine having two tool posts, both of which can be independently operated along the X–axis and Y–axis. If your machine uses other axes for the same purpose, substitute the corresponding axis names for X and Y.



Fig. 19.3 (a) Sample Axis Configuration of a Machine on which the Simple Synchronization Control Function is Executed

Explanations

- **Synchronous operation**

Synchronous operation is possible on a machine having two tool posts. In synchronous operation mode, movement on one axis can be synchronized with movement specified for another axis. The move command can be specified for one of the two axes, which is referred to as the master axis. The other axis, for referred synchronization with the master axis is maintained, is referred to as the slave axis. If the master axis is X and the slave axis is Y, synchronous operation on the X–axis (master axis) and Y–axis (slave axis) are performed according to Xxxxx commands issued for the master axis.
In synchronous operation mode, a move command specified for the master axis results in simultaneous operation of the servo motors of the master and slave axes.
In this mode, synchronization error compensation is not performed. That is, any positioning error between the two servo motors is not monitored, nor is the servo motor of the slave axis adjusted to minimize any error. No synchronization error alarm is output. Automatic operations can be synchronized, but manual operations cannot.

- **Normal operation**

Normal operation is performed when different workpieces are machined on different tables. As with normal CNC control, move commands for the master and slave axes are specified with the addresses of those axes (X and Y). Move commands for the two axes can be specified in an identical block.

1 According to the Xxxxx command programmed for the master axis, movement is performed along the X–axis, as in normal mode.

2 According to the Yyyyy command programmed for the slave axis, movement is performed along the Y–axis, as in normal mode.

3 According to the Xxxxx Yyyyy command, simultaneous movements are performed along both the X–axis and Y–axis, as in normal mode. Both automatic and manual operations can be controlled, as in normal CNC control.

- **Switching synchronous and normal operations**

For details of how to switch the synchronous and normal operations, refer to the manual supplied by the machine tool builder.

- **Automatic reference position return**

If a command for automatic reference position return (G28), or return to the second, third, or fourth reference position (G30), is issued in synchronous operation mode, a reference position return is performed for the X–axis, and an identical movement is performed for the Y–axis. If this Y–axis movement agrees with a return to the reference position on the Y–axis, a lamp indicating that reference position return has been completed for the Y–axis also lights.
It is recommended, however, that G28 and G30 be specified in normal operation mode.

- **Checking automatic reference position return**

If a command for checking automatic reference position return (G27) is issued in synchronous operation mode, identical movements are performed for the X–axis and Y–axis.
If these X–axis and Y–axis movements correspond to returns to the reference positions on the X–axis and Y–axis, the lamps indicating that reference position return has been completed for the X–axis and Y–axis light. If not, an alarm is output.
It is recommended, however, that G27 be specified in normal operation mode.

- **Slave axis command**

If a move command is specified for the slave axis in synchronous operation mode, P/S alarm 213 is output.

- **Master and slave axes**

The master axis is defined in parameter 8311. The slave axis is specified by an external signal.

Limitations

- **Coordinate system setting and tool compensation**

If coordinate system setting or tool compensation causing a shift in the coordinate system is performed in synchronous operation mode, P/S alarm 214 is output.

- **External deceleration, interlock, machine lock**

In synchronous operation mode, the signal for external deceleration, interlock, or machine lock of the master axis only is valid. The corresponding slave axis signal is ignored.

- **Pitch error compensation**

Pitch error compensation and backlash compensation are performed separately for the master and slave axes.

- **Manual absolute switch**

In synchronous operation mode, the manual absolute switch must be set to on (ABS must be set to 1). If the switch is set to off, the correct slave axis movement may not be made.

- **Manual operation**

Manual operations cannot be synchronized.

19.4 B–AXIS CONTROL (G100, G101, G102, G103, G110)

This function sets an axis (B–axis) independent of the basic controlled axes X_1, Z_1, X_2, and Z_2 and allows drilling, boring, or other machining along the B–axis, in parallel with the operations for the basic controlled axes. The X_2 and Z_2 axes can be used in two–path control mode.



Format

- **Registering operation programs**

G101–G100 : Starts registering the first program.
G102–G100 : Starts registering the second program.
G103–G100 : Starts registering the third program.
G100 : Ends registering of the programs.

Three operations (programs) on the B–axis can be registered. (In two–path control mode, three programs can be registered for each tool post.) The B–axis operation program must be specified in the blocks between G101, G102, or G103 and G100, allowing it to be discriminated from the normal NC program.
The registered operation is started upon executing the corresponding M code, described below.

```
O1234 ;
  :
        Normal NC program
G101 ;-  — — — — — — — — — — —   Starts registering of a B–axis
  :                               operation program.
        B–axis operation program
G100 ;   — — — — — — — — — — —   Ends registering of the B–axis
  :                               operation program.
        Normal NC program
M30 ;
```

Note) In the block of G101, G102, G103, or G100, specify no other codes.

- **Command used to start the operation**

To start an operation, the miscellaneous functions (M**) specified in parameters 8251 to 8253 are used.

Parameter 8251:
M code used to start operation of the first program
Parameter 8252:
M code used to start operation of the second program
Parameter 8253:
M code used to start operation of the third program

```
O1234 ;
  :
M** ; -
  :
M30 ;
```

Starts executing the registered B–axis operation. In subsequent blocks, the normal NC program and the B–axis operation program are executed in parallel. (** is specified in parameters 8251 to 8253.)

Example

```
01234 ;
G50 X100. Z200. ;
G101 ;                  [1] Starts registering of an
G00 B10. ;                  operation program.
M03 ;
G04 P2500 ;             [2] Blocks of the B–axis
G81 B20. R15. F500 ;        operation program
G28 ;
G100 ;                  [3] Ends registering of the
G00 X80. Z50. ;             operation program.
G01 X45. F1000 ;
  :
G00 X10. ;
M** ;                   [4] Command used to start the
G01 Z30. F300 ;             programmed operation
  :
M30 ;
```

[1] to [3] : Specify the B–axis operation program in blocks between G101, G102, or G103 and G100. The program is registered in program memory.

[4] : Starts executing the B–axis operation registered with [1] to [3] above. In subsequent blocks, the normal NC operation and the B–axis operation are executed in parallel. An M code of the miscellaneous function is used to start the B–axis operation. The M code, used to start the operation, is specified in parameters 8251 to 8253.

- **Single–motion operation**

G110 [operation command];

A single–motion operation for the B–axis can be specified and executed as shown above. Such an operation need not be registered as a special (first to third) program. Nor does it need to be by a special command, as described above.

Explanations

- **Specifying two–path control mode**

One of the following three two–path control modes can be selected:

1 B–axis control is executed for either tool post 1 or 2.
2 B–axis control is executed separately for tool posts 1 and 2.
3 Identical B–axis control is executed for tool posts 1 and 2.

The mode is selected according to the value specified for parameter 8250 for each tool post.

- **Codes that can be used in a B–axis operation program**

The following 13 G codes, and the M, S, and T codes of the miscellaneous functions, can be used in a B–axis operation program:

Code	Description
G00	Positioning (rapid traverse)
G01	Linear interpolation (cutting feed)
G04	Dwell
G28	Reference position return, automatic coordinate system setting
G80	Canned cycle, cancel
G81	Drilling cycle, spot drilling
G82	Drilling cycle, counterboring
G83	Peck drilling cycle
G84	Tapping cycle
G85	Boring cycle
G86	Boring cycle
G98	Feed per minute
G99	Feed per rotation
M**	Auxiliary function
S**	Auxiliary function
T**	Auxiliary function, tool offset

G28 (reference position return)
Unlike the normal G28 cycle, the G28 cycle for a B–axis operation does not include intermediate point processing. For example, the following cannot be specified:

G28 B99.9;

G80 to G86 (canned drilling cycle)
Of the canned drilling cycles supported by the FANUC Series 16 or Series 18 for machining centers, those cycles equivalent to G80 to G86 can be executed.
Data can be specified in the same way as for the FANUC Series 16 or Series 18 for machining centers, except for the following points:

1. The drilling position is not specified with X and Y.
2. The distance from point R to the bottom of the hole is specified with B.

3. All operations are executed in the initial level return mode.
4. The repetition count (K) cannot be specified.
5. In canned cycle mode, point R must be specified. (If point R is omitted, P/S alarm No. 5036 is output.)
6. The drilling start point (d) for the G83 (peck drilling) cycle is specified with parameter 8258.

G98, G99 (feed per minute, feed per rotation)

The MDF bit (bit 2 of parameter 8241) specifies an initial continuous–state G code for G110, or the G code to start registration of the operation program (G101, G102, G103).
When the MDF bit is set to 0, the initial continuous–state code is G98.
When the MDF bit is set to 1, the initial continuous–state code is G99.

Example)
When MDF is set to 0
G110 B100. F1000. ; 1000 mm/min
G110 G99 B100. F1 ; 1 mm/rev

NOTE
In two–path control mode, the system uses the actual spindle speed, calculated from the feedback signal output by the position coder connected to the tool post to which the controlled axis belongs.

M, S, and T codes (auxiliary functions)

According to a numeric value subsequent to address M, S, or T, the binary code and strobe signal are sent to the machine. The codes and signals for addresses M, S, and T are all output to an identical interface and can be used to control power–on or power–off of the machine. For this purpose, the axis control interface of the PMC is used, which differs from that used for the miscellaneous functions for the normal NC program. The following M codes, used to control the spindle, are automatically output during the G84 (tapping) or G86 (boring) cycle:

M03: Forward spindle rotation
M04: Reverse spindle rotation
M05: Spindle stop

T** to T(** + 9), where ** is the number specified in parameter 8257, are used as the codes of the auxiliary functions to adjust the tool offset.

Example)
T50 to T59 if parameter 8257 is set to 50

1. An M, S, or T code must not be specified in a block containing another move command. The M, S, and T codes must not be specified in an identical block.
2. Usually, normal NC operation and B–axis operation are independent of each other. Synchronization between operations can be established by coordinating the miscellaneous functions of the normal NC program and B–axis operation program.

```
(Normal NC operation)   (Registered B–axis operation)
    :       :
M11 ;   G00 B111 ;
G01 X999 :   G01 B222 ;
G28 Z777 ;   G28 ;
M50 ;   M50 ;
G00 X666 ;   G81 B444 R111 F222 ;
    :       :
```

Upon receiving M50 of both the normal NC program and the B–axis program, the PMC ladder outputs the completion signals (FIN) for the two miscellaneous functions. G00 X666 of the normal NC program and G81 B444 R111 F222 of the B–axis program are executed simultaneously.

Custom macro

Custom macro variables (local variables, common variables, system variables #****) can be used in an operation program between G101, G102, or G103 and G100.

1. The value of the macro variable is calculated not from the data existing upon execution of the B–axis operation, but from the data existing at registration of the operation program.
2. An instruction that causes a branch to a location beyond the range of G101, G102, or G103 to G100 is processed without being checked.
3. In the two–path control mode, tool posts 1 and 2 use different macro variables.

- **Operation program**

When a new operation program is registered, the previous operation program is automatically deleted.
If an error is detected in an operation program to be registered, the program is initialized but is not registered.

- **Modal**

In the same way as a normal NC program, the B–axis operation program can use the following as modal data: modal G codes, F codes, and P, Q, and F codes in the canned cycle. These codes do not affect the modal information of the normal NC program. When a B–axis operation program is started (by G101, G102, or G103), the initial modal data is set for the program. It is not affected by the previous modal information.

Example)

```
    :
G01 X10. F1000 ;                    [1]
G101 (G102, G103) ;                 [2]
B10. ;                              [3]
G01 B–10. F500 ;                    [4]
G100 ;                              [5]
X–10. ;                             [6]
    :
```

Irrespective of the modal information for normal operation (G01 specified in block), block [3] specifies G00 if the MDG bit (bit 1 of parameter 8241) is set to 0, or G01 if the MDG bit is set to 1.
Block [6] causes movement with F1000, specified in block 1.

- **Operation start command**

The MST bit (bit 7 of parameter 8240) specifies the method used to start the B–axis operation as described below:
If the MST bit is set to 1, the B–axis operation is started when the M code to start the operation is executed.
If the MST bit is set to 0, the B–axis operation is started when the M code used to start the operation is executed and the PMC outputs the miscellaneous function completion signal (FIN).
Up to five M codes for starting the programs can be stored. The programs corresponding to these M codes are executed in succession. (In two–path control mode, up to five codes can be stored for each tool post.)

Example)

When the first, second, and third programs are started by M40, M41, and M42, respectively

```
O1234. ;
    :
    :
M40 ;   M code for starting the first program
M41 ;   M code for starting the second program
M42 ;   M code for starting the third program
M40 ;   M code for starting the first program
M41 ;   M code for starting the second program
    :
    :
M30 ;
```

As M41 is specified while the program started by M40 is being executed, the second program is automatically started upon termination of the first program.
M42, M40, and M41, specified during execution of the first program, are stored such that the corresponding programs are executed in the same order as that in which the M codes are specified.
If six or more M codes for starting the programs are specified while a program is being executed, P/S alarm 5038 is output.
In two–path control mode, the M code specified for tool post 1 starts the B–axis program registered for tool post 1. The M code specified for tool post 2 starts the B–axis program registered for tool post 2.

- **Specifying absolute or incremental mode**

The amount of travel along the B–axis can be specified in either absolute or incremental mode. In absolute mode, the end point of travel along the B–axis is programmed. In incremental mode, the amount of travel along the B–axis is programmed directly.
The ABS bit (bit 6 of parameter 8240) is used to set absolute or incremental mode. When the ABS bit is set to 1, absolute mode is selected. When the ABS bit is set to 0, incremental mode is selected. The mode is specified with this parameter when the program is registered.

- **Specifying a tool offset**

The T**; command shifts the end point of the specified B–axis travel, in either the positive or negative direction, by the amount specified with the B–axis offset screen. If this function is used to set the difference between the programmed tool position and actual tool position in machining, the program need not be modified to correct the tool position.
The value specified with parameter 8257 is assigned to the auxiliary function to cancel the offset. The subsequent nine numbers are assigned to the tool offset functions. These auxiliary function numbers are displayed on the B–axis offset screen. For details, see “OPERATION.”

- **Single–motion operation**

If a G110 block is specified, a single–motion operation along the B–axis can be specified and executed. In single–motion operation mode, a single block results in a single operation. The single–motion operation is executed immediately provided if it is specified before the B–axis operation is started. If the operation is specified while a registered program is being executed, the operation is executed once that program has terminated.
After the specified single–motion operation has been executed, the next block is executed.

```
   :
G110 G01 B100. F200 ;    Block for single–motion
                         operation along B–axis
G00 X100. Z20. ;
   :
```

- **Program memory**

An operation program is registered in program memory as a series of different blocks of the move, dwell, auxiliary, and other functions. Program memory can hold a desired number of blocks, up to a maximum of 65535 blocks for each program. If the program memory contains no free space when an attempt is made to register a B–axis program, P/S alarm 5033 is output. Six blocks require 80 characters of program memory. A canned cycle (G81 to G86) is also registered as a series of blocks, such as travel and dwell.
The entire program memory is backed up by battery. The programs registered in program memory are thus retained even after the system power is turned off. After turning the system power on, the operation can be started simply by specifying the M code for starting the program.

Example)

```
   :
G101 ;
G00 B10. ; . . . . . One block
G04 P1500 ; . . . . . One block
G81 B20. R50. F600 ; . . . . . Three blocks
G28 ; . . . . . One block
M15 ; . . . . . One block
G100 ;
   :                              (Total 7 blocks)
```

- **Reset**

When the NC is reset by pressing the MDI reset key or by the issue of an external reset signal, reset and rewind signal, or emergency stop, B–axis control is also reset. The PMC interface signal can reset only B–axis control. For details, refer to the manual supplied by the machine tool manufacturer.

- **PMC–controlled axis**

A B–axis operation can be executed only when the B–axis can be controlled by the PMC. For details, refer to the manual supplied by the machine tool builder.

Limitations

- **Single–motion operation**

1. Only a single–motion operation can be specified with G110.

   G110 G00 B100. ; . . . . . OK
   G110 G28 ; . . . . . OK
   G110 G81 B100. R150.0 F100 ; . . . P/S alarm No.5034

2. A canned cycle (G81 to G86), and other operations containing multiple motions, cannot be specified with G110.
   If an inhibited operation is specified, P/S alarm No.5034 is output.
3. modal information specified with G110 does not affect the subsequent blocks. In the G110 block, the initial modal value specified at the start of the operation becomes valid, irrespective of the modal information specified the previous blocks.

   Example)

   When the MDG bit (bit 1 of parameter 8241) is set to 1 and the MDF bit (bit 2 of parameter 8241) is set to 1
   G98 G00 X100. F1000 ; . . . . . (1)
   G110 B200. F2 ; . . . . . (2)
   X200. ; . . . . . (3)
   G01 X200. ; . . . . . (4)

   Block (2) instigates cutting feed (G01) at 2.0 mm/rev (G99).
   Block (3) instigates rapid traverse (G00).
   Block (4) instigates cutting feed (G01) at 1000 mm/min (G98).
4. During tool–tip radius compensation, two or more G110 blocks cannot be specified in succession. If such blocks are specified in succession, P/S alarm No. 504 is output. To specify two or more G110 blocks in succession for a B–axis operation, register the blocks as a program with G101, G102, or G103 and G100.

Examples

- **Absolute or incremental mode**

Absolute or incremental mode



Incremental mode

```
  G101 (G012, 103) ;
(1) G01 B200. F100 ;
(2) G82 B100. R150. P5000 F200 ;
(3)     B200. R150. P5000 ;
(4) G00 B–100. ;
   G100 ;
      :
   M**
      :
   M30 ;
```

Absolute mode

```
  G101 (G012, G103) ;
(1) G01 B200. F100 ;
(2) G82 B450. R350. P5000 F200 ;
(3)     B550. R350. P5000 ;
(4) G00 B100. ;
   G100 ;
      :
   M**
      :
   M30 ;
```

- **Tool posts 1 and 2**

If a single axis is used as the common B–axis of the two tool posts in two–path control, tool posts 1 and 2 share the B coordinate.
For example, after program 1 for tool post 1 and program 2 for tool post 2 are executed in that order, the total travel along the B–axis appears to be +100.

```
 <Program 1>
   G101 ;
      :
   G00 B200. ; (Absolute mode)
   G100 ;
      :
   M30 ;

 <Program 2>
   G101 ;
   G00 B300. ; (Absolute mode)
      :
   G100 ;
      :
   M30 ;
```

- **Tool offset**

Example)
When parameter 8257 is set to 50
Auxiliary function used to cancel the offset: T50
Auxiliary functions used to adjust a tool offset: T51 to T59



(Absolute mode)



(Incremental mode)



Program

```
   G101 (G012, G103) ;
(1)  G01 B10. F100 ;
(2)  T51 ;
(3)  G00 B20. ;
(4)  T52 ;
(5)  B0. ;
(6)  T50 ;
   G100 ;
      :
   M**;
      :
```

Where the offset of T51 is 10.0 and the offset of T52 is 5.0

19.5 ANGULAR AXIS CONTROL / ARBITRARY ANGULAR AXIS CONTROL

When the angular axis makes an angle other than 90° with the perpendicular axis, the angular axis control function controls the distance traveled along each axis according to the inclination angle. For the ordinary angular axis control function, the X–axis is always used as the angular axis and the Z–axis is always used as the perpendicular axis. For angular axis control B, however, arbitrary axes can be specified as the angular and perpendicular axes, by specifying parameters accordingly. A program, when created, assumes that the angular axis and perpendicular axis intersect at right angles. However, the actual distance traveled is controlled according to an inclination angle.



Explanations

When the angular axis is the X–axis and the perpendicular axis is the Z–axis, the amount of travel along each axis is controlled according to the formulas shown below.

The distance to be traveled along the X–axis is determined by the following formula :

$$Xa = \frac{Xp}{\cos\theta}$$

The distance traveled along the Z–axis is corrected by the inclination of the X–axis, and is determined by the following formula:

$$Za = Zp - \frac{1}{2} Xp \tan\theta$$

The speed component along the X–axis of feed rate is determined by the following formula:

$$Fa = \frac{Fp}{\cos\theta}$$

Xa, Za, Fa: Actual distance and speed
Xp, Zp, Fp: Programmed distance and speed

• Method of use

The angular and perpendicular axes to which angular axis control is to be applied must be specified beforehand, using parameters (No. 8211 and 8212).

Parameter AAC (No. 8200#0) enables or disables the inclined axis control function. If the function is enabled, the distance traveled along each axis is controlled according to an inclination angle (No. 8210).

Parameter AZR (No. 8200#2) enables angular axis manual reference point return only with a distance along the angular axis.

If perpendicular/angular axis control disable signal NOZAGC has been set to 1, the angular axis control function is enabled only for the angular axis. In such a case, the move command for the angular axis is converted to angular coordinates. The perpendicular axis is not affected by the move command for the angular axis.

- **Absolute and relative position display**

An absolute and a relative position are indicated in the programmed Cartesian coordinate system. Machine position display

- **Machine position display**

A machine position indication is provided in the machine coordinate system where an actual movement is taking place according to an inclination angle. However, when inch/metric conversion is performed, a position is indicated which incorporates inch/metric conversion applied to the results of inclination angle operation.

WARNING

1 After inclined axis control parameter setting, be sure to perform manual reference point return operation.
2 If bit 2 (AZR) of parameter No. 8200 has been set to 0, such that manual reference position return along the angular axis also causes movement along the perpendicular axis, once manual reference position return has been performed along the angular axis, also perform manual reference position return along the perpendicular axis.
3 Once the tool has been moved along the angular axis with perpendicular/angular axis control disable signal NOZAGC set to 1, manual reference position return must be performed.
4 Before attempting to manually move the tool along both the angular and perpendicular axes simultaneously, set perpendicular/angular axis control disable signal NOZAGC to 1.

NOTE

1 If an inclination angle close to 0° or ±90° is set, an error can occur. A range from ±20° to ±60° should be used.
2 Before a perpendicular axis reference point return check (G37) can be made, angular axis reference point return operation must be completed.

20 PATTERN DATA INPUT FUNCTION

This function enables users to perform programming simply by extracting numeric data (pattern data) from a drawing and specifying the numerical values from the MDI panel.
This eliminates the need for programming using an existing NC language.

With the aid of this function, a machine tool builder can prepare the program of a hole machining cycle (such as a boring cycle or tapping cycle) using the custom macro function, and can store it into the program memory.
This cycle is assigned pattern names, such as BOR1, TAP3, and DRL2.

An operator can select a pattern from the menu of pattern names displayed on the screen.
Data (pattern data) which is to be specified by the operator should be created in advance with variables in a drilling cycle.
The operator can identify these variables using names such as DEPTH, RETURN RELIEF, FEED, MATERIAL or other pattern data names. The operator assigns values (pattern data) to these names.

20.1 DISPLAYING THE PATTERN MENU

Pressing the OFFSET SETTING key and ▷ **[MENU]** is displayed on the following pattern menu screen.

```
MENU : HOLE PATTERN            O0000 N00000
     1.  BOLT HOLE
     2.  GRID
     3.  LINE ANGLE
     4.  TAPPING
     5.  DRILLING
     6.  BORING
     7.  POCKET
     8.  PECK
     9.  TEST PATRN
    10.  BACK


> _
MDI **** *** ***      16:05:59
[ MACRO ] [ MENU ] [  OPR  ] [     ] [(OPRT)]
```

HOLE PATTERN :

This is the menu title. An arbitrary character string consisting of up to 12 characters can be specified.

BOLT HOLE :

This is the pattern name. An arbitrary character string consisting of up to 10 characters can be specified, including katakana.

The machine tool builder should specify the character strings for the menu title and pattern name using the custom macro, and load the character strings into program memory as a subprogram of program No. 9500.

- **Macro commands specifying the menu title**

Menu title : C_1 C_2 C_3 C_4 C_5 C_6 C_7 C_8 $C_9$$C_{10}$ C_{11} C_{12}
C_1,C_2, ,C_{12} : Characters in the menu title (12 characters)
Macro instruction
G65 H90 P_p Q_q R_r I_i J_j K_k :
H90:Specifies the menu title
p : Assume a1 and a2 to be the codes of characters C1 and C2. Then,



q : Assume a_3 and a_4 to be the codes of characters C_3 and C_4. Then,
$q=a_3 10^3+a_4$
r : Assume a_5 and a_6 to be the codes of characters C_5 and C_6. Then,
$r=a_5 10^3+a_6$
i : Assume a_7 and a_8 to be the codes of characters C_7 and C_8. Then,
$i=a_7 10^3+a_8$
j : Assume a_9 and a_{10} to be the codes of characters C_9 and C_{10}. Then,
$j=a_9 10^3+a_{10}$
k : Assume a_{11} and a_{12} to be the codes of characters C_{11} and C_{12}.Then,
$k=a_{11} 10^3+a_{12}$

Example)

If the title of the menu is “HOLE PATTERN” then the macro instruction is as follows:

G65 H90 P072079 Q076069 R032080
HO LE ␣ P
I065084 J084069 K082078;
AT TE RN

For codes corresponding to these characters, refer to the table in II–20.3.

- **Macro instruction describing the pattern name**

Pattern name: C_1 C_2 C_3 C_4 C_5 C_6 C_7 C_8 C_9C_{10}
C_1, C_2, ,C_{10}: Characters in the pattern name (10 characters)
Macro instruction
G65 H91 P_n Q_q R_r I_i J_j K_k ;
H91: Specifies the menu title
n : Specifies the menu No. of the pattern name
␣ n=1 to 10
q : Assume a_1 and a_2 to be the codes of characters C_1 and C_2. Then,
$q=a_1\times10^3+a_2$
r : Assume a_3 and a_4 to be the codes of characters C_3 and C_4. Then,
$r=a_3\times10^3+a_4$
i : Assume a_5 and a_6 to be the codes of characters C_5 and C_6. Then,
$i=a_5\times10^3+a_6$
j : Assume a_7 and a_8 to be the codes of characters C_7 and C_8. Then,
$j=a_7\times10^3+a_8$
k : Assume a_9 and a_{10} to be the codes of characters C_9 and C_{10}. Then,
$k=a_9\times10^3+a_{10}$

Example)
If the pattern name of menu No. 1 is “BOLT HOLE” then the macro instruction is as follows.

G65 H91 P1 Q066079 R076084 I032072 J079076 K069032 ;
BO LT ␣H OL E␣

- **Pattern No. selection**

To select a pattern from the pattern menu screen, enter the corresponding pattern No. The following is an example.

[1] [INPUT]

The selected pattern No. is assigned to system variable #5900. The custom macro of the selected pattern can be started by starting a fixed program (external program No. search) with an external signal then referring to the system variable #5900 in the program.

NOTE
If each characters of P, Q, R, I, J, and K are not specified in a macro instruction, two spaces are assigned to each omitted character.

Example

Custom macros for the menu title and hole pattern names.




```
O9500 ;
N1G65 H90 P072 079 Q076 069 R032 080 I 065 084 J 084 069 K082 078 ;   HOLE PATTERN
N2G65 H91 P1 Q066 079 R076 084 I 032 072 J 079 076 K069 032 ;         1.BOLT HOLE
N3G65 H91 P2 Q071 082 R073 068 ;                                      2.GRID
N4G65 H91 P3 Q076 073 R078 069 I 032 065 J 078071 K076069 ;           3.LINE ANGLE
N5G65 H91 P4 Q084 065 R080 080 I 073 078 J 071 032 ;                  4.TAPPING
N6G65 H91 P5 Q068 082 R073 076 I 076 073 J 078 071 ;                  5.DRILLING
N7G65 H91 P6 Q066079 R082073 I 078 071 ;                              6.BORING
N8G65 H91 P7 Q080 079 R067 075 I 069 084 ;                            7.POCKET
N9G65 H91 P8 Q080069 R067075 ;                                        8.PECK
N10G65 H91 P9 Q084 069 R083 084 I032 080 J065 084 K082 078 ;          9.TEST PATRN
N11G65 H91 P10 Q066 065 R067 0750 ;                                   10.BACK
N12M99 ;
```

20.2 PATTERN DATA DISPLAY

When a pattern menu is selected, the necessary pattern data is displayed.

```
VAR. : BOLT HOLE                    O0001 N00000
NO.   NAME          DATA   COMMENT
500   TOOL          0.000
501   STANDARD X    0.000  *BOLT HOLE
502   STANDARD Y    0.000  CIRCLE*
503   RADIUS        0.000  SET PATTERN
504   S. ANGL       0.000  DATA TO VAR.
505   HOLES NO      0.000  NO.500-505.
506                 0.000
507                 0.000

ACTUAL POSITION (RELATIVE)
   X    0.000      Y   0.000
   Z    0.000
> _
MDI **** *** ***       16:05:59
[ MACRO ] [ MENU ] [  OPR  ] [     ] [(OPRT)]
```

BOLT HOLE :

This is the pattern data title. A character string consisting of up to 12 characters can be set.

TOOL :

This is the variable name. A character string consisting of up to 10 characters can be set.

BOLT HOLE CIRCLE :

This is a comment statement. A character string can be displayed consisting of up to 8 lines, 12 characters per line.

(It is permissible to use katakana in a character string or line.)
The machine tool builder should program the character strings of pattern data title, pattern name, and variable name using the custom macro, and load them into the program memory as a subprogram whose No. is 9500 plus the pattern No. (O9501 to O9510).

- **Macro instruction specifying the pattern data title (the menu title)**

Menu title : C_1 C_2 C_3 C_4 C_5 C_6 C_7 C_8 $C_9C_{10}C_{11}C_{12}$
C_1 ,$C_{2,\cdots}$, C_{12} : Characters in the menu title (12 characters)
Macro instruction
G65 H92 P_n Q_q R_r I_i J_j K_k ;
H92 : Specifies the pattern name
p : Assume a_1 and a_2 to be the codes of characters C_1 and C_2. Then,
$p=a_{1\times}10^3+a_2$
See 17.3 for character codes.
q : Assume a_3 and a_4 to be the codes of characters C_3 and C_4. Then,
$q=a_{3\times}10^3+a_4$
r : Assume a_5 and a_6 to be the codes of characters C_5 and C_6. Then,
$r=a_{5\times}10^3+a_6$
i : Assume a_7 and a_8 to be the codes of characters C_7 and C_8. Then,
$i=a_{7\times}10^3+a_8$
j : Assume a_9 and a_{10} to be the codes of characters C_9 and C_{10}. Then,
$j=a_{9\times}10^3+a_{10}$
k : Assume a_{11} and a_{12} to be the codes of characters C_{11} and C_{12}. Then,
$k=a_{11\times}10^3{}_+a_{12}$

Example)
Assume that the pattern data title is “BOLT HOLE.”The macro instruction is given as follows:
G65 H92 P066079 Q076084 R032072 I079076 J069032;
BO LT ␣H OL E

- **Macro instruction specifying the variable name**

Variable name : C_1 C_2 C_3 C_4 C_5 C_6 C_7 C_8 C_9C_{10}
C_1, $C_{2,\cdots}$, C_{10} : Characters in the variable name (10 characters)
Macro instruction
G65 H93 P_n Q_q R_r I_i J_j K_k ;
H93 : Specifies the variable name
n : Specifies the menu No. of the variable name
n=1 to 10
q : Assume a_1 and a_2 to be the codes of characters C_1 and C_2. Then,
$q=a_{1\times}10^3+a_2$
r : Assume a_3 and a_4 to be the codes of characters C_3 and C_4. Then,
$r=a_{3\times}10^3+a_4$
i : Assume a_5 and a_6 to be the codes of characters C_5 and C_6. Then,
$i=a_{5\times}10^3+a_6$
j : Assume a_7 and a_8 to be the codes of characters C_7 and C_8. Then,
$j=a_{7\times}10^3+a_8$
k : Assume a_9 and a_{10} to be the codes of characters C_9 and C_{10}. Then,
$k=a_{9\times}10^3a+a_{10}$

Example)
Assume that the variable name of the variable No. 503 is “RADIUS.” The macro instruction is given as follows:

G65 H93 P503 Q082065 R068073 I085083 ;
RA DI US

NOTE
Variable names can be assigned to 32 common variables #500 to #531, which are not cleared when the power is turned off.

- **Macro instruction to describe a comment**

One comment line: C_1 C_2 C_3 C_4 C_5 C_6 C_7 C_8 C_9 C_{10} C_{11} C_{12}
C_1, C_2,..., C_{12} : Character string in one comment line (12 characters)
Macro instruction
G65 H94 P_n Q_q R_r I_i J_j K_k ;
H94 : Specifies the comment
p : Assume a_1 and a_2 to be the codes of characters C_1 and C_2. Then,
$p=a_1 \times 10^3+a_2$
See 17.7 for character codes.
q : Assume a_3 and a_4 to be the codes of characters C_3 and C_4. Then,
$q=a_3 \times 10^3+a_4$
r : Assume a_5 and a_6 to be the codes of characters C_5 and C_6. Then,
$r=a_5 \times 10^3+a_6$
i : Assume a_7 and a_8 to be the codes of characters C_7 and C_8. Then,
$i=a_7 \times 10^3+a_8$
j : Assume a_9 and a_{10} to be the codes of characters C_9 and C_{10}. Then,
$j=a_9 \times 10^3+a_{10}$
k : Assume a_{11} and a_{12} to be the codes of characters C_{11} and C_{12}. Then,
$k=a_{11} \times 10^3+a_{12}$
A comment can be displayed in up to eight lines. The comment consists of the first line to the eighth line in the programmed sequence of G65 H94 for each line.

Example)

Assume that the comment is “BOLT HOLE.” The macro instruction is given as follows:

G65 H94 P042066 Q079076 R084032 I072079 J076069;
*B OL T␣ HO LE

Examples

Macro instruction to describe a parameter title , the variable name, and a comment.




```
O9501 ;
N1G65 H92 P066 079 Q076 084 R032 072 I 079 076 J069 032 ;          VAR : BOLT HOLE
N2G65 H93 P500 Q084 079 R079076 ;                                  #500 TOOL
N3G65 H93 P501 Q075 073 R074 085 I078 032 J088 032 ;               #501 KIJUN X
N4G65 H93 P502 Q075 073 R074 085 I 078 032 J089 032 ;              #502 KIJUN Y
N5G65 H93 P503 Q082 065 R068 073 I 085 083 ;                       #503 RADIUS
N6G65 H93 P504 Q083 046 R032 065 I 078 071 J 076 032 ;             #504 S.ANGL
N7G65 H93 P505 Q072 079 R076 069 I 083 032 J078 079 K046 032 ;     #505 HOLES NO
N8G65 H94 ;                                                        Comment
N9G65 H94 P042 066 Q079 076 R084 032 I072 079 J076 069 ;           *BOLT HOLE
N10G65 H94 R032 067 I073 082 J067 076 K069 042 ;                   CIRCLE*
N11G65 H94 P083 069 Q084 032 080 065 I084 084 J069 082 K078 032 ;  SET PATTERN
N12G65 H94 P068 065 Q084 065 R032 084 I079 032 J086 065 K082046 ;  DATA NO VAR.
N13G65 H94 P078 079 Q046 053 R048 048 I045 053 J048 053 K046 032 ; No.500–505
N14M99 ;
```

20.3 CHARACTERS AND CODES TO BE USED FOR THE PATTERN DATA INPUT FUNCTION

Table.20.3(a) Characters and codes to be used for the pattern data input function

Character	Code	Comment	Character	Code	Comment
A	065		6	054	
B	066		7	055	
C	067		8	056	
D	068		9	057	
E	069			032	Space
F	070		!	033	Exclama–tion mark
G	071		”	034	Quotation mark
H	072		#	035	Hash sign
I	073		$	036	Dollar sign
J	074		%	037	Percent
K	075		&	038	Ampersand
L	076		’	039	Apostrophe
M	077		(	040	Left parenthesis
N	078		)	041	Right parenthesis
O	079		*	042	Asterisk
P	080		+	043	Plus sign
Q	081		,	044	Comma
R	082		–	045	Minus sign
S	083		.	046	Period
T	084		/	047	Slash
U	085		:	058	Colon
V	086		;	059	Semicolon
W	087		<	060	Left angle bracket
X	088		=	061	Equal sign
Y	089		>	062	Right angle bracket
Z	090		?	063	Question mark
0	048		@	064	HAt”mark
1	049		[	091	Left square bracket
2	050		^	092	
3	051		¥	093	Yen sign
4	052		]	094	Right squar bracket
5	053		_	095	Underscore

NOTE
Right and left parentheses cannot be used.

Table 20.3 (b)Numbers of subprograms employed in the pattern data input function

Subprogram No.	Function
O9500	Specifies character strings displayed on the pattern data menu.
O9501	Specifies a character string of the pattern data corresponding to pattern No.1
O9502	Specifies a character string of the pattern data corresponding to pattern No.2
O9503	Specifies a character string of the pattern data corresponding to pattern No.3
O9504	Specifies a character string of the pattern data corresponding to pattern No.4
O9505	Specifies a character string of the pattern data corresponding to pattern No.5
O9506	Specifies a character string of the pattern data corresponding to pattern No.6
O9507	Specifies a character string of the pattern data corresponding to pattern No.7
O9508	Specifies a character string of the pattern data corresponding to pattern No.8
O9509	Specifies a character string of the pattern data corresponding to pattern No.9
O9510	Specifies a character string of the pattern data corresponding to pattern No.10

Table. 20.3 (c)Macro instructions used in the pattern data input function

G code	H code	Function
G65	H90	Specifies the menu title.
G65	H91	Specifies the pattern name.
G65	H92	Specifies the pattern data title.
G65	G93	Specifies the variable name.
G65	H94	Specifies the comment.

Table. 20.3 (d)System variables employed in the pattern data input function

System variable	Function
#5900	Pattern No. selected by user.

III. OPERATION

1 GENERAL

1.1 MANUAL OPERATION

Explanations

- **Manual reference position return**

The CNC machine tool has a position used to determine the machine position.
This position is called the reference position, where the tool is replaced or the coordinate are set. Ordinarily, after the power is turned on, the tool is moved to the reference position.
Manual reference position return is to move the tool to the reference position using switches and pushbuttons located on the operator's panel.



Fig.1.1 (a) Manual reference position return

The tool can be moved to the reference position also with program commands.
This operation is called automatic reference position return (See Section II–6).

- **The tool movement by manual operation**

Using machine operator's panel switches, push buttons, or the manual handle, the tool can be moved along each axis.



Fig. 1.1 (b) The tool movement by manual operation

The tool can be moved in the following ways:

(i) Jog feed (See Section III–3.2)
The tool moves continuously while a push button remains pressed.

(ii) Incremental feed (See Section III–3.3)
The tool moves by the predetermined distance each time a button is pressed.

(iii) Manual handle feed (See Section III–3.4)
By rotating the manual handle,the tool moves by the distance corresponding to the degree of handle rotation.

1.2 TOOL MOVEMENT BY PROGRAMMING – AUTOMATIC OPERATION

Automatic operation is to operate the machine according to the created program. It includes memory, MDI, and DNC operations. (See Section III–4).



Fig.1.2 (a) Tool movement by programming

Explanations

● Memory operation

After the program is once registered in memory of CNC, the machine can be run according to the program instructions. This operation is called memory operation.



Fig.1.2 (b) Memory operation

● MDI operation

After the program is entered, as an command group, from the MDI keyboard, the machine can be run according to the program. This operation is called MDI operation.



Fig.1.2 (c) MDI operation

● DNC operation

The machine can be operated by reading a program directly from an external input/output device, without having to register the program in CNC memory. This is called DNC operation.

1.3 AUTOMATIC OPERATION

Explanations

- **Program selection**

Select the program used for the workpiece. Ordinarily, one program is prepared for one workpiece. If two or more programs are in memory, select the program to be used, by searching the program number (Section III–9.3).



Fig.1.3 (a) Program Selection for Automatic Operation

- **Start and stop (See Section III–4)**

Pressing the cycle start push button causes automatic operation to start. By pressing the feed hold or reset push button, automatic operation pauses or stops. By specifying the program stop or program termination command in the program, the running will stop during automatic operation. When one process machining is completed, automatic operation stops.



Fig.1.3 (b) Start and stop for automatic operation

- **Handle interruption (See Section III–4.6)**

While automatic operation is being executed, tool movement can overlap automatic operation by rotating the manual handle.



Fig.1.3 (c) Handle interruption for automatic operation

1.4 TESTING A PROGRAM

Before machining is started, the automatic running check can be executed. It checks whether the created program can operate the machine as desired. This check can be accomplished by running the machine actually or viewing the position display change (without running the machine) (See Section III–5).

1.4.1 Check by Running the Machine

Explanations

- **Dry run**

Remove the workpiece, check only movement of the tool. Select the tool movement rate using the dial on the operator's panel.



Fig.1.4.1 (a) Dry run

- **Feedrate override**

Check the program by changing the rate specified in the program.



Fig1.4.1 (b) Feedrate override

- **Single block**

When the cycle start push button is pressed, the tool executes one operation then stops. By pressing the cycle start again, the tool executes the next operation then stops. The program is checked in this manner.



Fig.1.4.1 (c) Single block

1.4.2 How to View the Position Display Change without Running the Machine

Explanations

- **Machine lock**



Fig1.4.2 Machine lock

- **Auxiliary function lock**

When automatic running is placed into the auxiliary function lock mode during the machine lock mode, all auxiliary functions (spindle rotation, tool replacement, coolant on/off, etc.) are disabled.

1.5 EDITING A PART PROGRAM

After a created program is once registered in memory, it can be corrected or modified from the MDI panel (See Section III–9).
This operation can be executed using the part program storage/edit function.



Fig.1.5 Part program editing

1.6 DISPLAYING AND SETTING DATA

The operator can display or change a value stored in CNC internal memory by key operation on the MDI screen (See III–11).



Fig.1.6 (a) Displaying and setting data

Explanations

- **Offset value**



Fig.1.6 (b) Displaying and setting offset values

The tool has the tool dimension (length, diameter). When a workpiece is machined, the tool movement value depends on the tool dimensions.
By setting tool dimension data in CNC memory beforehand, automatically generates tool routes that permit any tool to cut the workpiece specified by the program. Tool dimension data is called the offset value (See Section III–11.4.1).



Fig.1.6 (c) Offset value

- **Displaying and setting operator’s setting data**

Apart from parameters, there is data that is set by the operator in operation. This data causes machine characteristics to change.
For example, the following data can be set:
·Inch/Metric switching
·I/O devices selection
·Mirror image cutting on/off
The above data is called setting data (See Section III–11.4.3).



Fig.1.6 (d) Displaying and setting operator’s setting data

- **Displaying and setting parameters**

The CNC functions have versatility in order to take action in characteristics of various machines.

For example, CNC can specify the following:

·Rapid traverse rate of each axis

·Whether increment system is based on metric system or inch system.

·How to set command multiply/detect multiply (CMR/DMR)

Data to make the above specification is called parameters (See Section III–11.5.1).

Parameters differ depending on machine tool.



Fig.1.6 (e) Displaying and setting parameters

- **Data protection key**

A key called the data protection key can be defined. It is used to prevent part programs, offset values, parameters, and setting data from being registered, modified, or deleted erroneously (See Section III–11).



Fig.1.6 (f) Data protection key

1.7 DISPLAY

1.7.1 Program Display

The contents of the currently active program are displayed. In addition, the programs scheduled next and the program list are displayed. (See Section III–11.2.1)





1.7.2 Current Position Display

The current position of the tool is displayed with the coordinate values. The distance from the current position to the target position can also be displayed. (See Section III–11.1 to 11.1.3)



Workpiece coordinate system



1.7.3 Alarm Display

When a trouble occurs during operation, error code and alarm message are displayed on CRT screen. See APPENDIX G for the list of error codes and their meanings. (See Section III–7.1)



1.7.4 Parts Count Display, Run Time Display

When this option is selected, two types of run time and number of parts are displayed on the screen.(See Section lll–11.4.9)



1.7.5 Graphic Display (See Section III–12)

The graphic can be used to draw a tool path for automatic operation and manual operation, thereby indicating the progress of cutting and the position of the tool. (See Section III–12)



1–path control

1.8 DATA OUTPUT

Programs, offset values, parameters, etc. input in CNC memory can be output to paper tape, cassette, or a floppy disk for saving. After once output to a medium, the data can be input into CNC memory.



Fig.1.8 Data Output

2 OPERATIONAL DEVICES

The available operational devices include the setting and display unit attached to the CNC, the machine operator’s panel, and external input/output devices such as a tape reader, PPR, Handy File, Floppy Cassette, and FA Card.

2.1 SETTING AND DISPLAY UNITS

The setting and display units are shown in Subsections 2.1.1 to 2.1.6 of Part III.

CNC control unit with 7.2″/8.4″ LCD: III–2.1.1
CNC control unit with 9.5″/10.4″ LCD: III–2.1.2
Separate–type small MDI unit: III–2.1.3
Separate–type standard MDI unit (horizontal type): III–2.1.4
Separate–type standard MDI unit (vertical type): III–2.1.5
Separate–type standard MDI unit (vertical type) (for 210*i*): III–2.1.6

2.1.1 CNC Control Unit with 7.2″/8.4″ LCD



2.1.2 CNC Control Unit with 9.5″/10.4″ LCD



2.1.3 Separate–Type Small MDI Unit



2.1.4 Separate–Type Standard MDI Unit (Horizontal Type)



2.1.5
Separate–Type Standard MDI Unit (Vertical Type)



2.1.6 Separate–Type Standard MDI Unit (Vertical Type) (for 210*i*)



2.2 EXPLANATION OF THE KEYBOARD

Table 2.2 Explanation of the MDI keyboard

Number	Name	Explanation
1	RESET key	Press this key to reset the CNC, to cancel an alarm, etc.
2	HELP key	Press this key to display how to operate the machine tool, such as MDI key operation, or the details of an alarm which occurred in the CNC (Help function).
3	Soft keys	The soft keys have various functions, according to the Applications. The soft key functions are displayed at the bottom of the screen.
4	Address and numeric keys …	Press these keys to input alphabetic, numeric, and other characters.
5	SHIFT key	Some keys have two characters on their keytop. Pressing the <SHIFT> key switches the characters. Special character ∧ is displayed on the screen when a character indicated at the bottom right corner on the keytop can be entered.
6	INPUT key	When an address or a numerical key is pressed, the data is input to the buffer, and it is displayed on the screen. To copy the data in the key input buffer to the offset register, etc., press the <INPUT> key. This key is equivalent to the [INPUT] key of the soft keys, and either can be pressed to produce the same result.
7	Cancel key	Press this key to delete the last character or symbol input to the key input buffer. When the key input buffer displays >N001X100Z_ and the cancel key is pressed, Z is canceled and >N001X100_ is displayed.
8	Program edit keys	Press these keys when editing the program. : Alteration : Insertion : Deletion
9	Function keys …	Press theses keys to switch display screens for each function. See sec. 2.3 for details of the function keys.

Table 2.2 Explanation of the MDI keyboard

Number	Name	Explanation
10	Cursor move keys 	There are four different cursor move keys. : This key is used to move the cursor to the right or in the forward direction. The cursor is moved in short units in the forward direction. : This key is used to move the cursor to the left or in the reverse direction. The cursor is moved in short units in the reverse direction. : This key is used to move the cursor in a downward or forward direction. The cursor is moved in large units in the forward direction. : This key is used to move the cursor in an upward or reverse direction. The cursor is moved in large units in the reverse direction.
11	Page change keys	Two kinds of page change keys are described below. : This key is used to changeover the page on the screen in the forward direction. : This key is used to changeover the page on the screen in the reverse direction.

2.3 FUNCTION KEYS AND SOFT KEYS

The function keys are used to select the type of screen (function) to be displayed. When a soft key (section select soft key) is pressed immediately after a function key, the screen (section) corresponding to the selected function can be selected.

2.3.1 General Screen Operations



1 Press a function key on the MDI panel. The chapter selection soft keys that belong to the selected function appear.

2 Press one of the chapter selection soft keys. The screen for the selected chapter appears. If the soft key for a target chapter is not displayed, press the continuous menu key (next–menu key).
In some cases, additional chapters can be selected within a chapter.

3 When the target chapter screen is displayed, press the operation selection key to display data to be manipulated.

4 To redisplay the chapter selection soft keys, press the return menu key.

The general screen display procedure is explained above. However, the actual display procedure varies from one screen to another. For details, see the description of individual operations.

2.3.2 Function Keys

Function keys are provided to select the type of screen to be displayed. The following function keys are provided on the MDI panel:

Press this key to display the **position screen**.

Press this key to display the **program screen**.

Press this key to display the **offset/setting screen**.

Press this key to display the **system screen**.

Press this key to display the **message screen.**

Press this key to display the **graphics screen**.

Press this key to display the **custom screen (conversational macro screen)**.

2.3.3 Soft Keys

To display a more detailed screen, press a function key followed by a soft key. Soft keys are also used for actual operations.
The following illustrates how soft key displays are changed by pressing each function key.

The symbols in the following figures mean as shown below :

: Indicates screens

: Indicates a screen that can be displayed by pressing a function key(*1)

[ ] : Indicates a soft key(*2)

( ) : Indicates input from the MDI panel.

[__] : Indicates a soft key displayed in green (or highlighted).

: Indicates the continuous menu key (rightmost soft key)(*3).

*1 Press function keys to switch between screens that are used frequently.

*2 Some soft keys are not displayed depending on the option configuration.

*3 In some cases, the continuous menu key will not appear when a 12 soft key display unit is used.

POSITION SCREEN Soft key transition triggered by the function key POS



PROGRAM SCREEN

Soft key transition triggered by the function key PROG in the MEM mode

1/2



(2)(Continued on the next page)


2/2
(2)
[FL.SDL]
[PRGRM]
Return to (1) (Program display)
File directory display screen
[DIR]
[(OPRT)]
[SELECT]
(File No.)
[F SET]
[EXEC]
Schedule operation display screen
[SCHDUL]
[(OPRT)]
[CLEAR]
[CAN]
[EXEC]
(Schedule data)
[INPUT]

PROGRAM SCREEN

Soft key transition triggered by the function key PROG in the EDIT mode

1/2



(1)(Continued on the next page)


2/2
(1)
Program directory display
[LIB]
[(OPRT)]
[BG–EDT]
See“When the soft key [BG−EDT] is pressed”
(O number)
[O SRH]
Return to the program
[READ]
[CHAIN]
[STOP]
[CAN]
(O number)
[EXEC]
[PUNCH]
[STOP]
[CAN]
(O number)
[EXEC]
Graphic Conversational Programming
[C.A.P.]
[PRGRM]
Return to the program
[G.MENU]
(G number)
[BLOCK]
(Data)
[LINE]
[CHAMF]
[CNR.R]
[INPUT]
When a G number is omitted,
the standard screen appears.
Floppy directory display
[FLOPPY]
[PRGRM]
Return to the program
[DIR]
[(OPRT)]
[F SRH]
(Numeral)
[F SET]
[CAN]
[EXEC]
[READ]
(Numeral)
[F SET]
(Numeral)
[O SET]
[STOP]
[CAN]
[EXEC]
[PUNCH]
(Numeral)
[F SET]
(Numeral)
[O SET]
[STOP]
[CAN]
[EXEC]
[DELETE]
(Numeral)
[F SET]
[CAN]
[EXEC]

PROGRAM SCREEN

Soft key transition triggered by the function key PROG in the MDI mode



PROGRAM SCREEN

Soft key transition triggered by the function key in the HNDL, JOG, or REF mode



PROGRAM SCREEN

Soft key transition triggered by the function key in the TJOG or THDL mode



PROGRAM SCREEN

Soft key transition triggered by the function key PROG
(When the soft key [BG–EDT] is pressed in all modes)

1/2



(1)(Continued on the next page)

2/2


(1)
Program directory display
[LIB]
[(OPRT)]
[BG–EDT]
(O number)
[O SRH]
Return to the program
[READ]
[CHAIN]
[STOP]
[CAN]
(O number)
[EXEC]
[PUNCH]
[STOP]
[CAN]
(O number)
[EXEC]
Graphic Conversational Programming
[C.A.P.]
[PRGRM]
Return to the program
[G.MENU]
(G number)
[BLOCK]
(Data)
When a G number is omitted,
the standard screen appears.
[LINE]
[CHAMF]
[CNR.R]
[INPUT]
Floppy directory display
[FLOPPY]
[PRGRM]
Return to the program
[DIR]
[(OPRT)]
[F SRH]
(Numeral)
[F SET]
[CAN]
[EXEC]
[READ]
(Numeral)
[F SET]
(Numeral)
[O SET]
[STOP]
[CAN]
[EXEC]
[PUNCH]
(Numeral)
[F SET]
(Numeral)
[O SET]
[STOP]
[CAN]
[EXEC]
[DELETE]
(Numeral)
[F SET]
[CAN]
[EXEC]

OFFSET/SETTING SCREEN

Soft key transition triggered by the function key OFFSET SETTING

1/2



(1)(Continued on the next page)


(1)
Software operator’s panel screen
[OPR]
Tool life management setting screen
[TOOLLF]
[(OPRT)]
(Number)
[NO SRH]
[CLEAR]
[CAN]
[EXEC]
(Numeral)
[INPUT]
Y axis tool offset screen
[OFST.2]
[WEAR]
[GEOM]
[(OPRT)]
(Number)
[NO SRH]
(Axis name and numeral)
[MEASUR]
(Axis name)
[INP.C.]
(Numeral)
[+INPUT]
(Numeral)
[INPUT]
[CLEAR]
[ALL]
[WEAR]
[GEOM]
[READ]
[CAN]
[EXEC]
[PUNCH]
[CAN]
[EXEC]
Workpiece shift screen
[WK.SHFT]
[(OPRT)]
(Numeral)
[+INPUT]
(Numeral)
[INPUT]
Chuck and tailstock barriers setting screen
[BARRIER]
[(OPRT)]
(Numeral)
[INPUT]
(Numeral)
[+INPUT]
[SET]
B axis tool compensation screen
[OFST B]

SYSTEM SCREEN

Soft key transition triggered by the function key SYSTEM

1/2



(1)

(Continued on the next page)


2/2
(1)
Pitch error compensation screen
[PITCH]
[(OPRT)]
(No.)
[NO SRH]
[ON:1]
[OFF:0]
(Numeral)
[+INPUT]
(Numeral)
[INPUT]
[READ]
[CAN]
[EXEC]
[PUNCH]
[CAN]
[EXEC]
Servo parameter screen
[SV.PRM]
[SV.SET]
[SV.TUN]
[(OPRT)]
[ON:1]
[OFF:0]
(Numeral)
[INPUT]
[SV.TRC]
[(OPRT)]
[TRACE]
[TRNSF]
Spindle parameter screen
[SP.PRM]
[SP.SET]
[SP.TUN]
[SP.MON]
[(OPRT)]
[ON:1]
[OFF:0]
[INPUT]
Waveform diagnosis screen
[W.DGNS]
[W.PRM]
[W.GRPH]
[STSRT]
[TIME→]
[←TIME]
[H–DOBL]
[H–HALF]
[STSRT]
[CH–1↑]
[CH–1↓]
[V–DOBL]
[V–HALF]
[STSRT]
[CH–2↑]
[CH–2↓]
[V–DOBL]
[V–HALF]

MESSAGE SCREEN Soft key transition triggered by the function key [MESSAGE]



HELP SCREEN Soft key transition triggered by the function key [HELP]




GRAPHIC SCREEN
Soft key transition triggered by the function key
GRAPH
Tool path graphics
Mode 0
GRAPH
Tool path graphics
[G.PRM]
[(OPRT)]
[NORMAL]
[GRAPH]
[(OPRT)]
[ERASE]
[ZOOM]
[(OPRT)]
[ACT]
[HI/LO]

2.3.4 Key Input and Input Buffer

When an address and a numerical key are pressed, the character corresponding to that key is input once into the key input buffer. The contents of the key input buffer is displayed at the bottom of the screen. In order to indicate that it is key input data, a ">" symbol is displayed immediately in front of it. A "_" is displayed at the end of the key input data indicating the input position of the next character.



Fig. 2.3.4 Key input buffer display

To input the lower character of the keys that have two characters inscribed on them, first press the SHIFT key and then the key in question.

When the SHIFT key is pressed, "_" indicating the next character input position changes to " ∧ ". Now lowercase characters can be entered (shift state).

When a character is input in shift status the shift status is canceled. Furthermore, if the SHIFT key is pressed in shift status, the shift status is canceled.

It is possible to input up to 32 characters at a time in the key input buffer. Press the CAN key to cancel a character or symbol input in the key input buffer.

(Example)

When the key input buffer displays
>N001X100Z_

and the cancel CAN key is pressed, Z is canceled and

>N001X100_
is displayed.

2.3.5 Warning Messages

After a character or number has been input from the MDI panel, a data check is executed when INPUT key or a soft key is pressed. In the case of incorrect input data or the wrong operation a flashing warning message will be displayed on the status display line.



Fig. 2.3.5 Warning message display

Table2.3.5 Warning messages

Warning message	Content
FORMAT ERROR	The format is incorrect.
WRITE PROTECT	Key input is invalid because of data protection key or the parameter is not write enabled.
DATA IS OUT OF RANGE	The input value exceeds the permitted range.
TOO MANY DIGITS	The input value exceeds the permitted number of digits.
WRONG MODE	Parameter input is not possible in any mode other than MDI mode.
EDIT REJECTED	It is not possible to edit in the current CNC status.

2.3.6 Soft Key Configuration

There are 12 soft keys in the 10.4″ LCD/MDI or 9.5″ LCD/MDI panel. As illustrated below, the 5 soft keys on the right and those on the right and left edges operate in the same way as the 7.2″ LCD/8.4″ LCD, whereas the 5 keys on the left hand side are expansion keys dedicated to the 10.4″ LCD, 9.5″ LCD.



Fig. 2.3.6 LCD soft key configuration

Whenever a position display appears in the left half of the screen after a function key other than [POS] is pressed, the soft keys on the left half of the soft key display area are displayed as follows:

The soft key corresponding to the position display is indicated in reverse video.

2.4 EXTERNAL I/O DEVICES

Five types of external input/output devices are available. This section outlines each device. For details on these devices, refer to the corresponding manuals listed below.

Table 2.4 External I/O device

Device name	Usage	Max. storage capacity	Reference manual
FANUC Handy File	Easy–to–use, multi function input/output device. It is designed for FA equipment and uses floppy disks.	3600m	B–61834E
FANUC Floppy Cassette	Input/output device. Uses floppy disks.	2500m	B–66040E
FANUC FA Card	Compact input/output device. Uses FA cards.	160m	B–61274E
FANUC PPR	Input/output device consisting of a paper tape reader, tape punch, and printer.	275m	B–58584E
Portable Tape Reader	Input device for reading paper tape.	_____	Appendix H

The following data can be input/output to or from external input/output devices:

1. **Programs**
2. **Offset data**
3. **Parameters**
4. **Custom macro common variables**
5. **Pitch error compensation data**

For how data is input and output, see Chapter III–8.

Parameter

Before an external input/output device can be used, parameters must be set as follows.



This CNC has three channels of reader/punch interfaces. The input/output device to be used is specified by setting the channel connected to that device in setting parameter I/O CHANNEL.
The specified data, such as a baud rate and the number of stop bits, of an input/output device connected to a specific channel must be set in parameters for that channel in advance.
For channel 1, two combinations of parameters to specify the input/output device data are provided.
The following shows the interrelation between the reader/punch interface parameters for the channels.



2.4.1 FANUC Handy File

The Handy File is an easy–to–use, multi function floppy disk input/output device designed for FA equipment. By operating the Handy File directly or remotely from a unit connected to the Handy File, programs can be transferred and edited.
The Handy File uses 3.5–inch floppy disks, which do not have the problems of paper tape (i.e., noisy during input/output, easily broken, and bulky).
One or more programs (up to 1.44M bytes, which is equivalent to the memory capacity of 3600–m paper tape) can be stored on one floppy disk.



2.4.2 FANUC Floppy Cassette

When the Floppy Cassette is connected to the CNC, machining programs stored in the CNC can be saved on a Floppy Cassette, and machining programs saved in the Floppy Cassette can be transferred to the CNC.



2.4.3 FANUC FA Card

An FA Card is a memory card used as an input medium in the FA field. It is compact, but has a large memory capacity with high reliability, and requires no special maintenance.
When an FA Card is connected to the CNC via the card adapter, machining programs stored in the CNC can be transferred to and saved in an FA Card. Machining programs stored on an FA Card can also be transferred to the CNC.



2.4.4 FANUC PPR

The FANUC PPR consists of three units: A printer, paper tape punch, and paper tape reader.
When the PPR is used alone, data can be read from the tape reader and printed or punched out. It is also possible to perform TH and TV checks on data that was read.



2.4.5 Portable Tape Reader

The portable tape reader is used to input data from paper tape.



2.5 POWER ON/OFF

2.5.1 Turning on the Power

Procedure of turning on the power

1 Check that the appearance of the CNC machine tool is normal. (For example, check that front door and rear door are closed.)

2 Turn on the power according to the manual issued by the machine tool builder.

3 After the power is turned on, check that the position screen is displayed. An alarm screen is displayed if an alarm occurs upon power–on. If the screen shown in Section III–2.5.2 is displayed, a system failure may have occurred.



Position screen (7 soft keys type)

4 Check that the fan motor is rotating.

WARNING

Until the positional or alarm screen is displayed at the power on, do not touch them. Some keys are used for the maintenance or special operation purpose. When they are pressed, unexpected operation may be caused.

2.5.2 Screen Displayed at Power–on

If a hardware failure or installation error occurs, the system displays one of the following three types of screens then stops.
Information such as the type of printed circuit board installed in each slot is indicated. This information and the LED states are useful for failure recovery.

Slot status display



For more information about the types of printed circuit boards and module functions, refer to the maintenance manual (B–63085EN).

Screen indicating module setting status



Display of software configuration



2.5.3 Power Disconnection

Procedure for Poser Disconnection

1. Check that the LED indicating the cycle start is off on the operator's panel.
2. Check that all movable parts of the CNC machine tool is stopping.
3. If an external input/output device such as the Handy File is connected to the CNC, turn off the external input/output device.
4. Continue to press the POWER OFF pushbutton for about 5 seconds.
5. Refer to the machine tool builder's manual for turning off the power to the machine.

3 MANUAL OPERATION

MANUAL OPERATION are six kinds as follows :

3.1 Manual reference position return
3.2 Jog feed
3.3 Incremental feed
3.4 Manual handle feed
3.5 Manual absolute on/off

3.1 MANUAL REFERENCE POSITION RETURN

The tool is returned to the reference position as follows :
The tool is moved in the direction specified in parameter ZMI (bit 5 of No. 1006) for each axis with the reference position return switch on the machine operator's panel. The tool moves to the deceleration point at the rapid traverse rate, then moves to the reference position at the FL speed. The rapid traverse rate and FL speed are specified in parameters (No. 1420,1421, and 1425).
Four step rapid traverse override is effective during rapid traverse.
When the tool has returned to the reference position, the reference position return completion LED goes on. The tool generally moves along only a single axis, but can move along three axes simultaneously when specified so in parameter JAX(bit 0 of No.1002).



Procedure for Manual Reference Position Return







1 Press the reference position return switch, one of the mode selection switches.

2 To decrease the feedrate, press a rapid traverse override switch.

3 Press the feed axis and direction selection switch corresponding to the axis and direction for reference position return. Continue pressing the switch until the tool returns to the reference position. The tool can be moved along three axes simultaneously when specified so in an appropriate parameter setting. The tool moves to the deceleration point at the rapid traverse rate, then moves to the reference position at the FL speed set in a parameter.
When the tool has returned to the reference position, the reference position return completion LED goes on.

4 Perform the same operations for other axes, if necessary.
The above is an example. Refer to the appropriate manual provided by the machine tool builder for the actual operations.



Explanation

- **Automatically setting the coordinate system**

Bit 0 (ZPR) of parameter No. 1201 is used for automatically setting the coordinate system. When ZPR is set, the coordinate system is automatically determined when manual reference position return is performed.
When α and γ are set in parameter 1250, the workpiece coordinate system is determined so that the reference point on the tool holder or the position of the tip of the reference tool is X=α,Z=$\gamma$when reference position return is performed. This has the same effect as specifying the following command for reference position return:
G50XαZγ;

> **CAUTION**
> When options of the workpiece coordinate system is selected, it is not able to use. Once manual reference position return has been performed, workpiece coordinate systems are established based on the workpiece origin offsets corresponding to G54 to G59 (see Sections II–7.2 and III–11.4.10.)

Restrictions

- **Moving the tool again**

Once the REFERENCE POSITION RETURN COMPLETION LED lights at the completion of reference position return, the tool does not move unless the REFERENCE POSITION RETURN switch is turned off.

- **Reference position return completion LED**

The REFERENCE POSITION RETURN COMPLETION LED is extinguished by either of the following operations:
– Moving from the reference position.
– Entering an emergency stop state.

- **The distance to return to reference position**

For the distance (Not in the deceleration condition) to return the tool to the reference position, refer to the manual issued by the machine tool builder.

3.2 JOG FEED



In the JOG mode, pressing a feed axis and direction selection switch on the machine operator's panel continuously moves the tool along the selected axis in the selected direction.
The manual continuous feedrate is specified in a parameter (No.1423)
The manual continuous feedrate can be adjusted with the manual continuous feedrate override dial.
Pressing the rapid traverse switch moves the tool at the rapid traverse feedrate (No.1424) regardless of the position of the JOG feedrate override dial. This function is called the manual rapid traverse.
Manual operation is allowed for one axis at a time. 3 axes can be selected at a time by parameter JAX (No.1002#0).



Procedure for JOG Feed





JOG FEED RATE OVERRIDE



1 Press the manual continuous switch, one of the mode selection switches.

2 Press the feed axis and direction selection switch corresponding to the axis and direction the tool is to be moved. While the switch is pressed, the tool moves at the feedrate specified in a parameter (No. 1423). The tool stops when the switch is released.

3 The manual continuous feedrate can be adjusted with the manual continuous feedrate override dial.

4 Pressing the rapid traverse switch while pressing a feed axis and direction selection switch moves the tool at the rapid traverse rate while the rapid traverse switch is pressed. Rapid traverse override by the rapid traverse override switches is effective during rapid traverse.

The above is an example. Refer to the appropriate manual provided by the machine tool builder for the actual operations.

Explanations

- **Manual per revolution feed**

To enable manual per revolution feed, set bit 4 (JRV) of parameter No. 1402 to 1.
During manual per revolution feed, the tool is jogged at the following feedrate:
Feed distance per rotation of the spindle (mm/rev) (specified with parameter No. 1423) x JOG feedrate override x actual spindle speed (rev/min).

Restrictions

- **Acceleration/decelera–tion for rapid traverse**

Feedrate, time constant and method of automatic acceleration/ deceleration for manual rapid traverse are the same as G00 in programmed command.

- **Change of modes**

Changing the mode to the JOG feed mode while pressing a feed axis and direction selection switch does not enable JOG feed. To enable JOG feed, enter the JOG feed mode first, then press a feed axis and direction selection switch.

- **Rapid traverse prior to reference position return**

If reference position return is not performed after power–on, pushing RAPID TRAVERSE button does not actuate the rapid traverse but the remains at the manual continuous feedrate. This function can be disabled by setting parameter RPD (No.1401#01).

3.3 INCREMENTAL FEED

In the incremental (INC) mode, pressing a feed axis and direction selection switch on the machine operator's panel moves the tool one step along the selected axis in the selected direction. The minimum distance the tool is moved is the least input increment. Each step can be 10, 100, or 1000 times the least input increment.
This mode is effective when a manual pulse generator is not connected.



Procedure for Incremental Feed





1. Press the INC switch, one of the mode selection switches.
2. Select the distance to be moved for each step with the magnification dial.
3. Press the feed axis and direction selection switch corresponding to the axis and direction the tool is to be moved. Each time a switch is pressed, the tool moves one step. The feedrate is the same as the jog feedrate.
4. Pressing the rapid traverse switch while pressing a feed axis and direction selection switch moves the tool at the rapid traverse rate. Rapid traverse override by the rapid traverse override switch is effective during rapid traverse.

   The above is an example. Refer to the appropriate manual provided by the machine tool builder for the actual operations.

Explanation

- **Travel distance specified with a diameter**

The distance the tool travels along the X–axis can be specified with a diameter.

3.4 MANUAL HANDLE FEED

In the handle mode, the tool can be minutely moved by rotating the manual pulse generator on the machine operator's panel. Select the axis along which the tool is to be moved with the handle feed axis selection switches.
The minimum distance the tool is moved when the manual pulse generator is rotated by one graduation is equal to the least input increment. Or the distance the tool is moved when the manual pulse generator is rotated by one graduation can be magnified by 10 times or by one of the two magnifications specified by parameters (No. 7113 and 7114).



Manual pulse generator

Procedure for Manual Handle Feed



1 Press the HANDLE switch, one of the mode selection switches.

2 Select the axis along which the tool is to be moved by pressing a handle feed axis selection switch.

3 Select the magnification for the distance the tool is to be moved by pressing a handle feed magnification switch. The minimum distance the tool is moved when the manual pulse generator is rotated by one graduation is equal to the least input increment.

4 Move the tool along the selected axis by rotating the handle. Rotating the handle 360 degrees moves the tool the distance equivalent to 100 graduations.

The above is an example. Refer to the appropriate manual provided by the machine tool builder for the actual operations.



Manual pulse generator

Explanation

- **Availability of manual pulse generator in Jog mode (JHD)**

Parameter JHD (bit 0 of No. 7100) enables or disables the manual pulse generator in the JOG mode.
When the parameter JHD(bit 0 of No. 7100) is set 1,both manual handle feed and incremental feed are enabled.

- **Availability of manual pulse generator in TEACH IN JOG mode (THD)**

Parameter THD (bit 1 of No. 7100) enables or disables the manual pulse generator in the TEACH IN JOG mode.

- **A command to the MPG exceeding rapid traverse rate (HPF)**

Parameter HPF (bit 4 of No. 7100) or (No. 7117) specifies as follows:

- Parameter HPF (bit 4 of No. 7100)

Set value 0 : The feedrate is clamped at the rapid traverse rate and generated pulses exceeding the rapid traverse rate are ignored. (The distance the tool is moved may not match the graduations on the manual pulse generator.)

Set value 1 : The feedrate is clamped at the rapid traverse rate and generated pulses exceeding the rapid traverse rate are not ignored but accumulated in the CNC.
(No longer rotating the handle does not immediately stop the tool. The tool is moved by the pulses accumulated in the CNC before it stops.)

- Parameter HPF (No. 7177) (It is available when parameter HPF is 0.)

Set value 0 : The feedrate is clamped at the rapid traverse rate and generated pulses exceeding the rapid traverse rate are ignored. (The distance the tool is moved may not match the graduations on the manual pulse generator.)

Other than 0 : The feedrate is clamped at the rapid traverse rate and generated pulses exceeding the rapid traverse rate are not ignored but accumulated in the CNC until the limit specified in parameter No. 7117 is reached.
(No longer rotating the handle does not immediately stop the tool. The tool is moved by the pulses accumulated in the CNC before it stops.)

- **Movement direction of an axis to the rotation of MPG (HNGx)**

Parameter HNGx (bit 0 of No. 7102) switches the direction of MPG in which the tool moves along an axis, corresponding to the direction in which the handle of the manual pulse generator is rotated.

Restrictions

- **Number of MPGs**

Up to three manual pulse generators can be connected, one for each axis. The three manual pulse generators can be simultaneously operated.

WARNING

Rotating the handle quickly with a large magnification such as x100 moves the tool too fast. The feedrate is clamped at the rapid traverse feedrate.

NOTE

Rotate the manual pulse generator at a rate of five rotations per second or lower. If the manual pulse generator is rotated at a rate higher than five rotations per second, the tool may not stop immediately after the handle is no longer rotated or the distance the tool moves may not match the graduations on the manual pulse generator.

3.5 MANUAL ABSOLUTE ON AND OFF

Whether the distance the tool is moved by manual operation is added to the coordinates can be selected by turning the manual absolute switch on or off on the machine operator's panel. When the switch is turned on, the distance the tool is moved by manual operation is added to the coordinates. When the switch is turned off, the distance the tool is moved by manual operation is not added to the coordinates.



Fig. 3.5(a) Coordinates with the switch ON



Fig. 3.5(b) Coordinates with the switch OFF

Explanation

The following describes the relation between manual operation and coordinates when the manual absolute switch is turned on or off, using a program example.

```
G01G90  X100.0Z100.0F010 ;      (1)
        X200.0Z150.0     ;      (2)
        X300.0Z200.0     ;      (3)
```

The subsequent figures use the following notation:

——→ Movement of the tool when the switch is on
– – → Movement of the tool when the switch is off

The coordinates after manual operation include the distance the tool is moved by the manual operation. When the switch is off, therefore, subtract the distance the tool is moved by the manual operation.

- **Manual operation after the end of block**

Coordinates when block (2) has been executed after manual operation (X–axis +20.0, Z–axis +100.0) at the end of movement of block (1).



- **Manual operation after a feed hold**

Coordinates when the feed hold button is pressed while block (2) is being executed, manual operation (X–axis + 75.0) is performed, and the cycle start button is pressed and released



- **When reset after a manual operation following a feed hold**

Coordinates when the feed hold button is pressed while block (2) is being executed, manual operation (Y–axis +75.0) is performed, the control unit is reset with the RESET button, and block (2) is read again



- **When a movement command in the next block is only one axis**

When there is only one axis in the following command, only the commanded axis returns.



- **When the next move block is an incremental**

When the following commands are incremental commands, operation is the same as when the switch is OFF.

- **Manual operation during tool nose radius compensation**

When the switch is OFF

After manual operation is performed with the switch OFF during tool nose radius compensation, automatic operation is restarted then the tool moves parallel to the movement that would have been performed if manual movement had not been performed. The amount of separation equals to the amount that was performed manually.



When the switch is ON during tool nose radius compensation

Operation of the machine upon return to automatic operation after manual intervention with the switch is ON during execution with an absolute command program in the tool nose radius compensation mode will be described. The vector created from the remaining part of the current block and the beginning of the next block is shifted in parallel. A new vector is created based on the next block, the block following the next block and the amount of manual movement. This also applies when manual operation is performed during cornering.

Manual operation performed in other than cornering

Assume that the feed hold was applied at point P_H while moving from P_A to P_B of programmed path P_A, P_B, and P_C and that the tool was manually moved to $P_{H'}$. The block end point P_B moves to the point $P_{B'}$ by the amount of manual movement, and vectors V_{B1} and V_{B2} at P_B also move to $V_{B1'}$ and $V_{B2'}$. Vectors V_{C1} and V_{C2} between the next two blocks P_B – P_C and P_C – P_D are discarded and new vectors $V_{C1'}$ and $V_{C2'}$ ($V_{C2'}$ = V_{C2} in this example) are produced from the relation between $P_{B'}$ – P_C and P_C – P_D. However, since $V_{B2'}$ is not a newly calculated vector, correct offset is not performed at block $P_{B'}$ – P_C. Offset is correctly performed after P_C.



Manual operation during cornering

This is an example when manual operation is performed during cornering. $V_{A2'}$, $V_{B1'}$, and $V_{B2'}$ are vectors moved in parallel with V_{A2}, V_{B1} and V_{B2} by the amount of manual movement. The new vectors are calculated from V_{C1} and V_{C2}. Then correct tool nose radius compensation is performed for the blocks following Pc.



Manual operation after single block stop

Manual operation was performed when execution of a block was terminated by single block stop.

Vectors V_{B1} and V_{B2} are shifted by the amount of manual operation. Sub–sequent processing is the same as case a described above. An MDI operation can also be interveneted as well as manual operation. The movement is the same as that by manual operation.



4 AUTOMATIC OPERATION

Programmed operation of a CNC machine tool is referred to as automatic operation.
This chapter explains the following types of automatic operation:

- **MEMORY OPERATION**
  Operation by executing a program registered in CNC memory
- **MDI OPERATION**
  Operation by executing a program entered from the MDI panel
- **DNC operation**
  Operation while reading a program from external input/output device
- **PROGRAM RESTART**
  Restarting a program for automatic operation from an intermediate point
- **SCHEDULING FUNCTION**
  Scheduled operation by executing programs (files) registered in an external input/output device (Handy File, Floppy Cassette, or FA Card)
- **SUBPROGRAM CALL FUNCTION**
  Function for calling and executing subprograms (files) registered in an external input/output device (Handy File, Floppy Cassette, or FA Card) during memory operation
- **MANUAL HANDLE INTERRUPTION**
  Function for performing manual feed during movement executed by automatic operation
- **MIRROR IMAGE**
  Function for enabling mirror–image movement along an axis during automatic operation
- **MANUAL INTERVENTION AND RETURN**
  Function restarting automatic operation by returning the tool the position where manual intervention was started during automatic operation.

4.1 MEMORY OPERATION

Programs are registered in memory in advance. When one of these programs is selected and the cycle start switch on the machine operator's panel is pressed, automatic operation starts, and the cycle start LED goes on.
When the feed hold switch on the machine operator's panel is pressed during automatic operation, automatic operation is stopped temporarily. When the cycle start switch is pressed again, automatic operation is restarted.

When the RESET key on the MDI panel is pressed, automatic operation terminates and the reset state is entered.
For the two–path control, the programs for the two tool posts can be executed simultaneously so the two tool posts can operate independently at the same time.
The following procedure is given as an example. For actual operation, refer to the manual supplied by the machine tool builder.

Procedure for Memory Operation

1 Press the **MEMORY** mode selection switch.

2 Select a program from the registered programs. To do this, follow the steps below.

2–1 Press PROG to display the program screen.

2–2 Press address O .

2–3 Enter a program number using the numeric keys.

2–4 Press the **[O SRH]** soft key.
For the two–path control, select the program for the tool post to be operated. When operating the two tool posts at the same time, select a program for each tool post.

3 For the two–path control, select the tool post to be operated with the tool post selection switch on the machine operator's panel.

4 Press the cycle start switch on the machine operator's panel. Automatic operation starts, and the cycle start LED goes on. When automatic operation terminates, the cycle start LED goes off.

5 To stop or cancel memory operation midway through, follow the steps below.

a. Stopping memory operation
Press the feed hold switch on the machine operator's panel. The feed hold LED goes on and the cycle start LED goes off. The machine responds as follows:

(i) When the machine was moving, feed operation decelerates and stops.
(ii) When dwell was being performed, dwell is stopped.
(iii) When M, S, or T was being executed, the operation is stopped after M, S, or T is finished.

When the cycle start switch on the machine operator's panel is pressed while the feed hold LED is on, machine operation restarts.

b. Terminating memory operation

Press the RESET key on the MDI panel.

Automatic operation is terminated and the reset state is entered.
When a reset is applied during movement, movement decelerates then stops.

Explanation

Memory operation

After memory operation is started, the following are executed:

(1) A one–block command is read from the specified program.
(2) The block command is decoded.
(3) The command execution is started.
(4) The command in the next block is read.
(5) Buffering is executed. That is, the command is decoded to allow immediate execution.
(6) Immediately after the preceding block is executed, execution of the next block can be started. This is because buffering has been executed.
(7) Hereafter, memory operation can be executed by repeating the steps (4) to (6).

Stopping and terminating memory operation

Memory operation can be stopped using one of two methods: Specify a stop command, or press a key on the machine operator's panel.

– The stop commands include M00 (program stop), M01 (optional stop), and M02 and M30 (program end).
– There are two keys to stop memory operation: The feed hold key and reset key.

- **Program stop (M00)**

Memory operation is stopped after a block containing M00 is executed. When the program is stopped, all existing modal information remains unchanged as in single block operation. The memory operation can be restarted by pressing the cycle start button. Operation may vary depending on the machine tool builder. Refer to the manual supplied by the machine tool builder.

- **Optional stop (M01)**

Similarly to M00, memory operation is stopped after a block containing M01 is executed. This code is only effective when the Optional Stop switch on the machine operator's panel is set to ON. Operation may vary depending on the machine tool builder. Refer to the manual supplied by the machine tool builder.

- **Program end (M02, M30)**

When M02 or M30 (specified at the end of the main program) is read, memory operation is terminated and the reset state is entered.
In some machines, M30 returns control to the top of the program. For details, refer to the manual supplied by the machine tool builder.

- **Feed hold**

When Feed Hold button on the operator's panel is pressed during memory operation, the tool decelerates to a stop at a time.

- **Reset**

Automatic operation can be stopped and the system can be made to the reset state by using RESET key on the MDI or external reset signal. When reset operation is applied to the system during a tool moving status, the motion is slowed down then stops.

- **Optional block skip**

When the optional block skip switch on the machine operator's panel is turned on, blocks containing a slash (/) are ignored.

Calling a subprogram stored in an external input/output device

A file (subprogram) in an external input/output device such as a Floppy Cassette can be called and executed during memory operation. For details, see Section **4.5**.

4.2 MDI OPERATION

In the **MDI** mode, a program consisting of up to 10 lines can be created in the same format as normal programs and executed from the MDI panel. MDI operation is used for simple test operations.
The following procedure is given as an example. For actual operation, refer to the manual supplied by the machine tool builder.

Procedure for MDI Operation

1 Press the **MDI** mode selection switch.
For the two–path control, select the tool post for which a program is to be created with the tool post selection switch. Create a separate program for each tool post.

2 Press the [PROG] function key on the MDI panel to select the program screen. The following screen appears:



Program number O0000 is entered automatically.

3 Prepare a program to be executed by an operation similar to normal program editing. M99 specified in the last block can return control to the beginning of the program after operation ends. Word insertion, modification, deletion, word search, address search, and program search are available for programs created in the MDI mode. For program editing, see Chapter III–9.

4 To entirely erase a program created in MDI mode,use one of the following methods:

a. Enter address [O], then press the [DELETE] key on the MDI panel.

b. Alternatively, press the [RESET] key. In this case, set bit 7 of parameter 3203 to 1 in advance.

5 To execute a program, set the cursor on the head of the program. (Start from an intermediate point is possible.) Push Cycle Start button on the operator's panel. By this action, the prepared program will start. (For the two–path control, select the tool post to be operated with the tool post selection switch on the machine operator's panel beforehand.)
When the program end (M02, M30) or ER(%) is executed, the prepared program will be automatically erased and the operation will end.
By command of M99, control returns to the head of the prepared program.



6 To stop or terminate MDI operation in midway through, follow the steps below.

a. Stopping MDI operation
Press the feed hold switch on the machine operator's panel. The feed hold LED goes on and the cycle start LED goes off. The machine responds as follows:

(i) When the machine was moving, feed operation decelerates and stops.
(ii) When dwell was being performed, dwell is stopped.
(iii) When M, S, or T was being executed, the operation is stopped after M, S, or T is finished.
When the cycle start switch on the machine operator's panel is pressed, machine operation restarts.

b. Terminating MDI operation

Press the RESET key on the MDI panel.

Automatic operation is terminated and the reset state is entered. When a reset is applied during movement, movement decelerates then stops.

Explanation

The previous explanation of how to execute and stop memory operation also applies to MDI operation, except that in MDI operation, M30 does not return control to the beginning of the program (M99 performs this function).

- **Erasing the program**

Programs prepared in the **MDI** mode will be erased in the following cases:

- In MDI operation, if M02, M30 or ER(%) is executed.
  (If bit 6 (MER) of parameter No. 3203 is set to 1, however, the program is erased when execution of the last block of the program is completed by single–block operation.)
- In **MEMORY** mode, if memory operation is performed.
- In **EDIT** mode, if any editing is performed.
- Background editing is performed.
- Upon reset when bit 7 (MCL) of parameter No. 3203 is set to 1

- **Restart**

After the editing operation during the stop of MDI operation was done, operation starts from the current cursor position.

- **Editing a program during MDI operation**

A program can be edited during MDI operation. The editing of a program, however, is disabled until the CNC is reset, when bit 5 (MIE) of parameter No. 3203 is set accordingly.

Limitation

- **Program registration**

Programs created in MDI mode cannot be registered.

- **Number of lines in a program**

A program can have as many lines as can fit on one page of the screen. A program consisting of up to six lines can be created. When parameter MDL (No. 3107 #7) is set to 0 to specify a mode that suppresses the display of continuous–state information, a program of up to 10 lines can be created.
If the created program exceeds the specified number of lines, % (ER) is deleted (prevents insertion and modification).

- **Subprogram nesting**

Calls to subprograms (M98) can be specified in a program created in the MDI mode. This means that a program registered in memory can be called and executed during MDI operation. In addition to the main program executed by automatic operation, up to two levels of subprogram nesting are allowed (when the custom macro option is provided, up to four levels are allowed).



Fig. 4.2 Nesting level of subprograms called from the MDI program

- **Macro call**

When the custom macro option is provided, macro programs can also be created, called, and executed in the **MDI** mode. However, macro call commands cannot be executed when the mode is changed to **MDI** mode after memory operation is stopped during execution of a subprogram.

- **Memory area**

When a program is created in the **MDI** mode, an empty area in program memory is used. If program memory is full, no programs can be created in the **MDI** mode.

4.3 PROGRAM RESTART

This function specifies Sequence No. or Block No. of a block to be restarted when a tool is broken down or when it is desired to restart machining operation after a day off, and restarts the machining operation from that block. It can also be used as a high–speed program check function.
There are two restart methods: the P–type method and Q–type method.

P TYPE	Operation can be restarted anywhere. This restart method is used when operation is stopped because of a broken tool.



Q TYPE	Before operation can be restarted, the machine must be moved to the programmed start point (machining start point)



Procedure for Program restart by Specifying a sequence number

Procedure 1

[P TYPE]

1 Retract the tool and replace it with a new one. When necessary, change the offset. (Go to step 2.)

[Q TYPE]

1 When power is turned ON or emergency stop is released, perform all necessary operations at that time, including the reference position return.

2 Move the machine manually to the program starting point (machining start point), and keep the modal data and coordinate system in the same conditions as at the machining start.

3 If necessary, modify the offset amount.

Procedure 2

[COMMON TO P TYPE / Q TYPE]

1 Turn the program restart switch on the machine operator's panel ON.

2 Press function PROG key to display the desired program.



3 Find the program head.

4 Enter the sequence number of the block to be restarted, then press the **[P TYPE]** or **[Q TYPE]** soft key.



If the same sequence number appears more than once, the location of the target block must be specified. Specify a frequency and a sequence number.

5 The sequence number is searched for, and the program restart screen appears on the screen.



DESTINATION shows the position at which machining is to restart.
DISTANCE TO GO shows the distance from the current tool position to the position where machining is to restart. A number to the left of each axis name indicates the order of axes (determined by parameter setting) along which the tool moves to the restart position.
The coordinates and amount of travel for restarting the program can be displayed for up to five axes. If your system supports six or more axes, pressing the **[RSTR]** soft key again displays the data for the sixth and subsequent axes. (The program restart screen displays only the data for CNC–controlled axes.)
M: Fourteen most recently specified M codes
T: Two most recently specified T codes
S: Most recently specified S code
Codes are displayed in the order in which they are specified. All codes are cleared by a program restart command or cycle start in the reset state.

6 Turn the program re–start switch OFF. At this time, the figure at the left side of axis name DISTANCE TO GO blinks.

7 Check the screen for the M, S, and T codes to be executed. If they are found, enter the **MDI** mode, then execute the M, S and T functions. After execution, restore the previous mode.
These codes are not displayed on the program restart screen.

8 Check that the distance indicated under DISTANCE TO GO is correct. Also check whether there is the possibility that the tool might hit a workpiece or other objects when it moves to the machining restart position. If such a possibility exists, move the tool manually to a position from which the tool can move to the machining restart position without encountering any obstacles.

9 Press the cycle start button. The tool moves to the machining restart position at the dry run feedrate sequentially along axes in the order specified by parameter settings (No. 7310). Machining is then restarted.

Procedure for Program Restart by Specifying a Block Number

Procedure 1

[P TYPE]

1 Retract the tool and replace it with a new one. When necessary, change the offset. (Go to step 2.)

[Q TYPE]

1 When power is turned ON or emergency stop is released, perform all necessary operations at that time, including the reference position return.

2 Move the machine manually to the program starting point (machining start point), and keep the modal data and coordinate system in the same conditions as at the machining start.

3 If necessary, modify the offset amount.

Procedure 2

[COMMON TO P TYPE / Q TYPE]

1 Turn the program restart switch on the machine operator's panel ON.

2 Press function PROG key to display the desired program.



3 Find the program head. Press function RESET key.

4 Enter the number of the block to be restarted then press the **[P TYPE]** or **[Q TYPE]** soft key. The block number cannot exceed eight digits.

5 The block number is searched for, and the program restart screen appears on the CRT display.



DESTINATION shows the position at which machining is to restart. DISTANCE TO GO shows the distance from the current tool position to the position where machining is to restart. A number to the left of each axis name indicates the order of axes (determined by parameter setting) along which the tool moves to the restart position.

The coordinates and amount of travel for restarting the program can be displayed for up to five axes. If your system supports six or more axes, pressing the **[RSTR]** soft key again displays the data for the sixth and subsequent axes. (The program restart screen displays only the data for CNC–controlled axes.)
M: Fourteen most recently specified M codes
T: Two most recently specified T codes
S: Most recently specified S code
B: Most recently specified B code
Codes are displayed in the order in which they are specified. All codes are cleared by a program restart command or cycle start in the reset state.

6 Turn the program re–start switch OFF. At this time, the figure at the left side of axis name DISTANCE TO GO blinks.

7 Check the screen for the M, S, T, and B codes to be executed. If they are found, enter the **MDI** mode, then execute the M, S, T, and B functions. After execution, restore the previous mode.
These codes are not displayed on the program restart screen.

8 Check that the distance indicated under DISTANCE TO GO is correct. Also check whether there is the possibility that the tool might hit a workpiece or other objects when it moves to the machining restart position. If such a possibility exists, move the tool manually to a position from which the tool can move to the machining restart position without encountering any obstacles.

9 Press the cycle start button. The tool moves to the machining restart position at the dry run feedrate sequentially along axes in the order specified by parameter settings (No. 7310). Machining is then restarted.

Explanations

- **Block number**

When the CNC is stopped, the number of executed blocks is displayed on the program screen or program restart screen. The operator can specify the number of the block from which the program is to be restarted, by referencing the number displayed. The displayed number indicates the number of the block that was executed most recently. For example, to restart the program from the block at which execution stopped, specify the displayed number, plus one.

The number of blocks is counted from the start of machining, assuming one NC line of a CNC program to be one block.

< Example 1 >

CNC Program	Number of blocks
O 0001 ;	1
G90 G92 X0 Y0 Z0 ;	2
G01 X100. F100 ;	3
G03 X01 –50. F50 ;	4
M30 ;	5

< Example 2 >

CNC Program	Number of blocks
O 0001 ;	1
G90 G92 X0 Y0 Z0 ;	2
G90 G00 Z100. ;	3
G81 X100. Y0. Z–120. R–80. F50. ;	4
#1 = #1 + 1 ;	4
#2 = #2 + 1 ;	4
#3 = #3 + 1 ;	4
G00 X0 Z0 ;	5
M30 ;	6

Macro statements are not counted as blocks.

- **Storing / clearing the block number**

The block number is held in memory while no power is supplied. The number can be cleared by cycle start in the reset state.

- **Block number when a program is halted or stopped**

The program screen usually displays the number of the block currently being executed. When the execution of a block is completed, the CNC is reset, or the program is executed in single–block stop mode, the program screen displays the number of the program that was executed most recently.
When a CNC program is halted or stopped by feed hold, reset, or single–block stop, the following block numbers are displayed:
Feed hold : Block being executed
Reset : Block executed most recently
Single–block stop : Block executed most recently
For example, when the CNC is reset during the execution of block 10, the displayed block number changes from 10 to 9.

- **MDI intervention**

When MDI intervention is performed while the program is stopped by single–block stop, the CNC commands used for intervention are not counted as a block.

- **Block number exceeding eight digits**

When the block number displayed on the program screen exceeds eight digits, the block number is reset to 0 and counting continues.

Limitation

- **P–type restart**

Under any of the following conditions, P–type restart cannot be performed:

- When automatic operation has not been performed since the power was turned on
- When automatic operation has not been performed since an emergency stop was released
- When automatic operation has not been performed since the coordinate system was changed or shifted (change in an external offset from the workpiece reference point)

- **Restart block**

The block to be restarted need not be the block which was interrupted; operation can restart with any block. When P–type restart is performed, the restart block must use the same coordinate system as when operation was interrupted.

- **Single block**

When single block operation is ON during movement to the restart position, operation stops every time the tool completes movement along an axis. When operation is stopped in the single block mode, MDI intervention cannot be performed.

- **Manual intervention**

During movement to the restart position, manual intervention can be used to perform a return operation for an axis if it has not yet been performed for the axis. A return operation cannot be done further on axes for which a return has already been completed.

- **Reset**

Never reset during the time from the start of a search at restart until machining is restarted. Otherwise, restart must be performed again from the first step.

- **Manual absolute**

Regardless of whether machining has started or not, manual operation must be performed when the manual absolute mode is on.

- **Reference position return**

If no absolute–position detector (absolute pulse coder) is provided, be sure to perform reference position return after turning on the power and before performing restart.

Alarm

Alarm No.	Contents
071	The specified block number for restarting the program is not found.
094	After interruption, a coordinate system was set, then P–type restart was specified.
095	After interruption, the coordinate system shift was changed, then P–type restart was specified.
096	After interruption, the coordinate system was changed, then P–type restart was specified.
097	When automatic operation has not been performed since the power was turned on, emergency stop was released, or P/S alarm (Nos. 094 to 097) was reset, P–type restart was specified.
098	After the power was turned on, restart operation was performed without reference position return, but a G28 command was found in the program.
099	A move command was specified from the MDI panel during a restart operation.
5020	An erroneous parameter was specifiifed for restarting a program.

WARNING

As a rule, the tool cannot be returned to a correct position under the following conditions.

- Special care must be taken in the following cases since none of them cause an alarm:
- Manual operation is performed when the manual absolute mode is OFF.
- Manual operation is performed when the machine is locked.
- When the mirror image is used.
- When manual operation is performed in the course of axis movement for returning operation.
- When the program restart is commanded for a block between the block for skip cutting and subsequent absolute command block.
- When program restart specified for an intermediate block for a multiple repetitive canned cycle.

4.4 SCHEDULING FUNCTION

The schedule function allows the operator to select files (programs) registered on a floppy–disk in an external input/output device (Handy File, Floppy Cassette, or FA Card) and specify the execution order and number of repetitions (scheduling) for performing automatic operation. It is also possible to select only one file from the files in the external input/output device and execute it during automatic operation.



Procedure for Scheduling Function

·Procedure for executing one file

1 Press the **MEMORY** switch on the machine operator's panel, then press the PROG function key on the MDI panel.

2 Press the rightmost soft key (continuous menu key), then press the **[FL. SDL]** soft key. A list of files registered in the Floppy Cassette is displayed on screen No. 1. To display more files that are not displayed on this screen, press the page key on the MDI panel. Files registered in the Floppy Cassette can also be displayed successively.



Screen No.1

3 Press the **[(OPRT)]** and **[SELECT]** soft keys to display “SELECT FILE NO.” (on screen No. 2). Enter a file number, then press the **[F SET]** and **[EXEC]** soft keys. The file for the entered file number is selected, and the file name is indicated after “CURRENT SELECTED:”.



Screen No.2

4 Press the **REMOTE** switch on the machine operator’s panel to enter the **RMT** mode, then press the cycle start switch. The selected file is executed. For details on the **REMOTE** switch, refer to the manual supplied by the machine tool builder. The selected file number is indicated at the upper right corner of the screen as an F number (instead of an O number).



Screen No.3

- **Procedure for executing the scheduling function**

1 Display the list of files registered in the Floppy Cassette. The display procedure is the same as in steps 1 and 2 for executing one file.

2 On screen No. 2, press the **[(OPRT)]** and **[SELECT]** soft keys to display “SELECT FILE NO.”

3 Enter file number 0, and press the **[F SET]**, and **[EXEC]** soft keys. “SCHEDULE” is indicated after “CURRENT SELECTED:”.

4 Press the left most soft key (return menu key) and the **[SCHDUL]** soft key. Screen No. 4 appears.



Screen No.4

Move the cursor and enter the file numbers and number of repetitions in the order in which to execute the files. At this time, the current number of repetitions “CUR.REP” is 0.

5 Press the **REMOTE** switch on the machine operator’s panel to enter the **RMT** mode, then press the start switch. The files are executed in the specified order. When a file is being executed, the cursor is positioned at the number of that file.
The current number of repetitions CUR.REP is increased when M02 or M30 is executed in the program being run.



Screen No.5

Explanations

- **Specifying no file number**

  If no file number is specified on screen No. 4 (the file number field is left blank), program execution is stopped at that point. To leave the file number field blank, press numeric key 0 then INPUT.

- **Endless repetition**

  If a negative value is set as the number of repetitions, <**LOOP**> is displayed, and the file is repeated indefinitely.

- **Clear**

  When the **[(OPRT)]**, **[CLEAR]**, and **[EXEC]** soft keys are pressed on screen No. 4, all data is cleared. However, these keys do not function while a file is being executed.

- **Return to the program screen**

  When the **[PRGRM]** soft key is pressed on screen No. 1, 2, 3, 4, or 5, the program screen is displayed.

Limitation

- **Number of repetitions**

  Up to 9999 can be specified as the number of repetitions. If 0 is set for a file, the file becomes invalid and is not executed.

- **Number of files registered**

  By pressing the page key on screen No. 4, up to 20 files can be registered.

- **M code**

  When M codes other than M02 and M30 are executed in a program, the current number of repetitions is not increased.

- **Displaying the floppy disk directory during file execution**

  During the execution of file, the floppy directory display of background editing cannot be referenced.

- **Restarting automatic operation**

  To resume automatic operation after it is suspended for scheduled operation, press the reset button.

- **Scheduling function for the two–path control**

  The scheduling function can be used only for a single tool post.

Alarm

Alarm No.	Description
086	An attempt was made to execute a file that was not registered in the floppy disk.
210	M198 and M99 were executed during scheduled operation, or M198 was executed during DNC operation.

4.5 SUBPROGRAM CALL FUNCTION (M198)

The subprogram call function is provided to call and execute subprogram files stored in an external input/output device(Handy File, FLOPPY CASSETTE, FA Card)during memory operation.
When the following block in a program in CNC memory is executed, a subprogram file in the external input/output device is called:

To use this function, the Floppy Cassette directory display option must be installed.

Format

1. FS15 tape format



2. Other than FS15 tape format



Explanation

The subprogram call function is enabled when parameter No.0102 for the input/output device is set to 3. When the custom macro option is provided, either format 1 or 2 can be used. A different M code can be used for a subprogram call depending on the setting of parameter No.6030. In this case, M198 is executed as a normal M code. The file number is specified at address P. If the SBP bit (bit 2) of parameter No.3404 is set to 1, a program number can be specified. When a file number is specified at address P, Fxxxx is indicated instead of Oxxxx.



Fig. 4.5 (a) Program flow when M198 is specified

Restrictions

For the two–path control, subprograms in a floppy cassette cannot be called for the two tool posts at the same time.

NOTE

1 When M198 in the program of the file saved in a floppy cassette is executed, a P/S alarm (No.210) is given. When a program in the memory of CNC is called and M198 is executed during execution of a program of the file saved in a floppy cassette, M198 is changed to an ordinary M–code.

2 When MDI is intervened and M198 is executed after M198 is commanded in the memory mode, M198 is changed to an ordinary M–code. When the reset operation is done in the MDI mode after M198 is commanded in the MEMORY mode, it does not influence on the memory operation and the operation is continued by restarting it in the MEMORY mode.

4.6 MANUAL HANDLE INTERRUPTION

The movement by manual handle operation can be done by overlapping it with the movement by automatic operation in the automatic operation mode.



Fig. 4.6 Manual handle interruption

- Handle interruption axis selection signals
  For the handle interruption axis selection signals, refer to the manual supplied by the machine tool builder.

During automatic operation, handle interruption is enabled for an axis if the handle interruption axis selection signal for that axis is on. Handle interruption is performed by turning the handle of the manual pulse generator.

WARNING

The travel distance by handle interruption is determined according to the amount by which the manual pulse generator is turned and the handle feed magnification (x1, x10, xM, xN).
Since this movement is not accelerated or decelerated, it is very dangerous to use a large magnification value for handle interruption.
The move amount per scale at x1 magnification is 0.001 mm (metric output) or 0.0001 inch (inch output).

NOTE

Handle interruption is disabled when the machine is locked during automatic operation.

Explanations

- **Relation with other functions**

The following table indicates the relation between other functions and the movement by handle interrupt.

Display	Relation
Machine lock	Machine lock is effective. The tool does not move even when this signal turns on.
Interlock	Interlock is effective. The tool does not move even when this signal turns on.
Mirror image	Mirror image is not effective. Interrupt functions on the plus direction by plus direction command, even if this signal turns on.

- **Position display**

The following table shows the relation between various position display data and the movement by handle interrupt.

Display	Relation
Absolute coordinate value	Handle interruption does not change absolute coordinates.
Relative coordinate value	Handle interruption does not change relative coordinates.
Machine coordinate value	Machine coordinates are changed by the travel distance specified by handle interruption.

- **Travel distance display**

Press the function key POS , then press the chapter selection soft key **[HNDL]**.
The move amount by the handle interrupt is displayed. The following 4 kinds of data are displayed concurrently.



(a) INPUT UNIT :
Handle interrupt move amount in input unit system
Indicates the travel distance specified by handle interruption according to the least input increment.

(b) OUTPUT UNIT :
Handle interrupt move amount in output unit system
Indicates the travel distance specified by handlei nterruption according to the least command increment.

(c) RELATIVE :
Position in relative coordinate system
These values have no effect on the travel distance specified by handle interruption.

(d) DISTANCE TO GO :
The remaining travel distance in the current block has no effect on the travel distance specified by handle interruption.

The handle interrupt move amount is cleared when the manual reference position return ends every axis.

4.7 MIRROR IMAGE

During automatic operation, the mirror image function can be used for movement along an axis. To use this function, set the mirror image switch to ON on the machine operator's panel, or set the mirror image setting to ON from the CRT/MDI (or LCD/MDI).



Fig. 4.7 Mirror image

Procedure

The following procedure is given as an example. For actual operation, refer to the manual supplied by the machine tool builder.

1 Press the single block switch to stop automatic operation. When the mirror image function is used from the beginning of operation, this step is omitted.

2 Press the mirror image switch for the target axis on the machine operator's panel.
Alternatively, turn on the mirror image setting by following the steps below:

2–1 Set the **MDI** mode.

2–2 Press the OFFSET SETTING function key.

2–3 Press the **[SETING]** soft key for chapter selection to display the setting screen.



2–4 Move the cursor to the mirror image setting position, then set the target axis to 1.

3 Enter an automatic operation mode (memory mode or MDI mode), then press the cycle start button to start automatic operation.

Explanations

- The mirror image function can also be turned on and off by setting bit 0 (MIRx) of parameter (No.0012) to 1 or 0.
- For the mirror image switches, refer to the manual supplied by the machine tool builder.

Restrictions

The direction of movement during manual operation, the direction of movement from an intermediate point to the reference position during automatic reference position return (G28).

4.8 MANUAL INTERVENTION AND RETURN

In cases such as when tool movement along an axis is stopped by feed hold during automatic operation so that manual intervention can be used to replace the tool: When automatic operation is restarted, this function returns the tool to the position where manual intervention was started.
To use the conventional program restart function and tool withdrawal and return function, the switches on the operator's panel must be used in conjunction with the MDI keys. This function does not require such operations.

Explanations

- **Manual absolute on/off**

  In manual absolute off mode, the tool does not return to the stop position, but instead operates according to the manual absolute on/off function.

- **Override**

  For the return operation, the dry run feedrate is used, and the jog feedrate override function is enabled.

- **Return operation**

  Return operation is performed according to positioning based on nonlinear interpolation.

- **Single block**

  If the single block stop switch is on during return operation, the tool stops at the stop position and restarts movement when the cycle start switch is pressed.

- **Cancellation**

  If a reset occurs or an alarm is issued during manual intervention or the return operation, this function is cancelled.

- **MDI mode**

  This function can be used in the MDI mode as well.

Restrictions

- **Enabling and disabling manual intervention and return**

  This function is enabled only when the automatic operation hold LED is on. When there is no travel distance remaining, this function has no effect even if a feed hold stop is performed with the automatic operation hold signal *SP (bit 5 of G008).

- **Offset**

  When the tool is replaced using manual intervention for a reason such as damage, the tool movement cannot be restarted by a changed offset in the middle of the interrupted block.

- **Machine lock, mirror image, and scaling**

  When performing manual intervention, never use the machine lock, mirror image, or scaling functions.

Example

1. The N1 block cuts a workpiece



2. The tool is stopped by pressing the feed hold switch in the middle of the N1 block (point A).



3. After retracting the tool manually to point B, tool movement is restarted.



4. After automatic return to point A at the dry run feedrate, the remaining move command of the N1 block is executed.



WARNING

When performing manual intervention, pay particular attention of machining and the shape of the workpiece so that the machine and tool are not damaged.

4.9 DNC OPERATION

By activating automatic operation during the DNC operation mode (RMT), it is possible to perform machining (DNC operation) while a program is being read in via reader/puncher interface, or remote buffer. If the floppy cassette directory display option is available, it is possible to select files (programs) saved in an external input/output unit of a floppy format (Handy File, Floppy Cassettes, or FA card) and specify (schedule) the sequence and frequency of execution for automatic operation.
To use the DNC operation function, it is necessary to set the parameters related to the reader/punch interface, and remote buffer in advance.

DNC OPERATION

Procedure

1 Search for the program (file) to be executed.

2 Press the REMOTE switch on the machine operator's panel to set RMT mode, then press the cycle start switch. The selected file is executed. For details of the use of the REMOTE switch, refer to the relevant manual supplied by the machine tool builder.

- **Program check screen (7 soft key type)**



- **Program screen (7 soft key type)**



- **Program screen (12 soft key type)**



During DNC operation, the program currently being executed is displayed on the program check screen and program screen.
The number of displayed program blocks depends on the program being executed.
Any comment enclosed between a control–out mark (() and control–in mark ()) within a block is also displayed.

Explanations

- During DNC operation, programs and macro programs stored in memory can be called.

Limitations

- **Limit on number of characters**

In program display, no more than 256 characters can be displayed. Accordingly, character display may be truncated in the middle of a block.

- **M198 (command for calling a program from within an external input/output unit)**

In DNC operation, M198 cannot be executed. If M198 is executed, P/S alarm No. 210 is issued.

- **Custom macro**

In DNC operation, custom macros can be specified, but no repeat instruction and branch instruction can be programmed. If a repeat instruction or branch instruction is executed, P/S alarm No. 123 is issued. When reserved words (such as IF, WHILE, COS, and NE) used with custom macros in DNC operation are displayed during program display, a blank is inserted between adjacent characters.

Example

		[During DNC operation]
#102=SIN[#100] ;	→	#102 = S I N[#100] ;
IF[#100NE0]GOTO5 ;	→	I F[#100NE0] G O T O 5 ;

- **M99**

When control is returned from a subprogram or macro program to the calling program during DNC operation, it becomes impossible to use a return command (M99P****) for which a sequence number is specified.

Alarm

Number	Message	Contents
086	DR SIGNAL OFF	When entering data in the memory by using Reader / Puncher interface, the ready signal (DR) of reader / puncher was turned off. Power supply of I/O unit is off or cable is not connected or a P.C.B. is defective.
123	CAN NOT USE MACRO COMMAND IN DNC	Macro control command is used during DNC operation. Modify the program.
210	CAN NOT COMAND M198/M199	Or M198 is executed in the DNC operation. Modify the program.

5 TEST OPERATION

The following functions are used to check before actual machining whether the machine operates as specified by the created program.

1. Machine Lock and Auxiliary Function Lock
2. Feedrate Override
3. Rapid Traverse Override
4. Dry Run
5. Single Block

5.1 MACHINE LOCK AND AUXILIARY FUNCTION LOCK

To display the change in the position without moving the tool, use machine lock.
There are two types of machine lock, all–axis machine lock, which stops the movement along all axes, and specified–axis machine lock, which stops the movement along specified axes only. In addition, auxiliary function lock, which disables M, S, and T commands, is available for checking a program together with machine lock.



Fig. 5.1 Machine lock

Procedure for Machine Lock and Auxiliary Function Lock

- **Machine Lock**

Press the machine lock switch on the operator's panel. The tool does not move but the position along each axis changes on the display as if the tool were moving.
Some machines have a machine lock switch for each axis. On such machines, press the machine lock switches for the axes along which the tool is to be stopped. Refer to the appropriate manual provided by the machine tool builder for machine lock.

WARNING
The positional relationship between the workpiece coordinates and machine coordinates may differ before and after automatic operation using machine lock. In such a case, specify the workpiece coordinate system by using a coordinate setting command or by performing manual reference position return.

- **Auxiliary Function Lock**

Press the auxiliary function lock switch on the operator's panel. M, S, and T codes are disabled and not executed. Refer to the appropriate manual provided by the machine tool builder for auxiliary function lock.

Restrictions

- **M, S, T command by only machine lock**

  M, S, and T commands are executed in the machine lock state.

- **Reference position return under Machine Lock**

  When a G27, G28, or G30 command is issued in the machine lock state, the command is accepted but the tool does not move to the reference position and the reference position return LED does not go on.

- **M codes not locked by auxiliary function lock**

  M00, M01, M02, M30, M98, and M99 commands are executed even in the auxiliary function lock state.

5.2 FEEDRATE OVERRIDE

A programmed feedrate can be reduced or increased by a percentage (%) selected by the override dial. This feature is used to check a program. For example, when a feedrate of 100 mm/min is specified in the program, setting the override dial to 50% moves the tool at 50 mm/min.



Fig. 5.2 Feedrate override

Procedure for Feedrate Override



JOG FEED RATE OVERRIDE

Set the feedrate override dial to the desired percentage (%) on the machine operator's panel, before or during automatic operation. On some machines, the same dial is used for the feedrate override dial and manual continuous feedrate dial. Refer to the appropriate manual provided by the machine tool builder for feedrate override.

Restrictions

- **Override Range**

The override that can be specified ranges from 0 to 254%. For individual machines, the range depends on the specifications of the machine tool builder.

- **Override during thread**

During threading, the override is ignored and the feedrate remains as specified by program.

5.3 RAPID TRAVERSE OVERRIDE

An override of four steps (F0, 25%, 50%, and 100%) can be applied to the rapid traverse rate. F0 is set by a parameter (No. 1421).



Fig. 5.3 Rapid traverse override

Procedure for Rapid Traverse Override

Select one of the four feedrates with the rapid traverse override switch during rapid traverse. Refer to the appropriate manual provided by the machine tool builder for rapid traverse override.



Rapid traverse override

Explanation

The following types of rapid traverse are available. Rapid traverse override can be applied for each of them.

1) Rapid traverse by G00.
2) Rapid traverse during a canned cycle.
3) Rapid traverse in G27, G28 and G30.
4) Manual rapid traverse.
5) Rapid traverse of manual reference position return

5.4 DRY RUN

The tool is moved at the feedrate specified by a parameter regardless of the feedrate specified in the program. This function is used for checking the movement of the tool under the state that the workpiece is removed from the table.



Fig. 5.4 Dry run

Procedure for Dry Run

Press the dry run switch on the machine operator's panel during automatic operation. The tool moves at the feedrate specified in a parameter. The rapid traverse switch can also be used for changing the feedrate. Refer to the appropriate manual provided by the machine tool builder for dry run.

Explanation

- **Dry run feedrate**

The dry run feedrate changes as shown in the table below according to the rapid traverse switch and parameters.

Rapid traverse button	Program command	
	Rapid traverse	Feed
ON	Rapid traverse rate	Dry run feedrate×JVmax *2)
OFF	Dry run speed × JV,or rapid traverse rate *1)	Dry run feedrate × JV

Max. cutting feedrate . . . . . Setting by parameter No.1422
Rapid traverse rate . . . . . Setting by parameter No.1420
Dry run feedrate . . . . . Setting by parameter No.1410

JV: Jog feedrate override
*1) Dry run feedrate x JV when parameter RDR (bit 6 of No. 1401) is
1. Rapid traverse rate when parameter RDR is 0.
*2) Clamped to the maximum cutting feedrate
JVmax: Maximum value of jog feedrate override

5.5 SINGLE BLOCK

Pressing the single block switch starts the single block mode. When the cycle start button is pressed in the single block mode, the tool stops after a single block in the program is executed. Check the program in the single block mode by executing the program block by block.



Single block

Procedure for Single Block

1 Press the single block switch on the machine operator's panel. The execution of the program is stopped after the current block is executed.

2 Press the cycle start button to execute the next block. The tool stops after the block is executed.

Refer to the appropriate manual provided by the machine tool builder for single block execution.

Explanation

- **Reference position return and single block**

If G28 to G30 are issued, the single block function is effective at the intermediate point.

- **Single block during a canned cycle**

In a canned cycle, the single block stop points are as follows.

— — → Rapid traverse
S : Single block ——→ Cutting feed

	Tool path		Explanation
☆G90 (Outer/inner turning cycle)	Straight cutting cycle	Taper cutting cycle	Tool path 1 to 4 is assumed as one cycle. After 4 is finished, a stop is made.
☆G92 (Threading cycle)	Straight threading cycle	Taper threading cycle	Tool path 1 to 4 is assumed as one cycle. After 4 is finished, a stop is made.
☆G94 (End surface turning cycle)	Straight end surface cutting cycle	Taper end surface cutting cycle	Tool path 1 to 4 is assumed as one cycle. After 4 is finished, a stop is made.
☆G70 (Finishing cycle)			Tool path 1 to 7 is assumed as one cycle. After 7 is finished, a stop is made.
☆G71 (Outer surface rough machining cycle) G72 (End surface rough machining cycle)	This figure shows the case for G71. G72 is the same.		Each tool path 1 to 4,5 to 8,9 to 12, 13 to 16 and 17 to 20 is assumed as one cycle. After each cycle is finished, a stop is made.

Fig. 5.5 Single block during canned cycle (1/2)

— — → Rapid traverse
S : Single–block stop ——→ Cutting feed

	Tool path	Explanation
☆G73 (Closed–loop cutting cycle)		Tool path 1 to 6 is assumed as one cycle. After 10 is finished, a stop is made.
☆G74 (End surface cutting–off cycle) G75 (Outer/inner surface cutting–off cycle)	 This figure shows the case for G74. G75 is the same.	Tool path 1 to 10 is assumed as one cycle. After 10 is finished, a stop is made.
☆G76 (Multiple repetitive threading cycle)		Tool path 1 to 4 is assume as one cycle. After 4 is finished, a stop is made.

Fig. 5.5 Single block during canned cycle (2/2)

- **Subprogram call and single block**

Single block stop is not performed in a block containing M98P_;. M99; or G65.
However, single block stop is even performed in a block with M98P_ or M99 command, if the block contains an address other than O, N or P.

6 SAFETY FUNCTIONS

To immediately stop the machine for safety, press the Emergency stop button. To prevent the tool from exceeding the stroke ends, Overtravel check and Stroke check are available. This chapter describes emergency stop, overtravel check, and stroke check.

6.1 EMERGENCY STOP

If you press Emergency Stop button on the machine operator's panel, the machine movement stops in a moment.



Fig. 6.1 Emergency stop

This button is locked when it is pressed. Although it varies with the machine tool builder, the button can usually be unlocked by twisting it.

Explanation

EMERGENCY STOP interrupts the current to the motor.
Causes of trouble must be removed before the button is released.

6.2 OVERTRAVEL

When the tool tries to move beyond the stroke end set by the machine tool limit switch, the tool decelerates and stops because of working the limit switch and an OVER TRAVEL is displayed.



Fig. 6.2 Overtravel

Explanation

- **Overtravel during automatic operation**

When the tool touches a limit switch along an axis during automatic operation, the tool is decelerated and stopped along all axes and an overtravel alarm is displayed.

- **Overtravel during manual operation**

In manual operation, the tool is decelerated and stopped only along the axis for which the tool has touched a limit switch. The tool still moves along the other axes.

- **Releasing overtravel**

Press the reset button to reset the alarm after moving the tool to the safety direction by manual operation. For details on operation, refer to the operator's manual of the machine tool builder.

- **Alarm**

No.	Message	Description
506	Overtravel: +n	The tool has exceeded the hardware–specified overtravel limit along the positive nth axis (n: 1 to 8).
507	Overtravel: –n	The tool has exceeded the hardware–specified overtravel limit along the negative nth axis (n: 1 to 8).

6.3 STROKE CHECK

There areas which the tool cannot enter can be specified with stored stroke check 1, stored stroke check 2,and stored stroke check 3.



Fig. 6.3 (a) Stroke check

When the tool exceeds a stored stroke limit, an alarm is displayed and the tool is decelerated and stopped.
When the tool enters a forbidden area and an alarm is generated, the tool can be moved in the reverse direction from which the tool came.

Explanation

- **Stored stroke check 1**

Parameters (Nos. 1320, 1321 or Nos. 1326, 1327) set boundary. Outside the area of the set limits is a forbidden area. The machine tool builder usually sets this area as the maximum stroke.

- **Stored stroke check 2 (G22, G23)**

Parameters (Nos. 1322, 1323) or commands set these boundaries. Inside or outside the area of the limit can be set as the forbidden area. Parameter OUT (No. 1300#0) selects either inside or outside as the forbidden area.

In case of program command a G22 command forbids the tool to enter the forbidden area, and a G23 command permits the tool to enter the forbidden area. Each of G22; and G23; should be commanded independently of another commands in a block.
The command below creates or changes the forbidden area:



Fig. 6.3 (b) Creating or changing the forbidden area using a program

When setting the area by parameters, points A and B in the figure below must be set.



Fig. 6.3 (c) Creating or changing the forbidden area using a parameters

In stored stroke check 2, even if you mistake the order of the coordinate value of the two points, a rectangular, with the two points being the apexes, will be set as the area.
When you set the forbidden area X_1, Z_1, X_2, and Z_2 through parameters (Nos. 1322, 1323), the data should be specified by the distance from the reference position in the least command increment. (Output increment)

If set the forbidden area XZIK by a G22 command, specify the data by the distance from the reference position in the least input increment (Input increment.) The programmed data are then converted into the numerical values in the least command increment, and the values are set as the parameters.

- **Stored stroke check 3**

Set the boundary with parameters No. 1324 and 1325. The area inside the boundary becomes the forbidden area.

- **Checkpoint for the forbidden area**

The parameter setting or programmed value (XZIK) depends on which part of the tool or tool holder is checked for entering the forbidden area. Confirm the checking position (the top of the tool or the tool chuck) before programming the forbidden area.
If point C (The top of the tool) is checked in Fig. 6.3 (d) , the distance “c” should be set as the data for the stored stroke limit function. If point D (The tool chuck) is checked, the distance “d” must be set.



Fig. 6.3(d) Setting the forbidden area

- **Forbidden area over–lapping**

Area can be set in piles.



Fig. 6.3(e) Setting the forbidden area over lapping

Unnecessary limits should be set beyond the machine stroke.

- **Effective time for a forbidden area**

Each limit becomes effective after the power is turned on and manual reference position return or automatic reference position return by G28 has been performed.
After the power is turned on, if the reference position is in the forbidden area of each limit, an alarm is generated immediately. (Only in G22 mode for stored stroke limit 2).

- **Releasing the alarms**

When the tool has become unmovable in the forbidden area, push the emergency stop button to release the forbidden condition and move the tool out of the forbidden area in the G23 mode; then, if the setting is wrong, correct it and perform the reference position return again.

- **Change from G23 to G22 in a forbidden area**

When G23 is switched to G22 in the forbidden area, the following results.

(1) When the forbidden area is inside, an alarm is informed in the next move.

(2) When the forbidden area is outside, an alarm is informed immediately.

- **Setting the forbidden area for the two–path control**

For the two–path control, set a forbidden area for each tool post.

NOTE
In setting a forbidden area, if the two points to be set arethe same, the area is as follows:
(1) When the forbidden area is stored stroke check 1, all areas are forbidden areas.
(2) When the forbidden area is stored stroke check 2 or stored stroke check 3 all areas are movable areas.

- **Overrun amount of stored stroke limit**

If the maximum rapid traverse rate is F (mm/min), the maximum overrun amount, L (mm), of the stored stroke limit is obtained from the following expression:

L (mm) = F/7500

The tool enters the specified inhibited area by up to L (mm). Bit 7 (BFA) of parameter No. 1300 can be used to stop the tool when it reaches a point L mm short of the specified area. In the case, the tool will not enter the inhibited area.

- **Timing for displaying an alarm**

Parameter BFA (bit 7 of No. 1300) selects whether an alarm is displayed immediately before the tool enters the forbidden area or immediately after the tool has entered the forbidden area.

ALram

Number	Message	Contents
500	OVER TRAVEL: +n	Exceeded the n–th axis (1–8) + side stored stroke limit 1.
501	OVER TRAVEL: –n	Exceeded the n–th axis (1–8) – side stored stroke limit 1.
502	OVER TRAVEL: +n	Exceeded the n–th axis (1–8) + side stored stroke limit 2.
503	OVER TRAVEL: –n	Exceeded the n–th axis (1–8) – side stored stroke limit 2.
504	OVER TRAVEL: +n	Exceeded the n–th axis (1–8) + side stored stroke limit 3.
505	OVER TRAVEL: –n	Exceeded the n–th axis (1–8) – side stored stroke limit 3.

6.4 CHUCK AND TAILSTOCK BARRIERS

The chuck–tailstock barrier function prevents damage to the machine by checking whether the tool tip fouls either the chuck or tailstock.
Specify an area into which the tool may not enter (entry–inhibition area). This is done using the special setting screen, according to the shapes of the chuck and tailstock. If the tool tip should enter the set area during a machining operation, this function stops the tool and outputs an alarm message.
The tool can be cleared from the area only by retracting it in the direction opposite to that in which the tool entered the area.

Setting the chuck and tailstock barriers

● Setting the shapes of the chuck and tailstock

1 Press the OFFSET SETTING function key.

2 Press the ▷ continuous menu key. Then, press the **[BARIER]** chapter selection soft key.

3 Pressing the page key toggles the display between the chuck barrier setting screen and tailstock barrier setting screen.

Chuck barrier setting screen



Tailstock barrier setting screen



4 Position the cursor to each item defining the shape of the chuck or tailstock, enter the corresponding value, then press the **[INPUT]** soft key. The value is set. Pressing the **[+INPUT]** soft key after a value has been entered adds the entered value to the current value, the new setting being the sum of the two values.
Items CX and CZ, both on the chuck barrier setting screen, and item TZ on the tailstock barrier setting screen can also be set in another way. Manually move the tool to the desired position, then press the **[SET]** soft key to set the coordinate(s) of the tool in the workpiece coordinate system. If a tool having an offset other than 0 is manually moved to the desired position with no compensation applied, compensate for the tool offset in the set coordinate system.
Items other than CX, CZ, and TZ cannot be set by using the **[SET]** soft key.

Example)

When the tool tip enters the entry–inhibition area during machining, the function stops the movement of the tool and displays an alarm message. Since the machine system can stop only a slight delay after the CNC stops, the tool will actually stop moving at a point within the specified boundary. For safety, therefore, set an area a little larger than the determined area. The distance between the boundaries of these two areas, L, is calculated from the following equation, based on the rapid traverse rate.

$$L = \textit{(Rapid traverse Rate)} \times \frac{1}{7500}$$

When the rapid traverse rate is 15 m/min, for example, set an area having a boundary 2 mm outside that of the determined area.
The shapes of the chuck and tailstock can be set using parameters No. 1330 to 1345.

CAUTION
Set G23 mode before attempting to specify the shapes of the chuck and tailstock.

- **Reference position return**

1 Return the tool to the reference position along the X– and Z–axes. The chuck–tailstock barrier function becomes effective only once reference position return has been completed after power on.
When an absolute position detector is provided, reference position return need not always be performed. The positional relationship between the machine and the absolute position detector, however, must be determined.

- **G22, G23**

1 After reference position return, specifying G22 (stored stroke limit on) makes the entry–inhibition areas for the chuck and tailstock effective. Specifying G23 (stored stroke limit off) disables the function.
Even if G22 is specified, the entry–inhibition area for the tailstock can be disabled by issuing a tailstock barrier signal.
When the tailstock is pushed up against a workpiece or separated from the workpiece by using the miscellaneous functions, PMC signals are used to enable or disable the tailstock setting area.

G code	Tailstock barrier signal	Chuck barrier	Tailstock barrier
G22	0	Effective	Effective
	1	Effective	Ineffective
G23	No relation	Ineffective	Ineffective

G22 is usually selected when the power is turned on. Using G23, bit 7 of parameter No. 3402, however, it can be changed to G23.

Explanations

- **Setting the shape of the chuck barrier**



Note) The hatched areas indicate entry–inhibition areas.

Symbol	Description
TY	Chuck–shape selection (0: Holding the inner face of a tool, 1: Holding the outer face of a tool)
CX	Chuck position (along X–axis)
CZ	Chuck position (along Z–axis)
L	Length of chuck jaws
W	Depth of chuck jaws (radius)
L1	Holding length of chuck jaws
W1	Holding depth of chuck jaws (radius)

TY :

Selects a chuck type, based on its shape. Specifying 0 selects a chuck that holds the inner face of a tool. Specifying 1 selects a chuck that holds the outer face of a tool. A chuck is assumed to be symmetrical about its Z–axis.

CX, CZ:

Specify the coordinates of a chuck position, point A, in the workpiece coordinate system. These coordinates are not the same as those in the machine coordinate system. Table 1 lists the units used to specify the data.

WARNING

Whether diameter programming or radius programming is used for the axis determines the programming system. When diameter programming is used for the axis, use diameter programming to enter data for the axis.

Table 1 Units

Increment system	Data unit		Valid data range
	IS–A	IS–B	
Metric input	0.001 mm	0.0001 mm	–99999999 to +99999999
Inch input	0.0001 inch	0.00001 inch	–99999999 to +99999999

L, L1, W, W1:

Define the shape of a chuck. Table 2 lists the units used to specify the data.

WARNING

Always specify W and W1 in radius. When radius programming is used for the Z–axis, specify L and L1 in radius.

Table 2 Units

Increment system	Data unit		Valid data range
	IS–A	IS–B	
Metric input	0.001 mm	0.0001 mm	–99999999 to +99999999
Inch input	0.0001 inch	0.00001 inch	–99999999 to +99999999

- **Setting the shape of a tailstock barrier**



Symbol	Description
TZ	Tailstock position (along the Z–axis)
L	Tailstock length
D	Tailstock diameter
L1	Tailstock length (1)
D1	Tailstock diameter (1)
L2	Tailstock length (2)
D2	Tailstock diameter (2)
D3	Tailstock diameter (3)

TZ :

Specifies the Z coordinate of the chuck position, point B, in the workpiece coordinate system. These coordinates are not the same as those in the machine coordinate system. Table 3 lists the units used to specify the data. A tailstock is assumed to be symmetrical about its Z–axis.

WARNING

Whether diameter programming or radius programming is used for the Z–axis determines the programming system.

Table 3 Units

Increment system	Data unit		Valid data range
	IS–A	IS–B	
Metric input	0.001 mm	0.0001 mm	–99999999 to +99999999
Inch input	0.0001 inch	0.00001 inch	–99999999 to +99999999

L, L1, L2, D, D1, D2, D3:

Define the shape of a tailstock. Table 4 lists the units used to specify the data.

WARNING

Always specify D, D1, D2, and D3 in diameter programming. When radius programming is used for the Z–axis, specify L, L1, and L2 in radius.

Table 4 Units

Increment system	Data unit		Valid data range
	IS–A	IS–B	
Metric input	0.001 mm	0.0001 mm	–99999999 to +99999999
Inch input	0.0001 inch	0.00001 inch	–99999999 to +99999999

- **Setting the entry–inhibition area for the tailstock tip**

The tip angle of the tailstock is 60 degrees. The entry–inhibition area is set around the tip, assuming the angle to be 90 degrees, as shown below.



Limitations

- **Correct setting of an entry–inhibition area**

If an entry–inhibition area is incorrectly set, it may not be possible to make the area effective. Avoid making the following settings:

- L < L1 or W < W1 in the chuck–shape settings.
- D2 < D3 in the tailstock–shape settings.
- A chuck setting overlapping that of the tailstock.

- **Retraction from the entry–inhibition area**

If the tool enters the entry–inhibition area and an alarm is issued, switch to manual mode, retract the tool manually, then reset the system to release the alarm. In manual mode, the tool can be moved only in the opposite direction to that in which the tool entered the area. The tool cannot be moved in the same direction (further into the area) as it was travelling when the tool entered the area.
When the entry–inhibition areas for the chuck and tailstock are enabled, and the tool is already positioned within those areas, an alarm is issued when the tool moves. When the tool cannot be retracted, change the setting of the entry–inhibition areas, such that the tool is outside the areas, reset the system to release the alarm, then retract the tool. Finally, reinstall the original settings.

- **Coordinate system**

An entry–inhibition area is defined using the workpiece coordinate system. Note the following.

1 When the workpiece coordinate system is shifted by means of a command or operation, the entry–inhibition area is also shifted by the same amount.



Use of the following commands and operations will shift the workpiece coordinate system.

Commands:

G54 to G59, G52, G50 (G92 in G code system B or C)

Operations:

Manual handle interrupt, change in offset relative to the workpiece reference point, change in tool offset (tool geometry compensation), operation with machine lock, manual operation with machine absolute signal off

2 When the tool enters an entry–inhibition area during automatic operation, set the manual absolute signal, *ABSM, to 0 (on), then manually retract the tool from the area. If this signal is 1, the distance the tool moves in manual operation is not counted in the tool coordinates in the workpiece coordinate system. This results in the state where the tool can never be retracted from the entry–inhibition area.

- **Stored stroke limit 2**

When both stored stroke limit 2 and the chuck–tailstock barrier function are provided, the barrier takes priority over the stroke limit. Stored stroke limit 2 is ignored.

Alarms

Number	Message	Contents
502	OVER TRAVEL: +X	The tool has entered the entry–inhibition area during positive–direction movement along the X–axis.
	OVER TRAVEL: +Z	The tool has entered the entry–inhibition area during positive–direction movement along the Z–axis.
503	OVER TRAVEL: –X	The tool has entered the entry–inhibition area during negative–direction movement along the X–axis.
	OVER TRAVEL: –Z	The tool has entered the entry–inhibition area during negative–direction movement along the Z–axis.

7 ALARM AND SELF–DIAGNOSIS FUNCTIONS

When an alarm occurs, the corresponding alarm screen appears to indicate the cause of the alarm. The causes of alarms are classified by error codes. Up to 25 previous alarms can be stored and displayed on the screen (alarm history display).
The system may sometimes seem to be at a halt, although no alarm is displayed. In this case, the system may be performing some processing. The state of the system can be checked using the self–diagnostic function.

7.1 ALARM DISPLAY

Explanations

- **Alarm screen**

When an alarm occurs, the alarm screen appears.



- **Another method for alarm displays**

In some cases, the alarm screen does not appear, but an ALM is displayed at the bottom of the screen.



In this case, display the alarm screen as follows:

1 Press the function key MESSAGE .

2 Press the chapter selection soft key **[ALARM]**.

- **Reset of the alarm**

Error codes and messages indicate the cause of an alarm. To recover from an alarm, eliminate the cause and press the reset key.

- **Error codes**

The error codes are classified as follows:
No. 000 to 255: P/S alarms (Program errors)*1
No. 300 to 349: Absolute pulse coder (APC) alarms
No. 350 and 399: Serial pulse coder (SPC) alarms
No. 400 to 499: Servo alarms
No. 500 to 599: Overtravel alarms
No. 700 to 749: Overheat alarms
No. 750 to 799: Spindle alarms
No. 900 to 999: System alarms
No. 5000 to : P/S alarms (Program errors)

*1:For an alarm (No. 000 to 232) that occurs in association with background operation, the indication “xxxBP/S alarm” is provided (where xxx is an alarm number). Only a BP/S alarm is provided for No. 140.
See the error code list in the appendix for details of the error codes.

7.2 ALARM HISTORY DISPLAY

Up to 25 of the most recent CNC alarms are stored and displayed on the screen.
Display the alarm history as follows:

Procedure for Alarm History Display

1 Press the function key MESSAGE .

2 Press the chapter selection soft key **[HISTRY]**.
The alarm history appears.
The following information items are displayed.
(1)The date the alarm was issued
(2)Alarm No.
(3)Alarm message (some contains no message)
(4)Page number

3 Change the page by page key PAGE or PAGE.

4 To delete the recorded information, press the softkey **[(OPRT)]** then the **[DELETE]** key.



7.3 CHECKING BY SELF–DIAGNOSTIC SCREEN

The system may sometimes seem to be at a halt, although no alarm has occurred. In this case, the system may be performing some processing. The state of the system can be checked by displaying the self–diagnostic screen.

Procedure for Diagnostic

1 Press the function key SYSTEM .

2 Press the chapter select key **[DGNOS]**.

3 The diagnostic screen has more than 1 pages. Select the screen by the following operation.

(1) Change the page by page key PAGE ↑ or PAGE ↓.

(2) Method by soft key
– Key input the number of the diagnostic data to be displayed.
– Press **[N SRCH]**.

```
DIAGNOSTIC (GENERAL)                    O0020  N00001


000  WAITING FOR FIN SIGNAL                      :0
001  MOTION                                      :0
002  DWELL                                       :0
003  IN–POSITION  CHECK                          :0
004  FEEDRATE  OVERRIDE  0%                      :0
005  INTERLOCK/START–LOCK                        :0
006 SPINDLE  SPEED  ARRIVAL  CHECK               :0


>_
 EDIT  * * * *   * * *   * * *        14 : 51 : 55
(PARAM )(DGNOS )( PMC )(SYSTEM )(OPRT)
```

Explanations

- **Self diagnostic screen at 2–path control**

For the two–path control, the diagnostic screen for the tool post selected with the tool post selection switch is displayed. When displaying the diagnostic screen for the other tool post, specify the tool post with the tool post selection switch.

Explanations

Diagnostic numbers 000 to 015 indicate states when a command is being specified but appears as if it were not being executed. The table below lists the internal states when 1 is displayed at the right end of each line on the screen.

Table 7.3 (a) Alarm displays when a command is specified but appears as if it were not being executed

No.	Display	Internal status when 1 is displayed
000	WAITING FOR FIN SIGNAL	M, S. T function being executed
001	MOTION	Move command in automatic operation being executed
002	DWELL	Dwell being executed
003	IN–POSITION CHECK	In–position check being executed
004	FEEDRATE OVERRIDE 0%	Cutting feed override 0%
005	INTERLOCK/START–LOCK	Interlock ON
006	SPINDLE SPEED ARRIVAL CHECK	Waiting for spindle speed arrival signal to turn on
010	PUNCHING	Data being output via reader puncher interface
011	READING	Data being input via reader puncher interface
012	WAITING FOR (UN) CLAMP	Waiting for index table clamp/unclamp before B axis index table indexing start/after B axis index table indexing end to complete
013	JOG FEEDRATE OVERRIDE 0%	Jog override 0%
014	WAITING FOR RESET.ESP.RRW.OFF	Emergency stop, external reset, reset & rewind, or MDI panel reset key on
015	EXTERNAL PROGRAM NUMBER SEARCH	External program number searching

Diagnostic numbers 020 to 025 indicate the states when automatic operation is stopped or paused.

Table 7.3 (b) Alarm displays when an automatic operation is stopped or paused.

No.	Display	Internal status when 1 is displayed
020	CUT SPEED UP/DOWN	Set when emergency stop turns on or when servo alarm occurs
021	RESET BUTTON ON	Set when reset key turns on
022	RESET AND REWIND ON	Reset and rewind turned on
023	EMERGENCY STOP ON	Set when emergency stop turns on
024	RESET ON	Set when external reset, emergency stop, reset, or reset & rewind key turns on
025	STOP MOTION OR DWELL	A flag which stops pulse distribution. It is set in the following cases. (1)External reset turned on. (2)Reset & rewind turned on. (3)Emergency stop turned on. (4)Feed hold turned on. (5)The MDI panel reset key turned on. (6)Switched to the manual mode(JOG/HANDLE/INC). (7)Other alarm occurred. (There is also alarm which is not set.)

The table below shows the signals and states which are enabled when each diagnostic data item is 1. Each combination of the values of the diagnostic data indicates a unique state.

020	CUT SPEED UP/DOWN	1	0	0	0	1	0	0
021	RESET BUTTON ON	0	0	1	0	0	0	0
022	RESET AND REWIND ON	0	0	0	1	0	0	0
023	EMERGENCY STOP ON	1	0	0	0	0	0	0
024	RESET ON	1	1	1	1	0	0	0
025	STOP MOTION OR DWELL	1	1	1	1	1	1	0



Diagnostic numbers 030 and 031 indicate TH alarm states.

No.	Display	Meaning of data
030	CHARACTER NUMBER TH DATA	The position of the character which caused TH alarm is displayed by the number of characters from the beginning of the block at TH alarm
031	TH DATA	Read code of character which caused TH alarm

8 DATA INPUT/OUTPUT

NC data is transferred between the CNC and external input/output devices such as the Handy File.
The following types of data can be entered and output :

1.Program
2.Offset data
3.Parameter
4.Pitch error compensation data
5.Custom macro common variable

Before an input/output device can be used, the input/output related parameters must be set.
For how to set parameters, see Chapter III–2.



8.1 FILES

Of the external input/output devices, the FANUC Handy File and FANUC Floppy Cassette use floppy disks as their input/output medium, and the FANUC FA Card uses an FA card as its input/output medium.
In this manual, an input/output medium is generally referred to as a floppy. However, when the description of one input/output medium varies from the description of another, the name of the input/output medium is used. In the text below, a floppy represents a floppy disk or FA card.
Unlike an NC tape, a floppy allows the user to freely choose from several types of data stored on one medium on a file–by–file basis.
Input/output is possible with data extending over more than one floppy disk.

Explanations

• What is a File

The unit of data, which is input/output between the floppy and the CNC by one input/output operation (pressing the VREADW or VPUNCHW key), is called a HfileI. When inputting CNC programs from, or outputting them to the floppy, for example, one or all programs within the CNC memory are handled as one file.
Files are assigned automatically file numbers 1,2,3,4 and so on, with the lead file as 1.



• Request for floppy replacement

When one file has been entered over two floppies, LEDs on the adaptor flash alternately on completion of data input/output between the first floppy and the CNC, prompting floppy replacement. In this case, take the first floppy out of the adaptor and insert a second floppy in its place. Then, data input/output will continue automatically.
Floppy replacement is prompted when the second floppy and later is required during file search–out, data input/output between the CNC and the floppy, or file deletion.
Floppy 1



Floppy 2



Since floppy replacement is processed by the input/output device, no special operation is required. The CNC will interrupt data input/output operation until the next floppy is inserted into the adaptor.
When reset operation is applied to the CNC during a request for floppy replacement, the CNC is not reset at once, but reset after the floppy has been replaced.

- **Protect switch**

The floppy is provided with the write protect switch. Set the switch to the write enable state. Then, start output operation.



Fig. 8.1 Protect switch

- **Writing memo**

Once written in the cassette or card, data can subsequently be read out by correspondence between the data contents and file numbers. This correspondence cannot be verified, unless the data contents and file numbers are output to the CNC and displayed. The data contents can be displayed with display function for directory of floppy disk (See Section III–8.8).
To display the contents,write the file numbers and the contents on the memo column which is the back of floppy.

(Entry example on MEMO)
File 1 NC parameters
File 2 Offset data
File 3 NC program O0100
. .
. .
. .
File (n–1) NC program O0500
File n NC program O0600

8.2 FILE SEARCH

When the program is input from the floppy, the file to be input first must be searched.
For this purpose, proceed as follows:



Procedure for File Heading

1 Press the EDIT or MEMORY switch on the machine operator's panel.

2 Press function key [PROG], then the program contents display screen or program check screen appears.

3 Press soft key **[(OPRT)]**

4 Press the rightmost soft key [▷] (next–menu key).

5 Enter address N.

6 Enter the number of the file to search for.

· N0
The beginning of the cassette or card is searched.

· One of N1 to N9999
Of the file Nos. 1 to 9999, a designated file is searched.

· N–9999
The file next to that accessed just before is searched.

· N–9998
When N–9998 is designated, N–9999 is automatically inserted each time a file is input or output. This condition is reset by the designation of N1,N1 to 9999, or N − 9999 or reset.

7 Press soft keys **[FSRH]** and **[EXEC]**
The specified file is searched for.

Explanations

- **File search by N–9999**

The same result is obtained both by sequentially searching the files by specifying Nos. N1 to N9999 and by first searching one of N1 to N9999 and then using the N–9999 searching method. The searching time is shorter in the latter case.

Alarm

No.	Description
86	The ready signal (DR) of an input/output device is off. An alarm is not immediately indicated in the CNC even when an alarm occurs during head searching (when a file is not found, or the like). An alarm is given when the input/output operation is performed after that. This alarm is also raised when N1 is specified for writing data to an empty floppy. (In this case, specify N0.)

8.3 FILE DELETION

Files stored on a floppy can be deleted file by file as required.

Procedure for File Deletion

1. Insert the floppy into the input/output device so that it is ready for writing.
2. Press the EDIT switch on the machine operator's panel.
3. Press function key PROG , then the program contents display screen appears.
4. Press soft key **[(OPRT)]**
5. Press the rightmost soft key ▷ (next–menu key).
6. Enter address N.
7. Enter the number (from 1 to 9999) of the file to delete.
8. Press soft key **[DELETE]**, then press soft key **[EXEC]**.
   The file specified in step **7** is deleted.

Explanations

- **File number after the file is deleted**

When a file is deleted, the file numbers after the deleted file are each decremented by one. Suppose that a file numbered k was deleted. In this case, files are renumbered as follows:

Before deletion	after deletion
1 to (k–1)	1 to (k–1)
k	Deleted
(k+1) to n	k to (n–1)

- **Protect switch**

Set the write protect switch to the write enable state to delete the files.

8.4 PROGRAM INPUT/OUTPUT

8.4.1 Inputting a Program

This section describes how to load a program into the CNC from a floppy or NC tape.

Procedure for Inputting a Program

1 Make sure the input device is ready for reading.
For the two–path control, select the tool post for which a program to be input is used with the tool post selection switch.

2 Press the EDIT switch on the machine operator's panel.

3 When using a floppy, search for the required file according to the procedure in Section **III–8.2**.

4 Press function key [PROG] , then the program contents display screen or program directory screen appears.

5 Press soft key **[(OPRT)]**

6 Press the rightmost soft key [▷] (next–menu key).

7 After entering address O, specify a program number to be assigned to the program. When no program number is specified here, the program number used on the floppy or NC tape is assigned.

8 Press soft keys **[READ]** and **[EXEC]**
The program is input and the program number specified in step **7** is assigned to the program.

Explanations

- **Collation**

If a program is input while the data protect key on the machine operator's panel turns ON, the program loaded into the memory is verified against the contents of the floppy or NC tape.
If a mismatch is found during collation, the collation is terminated with an P/S alarm (No. 79).
If the operation above is performed with the data protection key turns OFF, collation is not performed, but programs are registered in memory.

- **Inputting multiple programs from an NC tape**

When a tape holds multiple programs, the tape is read up to ER (or %).



● Program numbers on a NC tape

- When a program is entered without specifying a program number.
- The O–number of the program on the NC tape is assigned to the program. If the program has no O–number, the N–number in the first block is assigned to the program.
- When the program has neither an O–number nor N–number, the previous program number is incremented by one and the result is assigned to the program.
- When the program does not have an O–number but has a five–digit sequence number at the start of the program, the lower four digits of the sequence number are used as the program number. If the lower four digits are zeros, the previously registered program number is incremented by one and the result is assigned to the program.
- When a program is entered with a program number
  The O–number on the NC tape is ignored and the specified number is assigned to the program. When the program is followed by additional programs, the first additional program is given the program number. Additional program numbers are calculated by adding one to the last program.

● Program registration in the background

The method of registration operation is the same as the method of foreground operation. However, this operation registers a program in the background editing area. As with edit operation, the operations described below are required at the end to register a program in foreground program memory.

[(OPRT)] [BG–END]

● Additional program input

You can input a program to be appended to the end of a registered program.

Registered program	Input program	Program after input
○1234 ; □□□□□□□□ ; □□□□□ ; □□□□ ; □□□ ; %	○5678 ; ○○○○○○○ ; ○○○○○ ; ○○○○ ; ○○○ ; %	○1234 ; □□□□□□□□ ; □□□□□ ; □□□□ ; □□□ ; % ○5678 ; ○○○○○○○ ; ○○○○○ ; ○○○○ ; ○○○ ; %

In the above example, all lines of program O5678 are appended to the end of program O1234. In this case, program number O5678 is not registered. When inputting a program to be appended to a registered program, press the **[READ]** soft key without specifying a program number in step 8. Then, press the **[CHAIN]** and **[EXEC]** soft keys.

- In entire program input, all lines of a program are appended, except for its O number.
- When canceling additional input mode, press the reset key or the **[CAN]** or **[STOP]** soft key.
- Pressing the **[CHAIN]** soft key positions the cursor to the end of the registered program. Once a program has been input, the cursor is positioned to the start of the new program.

- Additional input is possible only when a program has already been registered.

● Defining the same program number as that of an existing program

If an attempt has been made to register a program having the same number as that of a previously registered program, P/S alarm 073 is issued and the program cannot be registered.

Alarm

No.	Description
70	The size of memory is not sufficient to store the input programs
73	An attempt was made to store a program with an existing program number.
79	The verification operation found a mismatch between a program loaded into memory and the contents of the program on the floppy or NC tape.

8.4.2 Outputting a Program

A program stored in the memory of the CNC unit is output to a floppy or NC tape.

Procedure for Outputting a Program

1 Make sure the output device is ready for output.
For the two–path control, select the tool post for which a program to be output is used with the tool post selection switch.

2 To output to an NC tape, specify the punch code system (ISO or EIA) using a parameter.

3 Press the EDIT switch on the machine operator's panel.

4 Press function key PROG , then the program contents display screen or program directory screen appears.

5 Press soft key **[(OPRT)]**.

6 Press the rightmost soft key ▷ (next–menu key).

7 Enter address O.

8 Enter a program number. If –9999 is entered, all programs stored in memory are output.
To output multiple programs at one time, enter a range as follows :
OΔΔΔΔ,O□□□□
Programs No.ΔΔΔΔ to No.□□□□ are output.
The program library screen displays program numbers in ascending order when bit 4 (SOR) of parameter No. 3107 is set to 1.

9 Press soft keys **[PUNCH]** and **[EXEC]**
The specified program or programs are output.

Explanations (Output to a floppy)

- **File output location**

When output is conducted to the floppy, the program is output as the new file after the files existing in the floppy. New files are to be written from the beginning with making the old files invalid, use the above output operation after the N0 head searching.

- **An alarm while a program is output**

When P/S alarm (No.086) occurs during program output, the floppy is restored to the condition before the output.

- **Outputting a program after file heading**

When program output is conducted after N1 to N9999 head searching, the new file is output as the designated n–th position. In this case, 1 to n–1 files are effective, but the files after the old n–th one are deleted. If an alarm occurs during output, only the 1 to n–1 files are restored.

- **Efficient use of memory**

To efficiently use the memory in the cassette or card, output the program by setting parameter NFD (No. 0101#7,No. 0111#7 or 0121#7) to 1. This parameter makes the feed is not output, utilizing the memory efficiently.

- **On the memo record**

Head searching with a file No. is necessary when a file output from the CNC to the floppy is again input to the CNC memory or compared with the content of the CNC memory. Therefore, immediately after a file is output from the CNC to the floppy, record the file No. on the memo.

- **Punching programs in the background**

Punch operation can be performed in the same way as in the foreground. This function alone can punch out a program selected for foreground operation.
<O> (Program No.) **[PUNCH] [EXEC]**: Punches out a specified program.
<O> H–9999I **[PUNCH] [EXEC]**: Punches out all programs.

Explanations (Output to an NC tape)

- **Format**

A program is output to paper tape in the following format:



If three–feet feeding is too long, press the CAN key during feed punching to cancel the subsequent feed punching.

- **TV check**

A space code for TV check is automatically punched.

- **ISO code**

When a program is punched in ISO code, two CR codes are punched after an LF code.

By setting NCR (bit 3 of parameter No. 0100), CRs can be omitted so that each LF appears without a CR.

- **Stopping the punch**

Press the RESET key to stop punch operation.

- **Punching all programs**

All programs are output to paper tape in the following format.



The sequence of the programs punched is undefined.

8.5 OFFSET DATA INPUT AND OUTPUT

8.5.1 Inputting Offset Data

Offset data is loaded into the memory of the CNC from a floppy or NC tape. The input format is the same as for offset value output. See section **III–8.5.2.** When an offset value is loaded which has the same offset number as an offset number already registered in the memory, the loaded offset data replaces existing data.

Procedure for Inputting Offset Data

1 Make sure the input device is ready for reading
For the two–path control, select the tool post for which offset data to be input is used with the tool post selection switch.

2 Press the EDIT switch on the machine operator's panel.

3 When using a floppy, search for the required file according to the procedure in Section III–8.2.

4 Press function key

to display tool offset screeen.

5 Press soft keys **[(OPRT)]**, then the tool compensation screen appears.

6 Press rightmost soft key (continuous menu key).

7 Press soft keys **[READ]** and **[EXEC]**.

8 The input offset data will be displayed on the screen after completion of input operation.

8.5.2 Outputting Offset Data

All offset data is output in a output format from the memory of the CNC to a floppy or NC tape.

Procedure for Outputting Offset Data

1 Make sure the output device is ready for output.
For the two–path control, select the tool post for which offset data to be output is used with the tool post selection switch.

2 Specify the punch code system (ISO or EIA) using a parameter.

3 Press the EDIT switch on the machine operator's panel.

4 Press function key [OFFSET SETTING] to display tool offset screen.

5 Press soft key **[(OPRT)]**.

6 Press the rightmost soft key [▷] (continuous menu key)

7 Press soft keys **[PUNCH]** and **[EXEC]**.
Offset data is output in the output format described below.

Explanations

- **Output format**

Output format is as follows:

Format

G10P_X_Y_Z_R_Q_;
P: Offset number
. . . . Work sheet : P=0
. . . . For wear offset amount : P=Wear offset number
. . . . For geometry offset amount : p=10000+geometry offset number
X:Offset value on X axis
Y: Offset value on Y axis
Z:Offset value on Z axis
Q:Imaginary tool nose number
R:Tool nose radius offset value

The L1 command may be used instead of L11 for format compatibility of the conventional CNC.

- **Output file name**

When the floppy disk directory display function is used, the name of the output file is OFFSET.

8.6 INPUTTING AND OUTPUTTING PARAMETERS AND PITCH ERROR COMPENSATION DATA

Parameters and pitch error compensation data are input and output from different screens, respectively. This chapter describes how to enter them.

8.6.1 Inputting Parameters

Parameters are loaded into the memory of the CNC unit from a floppy or NC tape. The input format is the same as the output format. See Subsec. **III–8.6.2**. When a parameter is loaded which has the same data number as a parameter already registered in the memory, the loaded parameter replaces the existing parameter.

Procedure for Inputting Parameters

1 Make sure the input device is ready for reading.
For the two–path control, select the tool post for which parameters to be input are used with the tool post selection switch.

2 When using a floppy, search for the required file according to the procedure in Section **III–8.2**.

3 Press the EMERGENCY STOP button on the machine operator's panel.

4 Press function key [OFFSET SETTING] .

5 Press the soft key **[SETING]** for chapter selection, then the setting screen appears.

6 Enter 1 in response to the prompt for "PARAMETER WRITE (PWE)" in setting data. P/S alarm (No.100(indicating that parameters can be written)) appears.

7 Press soft key [SYSTEM] .

8 Press chapter selection soft key **[PARAM]**, then the parameter screen appears.

9 Press soft key **[(OPRT)]**.

10 Press the rightmost soft key [▷] (continuous menu key).

11 Press soft keys **[READ]** and **[EXEC]**.
Parameters are read into memory. Upon completion of input, the "INPUT" indicator at the lower–right corner of the screen disappears.

12 Press function key [OFFSET SETTING] .

13 Press soft key **[SETING]** for chapter selection.

14 Enter 0 in response to the prompt for “PARAMETER WRITE (PWE)” in setting data.

15 Turn the power to the NC back on.

16 Release the EMERGENCY STOP button on the machine operator’s panel.

8.6.2 Outputting Parameters

All parameters are output in the defined format from the memory of the CNC to a floppy or NC tape.

Procedure for Outputting Parameters

1 Make sure the output device is ready for output.
For the two–path control, select the tool post for which parameters to be input are used with the tool post selection switch.

2 Specify the punch code system (ISO or EIA) using a parameter.

3 Press the EDIT switch on the machine operator’s panel.

4 Press function key [SYSTEM] .

5 Press chapter selection soft key **[PARAM]** to display the parameter screen.

6 Press soft key **[(OPRT)]**.

7 Press rightmost soft key [▷] (continuous menu key).

8 Press soft key **[PUNCH]**.

9 To output all parameters, press the **[ALL]** soft key. To output only parameters which are set to other than 0, press the **[NON–0]** soft key.

10 Press soft key **[EXEC]**.
All parameters are output in the defined format.

Explanations

- **Output format**

Output format is as follows:
N . P . . ;
N . A1P . . . A2P . . . AnP . . . ;
N . P . . ;

N:Parameter No.
A:Axis No.(n is the number of control axis)
P:Parameter setting value .

- **Suppressing output of parameters set to 0**

To suppress the output of the following parameters, press the **[PUNCH]** soft key then **[NON–0]** soft key.

	Other than axis type	Axis type
Bit type	Parameter for which all bits are set to 0	Parameter for an axis for which all bits are set to 0.
Value type	Paramter whose value is 0.	Parameter for an axis for which the value is 0.

- **Output file name**

When the floppy disk directory display function is used, the name of the output file is PARAMETER.

Once all parameters have been output, the output file is named ALL PARAMETER. Once only parameters which are set to other than 0 have been output, the output file is named NON–0. PARAMETER.

8.6.3 Inputting Pitch Error Compensation Data

Pitch error compensation data are loaded into the memory of the CNC from a floppy or NC tape. The input format is the same as the output format. See Section **8.6.4.** When a pitch error compensation data is loaded which has the corresponding data number as a pitch error compensation data already registered in the memory, the loaded data replaces the existing data.

Procedure for Pitch Error Compensation Data

1 Make sure the input device is ready for reading.
For the two–path control, select the tool post for which pitch error compensation data to be input is used with the tool post selection switch.

2 When using a floppy, search for the required file according to the procedure in Section **III–8.2**.

3 Press the EMERGENCY STOP button on the machine operator's panel.

4 Press function key [OFFSET SETTING] .

5 Press the soft key **[SETING]** for chapter selection.

6 Enter 1 in response to the prompt for "PARAMETER WRITE (PWE)" in setting data. P/S alarm (No. 100 (indicating that parameters can be written)) appears.

7 Press soft key [SYSTEM] .

8 Press the rightmost soft key [▷] (continuous menu key)and press chapter selection soft key **[PITCH]**.

9 Press soft key **[(OPRT)]**.

10 Press the rightmost soft key [▷] (continuous menu key).

11 Press soft keys **[READ]** and **[EXEC]**.
Pitch error compensation data are read into memory. Upon completion of input, the "INPUT" indicator at the lower–right corner of the screen disappears.

12 Press function key [OFFSET SETTING] .

13 Press soft key **[SETING]** for chapter selection.

14 Enter 0 in response to the prompt for “PARAMETER WRITE (PWE)” of setting data.

15 Turn the power to the NC back on.

16 Release the EMERGENCY STOP button on the machine operator’s panel.

Explanations

- **Pitch error compensation**

Parameters 3620 to 3624 and pitch error compensation data must be set correctly to apply pitch error compensation correctly
(See subsec. **III–11.5.2**)

8.6.4 Outputting Pitch Error Compensation Data

All pitch error compensation data are output in the defined format from the memory of the CNC to a floppy or NC tape.

Procedure for Outputting Pitch Error Compensation Data

1 Make sure the output device is ready for output.
For the two–path control, select the tool post for which pitch error compensation data to be output is used with the tool post selection switch.

2 Specify the punch code system (ISO or EIA) using a parameter.

3 Press the EDIT switch on the machine operator’s panel.

4 Press function key [SYSTEM] .

5 Press the rightmost soft key [▷] (continuous menu key) and press chapter selection soft key **[PITCH]**.

6 Press soft key **[(OPRT)]**.

7 Press rightmost soft key [▷] (continuous menu key).

8 Press soft keys **[PUNCH]** and **[EXEC]**.
All pitch error compensation data are output in the defined format.

Explanations

- **Output format**

Output format is as follows:
N 10000 P ;
N 11023 P ;
N:Pitch error compensation point No. +10000
P:Pitch error compensation data

- **Output file name**

When the floppy disk directory display function is used, the name of the output file is “**PITCH ERROR**”.

8.7 INPUTTING/ OUTPUTTING CUSTOM MACRO COMMON VARIABLES

8.7.1 Inputting Custom Macro Common Variables

The value of a custom macro common variable (#500 to #999) is loaded into the memory of the CNC from a floppy or NC tape. The same format used to output custom macro common variables is used for input. See Subsec. **8.7.2.** For a custom macro common variable to be valid, the input data must be executed by pressing the cycle start button after data is input. When the value of a common variable is loaded into memory, this value replaces the value of the same common variable already existing (if any) in memory.

Procedure for Inputting Custom Macro Common Variables

1 Register the program which has been output, as described in Section III–8.7.2, in memory according to the program input procedure described in Section III–8.4.1.

2 Press the MEMORY switch on the machine operator's panel upon completing input.

3 Press the cycle start button to execute the loaded program.

4 Display the macro variable screen to check whether the values of the common variables have been set correctly.

Display of the macro variable screen

· Press function key [OFFSET SETTING] .
· Press the rightmost soft key (continuous menu key).
· Press soft key **[MACRO]**.
· Select a variable with the page keys or numeric keys and soft key **[NO.SRH]**.

Explanations

- **Common variables**

The common variables (#500 to #531) can be input and output.
When the option for adding a common variable is specified, values from #500 to #999 can be input and output.
#100 to #199 can be input and output when bit 3 (PU5) of parameter No. 6001 is set to 1.

8.7.2 Outputting Custom Macro Common Variable

Custom macro common variables (#500 to #999) stored in the memory of the CNC can be output in the defined format to a floppy or NC tape.

Procedure for Outputting Custom Macro Common Variable

1 Make sure the output device is ready for output.

2 Specify the punch code system (ISO or EIA) using a parameter.

3 Press the EDIT switch on the machine operator's panel.

4 Press function key [OFFSET SETTING].

5 Press the rightmost soft key [▷] (continuous menu key), then press soft key **[MACRO]**.

6 Press soft key **[(OPRT)]**.

7 Press the rightmost soft key [▷] (continuous menu key).

8 Press soft keys **[PUNCH]** and **[EXEC]**.
Common variables are output in the defined format.

Explanations

- **Output format**

The output format is as follows:

```
%
;
#500=[25283*65536+65536]/134217728 ..... (1)
#501=#0; ..... (2)
#502=0; ..... (3)
#503= ..... ;
..... ;
..... ;
#531= ..... ;
M02;
%
```

(1) The precision of a variable is maintained by outputting the value of the variable as <expression>.

(2) Undefined variable

(3) When the value of a variable is 0

- **Output file name**

When the floppy disk directory display function is used, the name of the output file is **"MACRO VAR"**.

- **Common variable**

The common variables (#500 to #531) can be input and output.
When the option for adding a common variable is specified, values from #500 to #999 can be input and output.
#100 to #199 can be input and output when bit 3 (PU5) of parameter No. 6001 is set to 1.

8.8 DISPLAYING DIRECTORY OF FLOPPY DISK

On the floppy directory display screen, a directory of the FANUC Handy File, FANUC Floppy Cassette, or FANUC FA Card files can be displayed. In addition, those files can be loaded, output, and deleted.



8.8.1 Displaying the Directory

Displaying the Directory of Floppy Disk Files

Procedure 1

Use the following procedure to display a directory of all the files stored in a floppy:

1 Press the EDIT switch on the machine operator's panel.

2 Press function key [PROG] .

3 Press the rightmost soft key [▷] (continuous menu key).

4 Press soft key **[FROPPY]**.

5 Press page key [PAGE ↑] or [PAGE ↓].

6 The screen below appears.



Fig.8.8.1 (a)

7 Press a page key again to display another page of the directory.

Procedure 2

Use the following procedure to display a directory of files starting with a specified file number :

1 Press the EDIT switch on the machine operator's panel.

2 Press function key PROG .

3 Press the rightmost soft key ▷ (continuous menu key).

4 Press soft key **[FLOPPY]**.

5 Press soft key **[(OPRT)]**.

6 Press soft key **[F SRH]**.

7 Enter a file number.

8 Press soft keys **[F SET]** and **[EXEC]**.

9 Press a page key to display another page of the directory.

10 Press soft key **[CAN]** to return to the soft key display shown in the screen of **Fig. 8.8.1(b).**



Fig.8.8.1 (b)

Explanations

- **Screen fields and their meanings**

NO :Displays the file number
FILE NAME :Displays the file name.
(METER) :Converts and prints out the file capacity to paper tape length. You can also produce H (FEET)I by setting the INPUT UNIT to INCH of the setting data.
VOL. :When the file is multi–volume, that state is displayed.



8.8.2 Reading Files

The contents of the specified file number are read to the memory of NC.

Procedure for Reading Files

1 Press the EDIT switch on the machine operator's panel.
For the two–path control, select the tool post for which a file is to be input in memory with the tool post selection switch.

2 Press function key [PROG] .

3 Press the rightmost soft key [▷] (continuous menu key).

4 Press soft key **[FLOPPY]**.

5 Press soft key **[(OPRT)]**.

6 Press soft key **[READ]**.



7 Enter a file number.

8 Press soft key **[F SET]**.

9 To modify the program number, enter the program number, then press soft key **[O SET]**.

10 Press soft key **[EXEC]**. The file number indicated in the lower–left corner of the screen is automatically incremented by one.

11 Press soft key **[CAN]** to return to the soft key display shown in the screen of **Fig. 8.8.1.(b)**.

8.8.3 Outputting Programs

Any program in the memory of the CNC unit can be output to a floppy as a file.

Procedure for Outputting Programs

1 Press the EDIT switch on the machine operator's panel.

2 Press function key [PROG] .

3 Press the rightmost soft key [▷] (continuous menu key).

4 Press soft key **[FLOPPY]**.

5 Press soft key **[(OPRT)]**.

6 Press soft key **[PUNCH]**

```
DIRECTORY (FLOPPY)                    O0002  N01000
  NO. FILE NAME                       (METER) VOL
  0001  PARAMETER                        58.5
  0002  O0001                             1.9
  0003  O0002                             1.9
  0004  O0010                             1.3
  0005  O0040                             1.3
  0006  O0050                             1.9
  0007  O0100                             1.9
  0008  O1000                             1.9
  0009  O9500                             2.6
PUNCH
 FILE NO. =                     PROGRAM NO. =
>_
EDIT  ****  ***  ***            11 : 55 : 26
[F SET ][ O SET ][ STOP ][ CAN ][ EXEC ]
```

7 Enter a program number. To write all programs into a single file, enter –9999 in the program number field. In this case, the file name **"ALL.PROGRAM**" is registered.

8 Press soft key **[O SET]**.

9 Press soft key **[EXEC]**. The program or programs specified in step **7** are written after the last file on the floppy. To output the program after deleting files starting with an existing file number, key in the file number, then press soft key **[F SET]** followed by soft key **[EXEC]**.

10 Press soft key **[CAN]** to return to the soft key display shown in the screen of **Fig.8.8.1(b)**.

8.8.4 Deleting Files

The file with the specified file number is deleted.

Procedure for Deleting Files

1 Press the EDIT switch on the machine operator's panel.

2 Press function key [PROG] .

3 Press the rightmost soft key [▷] (continuous menu key).

4 Press soft key **[FLOPPY]**.

5 Press soft key **[(OPRT)]**.

6 Press soft key **[DELETE]**.



7 Specify the file to be deleted.
When specifying the file with a file number, type the number and press soft key **[F SET]**.When specifying the file with a file name, type the name and press soft key **[F NAME]**.

8 Press soft key **[EXEC]**.
The file specified in the file number field is deleted. When a file is deleted, the file numbers after the deleted file are each decremented by one.

9 Press soft key **[CAN]** to return to the soft key display shown in the screen of **Fig. 8.8.1(b)**.

Limitations

- **Inputting file numbers and program numbers with keys**

If **[F SET]** or **[O SET]** is pressed without key inputting file number and program number, file number or program number shows blank. When 0 is entered for file numbers or program numbers, 1 is displayed.

- **I/O devices**

To use channel 0 ,set a device number in parameter 102.
Set the I/O device number to parameter No. 0112 when channel 1 is used.
Set it to No. 0122 when channel 2 is used.

- **Significant digits**

For the numeral input in the data input area with FILE NO. and PROGRAM NO., only lower 4 digits become valid.

- **Collation**

When the data protection key on the machine operator's panel is ON, no programs are read from the floppy. They are verified against the contents of the memory of the CNC instead.

ALARM

No.	Contents
71	An invalid file number or program number was entered. (Specified program number is not found.)
79	Verification operation found a mismatch between a program loaded into memory and the contents of the floppy
86	The datas et–ready signal (DR) for the input/output device is turned off. (The no file error or duplicate file error occurred on the input/output device because an invalid file number, program number, or file name was entered.

8.9 OUTPUTTING A PROGRAM LIST FOR A SPECIFIED GROUP

CNC programs stored in memory can be grouped according to their names, thus enabling the output of CNC programs in group units. Section III–11.3.3 explains the display of a program listing for a specified group.

Procedure for Outputting a Program List for a Specified Group

Procedure

1 Display the program list screen for a group of programs, as described in Section III–11.3.3.

```
PROGRAM DIRECTORY (GROUP)          O0001  N00010

        PROGRAM (NUM.)        MEMORY (CHAR.)
        USED:          60                3321
        FREE:           2                 429
  O0020  (GEAR–1000  MAIN     )
  O0040  (GEAR–1000  SUB–1    )
  O0200  (GEAR–1000  SUB–2    )
  O2000  (GEAR–1000  SUB–3    )

 >_
 EDIT  ****  ***  ***  ***      16 : 52 : 13
(PRGRM)( DIR )(      )(      )(  (OPRT) )
```



2 Press the **[(OPRT)]** operation soft key.

3 Press the right–most soft key ▷ (continuous menu key).

4 Press the **[PUNCH]** operation soft key.

5 Press the **[AL–GRP]** operation soft key.

The CNC programs in the group for which a search is made are output. When these programs are output to a floppy disk, they are output to a file named GROUP.PROGRAM.

8.10 DATA INPUT/OUTPUT ON THE ALL IO SCREEN

To input/output a particular type of data, the corresponding screen is usually selected. For example, the parameter screen is used for parameter input from or output to an external input/output unit, while the program screen is used for program input or output. However, programs, parameters, offset data, and macro variables can all be input and output using a single common screen, that is, the ALL IO screen.



Fig. 8.10 ALL IO screen (when channel 3 is being used for input/output)

8.10.1 Setting Input/Output–Related Parameters

Input/output–related parameters can be set on the ALL IO screen. Parameters can be set, regardless of the mode.

Setting input/output–related parameters

Procedure

1 Press function key [SYSTEM] .

2 Press the rightmost soft key [▷] (continuous menu key) several times.

3 Press soft key **[ALL IO]** to display the ALL IO screen.

NOTE
1 If program or floppy is selected in EDIT mode, the program directory or floppy screen is displayed.
2 When the power is first turned on, program is selected by default.



NOTE
Baud rate clock, CD check (232C), reset/alarm report, and the parity bit for parameter No. 134, as well as the communication code, end code, communication protocol, interface, and SAT command for parameter No. 135 are displayed only when channel 3 is being used for input/output.

4 Select the soft key corresponding to the desired type of data (program, parameter, and so forth).

5 Set the parameters corresponding to the type of input/output unit to be used. (Parameter setting is possible regardless of the mode.)

8.10.2 Inputting and Outputting Programs

A program can be input and output using the ALL IO screen.
When entering a program using a cassette or card, the user must specify the input file containing the program (file search).

File search

Procedure

1 Press soft key **[PRGRM]** on the ALL IO screen, described in Section 8.10.1.

2 Select EDIT mode. A program directory is displayed.

3 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.

- A program directory is displayed only in EDIT mode. In all other modes, the ALL IO screen is displayed.



4 Enter address N.

5 Enter the number of the file to be found.

- N0
  The first floppy file is found.
- One of N1 to N9999
  Among the files numbered from 1 to 9999, a specified file is found.
- N–9999
  The file immediately after that used most recently is found.
- N–9998
  When –9998 is specified, the next file is found. Then, each time a file input/output operation is performed, N–9999 is automatically inserted. This means that subsequent files can be sequentially found automatically.
  This state is canceled by specifying N0, N1 to N9999, or N–9999, or upon a reset.

6 Press soft keys **[F SRH]** and **[EXEC]**.
The specified file is found.



Explanations

- **Difference between N0 and N1**

When a file already exists in a cassette or card, specifying N0 or N1 has the same effect. If N1 is specified when there is no file on the cassette or card, an alarm is issued because the first file cannot be found. Specifying N0 places the head at the start of the cassette or card, regardless of whether the cassette/card already contains files. So, no alarm is issued in this case. N0 can be used, for example, when a program is written into a new cassette or card, or when a previously used cassette or card is used once all the files it contains have been erased.

- **Alarm issue during file search**

If an alarm (file search failure, for example) is generated during file search, the CNC does not issue an alarm immediately. However, a P/S alarm (No. 086) is issued if input/output is subsequently performed on that file.

- **File search using N–9999**

Instead of sequentially searching for files by specifying actual file numbers every time, the user can specify the first file number, then find the subsequent files by specifying N–9999. When N–9999 is specified, the time required for file search can be reduced.

Inputting a program

Procedure

1 Press soft key **[PRGRM]** on the ALL IO screen, described in Section 8.10.1.

2 Select EDIT mode. A program directory is displayed.

3 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.

- A program directory is displayed only in EDIT mode. In all other modes, the ALL IO screen is displayed.



4 To specify a program number to be assigned to an input program, enter address O, followed by the desired program number.
If no program number is specified, the program number in the file or on the NC tape is assigned as is.

〔 〕〔 〕〔STOP〕〔 CAN 〕〔 EXEC〕

5 Press soft key **[READ]**, then **[EXEC]**.
The program is input with the program number specified in step 4 assigned.
To cancel input, press soft key **[CAN]**.
To stop input prior to its completion, press soft key **[STOP]**.

Outputting a program

Procedure

1 Press soft key **[PRGRM]** on the ALL IO screen, described in Section 8.10.1.

2 Select EDIT mode. A program directory is displayed.

3 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.

- A program directory is displayed only in EDIT mode. In all other modes, the ALL IO screen is displayed.



4 Enter address O.

5 Enter a desired program number.
If –9999 is entered, all programs in memory are output.
To output a range of programs, enter O△△△△, O□□□□. The programs numbered from △△△△ to □□□□ are output.
When bit 4 (SOR) of parameter No. 3107 for sorted display is set to 1 on the program library screen, programs are output in order, starting from those having the smallest program numbers.

〔 〕〔 〕〔STOP〕〔 CAN 〕〔 EXEC〕

6 Press soft key **[PUNCH]**, then **[EXEC]**.
The specified program or programs are output. If steps 4 and 5 are omitted, the currently selected program is output.
To cancel output, press soft key **[CAN]**.
To stop output prior to its completion, press soft key **[STOP]**.

Deleting files

Procedure

1 Press soft key **[PRGRM]** on the ALL IO screen, described in Section 8.10.1.

2 Select EDIT mode. A program directory is displayed.

3 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.

- A program directory is displayed only in EDIT mode. In all other modes, the ALL IO screen is displayed.



4 Press soft key **[DELETE]**.

5 Enter a file number, from 1 to 9999, to indicate the file to be deleted.

6 Press soft key **[EXEC]**.
The k–th file, specified in step 5, is deleted.



Explanations

- **File numbers after deletion**

After deletion of the k–th file, the previous file numbers (k+1) to n are decremented by 1 to k to (n–1).

Before deletion	After deletion
1 to (k–1)	1 to (k–1)
k	Deleted
(k+1) to n	k to (n–1)

- **Write protect**

Before a file can be deleted, the write protect switch of the cassette must be set to make the cassette writable.

8.10.3 Inputting and Outputting Parameters

Parameters can be input and output using the ALL IO screen.

Inputting parameters

Procedure

1 Press soft key **[PARAM]** on the ALL IO screen, described in Section 8.10.1.

2 Select EDIT mode.

3 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.





4 Press soft key **[READ]**, then **[EXEC]**.
The parameters are read, and the “INPUT” indicator blinks at the lower–right corner of the screen. Upon the completion of input, the “INPUT” indicator is cleared from the screen.
To cancel input, press soft key **[CAN]**.

Outputting parameters

Procedure

1 Press soft key **[PARAM]** on the ALL IO screen, described in Section 8.10.1.

2 Select EDIT mode.

3 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.





4 Press soft key **[PUNCH]**, then **[EXEC]**.
The parameters are output, and the “OUTPUT” indicator blinks at the lower–right corner of the screen. Upon the completion of output, the “OUTPUT” indicator is cleared from the screen.
To cancel output, press soft key **[CAN]**.

8.10.4 Inputting and Outputting Offset Data

Offset data can be input and output using the ALL IO screen.

Inputting offset data

Procedure

1 Press soft key **[OFFSET]** on the ALL IO screen, described in Section 8.10.1.

2 Select EDIT mode.

3 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.





4 Press soft key **[READ]**, then **[EXEC]**.
The offset data is read, and the “INPUT” indicator blinks at the lower–right corner of the screen.
Upon the completion of input, the “INPUT” indicator is cleared from the screen.
To cancel input, press soft key **[CAN]**.

Outputting offset data

Procedure

1 Press soft key **[OFFSET]** on the ALL IO screen, described in Section 8.10.1.

2 Select EDIT mode.

3 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.





4 Press soft key **[PUNCH]**, then **[EXEC]**.
The offset data is output, and the “OUTPUT” indicator blinks at the lower–right corner of the screen. Upon the completion of output, the “OUTPUT” indicator is cleared from the screen.
To cancel output, press soft key **[CAN]**.

8.10.5 Outputting Custom Macro Common Variables

Custom macro common variables can be output using the ALL IO screen.

Outputting custom macro common variables

Procedure

1 Press soft key **[MACRO]** on the ALL IO screen, described in Section 8.10.1.

2 Select EDIT mode.

3 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.





4 Press soft key **[PUNCH]**, then **[EXEC]**.
The custom macro common variables are output, and the “OUTPUT” indicator blinks at the lower–right corner of the screen. Upon the completion of output, the “OUTPUT” indicator is cleared from the screen.
To cancel output, press soft key **[CAN]**.

NOTE
To input a macro variable, read the desired custom macro statement as a program, then execute the program.

8.10.6 Inputting and Outputting Floppy Files

The ALL IO screen supports the display of a directory of floppy files, as well as the input and output of floppy files.

Displaying a file directory

Procedure

1 Press the rightmost soft key [▷] (continuous menu key) on the ALL IO screen, described in Section 8.10.1.

2 Press soft key **[FLOPPY]**.

3 Select EDIT mode. The floppy screen is displayed.

4 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.
The floppy screen is displayed only in EDIT mode. In all other modes, the ALL IO screen is displayed.



5 Press soft key **[F SRH]**.



6 Enter the number of the desired file, then press soft key **[F SET]**.

7 Press soft key **[EXEC]**. A directory is displayed, with the specified file uppermost. Subsequent files in the directory can be displayed by pressing the page key.



A directory in which the first file is uppermost can be displayed simply by pressing the page key. (Soft key **[F SRH]** need not be pressed.)

Inputting a file

Procedure

1 Press the rightmost soft key ▷ (continuous menu key) on the ALL IO screen, described in Section 8.10.1.

2 Press soft key **[FLOPPY]**.

3 Select EDIT mode. The floppy screen is displayed.

4 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.
The floppy screen is displayed only in EDIT mode. In all other modes, the ALL IO screen is displayed.



5 Press soft key **[READ]**.

6 Enter the number of a file or program to be input.

- Setting a file number: Enter the number of the desired file, then press soft key **[F SET]**.
- Setting a program number: Enter the number of the desired program, then press soft key **[O SET]**.

7 Press soft key **[EXEC]**.
The specified file or program is read, and the “INPUT” indicator blinks at the lower–right corner of the screen. Upon the completion of input, the “INPUT” indicator is cleared from the screen.

Outputting a file

Procedure

1 Press the rightmost soft key [▷] (continuous menu key) on the ALL IO screen, described in Section 8.10.1.

2 Press soft key **[FLOPPY]**.

3 Select EDIT mode. The floppy screen is displayed.

4 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.
The floppy screen is displayed only in EDIT mode. In all other modes, the ALL IO screen is displayed.



5 Press soft key **[PUNCH]**.



6 Enter the number of the program to be output, together with a desired output file number.

- Setting a file number: Enter the number of the desired file, then press soft key **[F SET]**.
- Setting a program number: Enter the number of the desired program, then press soft key **[O SET]**.

7 Press soft key **[EXEC]**.
The specified program is output, and the “OUTPUT” indicator blinks at the lower–right corner of the screen. Upon the completion of output, the “OUTPUT” indicator is cleared from the screen.
If no file number is specified, the program is written at the end of the currently registered files.

Deleting a file

Procedure

1 Press the rightmost soft key [▷] (continuous menu key) on the ALL IO screen, described in Section 8.10.1.

2 Press soft key **[FLOPPY]**.

3 Select EDIT mode. The floppy screen is displayed.

4 Press soft key **[(OPRT)]**. The screen and soft keys change as shown below.
The floppy screen is displayed only in EDIT mode. In all other modes, the ALL IO screen is displayed.



5 Press soft key **[DELETE]**.



6 Enter the number of the desired file, then press soft key **[F SET]**.

7 Press soft key **[EXEC]**. The specified file is deleted. After the file has been deleted, the subsequent files are shifted up.

8.10.7 Memory Card Input/Output

Data held in CNC memory can be saved to a memory card in MS–DOS format. Data held on a memory card can be loaded into CNC memory. A save or load operation can be performed using soft keys while the CNC is operating.
Loading can be performed in either of two ways. In the first method, all saved memory data is loaded. In the second method, only selected data is loaded.



- The CNC memory size (*1) is displayed at all times.
- When no memory card is inserted, the message field (*4) displays a message prompting the user to insert a memory card, but does not display the memory card states (*2 and *3).
- If an inserted memory card is invalid (if there is no attribute memory, or if the attribute memory does not contain any device information), the message field (*4) displays an error message, but does not display the memory card states (*2 and *3).

Saving memory data

Data held in CNC memory can be saved to a memory card in MS–DOS format.

Saving memory data

Procedure

1 Press the rightmost soft key [▷] (continuous menu key) on the ALL IO screen, described in Section 8.10.1.

2 Press soft key **[M–CARD]**.

3 Place the CNC in the emergency stop state.

4 When a memory card is inserted, the state of the memory card is displayed as shown below.



5 Press soft key **[SAVE]**.

[ ] [ ] [ ] [CAN] [EXEC]

6 A message prompting the user to confirm the operation is displayed. Press soft key **[EXEC]** to execute the save operation.

7 As the data is being saved to the card, the message “RUNNING” blinks, and the number of bytes saved is displayed in the message field.

8 Once all data has been saved to the card, the message “COMPLETED” is displayed in the message field, with the message “PRESS RESET KEY.” displayed on the second line.

9 Press the RESET key. The displayed messages are cleared from the screen, and the display of the memory card state is replaced with that of the saved file.

NOTE
All CNC memory data is saved to a memory card. CNC memory data cannot be saved selectively.

Explanations

- **File name**

The file name used for save operation is determined by the amount of SRAM mounted in the CNC. A file holding saved data is divided into blocks of 512KB.

HEAD1 SRAM file

Amount of SRAM		256 KB	0.5 MB
Number of files	1	SRAM256A. FDB	SRAM0_5A. FDB

- **Canceling saving**

To cancel file save prior to its completion, press the RESET key on the MDI panel.

- **Memory card replacement request**

When the memory card has less than 512K bytes of free space, a memory card replacement request is displayed. Insert a new memory card.

Loading data into memory (restoration)

CNC memory data that has been saved to a memory card can be loaded (restored) back into CNC memory.
CNC memory data can be loaded in either of two ways. In the first method, all saved memory data is loaded. In the second method, only selected data is loaded.

Loading memory data

Procedure

1 Press the rightmost soft key ▷ (continuous menu key) on the ALL IO screen, described in Section 8.10.1.

2 Press soft key **[M–CARD]**.

3 Place the CNC in the emergency stop state.

4 When a memory card is inserted, the state of the memory card is displayed as shown below.



5 Press soft key **[LOAD]**.

6 With cursor keys ↑ and ↓, select the file to be loaded from the memory card.
A system having 1.0MB or 2.5MB of CNC RAM may require the loading of multiple files. All or selective data load can be specified for each file.

〔SELECT〕〔 〕〔 〕〔CAN〕〔EXEC〕

7 To perform selective data loading, press soft key **[SELECT]**, then select the data to be loaded. Each time the soft key is pressed, the information displayed changes cyclically, as shown below.



8 After checking the file selection, press soft key **[EXEC]**.

9 During loading, the message “RUNNING” blinks, and the number of bytes loaded is displayed in the message field.

10 Upon the completion of loading, the message “COMPLETED” is displayed in the message field, with the message “PRESS RESET KEY.” displayed on the second line.

11 Press the RESET key. The messages are cleared from the screen.

Explanations

- **Canceling loading**

To cancel file load prior to its completion, press the RESET key on the MDI panel.

- **Turning off the power after loading**

Depending on the type of data, the system power may have to be turned off, then back on, for the load to become effective. When necessary, the message “TURN OFF POWER.” is displayed in the message field.

- **Parameter/PMC data**

Before performing parameter/PMC data load, enable parameter write.

- **Program/offset data**

Before performing program/offset data load, set the data protection key, on the machine operator’s panel, to the ON position.

- **Loading files from multiple memory cards**

When multiple files are to be loaded from multiple memory cards, a message requesting memory card replacement is displayed.

NOTE

If the saved data and CNC system onto which the saved data is to be loaded do not satisfy the conditions described below, an error message is displayed in the message field, and loading is disabled. Note, however, that in selective loading, even if the CNC system structure differs from that of a saved file, the file is never the less loaded.

- The size of a saved file does not match the size of CNC RAM.
- The saved file has a different extension.

Memory card formatting

Before a file can be saved to a memory card, the memory card must be formatted.

Formatting a memory card

Procedure

1 Press the rightmost soft key ▷ (continuous menu key) on the ALL IO screen, described in Section 8.10.1.

2 Press soft key **[M–CARD]**.

3 Place the CNC in the emergency stop state.

4 When a memory card is inserted, the state of the memory card is displayed as shown below.



5 Press soft key **[FORMAT]**.



6 A message prompting the user to confirm the operation is displayed. Press soft key **[EXEC]** to execute the formatting operation.

7 As formatting is being performed, the message “FORMATTING” blinks.

8 Upon the completion of formatting, the message “COMPLETED” is displayed in the message field.

Deleting files

Unnecessary saved files can be deleted from a memory card.

Deleting files

Procedure

1 Press the rightmost soft key ▷ (continuous menu key) on the ALL IO screen, described in Section 8.10.1.

2 Press soft key **[M–CARD]**.

3 Place the CNC in the emergency stop state.

4 When a memory card is inserted, the state of the memory card is displayed as shown below.



5 Press soft key **[DELETE].**

6 With cursor keys ↑ and ↓, select the file to be deleted from the memory card.

( ) ( ) ( ) (CAN) (EXEC)

7 After checking the file selection, press soft key **[EXEC]**.

8 As detection is being performed, the message “DELETING” blinks in the message field.

9 Upon the completion of deletion, the message “COMPLETED” is displayed in the message field.

NOTE
An SRAM of 1M bytes or more will contain multiple files. To delete the contents of such an SRAM, delete all the contained files.

Message and restrictions

Messages

Message	Description
INSERT MEMORY CARD.	No memory card is inserted.
UNUSABLE MEMORY CARD	The memory card does not contain device information.
FORMAT MEMORY CARD.	The memory card is not formatted. Format the memory card before use.
THE FILE IS UNUSABLE.	The format or extension of the file to be loaded is invalid. Alternatively, the data stored on the memory card does not match the CNC memory size.
REPLACE MEMORY CARD.	Replace the memory card.
FILE SYSTEM ERROR □□□	An error occurred during file system processing. □□□ represents a file system error code.
SET EMERGENCY STOP STATE.	Save/load operation is enabled in the emergency stop state only.
WRITE–PROTECTED	Save operation: The protect switch of the memory card is set to the disabled position. Load operation: Parameter write is disabled.
VOLTAGE DECREASED.	The battery voltage of the memory card has dropped. (The battery requires replacement.)
DEVICE IS BUSY.	Another user is using the memory card. Alternatively, the device cannot be accessed because automatic operation is in progress.
SRAM → MEMORY CARD?	This message prompts the user to confirm the start of data saving.
MEMORY CARD → SRAM?	This message prompts the user to confirm the start of data loading.
DO YOU WANT TO DELETE FILE(S)?	This message prompts the user to confirm the start of deletion.
DO YOU WANT TO PERFORM FORMATTING?	This message prompts the user to confirm the start of formatting.
SAVING	Saving is currently being performed.
LOADING	Loading is currently being performed.
DELETING	File deletion is currently being performed.
FORMATTING	Memory card formatting is currently being performed.
COMPLETED	Save or load processing has been completed.
PRESS RESET KEY.	Press the RESET key.
TURN OFF POWER.	Turn the power off, then back on again.

File system error codes

Code	Meaning
102	The memory card does not have sufficient free space.
105	No memory card is mounted.
106	A memory card is already mounted.
110	The specified directory cannot be found.
111	There are too many files under the root directory to allow a directory to be added.
114	The specified file cannot be found.
115	The specified file is protected.
117	The file has not yet been opened.
118	The file is already open.
119	The file is locked.
122	The specified file name is invalid.
124	The extension of the specified file is invalid.
129	A non–corresponding function was specified.
130	The specification of a device is invalid.
131	The specification of a pathname is invalid.
133	Multiple files are open at the same time.
135	The device is not formatted.
140	The file has the read/write disabled attribute.

Restrictions

- **Memory card size**

  The size of the memory card to be used must be larger than that of the RAM module mounted in the CNC. The size of the RAM module can be determined from the system configuration screen.

- **Memory card specifications**

  Use a memory card that conforms to PCMCIA Ver. 2.0, or JEIDA Ver. 4.1.

- **Attribute memory**

  A memory card which has no attribute memory, or no device information in its attribute memory, cannot be used.

- **Compatibility of saved data**

  Data saved to a memory card is compatible only with CNCs that have the same hardware configuration and the same option configuration.

- **Flash ROM card**

  A flash ROM card can be used only for data loading.

- **Operation during automatic operation**

  During automatic operation, the contents of a memory card cannot be displayed, formatted, or deleted. To enable these operations, therefore, stop or suspend automatic operation.

8.11 DATA INPUT/OUTPUT USING A MEMORY CARD

By setting the I/O channel (parameter No. 20) to 4, files on a memory card can be referenced, and different types of data such as part programs, parameters, and offset data on a memory card can be input and output in text file format.
The major functions are listed below.

- Displaying a directory of stored files
  The files stored on a memory card can be displayed on the directory screen.
- Searching for a file
  A search is made for a file on a memory card and, if found, it is displayed on the directory screen.
- Reading a file
  Text–format files can be read from a memory card.
- Writing a file
  Data such as part programs can be stored to a memory card in text file format.
- Deleting a file
  A file can be selected and deleted from a memory card.



Displaying a directory of stored files

Procedure

1 Press the EDIT switch on the machine operator's panel.

2 Press function key [PROG] .

3 Press the rightmost soft key [▷] (continuous menu key).

4 Press soft key **[CARD]**. The screen shown below is displayed. Using page keys [↑] and [↓], the screen can be scrolled.



5 Comments relating to each file can be displayed by pressing soft key **[DIR+]**.



6 Repeatedly pressing soft key **[DIR+]** toggles the screen between the display of comments and the display of sizes and dates.
Any comment described after the O number in the file is displayed. Up to 18 characters can be displayed on the screen.

Searching for a file

Procedure

1 Press the EDIT switch on the machine operator's panel.

2 Press function key [PROG] .

3 Press the rightmost soft key [▷] (continuous menu key).

4 Press soft key **[CARD]**. The screen shown below is displayed.

```
DIRECTORY (M–CARD)                    O0034 N00045
  No.    FILE NAME        SIZE          DATE
 0001    O1000          123456        96/07/10
 0002    O1001            8458        96/07/30
 0003    O0002            3250        96/07/30
 0004    O2000           73456        96/07/31
 0005    O2001            3444        96/07/31
 0006    O3001            8483        96/08/02
 0007    O3300             406        96/08/05
 0008    O3400            2420        96/07/31
 0009    O3500            7460        96/07/31
~
[ PROG ][      ][ DIR + ][      ][ (OPRT) ]                ~
```

5 Press soft key **[(OPRT)]**.

[F SRH][F READ][N READ][PUNCH][DELETE]

6 Set the number of the desired file number with soft key **[F SRH]**. Then, start the search by pressing soft key **[EXEC]**. If found, the file is displayed at the top of the directory screen.

When a search is made for file number 19

```
DIRECTORY (M–CARD)                    O0034 N00045
  No.    FILE NAME          COMMENT
 0019    O1000          (MAIN PROGRAM)
 0020    O1010          (SUBPROGRAM–1)
 0021    O1020          (COMMENT      )
 0022    O1030          (COMMENT      )
~                                                    ~
```

Reading a file

Procedure

1 Press the EDIT switch on the machine operator's panel.

2 Press function key [PROG].

3 Press the rightmost soft key [▷] (continuous menu key).

4 Press soft key **[CARD]**. Then, the screen shown below is displayed.

```
DIRECTORY (M–CARD)                    O0034 N00045
  No.    FILE NAME        SIZE          DATE
 0001    O1000           123456        96/07/10
 0002    O1001             8458        96/07/30
 0003    O0002             3250        96/07/30
 0004    O2000            73456        96/07/31
 0005    O2001             3444        96/07/31
 0006    O3001             8483        96/08/02
 0007    O3300              406        96/08/05
 0008    O3400             2420        96/07/31
 0009    O3500             7460        96/07/31
~
[ PROG ][      ][ DIR  + ][      ][ (OPRT) ]                ~
```

5 Press soft key **[(OPRT)]**.

[F SRH][F READ][N READ][PUNCH][DELETE]

6 To specify a file number, press soft key **[F READ]**. The screen shown below is displayed.

```
DIRECTORY (M–CARD)                    O0001 N00010
  No.    FILE NAME                    COMMENT
 0019    O1000                 (MAIN  PROGRAM)
 0020    O1010                 (SUBPROGRAM–1)
 0021    O1030                 (COMMENT       )
~                                                  ~
 READ
         FILE NAME=20          PROGRAM No.=120
 >
 EDIT  ***  ****  ***  ****                15:40:21
[F NAME][ O SET ][ STOP ][ CAN ][ EXEC ]
```

7 Enter file number 20 from the MDI panel, then set the file number by pressing soft key **[F SET]**. Next, enter program number 120, then set the program number by pressing soft key **[O SET]**. Then, press soft key **[EXEC]**.

- File number 20 is registered as O0120 in the CNC.
- Set a program number to register a read file with a separate O number. If no program number is set, the O number in the file name column is registered.

8 To specify a file with its file name, press soft key **[N READ]** in step 6 above. The screen shown below is displayed.



9 To register file name TESTPRO as O1230, enter file name TESTPRO from the MDI panel, then set the file name with soft key **[F NAME]**. Next, enter program number 1230, then set the program number with soft key **[O SET]**. Then, press soft key **[EXEC]**.

Writing a file

Procedure

1 Press the EDIT switch on the machine operator's panel.

2 Press function key [PROG] .

3 Press the rightmost soft key [▷] (continuous menu key).

4 Press soft key **[CARD]**. The screen shown below is displayed.

```
DIRECTORY (M–CARD)                    O0034 N00045
  No.   FILE NAME        SIZE          DATE
 0001   O1000           123456        96/07/10
 0002   O1001             8458        96/07/30
 0003   O0002             3250        96/07/30
 0004   O2000            73456        96/07/31
 0005   O2001             3444        96/07/31
 0006   O3001             8483        96/08/02
 0007   O3300              406        96/08/05
 0008   O3400             2420        96/07/31
 0009   O3500             7460        96/07/31
~ [ PROG ][      ][ DIR + ][      ][ (OPRT) ] ~
```

5 Press soft key **[(OPRT)]**.

```
[ F SRH ][ F READ ][ N READ ][ PUNCH ][ DELETE ]
```

6 Press soft key **[PUNCH]**.

7 Enter a desired O number from the MDI panel, then set the program number with soft key **[O SET]**.
When soft key **[EXEC]** is pressed after the setting shown below has been made, for example, the file is written under program number O1230.

```
~ PUNCH          FILE NAME  =                    ~
                 PROGRAM No. =1230
>
 EDIT  ***  ****  ***  ****              15:40:21
[F NAME][ O SET ][ STOP ][ CAN ][ EXEC ]
```

8 In the same way as for O number setting, enter a desired file name from the MDI panel, then set the file name with soft key **[F SET]**.
When soft key **[EXEC]** is pressed after the setting shown below has been made, for example, the file is written under program number O1230 and file name ABCD12.

```
~ PUNCH          FILE NAME  =ABCD12              ~
                 PROGRAM No. =1230
>
 EDIT  ***  ****  ***  ****              15:40:21
[F NAME][ O SET ][ STOP ][ CAN ][ EXEC ]
```

Explanations

- **Registering the same file name**

When a file having the same name is already registered in the memory card, the existing file will be overwritten.

- **Writing all programs**

To write all programs, set program number = –9999. If no file name is specified in this case, file name PROGRAM.ALL is used for registration.

- **File name restrictions**

The following restrictions are imposed on file name setting:

<File name setting> ×××××××××.□□□

↑ Not longer than 8 characters

↑ Extension not longer than 3 characters

Deleting a file

Procedure

1 Press the EDIT switch on the machine operator's panel.

2 Press function key [PROG] .

3 Press the rightmost soft key [▷] (continuous menu key).

4 Press soft key **[CARD]**. The screen shown below is displayed.

```
DIRECTORY (M–CARD)                    O0034 N00045
  No.    FILE NAME        SIZE          DATE
 0001    O1000          123456        97/07/10
 0002    O1001            8458        97/07/30
 0003    O0002            3250        97/07/30
 0004    O2000           73456        97/07/31
 0005    O2001            3444        97/07/31
 0006    O3001            8483        97/08/02
 0007    O3300             406        97/08/05
 0008    O3400            2420        97/07/31
 0009    O3500            7460        97/07/31
~                                              ~
[ PROG ][      ][ DIR + ][      ][ (OPRT) ]
```

5 Press soft key **[(OPRT)]**.

[F SRH] [F READ] [N READ] [PUNCH] [DELETE]

6 Set the number of the desired file with soft key **[DELETE]**, then press soft key **[EXEC]**. The file is deleted, and the directory screen is displayed again.

When file number 21 is deleted

```
DIRECTORY (M–CARD)                    O0034 N00045
  No.    FILE NAME                      COMMENT
 0019    O1000          (MAIN PROGRAM)
 0020    O1010          (SUBPROGRAM–1)
 0021    O1020          (COMMENT      )
 0022    O1030          (COMMENT      )
~                                              ~
```

File name O1020 is deleted.

```
DIRECTORY (M–CARD)                    O0034 N00045
  No.    FILE NAME                      COMMENT
 0019    O1000          (MAIN PROGRAM)
 0020    O1010          (SUBPROGRAM–1)
 0021    O1020          (COMMENT      )
 0022    O1030          (COMMENT      )
~                                              ~
```

File number 21 is assigned to the next file name.

Batch input/output with a memory card

On the ALL IO screen, different types of data including part programs, parameters, offset data, pitch error data, custom macros, and workpiece coordinate system data can be input and output using a memory card; the screen for each type of data need not be displayed for input/output.



Procedure

1 Press the EDIT switch on the machine operator's panel.

2 Press function key [SYSTEM] .

3 Press the rightmost soft key [▷] (continuous menu key) several times.

4 Press soft key **[ALL IO]**. The screen shown below is displayed.

```
READ/PUNCH (PROGRAM)                    O0001 N00001
   No.    FILE NAME          SIZE          DATE
  *0001   O0222              332010        96–04–06
  *0002   O1003              334450        96–05–04
  *0003   MACROVAR.DAT       653400        96–05–12
  *0004   O0002              341205        96–05–13
     [PROGRAM]
  *O0001  O0002  O0003  O0005  O0100  O0020
  *O0006  O0004  O0110  O0200  O2200  O0441
  *O0330
  >
  EDIT  ***  ****  ***  ****              10:07:37
 [ PROG ][ PARAM ][OFFSET][      ][ (OPRT) ]
```

Upper part: Directory of files on the memory card
Lower part: Directory of registered programs

5 With cursor keys [↑] and [↓] , the user can choose between upper part scrolling and lower part scrolling. (An asterisk (*) displayed at the left edge indicates the part for which scrolling is possible.)

[↑] : Used for memory card file directory scrolling.

[↓] : Used for program directory scrolling.

6 With page keys [↑] and [↓], scroll through the file directory or program directory.

Explanations

- **Each data item**

When this screen is displayed, the program data item is selected. The soft keys for other screens are displayed by pressing the rightmost soft key [▷] (continuous menu key). Soft key **[M–CARD]** represents a separate memory card function for saving and restoring system RAM data. (See Section 8.10.7.)



When a data item other than program is selected, the screen displays only a file directory.
A data item is indicated, in parentheses, on the title line.



READ/PUNCH (PARAMETER) O0001 N00001

No.	FILE NAME	SIZE	DATE
0001	O0222	32010	96/04/06
0002	O1003	4450	96/05/04
0003	MACROVAR.DAT	653400	96/05/12
0004	O0003	4610	96/05/04
0005	O0001	4254	96/06/04
0006	O0002	750	96/06/04
0007	CNCPARAM.DAT	34453	96/06/04

- **Program directory display**

Program directory display does not match bit 0 (NAM) of parameter No. 3107, or bit 4 (SOR) of parameter No. 3107.

- **Using each function**

Display the following soft keys with soft key **[(OPRT)]**.

The operation of each function is the same as on the directory (memory card) screen. Soft key **[O SET]**, used for program number setting, and the "PROGRAM NUMBER =" indication are not displayed for data items other than program.

[F SRH]: Finds a specified file number.
[F READ]: Reads a specified file number.
[PUNCH]: Writes a file.
[N READ]: Reads a file under a specified file name.
[DELETE]: Deletes a specified file number.

NOTE
With a memory card, RMT mode operation and the subprogram call function (based on the M198 command) cannot be used.

File format and error messages

File format

All files that are read from and written to a memory card are of text format. The format is described below.

A file starts with % or LF, followed by the actual data. A file always ends with %. In a read operation, data between the first % and the next LF is skipped. Each block ends with an LF, not a semicolon (;).

- LF: 0A (hexadecimal) of ASCII code
- When a file containing lowercase letters, kana characters, and several special characters (such as $, ¥, and !) is read, those letters and characters are ignored.

Example:

```
%
O0001(MEMORY CARD SAMPLE FILE)
G17 G49 G97
G92X–11.3Y2.33
  .
  .
M30
%
```

- ASCII code is used for input/output, regardless of the setting parameter (ISO/EIA).
- Bit 3 (NCR) of parameter No. 0100 can be used to specify whether the end of block code (EOB) is output as “LF” only, or as “LF, CR, CR.”

Error messages

If an error occurs during memory card input/output, a corresponding error message is displayed.



×××× represents a memory card error code.

Memory card error codes

Code	Meaning
102	The memory card does not have sufficient free space.
105	No memory card is mounted.
106	A memory card is already mounted.
110	The specified directory cannot be found.
111	There are too many files under the root directory to allow a directory to be added.
114	The specified file cannot be found.
115	The specified file is protected.
117	The file has not yet been opened.
118	The file is already open.
119	The file is locked.
122	The specified file name is invalid.
124	The extension of the specified file is invalid.
129	A non–corresponding function was specified.
130	The specification of a device is invalid.
131	The specification of a pathname is invalid.
133	Multiple files are open at the same time.
135	The device is not formatted.
140	The file has the read/write disabled attribute.

9 EDITING PROGRAMS

General

This chapter describes how to edit programs registered in the CNC. Editing includes the insertion, modification, deletion, and replacement of words. Editing also includes deletion of the entire program and automatic insertion of sequence numbers. The extended part program editing function can copy, move, and merge programs. This chapter also describes program number search, sequence number search, word search, and address search, which are performed before editing the program.



9.1 INSERTING, ALTERING AND DELETING A WORD

This section outlines the procedure for inserting, modifying, and deleting a word in a program registered in memory.

Procedure for inserting, altering and deleting a word

1 Select **EDIT** mode.

2 Press PROG .

3 Select a program to be edited.
If a program to be edited is selected, perform the operation 4.
If a program to be edited is not selected, search for the program number.

4 Search for a word to be modified.
·Scan method
·Word search method

5 Perform an operation such as altering, inserting, or deleting a word.

Explanation

- **Concept of word and editing unit**

A word is an address followed by a number. With a custom macro, the concept of word is ambiguous.
So the editing unit is considered here.
The editing unit is a unit subject to alteration or deletion in one operation.
In one scan operation, the cursor indicates the start of an editing unit.
An insertion is made after an editing unit.
Definition of editing unit

(i) Program portion from an address to immediately before the next address

(ii) An address is an alphabet, **IF**, **WHILE**, **GOTO**, **END**, **DO=**,or **; (EOB)**.

According to this definition, a word is an editing unit.
The word “word,” when used in the description of editing, means an editing unit according to the precise definition.

WARNING
The user cannot continue program execution after altering, inserting, or deleting data of the program by suspending machining in progress by means of an operation such as a single block stop or feed hold operation during program execution. If such a modification is made, the program may not be executed exactly according to the contents of the program displayed on the screen after machining is resumed. So, when the contents of memory are to be modified by part program editing, be sure to enter the reset state or reset the system upon completion of editing before executing the program.

9.1.1 Word Search

A word can be searched for by merely moving the cursor through the text (scanning), by word search, or by address search.

Procedure for scanning a program

1 Press the cursor key [→]

The cursor moves forward word by word on the screen; the cursor is displayed at a selected word.

2 Press the cursor key [←]

The cursor moves backward word by word on the screen; the cursor is displayed at a selected word.

Example) When Z1250.0 is scanned

```
Program                                  O0050  N01234
 O0050  ;
 N01234  X100.0 Z1250.0  ;
 S12  ;
 N56789  M03  ;
 M02  ;
 %
```

3 Holding down the cursor key [→] or [←] scans words continuously.

4 The first word of the next block is searched for when the cursor key [↓] is pressed.

5 The first word of the previous block is searched for when the cursor key [↑] is pressed.

6 Holding down the cursor key [↓] or [↑] moves the cursor to the head of a block continuously.

7 Pressing the page key [PAGE ↓] displays the next page and searches for the first word of the page.

8 Pressing the page key [↑ PAGE] displays the previous page and searches for the first word of the page.

9 Holding down the page key [PAGE ↓] or [↑ PAGE] displays one page after another.

Procedure for searching a word

Example) of Searching for S12



1 Key in address [S] .

2 Key in [1] [2] .

- S12 cannot be searched for if only S1 is keyed in.
- S09 cannot be searched for by keying in only S9.
  To search for S09, be sure to key in S09.

3 Pressing the **[SRH↓]** key starts search operation.
Upon completion of search operation, the cursor is displayed at S12.
Pressing the **[SRH↑]** key rather than the **[SRH↓]** key performs search operation in the reverse direction.

Procedure for searching an address

Example) of Searching for M03



1 Key in address [M] .

2 Press the **[SRH↓]** key.
Upon completion of search operation, the cursor is displayed at M03.
Pressing the **[SRH↑]** key rather than the **[SRH↓]** key performs search operation in the reverse direction.

Alarm

Alarm number	Description
71	The word or address being searched for was not found.

9.1.2 Heading a Program

The cursor can be jumped to the top of a program. This function is called heading the program pointer. This section describes the three methods for heading the program pointer.

Procedure for Heading a Program

Method 1

1 Press RESET when the program screen is selected in EDIT mode. When the cursor has returned to the start of the program, the contents of the program are displayed from its start on the screen.

Method 2

Search for the program number.

1 Press address O ,when a program screen is selected in the **MEMORY** or **EDIT** mode.

2 Input a program number.

3 Press the soft key **[O SRH]**.

Method 3

1 Select **MEMORY** or **EDIT** mode.

2 Press PROG .

3 Press the **[(OPRT)]** key.

4 Press the **[REWIND]** key.

9.1.3 Inserting a Word

Procedure for inserting a word

1 Search for or scan the word immediately before a word to be inserted.

2 Key in an address to be inserted.

3 Key in data.

4 Press the INSERT key.

Example of Inserting T15

Procedure

1 Search for or scan Z1250.

```
Program                                  O0050  N01234
O0050 ;
N01234 X100.0 Z1250.0 ;   <-- Z1250.0 is searched for/ scanned.
S12 ;
N56789 M03 ;
M02 ;
%
```

2 Key in T 1 5 .

3 Press the INSERT key.

```
Program                                  O0050  N01234
O0050 ;
N01234 X100.0 Z1250.0 T15 ;   <-- T15 is inserted.
S12 ;
N56789 M03 ;
M02 ;
%
```

9.1.4 Altering a Word

Procedure for altering a word

1 Search for or scan a word to be altered.

2 Key in an address to be inserted.

3 Key in data.

4 Press the ALTER key.

Example of changing T15 to M15

Procedure

1 Search for or scan T15.

```
Program                              O0050  N01234
O0050 ;
N01234 X100.0 Z1250.0 T15 ;
S12 ;
N56789 M03 ;
M02 ;
%
```

T15 is searched for/scanned.

2 Key in M 1 5 .

3 Press the ALTER key.

```
Program                              O0050  N01234
O0050 ;
N1234 X100.0 Z1250.0 M15 ;
S12 ;
N5678 M03 ;
M02 ;
%
```

T15 is changed to M15.

9.1.5 Deleting a Word

Procedure for deleting a word

1 Search for or scan a word to be deleted.

2 Press the DELETE key.

Example of deleting X100.0

Procedure

1 Search for or scan X100.0.



2 Press the DELETE key.

9.2 DELETING BLOCKS

A block or blocks can be deleted in a program.

9.2.1 Deleting a Block

The procedure below deletes a block up to its EOB code; the cursor advances to the address of the next word.

Procedure for deleting a block

1 Search for or scan address N for a block to be deleted.

2 Key in EOB.

3 Press the DELETE.

Example of deleting a block of No.1234

Procedure

1 Search for or scan N01234.

2 Key in EOB.

3 Press the DELETE key.



9.2.2 Deleting Multiple Blocks

The blocks from the currently displayed word to the block with a specified sequence number can be deleted.

Procedure for deleting multiple blocks

1 Search for or scan a word in the first block of a portion to be deleted.

2 Key in address [N] .

3 Key in the sequence number for the last block of the portion to be deleted.

4 Press the [DELETE] key.

Example of deleting blocks from a block containing N01234 to a block containing N56789

Procedure

1 Search for or scan N01234.



2. Key in [N] [5] [6] [7] [8] [9] .



3 Press the [DELETE] key.



9.3 PROGRAM NUMBER SEARCH

When memory holds multiple programs, a program can be searched for. There are three methods as follows.

Procedure for program number search

Method 1

1 Select **EDIT** or **MEMORY** mode.

2 Press PROG to display the program screen.

3 Key in address O .

4 Key in a program number to be searched for.

5 Press the **[O SRH]** key.

6 Upon completion of search operation, the program number searched for is displayed in the upper–right corner of the CRT screen.
If the program is not found , P/S alarm No. 71 occurs.

Method 2

1 Select **EDIT** or **MEMORY** mode.

2 Press PROG to display the program screen.

3 Press the **[O SRH]** key.
In this case, the next program in the directory is searched for .

Method 3

This method searches for the program number (0001 to 0015) corresponding to a signal on the machine tool side to start automatic operation. Refer to the relevant manual prepared by the machine tool builder for detailed information on operation.

1 Select **MEMORY** mode.

2 Set the reset state(*1)

· The reset state is the state where the LED for indicating that automatic operation is in progress is off. (Refer to the relevant manual of the machine tool builder.)

3 Set the program number selection signal on the machine tool side to a number from 01 to 15.

· If the program corresponding to a signal on the machine tool side is not registered, P/S alarm (No. 059) is raised.

4 Press the cycle start button.

· When the signal on the machine tool side represents 00, program number search operation is not performed.

Alarm

Alarm No.	Contents
59	The program with the selected number cannot be searched during external program number search.
71	The specified program number was not found during program number search.

9.4 SEQUENCE NUMBER SEARCH

Sequence number search operation is usually used to search for a sequence number in the middle of a program so that execution can be started or restarted at the block of the sequence number.

Example) Sequence number 02346 in a program (O0002) is searched for.



Procedure for sequence number search

1 Select **MEMORY** mode.

2 Press PROG .

3 · If the program contains a sequence number to be searched for, perform the operations 4 to 7 below.

· If the program does not contain a sequence number to be searched for,select the program number of the program that contains the sequence number to be searched for.

4 Key in address N .

5 Key in a sequence number to be searched for.

6 Press the **[N SRH]** key.

7 Upon completion of search operation, the sequence number searched for is displayed in the upper–right corner of the CRT screen.
If the specified sequence number is not found in the program currently selected, P/S alarm (No. 060) occurs.

Explanations

- **Operation during Search**

Those blocks that are skipped do not affect the CNC. This means that the data in the skipped blocks such as coordinates and M, S, and T codes does not alter the CNC coordinates and modal values.
So, in the first block where execution is to be started or restarted by using a sequence number search command, be sure to enter required M, S, and T codes and coordinates. A block searched for by sequence number search usually represents a point of shifting from one process to another. When a block in the middle of a process must be searched for to restart execution at the block, specify M, S, and T codes, G codes, coordinates, and so forth as required from the MDI after closely checking the machine tool and CNC states at that point.

- **Checking during search**

During search operation, the following checks are made:
·Optional block skip
·P/S alarm (No. 003 to 010)

Restrictions

- **Searching in sub–program**

During sequence number search operation, M98Pxxxx (subprogram call) is not executed. So an P/S alarm (No.060) is raised if an attempt is made to search for a sequence number in a subprogram called by the program currently selected.



If an attempt is made to search for N8888 in the example above, an alarm is raised.

Alarm

Alarm No.	Contents
60	Command sequence number was not found in the sequence number search.

9.5 DELETING PROGRAMS

Programs registered in memory can be deleted,either one program by one program or all at once. Also, More than one program can be deleted by specifying a range.

9.5.1 Deleting One Program

A program registered in memory can be deleted.

Procedure for deleting one program

1 Select the **EDIT** mode.

2 Press PROG to display the program screen.

3 Key in address O .

4 Key in a desired program number.

5 Press the DELETE key.
The program with the entered program number is deleted.

9.5.2 Deleting All Programs

All programs registered in memory can be deleted.

Procedure for deleting all programs

1 Select the **EDIT** mode.

2 Press PROG to display the program screen.

3 Key in address O .

4 Key in –9999.

5 Press edit key DELETE to delete all programs.

9.5.3 Deleting More Than One Program by Specifying a Range

Programs within a specified range in memory are deleted.

Procedure for deleting more than one program by specifying a range

1 Select the **EDIT** mode.

2 Press PROG to display the program screen.

3 Enter the range of program numbers to be deleted with address and numeric keys in the following format:
OXXXX,OYYYY
where XXXX is the starting number of the programs to be deleted and YYYY is the ending number of the programs to be deleted.

4 Press edit key DELETE to delete programs No. XXXX to No. YYYY.

9.6 EXTENDED PART PROGRAM EDITING FUNCTION

With the extended part program editing function, the operations described below can be performed using soft keys for programs that have been registered in memory.
Following editing operations are available :

- All or part of a program can be copied or moved to another program.
- One program can be merged at free position into other programs.
- A specified word or address in a program can be replaced with another word or address.

9.6.1 Copying an Entire Program

A new program can be created by copying a program.



Fig. 9.6.1 Copying an entire program

In Fig. 9.6.1, the program with program number xxxx is copied to a newly created program with program number yyyy. The program created by copy operation is the same as the original program except the program number.

Procedure of copying an entire program

1 Enter the **EDIT** mode.

2 Press function key [PROG] .



3 Press soft key **[(OPRT)]**.

Continuous menu key

4 Press the continuous menu key.



5 Press soft key **[EX–EDT]**.



6 Check that the screen for the program to be copied is selected and press soft key **[COPY]**.



7 Press soft key **[ALL]**.

Numeric keys [0] to [9]

8 Enter the number of the new program (with only numeric keys) and press the [INPUT] key.



9 Press soft key **[EXEC]**.

9.6.2 Copying Part of a Program

A new program can be created by copying part of a program.



Fig. 9.6.2 Copying part of a program

In Fig. 9.6.2, part B of the program with program number xxxx is copied to a newly created program with program number yyyy. The program for which an editing range is specified remains unchanged after copy operation.

Procedure for copying part of a program

1 Perform steps **1** to **6** in subsection III–9.6.1.



2 Move the cursor to the start of the range to be copied and press soft key **[CRSR~]**.



3 Move the cursor to the end of the range to be copied and press soft key **[~CRSR]** or **[~BTTM]** (in the latter case, the range to the end of the program is copied regardless of the position of the cursor).

Numeric keys 0 to 9

4 Enter the number of the new program (with only numeric keys) and press the INPUT key.



5 Press soft key **[EXEC]**.

9.6.3 Moving Part of a Program

A new program can be created by moving part of a program.



Fig. 9.6.3 Moving part of a program

In **Fig. 9.6.3**, part B of the program with program number xxxx is moved to a newly created program with program number yyyy; part B is deleted from the program with program number xxxx.

Procedure for moving part of a program

1 Perform steps 1 to 5 in subsection III–9.6.1.



2 Check that the screen for the program to be moved is selected and press soft key **[MOVE]**.



3 Move the cursor to the start of the range to be moved and press soft key **[CRSR~]**.



4 Move the cursor to the end of the range to be moved and press soft key **[~CRSR]** or **[~BTTM]**(in the latter case, the range to the end of the program is copied regardless of the position of the cursor).

Numeric keys 0 to 9

5 Enter the number of the new program (with only numeric keys) and press the INPUT key.



6 Press soft key **[EXEC]**.

9.6.4 Merging a Program

Another program can be inserted at an arbitrary position in the current program.



Fig. 9.6.4 Merging a program at a specified location

In **Fig. 9.6.4,** the program with program number XXXX is merged with the program with program number YYYY. The OYYYY program remains unchanged after merge operation.

Procedure for merging a program



1 Perform steps **1** to **5** in subsection III–9.6.1.

2 Check that the screen for the program to be edited is selected and press soft key **[MERGE]**.

3 Move the cursor to the position at which another program is to be inserted and press soft key **[~'CRSR]** or **[~BTTM']**(in the latter case, the end of the current program is displayed).

4 Enter the number of the program to be inserted (with only numeric keys) and press the INPUT key.

5 Press soft key **[EXEC]**.
The program with the number specified in step 4 is inserted before the cursor positioned in step 3.

9.6.5 Supplementary Explanation for Copying, Moving and Merging

Explanations

- **Setting an editing range**

The setting of an editing range start point with **[CRSR~]** can be changed freely until an editing range end point is set with **[~CRSR]** or **[~BTTM]**. If an editing range start point is set after an editing range end point, the editing range must be reset starting with a start point.
The setting of an editing range start point and end point remains valid until an operation is performed to invalidate the setting.
One of the following operations invalidates a setting:

- An edit operation other than address search, word search/scan, and search for the start of a program is performed after a start point or end point is set.
- Processing is returned to operation selection after a start point or end point is set.

- **Without specifying a program number**

In copying program and moving program, if **[EXEC]** is pressed without specifying a program number after an editing range end point is set, a program with program number O0000 is registered as a work program. This O0000 program has the following features:

- The program can be edited in the same way as a general program. (Do not run the program.)
- If a copy or move operation is newly performed, the previous information is deleted at execution time, and newly set information (all or part of the program) is re–registered. (In merge operation, the previous information is not deleted.) However, the program, when selected for foreground operation, cannot be re–registered in the background. (A BP/S140 alarm is raised.) When the program is re–registered, a free area is produced. Delete such a free area with the RESET key.
- When the program becomes unnecessary, delete the program by a normal editing operation.

- **Editing when the system waiting for a program number to be entered**

When the system is waiting for a program number to be entered, no edit operation can be performed.

Restrictions

- **Number of digits for program number**

If a program number is specified by 5 or more digits, a format error is generated.

Alarm

Alarm No.	Contents
70	Memory became insufficient while copying or inserting a program. Copy or insertion is terminated.
101	The power was interrupted during copying, moving, or inserting a program and memory used for editing must be cleared. When this alarm occurs, press the key PROG while pressing function key RESET. Only the program being edited is deleted.

9.6.6 Replacement of Words and Addresses

Replace one or more specified words.
Replacement can be applied to all occurrences or just one occurrence of specified words or addresses in the program.

Procedure for change of words or addresses



1 Perform steps 1 to 5 in subsection 9.6.1.

2 Press soft key **[CHANGE]**.

3 Enter the word or address to be replaced.



4 Press soft key **[BEFORE]**.

5 Enter the new word or address.



6 Press soft key **[AFTER]**.



7 Press soft key **[EXEC]** to replace all the specified words or addresses after the cursor.
Press soft key **[1–EXEC]** to search for and replace the first occurrence of the specified word or address after the cursor.
Press soft key **[SKIP]** to only search for the first occurrence of the specified word or address after the cursor.

EXAMPLES

- **Replace X100 with Z200**

  [CHANGE] X 1 0 0 **[BEFORE]** Z 2 0 0 **[AFTER] [EXEC]**

- **Replace X100Z200 with X30**

  [CHANGE] X 1 0 0 Z 2 0 0 **[BEFORE]** X 3 0 **[AFTER] [EXEC]**

- **Replace IF with WHILE**

  [CHANGE] I F **[BEFORE]** W H I L E **[AFTER] [EXEC]**

- **Replace X with ,C10**

  [CHANGE] X **[BEFOR]** , C 1 0 **[AFTER] [EXEC]**

Explanation

- **Replacing custom macros**

  The following custom macro words are replaceable:
  IF, WHILE, GOTO, END, DO, BPRNT, DPRNT, POPEN, PCLOS
  The abbreviations of custom macro words can be specified.
  When abbreviations are used, however, the screen displays the abbreviations as they are key input, even after soft key **[BEFORE]** and **[AFTER]** are pressed.

Restrictions

- **The number of characters for replacement**

  Up to 15 characters can be specified for words before or after replacement. (Sixteen or more characters cannot be specified.)

- **The characters for replacement**

  Words before or after replacement must start with a character representing an address.(A format error occurs.)

9.7 EDITING OF CUSTOM MACROS

Unlike ordinary programs, custom macro programs are modified, inserted, or deleted based on editing units.
Custom macro words can be entered in abbreviated form.
Comments can be entered in a program.
Refer to the section 10.1 for the comments of a program.

Explanations

● Editing unit

When editing a custom macro already entered, the user can move the cursor to each editing unit that starts with any of the following characters and symbols:

(a) Address

(b) # located at the start of the left side of a substitution statement

(c) /, (,=, and ;

(d) First character of IF, WHILE, GOTO, END, DO, POPEN, BPRNT, DPRNT and PCLOS
On the CRT screen, a blank is placed before each of the above characters and symbols.

(Example) Head positions where the cursor is placed

```
N001 X–#100 ;
#1 =123 ;
N002 /2 X[12/#3] ;
N003 X–SQRT[#3/3*[#4+1]] ;
N004 X–#2 Z#1 ;
N005 #5 =1+2–#10 ;
IF[#1NE0] GOTO10 ;
WHILE[#2LE5] DO1 ;
#[200+#2] =#2*10 ;
#2 =#2+1 ;
END1 ;
```

● Abbreviations of custom macro word

When a custom macro word is altered or inserted, the first two characters or more can replace the entire word.
Namely,

WHILE → WH	**GOTO → GO**	**XOR → XO**	**AND → AN**
SIN → SI	**ASIN → AS**	**COS → CO**	**ACOS → AC**
TAN → TA	**ATAN → AT**	**SQRT → SQ**	**ABS → AB**
BCD → BC	**BIN → BI**	**FIX → FI**	**FUP → FU**
ROUND → RO	**END → EN**	**POPEN → PO**	**BPRNT → BP**
DPRNT → DP	**PCLOS→PC**	**EXP → EX**	**THEN → TH**

(Example) Keying in

```
WH [AB [#2 ] LE RO [#3 ] ]
```

has the same effect as

```
WHILE  [ABS  [#2 ] LE ROUND [#3 ] ]
```

The program is also displayed in this way.

9.8 BACKGROUND EDITING

Editing a program while executing another program is called background editing. The method of editing is the same as for ordinary editing (foreground editing).
A program edited in the background should be registered in foreground program memory by performing the following operation:
During background editing, all programs cannot be deleted at once.

Procedure for background editing

1 Enter **EDIT** or **MEMORY** mode.
Memory mode is allowed even while the program is being executed.

2 Press function keym [PROG] .

3 Press soft key **[(OPRT)]**, then press soft key **[BG–EDT]**.
The background editing screen is displayed (PROGRAM (BG–EDIT) is displayed at the top left of the screen).

4 Edit a program on the background editing screen in the same way as for ordinary program editing.

5 After editing is completed, press soft key **[(OPRT)]**, then press soft key **[BG–EDT].** The edited program is registered in foreground program memory.

Explanation

- **Alarms during background editing**

Alarms that may occur during background editing do not affect foreground operation. Conversely, alarms that may occur during foreground operation do not affect background editing. In background editing, if an attempt is made to edit a program selected for foreground operation, a BP/S alarm (No. 140) is raised. On the other hand, if an attempt is made to select a program subjected to background editing during foreground operation (by means of subprogram calling or program number search operation using an external signal), a P/S alarm (Nos. 059, 078) is raised in foreground operation. As with foreground program editing, P/S alarms occur in background editing. However, to distinguish these alarms from foreground alarms, BP/S is displayed in the data input line on the background editing screen.

9.9 PASSWORD FUNCTION

The password function (bit 4 (NE9) of parameter No. 3202) can be locked using parameter No. 3210 (PASSWD) and parameter No. 3211 (KEYWD) to protect program Nos. O9000 to O9999. In the locked state, parameter NE9 cannot be set to 0. In this state, program Nos. O9000 to O9999 cannot be modified unless the correct keyword is set.
A locked state means that the value set in the parameter PASSWD differs from the value set in the parameter KEYWD. The values set in these parameters are not displayed. The locked state is released when the value already set in the parameter PASSWD is also set in parameter KEYWD. When 0 is displayed in parameter PASSWD, parameter PASSWD is not set.

Procedure for locking and unlocking

Locking

1 Set the MDI mode.

2 Enable parameter writing. At this time, P/S alarm No. 100 is issued on the CNC.

3 Set parameter No. 3210 (PASSWD). At this time, the locked state is set.

4 Disable parameter writing.

5 Press the RESET key to release the alarm state.

Unlocking

1 Set the MDI mode.

2 Enable parameter writing. At this time, P/S alarm No. 100 is issued on the CNC.

3 In parameter No. 3211 (KEYWD), set the same value as set in parameter No. 3210 (PASSWD) for locking. At this time, the locked state is released.

4 Set bit 4 (NE9) of parameter No. 3202 to 0.

5 Disable parameter writing.

6 Press the RESET key to release the alarm state.

7 Subprograms from program Nos. 9000 to 9999 can now be edited.

Explanations

- **Setting parameter PASSWD**

The locked state is set when a value is set in the parameter PASSWD. However, note that parameter PASSWD can be set only when the locked state is not set (when PASSWD = 0, or PASSWD = KEYWD). If an attempt is made to set parameter PASSWD in other cases, a warning is given to indicate that writing is disabled. When the locked state is set (when PASSWD = 0 and PASSWD = KEYWD), parameter NE9 is automatically set to 1. If an attempt is made to set NE9 to 0, a warning is given to indicate that writing is disabled.

- **Changing parameter PASSWD**

Parameter PASSWD can be changed when the locked state is released (when PASSWD = 0, or PASSWD = KEYWD). After step 3 in the procedure for unlocking, a new value can be set in the parameter PASSWD. From that time on, this new value must be set in parameter KEYWD to release the locked state.

- **Setting 0 in parameter PASSWD**

When 0 is set in the parameter PASSWD, the number 0 is displayed, and the password function is disabled. In other words, the password function can be disabled by either not setting parameter PASSWD at all, or by setting 0 in parameter PASSWD after step 3 of the procedure for unlocking. To ensure that the locked state is not entered, care must be taken not to set a value other than 0 in parameter PASSWD.

- **Re–locking**

After the locked state has been released, it can be set again by setting a different value in parameter PASSWD, or by turning the power to the NC off then on again to reset parameter KEYWD.

CAUTION
Once the locked state is set, parameter NE9 cannot be set to 0 and parameter PASSWD cannot be changed until the locked state is released or the memory all–clear operation is performed. Special care must be taken in setting parameter PASSWD.

10 CREATING PROGRAMS

Programs can be created using any of the following methods:

- MDI keyboard
- PROGRAMMING IN TEACH IN MODE
- AUTOMATIC PROGRAM PREPARATION DEVICE (FANUC SYSTEM P)

This chapter describes creating programs using the MDI panel, TEACH IN mode, and conversational programming with graphic function. This chapter also describes the automatic insertion of sequence numbers.

10.1 CREATING PROGRAMS USING THE MDI PANEL

Programs can be created in the **EDIT** mode using the program editing functions described in Chapter III–9.

Procedure for Creating Programs Using the MDI Panel

Procedure

1 Enter the **EDIT** mode.

2 Press the PROG key.

3 Press address key O and enter the program number.

4 Press the INSERT key.

5 Create a program using the program editing functions described in Chapter 9.

Explanation

- **Comments in a program**

Comments can be written in a program using the control in/out codes.

```
Example)O0001 (FANUC SERIES 16) ;
        M08   (COOLANT ON) ;
```

- When the INSERT key is pressed after the control–out code "(", comments, and control–in code ")" have been typed, the typed comments are registered.
- When the INSERT key is pressed midway through comments, to enter the rest of comments later, the data typed before the INSERT key is pressed may not be correctly registered (not entered, modified, or lost) because the data is subject to an entry check which is performed in normal editing.

Note the following to enter a comment:

- Control–in code ")" cannot be registered by itself.
- Comments entered after the INSERT key is pressed must not begin with a number, space, or address O.
- If an abbreviation for a macro is entered, the abbreviation is converted into a macro word and registered (see Section 9.7).
- Address O and subsequent numbers, or a space can be entered but are omitted when registered.

10.2 AUTOMATIC INSERTION OF SEQUENCE NUMBERS

Sequence numbers can be automatically inserted in each block when a program is created using the MDI keys in the EDIT mode.
Set the increment for sequence numbers in parameter 3216.

Procedure for automatic insertion of sequence numbers

Procedure

1 Set 1 for SEQUENCE NO. (see subsection III–11.4.3).

2 Enter the **EDIT** mode.

3 Press [PROG] to display the program screen.

4 Search for or register the number of a program to be edited and move the cursor to the EOB (;) of the block after which automatic insertion of sequence numbers is started.
When a program number is registered and an EOB (;) is entered with the [INSERT] key, sequence numbers are automatically inserted starting with 0. Change the initial value, if required, according to step 10, then skip to step 7.

5 Press address key [N] and enter the initial value of N.

6 Press [INSERT] key.

7 Enter each word of a block.

8 Press [EOB] key.

9 Press INSERT . The EOB is registered in memory and sequence numbers are automatically inserted. For example, if the initial value of N is 10 and the parameter for the increment is set to 2, N12 inserted and displayed below the line where a new block is specified.



10

- In the example above, if N12 is not necessary in the next block, pressing the DELETE key after N12 is displayed deletes N12.
- To insert N100 in the next block instead of N12, enter N100 and press ALTER after N12 is displayed. N100 is registered and initial value is changed to 100.

10.3 CREATING PROGRAMS IN TEACH IN MODE (PLAYBACK)

When the playback option is selected, the **TEACH IN JOG** mode and **TEACH IN HANDLE** mode are added. In these modes, a machine position along the X, Z, and Y axes obtained by manual operation is stored in memory as a program position to create a program.
The words other than X, Z, and Y, which include O, N, G, R, F, C, M, S, T, P, Q, and EOB, can be stored in memory in the same way as in **EDIT** mode.

Procedure for Creating Programs in TEACH IN Mode

The procedure described below can be used to store a machine position along the X, Z, and Y axes.

1 Select the **TEACH IN JOG** mode or **TEACH IN HANDLE** mode.

2 Move the tool to the desired position with jog or handle.

3 Press [PROG] key to display the program screen. Search for or register the number of a program to be edited and move the cursor to the position where the machine position along each axis is to be registered (inserted).

4 Key in address [X] .

5 Press the [INSERT] key. Then a machine position along the X axis is stored in memory.

(Example) X10.521 Absolute position (for mm input)
X10521 Data stored in memory

6 Similarly, key in [Z] , then press the [INSERT] key. Then a machine position along the Z axis is stored in memory. Further, key in [Y] , then press the [INSERT] key. Then a machine position along the Y axis is stored in memory.

All coordinates stored using this method are absolute coordinates.

Examples

```
O1234 ;
N1 G50 X100000 Z200000 ;
N2 G00 X14784 Z8736 ;
N3 G01 Z103480 F300 ;
N4 M02 ;
```



1 Set the setting data SEQUENCE NO. to 1 (on). (The incremental value parameter (No. 3212) is assumed to be “1”.)

2 Select the **TEACH IN HANDLE** mode.

3 Make positioning at position P0 by the manual pulse generator.

4 Select the program screen.

5 Enter program number O1234 as follows:

O 1 2 3 4 INSERT

This operation registers program number O1234 in memory.
Next, press the following keys:

EOB INSERT

An EOB (;) is entered after program number O1234. Because no number is specified after N, sequence numbers are automatically inserted for N0 and the first block (N1) is registered in memory.

6 Enter the P0 machine position for data of the first block as follows:

G 5 0 INSERT X INSERT Z INSERT EOB INSERT

This operation registers G50 X100000 Z200000 ; in memory. The automatic sequence number insertion function registers N2 of the second block in memory.

7 Position the tool at P1 with the manual pulse generator.

8 Enter the P1 machine position for data of the second block as follows:

G 0 0 INSERT X INSERT Z INSERT EOB INSERT

This operation registers G00 X14784 Z8736; in memory. The automatic sequence number insertion function registers N3 of the third block in memory.

9 Position the tool at P2 with the manual pulse generator.

10 Enter the P2 machine position for data of the third block as follows:

[G] [0] [1] [INSERT] [Z] [INSERT] [F] [3] [0] [0]
[INSERT] [EOB] [INSERT]

This operation registers G01 Z103480 F300; in memory.
The automatic sequence number insertion function registers N4 of the fourth block in memory.

11 Register M02; in memory as follows:

[M] [0] [2] [INSERT] [EOB] [INSERT]

N5 indicating the fifth block is stored in memory using the automatic sequence number insertion function. Press the [DELETE] key to delete it.

This completes the registration of the sample program.

Explanations

- **Checking contents of the memory**

The contents of memory can be checked in the **TEACH IN** mode by using the same procedure as in **EDIT** mode.



- **Registering a position with compensation**

When a value is keyed in after keying in address [X], [Z], or [Y], then the [INSERT] key is pressed, the value keyed in for a machine position is added for registration. This operation is useful to correct a machine position by key–in operation.

- **Registering commands other than position commands**

Commands to be entered before and after a machine position must be entered before and after the machine position is registered, by using the same operation as program editing in **EDIT** mode.

11 SETTING AND DISPLAYING DATA

General

To operate a CNC machine tool, various data must be set on the MDI for the CNC. The operator can monitor the state of operation with data displayed during operation.
This chapter describes how to display and set data for each function.

Explanations

● Screen transition chart



MDI function keys
(Shaded keys (▢) are described in this chapter.)

The screen transition for when each function key on the MDI panel is pressed is shown below. The subsections referenced for each screen are also shown. See the appropriate subsection for details of each screen and the setting procedure on the screen. See other chapters for screens not described in this chapter.

See Chapter III–7 for the screen that appears when function key MESSAGE is pressed. See Chapter III–12 for the screen that appears when function key GRAPH is pressed. See Chapter III–13 for the screen that appears when function key HELP is pressed. In general, function key CUSTOM is prepared by the machine tool builder and used for macros. Refer to the manual issued by the machine tool builder for the screen that appears when function key CUSTOM is pressed.

● Data protection key

The machine may have a data protection key to protect part programs, tool compensation values, setting data, and custom macro variables. Refer to the manual issued by the machine tool builder for where the data protection key is located and how to use it.

POSITION DISPLAY SCREEN

Screen transition triggered by the function key POS



PROGRAM SCREEN

Screen transition triggered by the function key PROG in the MEMORY or MDI mode



PROGRAM SCREEN

Screen transition triggered by the function key PROG in the EDIT mode




OFFSET/SETTING SCREEN
Screen transition triggered by the function key
OFFSET SETTING
1/2
OFFSET SETTING
Tool offset value
OFFSET
SETTING
WORK
(OPRT)
Display of tool offset value
⇒See III−11.4.1.
Display of setting data
⇒See III−11.4.7
Display of workpiece coordinate system
⇒See III−11.4.10
Setting of tool offset data
⇒See III−11.4.1.
Setting of direct input of tool offset value
⇒See III−11.4.2.
Setting of direct input of tool offset measured B
⇒See III−11.4.3.
Setting of counter input of offset value
⇒See III−11.4.4.
Parameter setting
⇒See III−11.4.7.
Setting sequence number comparison and stop
⇒See III−11.4.8.
Displaying run time and parts count
⇒See III−11.4.9.
Setting the number of parts required
⇒See III−11.4.9.
Displaying setting time
⇒See III−11.4.9.
Setting of work origin offset value
⇒See III−11.4.10.
Tool offset value
MACRO
OPR
TOOLLF
(OPRT)
Display of macro variables
⇒See III−11.4.13.
Setting macro variables
⇒See III−11.4.12.
Displaying software operator's panel
⇒See III−11.4.13.
Software operator's panel switch
⇒See III−11.4.13.
Displaying tool life management data
⇒See III− 11.4.14.
Presetting tool life counter
Clearing executing data
⇒See III−11.4.14.
1*
To next page


2/2
1*
Tool offset value
OFST.2
W.SHFT
(OPRT)
Display of Y axis offset value
⇒See III–11.4.6.
Display of work coordinate system value
⇒See III–11.4.5
Setting of Y axis offset data
⇒See III–11.4.6.
Setting of work coordinate system shift value
⇒See III–11.4.5
Setting of work-piece coordinate shift value by direct input function B for tool offset measured 2.
⇒See III–11.4.3.
Tool offset value
OFST. B
(OPRT)
Display of B axis offset value
⇒See III–11.4.15.
Setting of B axis offset data
⇒See III–11.4.15.

SYSTEM SCREEN Screen transition triggered by the function key [SYSTEM]



● **Setting screens** The table below lists the data set on each screen.

Table 11 Setting screens and data on them

No.	Setting screen	Contents of setting	Reference item
1	Tool offset value	Tool offset value Tool nose radius compensation value	Subsec. 11.4.1
		Direct input of tool offset value	Subsec. 11.4.2
		Direct input of tool offset value measured B	Subsec. 11.4.3
		Counter input of offset value	Subsec. 11.4.4
		Y axis offset	Subsec. 11.4.6
2	Workpiece coordinate system setting	Workpiece coordinate system shift value	Subsec. 11.4.5
		Workpiece origin offset value	Subsec. 11.4.10
3	Setting data (handy)	Parameter write TV check Punch code (EIA/ISO) Input unit (mm/inch) I/O channel Automatic insert of Sequence No. Conversion of tape format (F15)	Subsec. 11.4.7
		Sequence number comparison and stop	Subsec. 11.4.8
4	Setting data (mirror image)	Mirror image	Subsec. 11.4.7
5	Setting data (timer)	Parts required	Subsec. 11.4.9
6	Macro variables	Custom macro common variables (#100 to #149) or (#100 to #199) (#500 to #531) or (#500 to #599)	Subsec. 11.4.12
7	Parameter	Parameter	Subsec. 11.5.1
8	Pitch error	Pitch error compensation data	Subsec. 11.5.2
9	software operator’s panel	Mode selection Jog feed axis selection Jog rapid traverse Axis selection for Manual pulse generator Multiplication for manual pulse generator Jog feedrate Feedrate override Rapid traverse override Optional block skip Single block Machine lock Dry run Protect key Feed hold	Subsec. 11.4.13
10	Tool life data (Tool life management)	Life count	Subsec. 11.4.14

11.1 SCREENS DISPLAYED BY FUNCTION KEY POS

Press function key POS to display the current position of the tool.

The following three screens are used to display the current position of the tool:

·**Position display screen for the work coordinate system.**
·**Position display screen for the relative coordinate system.**
·**Overall position display screen.**

The above screens can also display the feedrate, run time, and the number of parts. In addition, a floating reference position can be set on these screens.

Function key POS can also be used to display the load on the servo motor and spindle motor and the rotation speed of the spindle motor (operating monitor display).

Function key POS can also be used to display the screen for displaying the distance moved by handle interruption. See Section 4.6 for details on this screen.

11.1.1 Position Display in the Workpiece Coordinate System

Displays the current position of the tool in the workpiece coordinate system. The current position changes as the tool moves. The least input increment is used as the unit for numeric values. The title at the top of the screen indicates that absolute coordinates are used.

Display procedure for the current position screen in the workpiece coordinate system

1 Press function key POS .

2 Press soft key **[ABS]**.

3 On (7 soft keys display unit), press the **[ABS]** soft key one more time to display the coordinates along axes other than the six standard axes.

- **Display with one–path control**



Explanations

- **Display including compensation values**

Bits 6 and 7 of parameter 3104 can be used to select whether the displayed values include tool offset value and tool nose radius compensation.

11.1.2 Position Display in the Relative Coordinate System

Displays the current position of the tool in a relative coordinate system based on the coordinates set by the operator. The current position changes as the tool moves. The increment system is used as the unit for numeric values. The title at the top of the screen indicates that relative coordinates are used.

Display procedure for the current position screen with the relative coordinate system

1 Press function key [POS] .

2 Press soft key **[REL]**.

- **Display with one–path control**



Explanations

- **Setting the relative coordinates**

The current position of the tool in the relative coordinate system can be reset to 0 or preset to a specified value as follows:

Procedure to set the axis coordinate to a specified value



1 Enter an axis address (such as X or Z) on the screen for the relative coordinates. The indication for the specified axis blinks and the soft keys change as shown on the left.

2
- To reset the coordinate to 0, press soft key **[ORIGIN]**. The relative coordinate for the blinking axis is reset to 0.
- To preset the coordinate to a specified value, enter the value and press soft key **[PRESET]**. The relative coordinate for the blinking axis is set to the entered value.

Procedure to reset all axes



1 Press soft key **[(OPRT)]**.

2 Press soft key **[ORIGIN]**.

3 Press soft key **[ALLEXE]**.
The relative coordinates for all axes are reset to 0.

- **Display including compensation values**

Bits 4 (DRL) and 5 (DRC) of parameter 3104 can be used to select whether the displayed values include tool offset and tool nose radius compensation.

- **Presetting by setting a coordinate system**

Bit 3 of parameter 3104 is used to specify whether the displayed positions in the relative coordinate system are preset to the same values as in the workpiece coordinate system when a coordinate system is set by a G50 (G code system A) or a G92 (G code system B or C) command or when the manual reference position return is made.

11.1.3 Overall Position Display

Displays the following positions on a screen : Current positions of the tool in the workpiece coordinate system, relative coordinate system, and machine coordinate system, and the remaining distance. The relative coordinates can also be set on this screen. See subsection III–11.1.2 for the procedure.

Procedure for displaying overall position display screen

1 Press function key [POS] .

2 Press soft key **[ALL]**.

- **Display with one–path control (7 soft keys display unit)**

```
ACTUAL POSITION          O1000 N00010
  (RELATIVE)               (ABSOLUTE)
U   246.912              X   123.456
W   913.780              Z   456.890

  (MACHINE)              (DISTANCE TO
X     0.000              GO)
Z     0.000              X     0.000
                         Z     0.000
                              PART COUNT      5
RUN TIME    0H15M    CYCLE TIME   0H 0M38S
ACT.F    3000 MM/M                  S   0 T0000

MEM **** *** ***          09:06:35
[  ABS  ] [  REL  ] [ ALL ] [  HNDL ] [(OPRT)]
```

Explanations

- **Coordinate display**

The current positions of the tool in the following coordinate systems are displayed at the same time:

- Current position in the relative coordinate system (relative coordinate)
- Current position in the work coordinate system (absolute coordinate)
- Current position in the machine coordinate system (machine coordinate)
- Distance to go (distance to go)

- **Distance to go**

The distance remaining is displayed in the MEMORY or MDI mode. The distance the tool is yet to be moved in the current block is displayed.

- **Machine coordinate system**

The least command increment is used as the unit for values displayed in the machine coordinate system. However, the least input increment can be used by setting bit 0 (MCN) of parameter 3104.

- **Resetting relative coordinates**

On the overall position display screen, relative coordinates can be reset to 0 or preset to specified values. The procedure is the same as that for resetting the relative coordinates described in III–11.1.2.

- **Displaying the sixth and subsequent axes**

On the shared screen of 12 soft keys display unit, only the coordinates for the first to fifth axes are displayed initially whenever there are six or more controlled axes. Pressing the **[ALL]** soft keys displays the coordinates for the sixth and subsequent axes. On the shared screen of 12 soft keys display unit, the tool post selection signal is used to select the display for path 1 or 2.

11.1.4 Presetting the Workpiece Coordinate System

A workpiece coordinate system shifted by an operation such as manual intervention can be preset using MDI operations to a pre–shift workpiece coordinate system. The latter coordinate system is displaced from the machine zero point by a workpiece zero point offset value.
A command (G92.1) can be programmed to preset a workpiece coordinate system. (See Subsec. III–7.2.4.)

Procedure for Presetting the Workpiece Coordinate System



1 Press function key [POS] .

2 Press soft key **[(OPRT)]**.

3 When **[WRK–CD]** is not displayed, press the continuous menu key [▷].

4 Press soft key **[WRK–CD]**.

5 Press soft key **[ALLAXS]** to preset all axes.

6 To preset a particular axis in step 5, enter the axis name ([X], [Y], ...) and [0], then press soft key **[AXS–CD]**.

Explanations

- **Operation mode**

This function can be executed when the reset state or automatic operation stop state is entered, regardless of the operation mode.

- **Presetting relative coordinates**

As with absolute coordinates, bit 3 (PPD) of parameter No. 3104 is used to specify whether to preset relative coordinates (RELATIVE).

11.1.5 Actual Feedrate Display

The actual feedrate on the machine (per minute) can be displayed on a current position display screen or program check screen by setting bit 0 (DPF) of parameter 3015. On 12 soft keys display unit, the actual feedrate is always displayed.

Display procedure for the actual feedrate on the current position display screen

1 Press function key [POS] to display a current position display screen.



Actual feedrate is displayed after ACT.F.

The actual feedrate is displayed in units of millimeter/min or inch/min (depending on the specified least input increment) under the display of the current position.

Explanations

- **Actual feedrate value**

The actual rate is calculated by the following expression:

$$Fact = \sqrt{\sum_{i=1}^{n}(fi)^2}$$

where

n : Number of axes

fi : Cutting feed rate in the tangential direction of each axis or rapid traverse rate

Fact : Actual feedrate displayed

The display unit: mm/min (metric input).
inch/min (Inch input, Two digits below the decimal point are displayed.)

The feedrate along the PMC axis can be omitted by setting bit 1 (PCF) of parameter 3105.

- **Actual feedrate display of feed per revolution**

In the case of feed per revolution and thread cutting, the actual feedrate displayed is the feed per minute rather than feed per revolution.

- **Actual feedrate display of rotary axis**

In the case of movement of rotary axis, the speed is displayed in units of deg/min but is displayed on the screen in units of input system at that time. For example, when the rotary axis moves at 50 deg/min, the following is displayed: 0.50 INCH/M

- **Actual feedrate display on the other screen**

The program check screen also displays the actual feedrate.

11.1.6 Display of Run Time and Parts Count

The run time, cycle time, and the number of machined parts are displayed on the current position display screens.

Procedure for displaying run time and parts count on the current position display screen

1 Press function key [POS] to display a current position display screen.



The number of machined parts (PART COUNT), run time (RUN TIME), and cycle time (CYCLE TIME) are displayed under the current position.

Explanations

- **PART COUNT**

  Indicates the number of machined parts. The number is incremented each time M02, M30, or an M code specified by parameter 6710 is executed.

- **RUN TIME**

  Indicates the total run time during automatic operation, excluding the stop and feed hold time.

- **CYCLE TIME**

  Indicates the run time of one automatic operation, excluding the stop and feed hold time. This is automatically preset to 0 when a cycle start is performed at reset state. It is preset to 0 even when power is removed.

- **Display on the other screen**

  Details of the run time and the number of machined parts are displayed on the setting screen. See subsection III–11.4.9.

- **Parameter setting**

  The number of machined parts and run time cannot be set on current position display screens. They can be set by parameters 6711, 6751, and 6752 or on the setting screen.

- **Incrementing the number of machined parts**

  Bit 0 (PCM) of parameter 6700 is used to specify whether the number of machined parts is incremented each time M02, M30, or an M code specified by parameter 6710 is executed, or only each time an M code specified by parameter 6710 is executed.

11.1.7 Operating Monitor Display

The reading on the load meter can be displayed for each servo axis and the serial spindle by setting bit 5 (OPM) of parameter 3111 to 1. The reading on the speedometer can also be displayed for the serial spindle.

Procedure for displaying the operating monitor

1 Press function key [POS] to display a current position display screen.

2 Press the continuous–menu key [▷].

3 Press soft key **[MONI]**.



Explanations

- **Display of the servo axes**

The reading on the load meter can be displayed for up to three servo axes by setting parameters 3151 to 3158.
When all these parameters are set to 0, data is displayed only for the basic axes.

- **Display of the spindle axes**

When serial spindles are used, the reading on the load meter and speedometer can be displayed only for the main serial spindle.

- **Unit of graph**

The bar graph for the load meter shows load up to 200% (only a value is displayed for load exceeding 200%). The bar graph for the speedometer shows the ratio of the current spindle speed to the maximum spindle speed (100%).

- **Load meter**

The reading on the load meter depends on servo parameter 2086 and spindle parameter 4127.

- **Speed meter**

Although the speedometer normally indicates the speed of the spindle motor, it can also be used to indicate the speed of the spindle by setting bit 6 (OPS) of parameter 3111 to 1.

The spindle speed to be displayed during operation monitoring is calculated from the speed of the spindle motor (see the formula below). The spindle speed can therefore be displayed, during operation monitoring, even when no position coder is used. To display the correct spindle speed, however, the maximum spindle speed for each gear (spindle speed at each gear ratio when the spindle motor rotates at the maximum speed) must be set in parameters No. 3741 to 3744.

The input of the clutch and gear signals for the first serial spindle is used to determine the gear which is currently selected. Control the input of the CTH1A and CTH2A signals according to the gear selection, by referring to the table below.

(Formula for calculating the spindle speed to be displayed)

$$\text{Spindle speed displayed during operation monitoring} = \frac{\text{Speed of spindle motor}}{\text{Maximum speed of spindle motor}} \times \text{Maximum spindle speed with the gear being used}$$

The following table lists the correspondence between clutch and gear selection signals CTH1A and CTH2A <G070#3, #2>, used to determine the gear being used, and parameters:

CTH1A	CTH2A	Parameter	Serial spindle specification
0	0	=No.3741 (Maximum spindle speed with gear 1)	HIGH
0	1	=No.3742 (Maximum spindle speed with gear 2)	MEDIUM HIGH
1	0	=No.3743 (Maximum spindle speed with gear 3)	MEDIUM LOW
1	1	=No.3744 (Maximum spindle speed with gear 4)	LOW

The speed of the spindle motor and spindle can be displayed, during operation monitoring, only for the first serial spindle and the spindle switching axis for the first serial spindle. It cannot be displayed for the second spindle.

- **Color of graph**

If the value of a load meter exceeds 100%, the bar graph turns purple.

11.2 SCREENS DISPLAYED BY FUNCTION KEY PROG (IN MEMORY MODE OR MDI MODE)

This section describes the screens displayed by pressing function key PROG in MEMORY or MDI mode.The first four of the following screens display the execution state for the program currently being executed in MEMORY or MDI mode and the last screen displays the command values for MDI operation in the MDI mode:

11.2.1 Program contents display screen
11.2.2 Current block display screen
11.2.3 Next block display screen
11.2.4 Program check screen
11.2.5 Program screen for MDI operation
11.2.6 Displaying the B–axis operation state

Function key PROG can also be pressed in MEMORY mode to display the program restart screen and scheduling screen.
See Section III–4.3 for the program restart screen.
See Section III–4.4 for the scheduling screen.

11.2.1 Program Contents Display

Displays the program currently being executed in MEMORY or MDI mode.

Procedure for displaying the program contents

1 Press function key PROG to display a program screen.

2 Press chapter selection soft key **[PRGRM]**.
The cursor is positioned at the block currently being executed.



Explanations

- **12 soft keys display unit**

On 12 soft keys display unit, the contents of the program are displayed on the right half of the screen or on the entire screen (switched each time soft key **[PRGRM]** is pressed).



11.2.2 Current Block Display Screen

Displays the block currently being executed and modal data in the MEMORY or MDI mode.

Procedure for displaying the current block display screen

1 Press function key PROG .

2 Press chapter selection soft key **[CURRNT]**.
The block currently being executed and modal data are displayed.
The screen displays up to 22 modal G codes and up to 11 G codes specified in the current block.



Explanations

- **12 soft keys display unit**

The current block display screen is not provided for 12 soft keys display unit. Press soft key **[PRGRM]** to display the contents of the program on the right half of the screen. The block currently being executed is indicated by the cursor. Modal data is displayed on the left half of the screen.
The screen displays up to 18 modal G codes.



11.2.3 Next Block Display Screen

Displays the block currently being executed and the block to be executed next in the MEMORY or MDI mode.

Procedure for displaying the next block display screen

1 Press function key PROG .

2 Press chapter selection soft key **[NEXT]**.
The block currently being executed and the block to be executed next are displayed.
The screen displays up to 11 G codes specified in the current block and up to 11 G codes specified in the next block.



11.2.4 Program Check Screen

Displays the program currently being executed, current position of the tool, and modal data in the MEMORY mode.

Procedure for displaying the program check screen

1 Press function key PROG .

2 Press chapter selection soft key **[CHECK]**.
The program currently being executed, current position of the tool, and modal data are displayed.

- **Display with one–path control**



Explanations

- **Program display**

The screen displays up to four blocks of the current program, starting from the block currently being executed. The block currently being executed is displayed in reverse video. During DNC operation, however, only three blocks can be displayed.

- **Current position display**

The position in the workpiece coordinate system or relative coordinate system and the remaining distance are displayed. The absolute positions and relative positions are switched by soft keys **[ABS]** and **[REL]**.

- **Modal G codes**

Up to 12 modal G codes are displayed.
(12 G codes for each path, on 12 soft keys display unit when two–path control is being used)

- **Displaying during automatic operation**

During automatic operation, the actual speed, SCAT, and repeat count are displayed. The key input prompt (> _) is displayed otherwise.

- **12 soft keys display unit**

The program check screen is not provided for 12 soft keys display unit. Press soft key **[PRGRM]** to display the contents of the program on the right half of the screen. The block currently being executed is indicated by the cursor. The current position of the tool and modal data are displayed on the left half of the screen.
Up to 18 modal G codes are displayed.



11.2.5 Program Screen for MDI Operation

Displays the program input from the MDI and modal data in the **MDI** mode.

Procedure for displaying the program screen for MDI operation

1 Press function key PROG .

2 Press chapter selection soft key **[MDI]**.
The program input from the MDI and modal data are displayed.



Explanations

- **MDI operation**

  See Section II–4.2 for MDI operation.

- **Modal information**

  The modal data is displayed when bit 7 (MDL) of parameter 3107 is set to 1. Up to 16 modal G codes are displayed.
  On 12 soft keys display unit, however, the contents of the program are displayed on the right half of the screen and the modal data is displayed on the left half of the screen, regardless of this parameter.

- **Displaying during automatic operation**

  During automatic operation, the actual speed, SCAT, and repeat count are displayed. The key input prompt (> _) is displayed otherwise.

11.2.6 Displaying the B–axis Operation State

Displaying the B–axis operation state

1 Press the PROG function key.

2 Press the **[CHECK]** chapter selection soft key.

3 Press the **[B–DSP]** chapter selection soft key. Then, the B–axis operation state is displayed on the program check screen. The command currently being executed and the next command are displayed.

```
PROGRAM CHECK              O0001 N00001
 M102 ;
 G00 X10. Z20. ;
 G01 X20. Z30. F1000 ;
 G04 P1000 ;
 (ABSOLUTE)  (B–AXIS)  G00   G95   G22
 X   40.000  G01(CURR) G97   G21   G80
 Z   40.000  B –200.000G90   G40   G50
 Y    0.000  F 0.1500  G69   G25   G67
 B –125.994  G00(NEXT)
             B 250.000         M         102
    T
    F     0.1000    S
 ACT.F       0   SCAT     0S    0 T0000
MEM STRT *** FIN     21:20:05
[  ABS  ][  REL  ][ B.DSP ][       ][ (OPRT) ]
```

11.3 SCREENS DISPLAYED BY FUNCTION KEY PROG (IN THE EDIT MODE)

This section describes the screens displayed by pressing function key PROG in the EDIT mode. Function key PROG in the EDIT mode can display the program editing screen and the program display screen (displays memory used and a list of programs). Pressing function key PROG in the EDIT mode can also display the conversational graphics programming screen and the floppy file directory screen. See Chapter 9, 10 for the program editing screen and conversational graphics programming screen. See Chapter 8 for the floppy file directory screen.

11.3.1 Displaying Memory Used and a List of Programs

Displays the number of registered programs, memory used, and a list of registered programs.

Procedure for displaying memory used and a list of programs

1 Select the **EDIT** mode.
For the two–path control, select the tool post for which a program is to be displayed with the tool post selection switch.

2 Press function key PROG .

3 Press chapter selection soft key **[LIB]**.



Explanations

- **Details of memory used**

PROGRAM NO. USED

PROGRAM NO. USED : The number of the programs registered (including the subprograms)

FREE : The number of programs which can be registered additionally.

MEMORY AREA USED

MEMORY AREA USED : The capacity of the program memory in which data is registered (indicated by the number of characters).

FREE : The capacity of the program memory which can be used additionally (indicated by the number of characters).

- **Program library list**

Program Nos. registered are indicated.
Also, the program name can be displayed in the program table by setting parameter NAM (No. 3107#0) to 1.

```
PROGRAM DIRECTORY              O0001 N00010

        PROGRAM(NUM.)       MEMORY(CHAR.)
    USED:       17                 4,320
    FREE:       16                 3,960
   O0001(MACRO-GCODE.MAIN)
   O0002(MACRO-GCODE.SUB1)
   O0010(TEST-PROGRAM.ARTHMETIC NO.1)
   O0020(TEST-PROGRAM.F10-MACRO)
   O0040(TEST-PROGRAM.OFFSET)
   O0050
   O0100(INCH/MM CONVERT CHECK NO.1)

> _
EDIT **** *** ***     16:52:13
[ PRGRM ][  DIR  ][       ][       ][ (OPRT) ]
```

```
PROGRAM DIRECTORY              O0001 N00010

        PROGRAM(NUM.)       MEMORY(CHAR.)
    USED:       17                 4,320
    FREE:       46                 3,960
   O NO.    SIZE (CHAR.)       DATE
   O0001         360         1966-06-12 14:40
   O0002         240         1966-06-12 14:55
   O0010         420         1966-07-01 11:02
   O0020         180         1966-08-14 09:40
   O0040       1,140         1966-03-25 18:40
   O0050          60         1966-08-26 16:40
   O0100         120         1996-04-30 13:11
> _
EDIT **** *** *** ***    16:52:13
[ PRGRM ][  DIR  ][       ][       ][ (OPRT) ]
```

- **Program name**

Always enter a program name between the control out and control in codes immediately after the program number.
Up to 31 characters can be used for naming a program within the parentheses. If 31 characters are exceeded, the exceeded characters are not displayed.
Only program number is displayed for the program without any program name.



- **Software series**

Software series of the system is displayed.
It is used for maintenance ; user is not required this information.

- **Order in which programs are displayed in the program library list**

Programs are displayed in the same order that they are registered in the program library list. However, if bit 4 (SOR) of parameter 3107 is set to 1, programs are displayed in the order of program number starting from the smallest one.

- **Order in which programs are registered**

Immediately after all programs are cleared (by turning on the power while pressing the DELETE key), each program is registered after the last program in the list.
If some programs in the list were deleted, then a new program is registered, the new program is inserted in the empty location in the list created by the deleted programs.

Example) When bit 4 (SOR) of parameter 3107 is 0

1. **After clearing all programs, register programs O0001, O0002, O0003, O0004, and O0005 in this order. The program library list displays the programs in the following order:**
   O0001, O0002, O0003, O0004, O0005
2. **Delete O0002 and O0004. The program library list displays the programs in the following order:**
   O0001, O0003, O0005
3. **Register O0009. The program library list displays the programs in the following order:**
   O0001, O0009, O0003, O0005

11.3.2 Displaying a Program List for a Specified Group

In addition to the normal listing of the numbers and names of CNC programs stored in memory, programs can be listed in units of groups, according to the product to be machined, for example.

To assign CNC programs to the same group, assign names to those programs, beginning each name with the same character string.

By searching through the program names for a specified character string, the program numbers and names of all the programs having names including that string are listed.

Procedure for Displaying a Program List for a Specified Group

Procedure

1 Enter EDIT or background editing mode.

2 Press the PROG function key.

3 Press the PROG function key or **[DIR]** soft key to display the program list.

```
PROGRAM DIRECTORY                O0001 N00010
          PROGRAM (NUM.)    MEMORY (CHAR.)
   USED:          60              3321
   FREE:           2               429

  O0020  (GEAR–1000 MAIN)
  O0040  (GEAR–1000 SUB–1)
  O0060  (SHAFT–2000 MAIN)
  O0100  (SHAFT–2000 SUB–1)
  O0200  (GEAR–1000 SUB–2)
  O1000  (FRANGE–3000 MAIN)
  O2000  (GEAR–1000 SUB–3)
  O3000  (SHAFT–2000 SUB–2)

> _
EDIT  **** *** *** ***     16:52:13
[ PRGRM ]  [  DIR  ]  [         ]  [         ]  [ (OPRT) ]
```

4 Press the **[(OPRT)]** operation soft key.



5 Press the **[GROUP]** operation soft key.

6 Press the **[NAME]** operation soft key.

7 Enter the character string corresponding to the group for which a search is to be made, using the MDI keys. No restrictions are imposed on the length of a program name. Note, however, that search is made based on only the first 32 characters.

Example: To search for those CNC programs having names that begin with character string “GEAR–1000,” enter the following:
>GEAR–1000*_



8 Pressing the **[EXEC]** operation soft key displays the group–unit program list screen, listing all those programs whose name includes the specified character string.



[Group–unit program list screen displayed when a search is made for “GEAR–1000*”]

When the program list consists of two or more pages, the pages can be changed by using a page key.

Explanations

- *** and ?**

In the above example, the asterisk (*) must not be omitted. The asterisk indicates an arbitrary character string (wild card specification).

“GEAR–1000*” indicates that the first nine characters of the target program names must be “GEAR–1000,” followed by an arbitrary character string. If only “GEAR–1000” is entered, a search is made only for those CNC programs having the nine–character name “GEAR–1000.”

A question mark (?) can be used to specify a single arbitrary character. For example, entering “????–1000” enables a search to be made for programs having names which start with four arbitrary characters, followed by “–1000”.

[Example of using wild cards]

(Entered character string)		(Group for which the search will be made)
(a)	“*”	CNC programs having any name
(b)	“*ABC”	CNC programs having names which end with “ABC”
(c)	“ABC*”	CNC programs having names which start with “ABC”
(d)	“*ABC*”	CNC programs having names which include “ABC”
(e)	“?A?C”	CNC programs having four–character names, the second and fourth characters of which are A and C, respectively
(f)	“??A?C”	CNC programs having five–character names, the third and fifth characters of which are A and C, respectively
(g)	“123*456”	CNC programs having names which start with “123” and which end with “456”

- **When the specified character string cannot be found**

If no program is located as a result of a search for an entered character string, warning message “DATA NOT FOUND” is displayed on the program list screen.

- **Holding the group for which a search is made**

A group–unit program list, generated by a search, is held until the power is turned off or until another search is performed.

- **Group for which previous search was made**

After changing the screen from the group–unit program list to another screen, pressing the **[PR–GRP]** operation soft key (displayed in step 6) redisplays the group–unit program list screen, on which the program names for the previously searched group are listed. Using this soft key eliminates the need to enter the relevant character string again to redisplay the search results after changing the screen.

Examples

Assume that the main programs and subprograms for machining gear part number 1000 all have names which include character string “GEAR–1000.” The numbers and names of those programs can be listed by searching through the names of all CNC programs for character string “GEAR–1000.” This function facilitates the management of the CNC programs stored in large–capacity memory.

11.4 SCREENS DISPLAYED BY FUNCTION KEY OFFSET SETTING

Press function key OFFSET SETTING to display or set tool compensation values and other data.
This section describes how to display or set the following data:

1. Tool offset value
2. Settings
3. Run time and part count
4. Workpiece origin offset value or workpiece coordinate system shift value
5. Custom macro common variables
6. Software operator's panel
7. Tool life management data

This section also describes following functions.

- Direct input of tool offset value
- Direct input of tool offset value measured B
- Counter input of offset value
- Direct input of workpiece coordinate system shift
- Y axis offset
- Sequence number comparison and stop function

The following functions depend on the specifications of the machine tool builder. See the manual issued by the machine tool builder for details.

- Direct input of tool offset value
- Direct input of tool offset value measured B
- Software operator's panel
- Tool life management data

11.4.1 Setting and Displaying the Tool Offset Value

Dedicated screens are provided for displaying and setting tool offset values and tool nose radius compensation values.

Procedure for setting and displaying the tool offset value and the tool nose radius compensation value

1 Press function key [OFFSET SETTING] .

For the two–path control, select the tool post for which tool compensation values are to be displayed with the tool post selection switch.

2 Press chapter selection soft key **[OFFSET]** or press [OFFSET SETTING] several times until the tool compensation screen is displayed.
Different screens are displayed depending on whether tool geometry offset, wear offset, or neither is applied.

```
OFFSET                              O0001 N00000
   NO.          X              Z.          R      T
   001       0.000          10.000       0.000    0
   002        0.000          0.000       0.000    0
   003        0.000          0.000       0.000    0
   004       40.000         -40.000      0.000    0
   005        0.000          0.000       0.000    0
   006        0.000          0.000       0.000    0
   007        0.000          0.000       0.000    0
   008        0.000          0.000       0.000    0
ACTUAL POSITION (RELATIVE)
    U   101.000              W   202.094

> _
MDI **** *** ***      16:05:59
[ OFFSET ][ SETING ][ WORK ][     ][ (OPRT) ]
```

Without tool geometry/wear offset

```
OFFSET/GEOMETRY                     O0001 N00000
   NO.          X              Z.          R      T
 G 001       0.000          1.000       0.000    0
 G 002        1.486        -49.561       0.000    0
 G 003        1.486        -49.561       0.000    0
 G 004        1.486          0.000       0.000    0
 G 005        1.486        -49.561       0.000    0
 G 006        1.486        -49.561       0.000    0
 G 007        1.486        -49.561       0.000    0
 G 008        1.486        -49.561       0.000    0
ACTUAL POSITION (RELATIVE)
    U   101.000              W   202.094

> _
MDI **** *** ***      16:05:59
[ WEAR ][  GEOM  ][ WORK ][     ][ (OPRT) ]
```

With tool geometry offset



With tool wear offset

3 Move the cursor to the compensation value to be set or changed using page keys and cursor keys, or enter the compensation number for the compensation value to be set or changed and press soft key **[NO.SRH]**.

4 To set a compensation value, enter a value and press soft key **[INPUT]**. To change the compensation value, enter a value to add to the current value (a negative value to reduce the current value) and press soft key **[+INPUT]**. Or, enter a new value and press soft key **[INPUT]**.
TIP is the number of the virtual tool tip (see Programming).
TIP may be specified on the geometry compensation screen or on the wear compensation screen.

Explanations

- **Decimal point input**

A decimal point can be used when entering a compensation value.

- **Other method**

An external input/output device can be used to input or output a cutter compensation value. See Chapter III–8.
Tool length compensation values can be set using the following functions described in subsequent subsections: direct input of tool offset value, direct–input function B for tool offset measured, and counter input of offset value.

- **Tool offset memory**

16 groups are provided for tool compensation. The number of groups can be optionally extended to 32, 64. For the two–path control, the above number of groups can be used for each tool post. Tool geometry compensation or wear compensation can be selected for each group.

- **Disabling entry of compensation values**

In some cases, tool wear compensation or tool geometry compensation values cannot be input because of the settings in bits 0 (WOF) and 1 (GOF) of parameter 3290. The input of tool compensation values from the MDI can be inhibited for a specified range of offset numbers. The first offset number for which the input of a value is inhibited is set in parameter No. 3294. The number of offset numbers, starting from the specified first number, for which the input of a value is inhibited is set in parameter No. 3295.
Consecutive input values are set as follows:

1) When values are input for offset numbers, starting from one for which input is not inhibited to one for which input is inhibited, a warning is issued and values are set only for those offset numbers for which input is not inhibited.
2) When values are input for offset numbers, starting from one for which input is inhibited to one for which input is not inhibited, a warning is issued and no values are set.

- **Displaying radius and TIP**

The radius and TIP are not displayed if the tool tip radius compensation option is not displayed.

- **Changing offset values during automatic operation**

When offset values have been changed during automatic operation, bit 4 (LGT) and bit 6 (LWM) of parameter 5002 can be used for specifying whether new offset values become valid in the next move command or in the next T code command.

LGT	LWM	When geometry compensation values and wear compensation values are separately specified	When geometry compensation values and wear compensation values are not separately specified
0	0	Become valid in the next T code block	Become valid in the next T code block
1	0	Become valid in the next T code block	Become valid in the next T code block
0	1	Become valid in the next T code block	Become valid in the next move command
1	1	Become valid in the next move command	Become valid in the next move command

11.4.2 Direct Input of Tool Offset Value

To set the difference between the tool reference position used in programming (the nose of the standard tool, turret center, etc.) and the tool tip position of a tool actually used as an offset value

Procedure for direct input of tool offset value

- **Setting of Z axis offset value**

1 Cut surface A in manual mode with an actual tool.
Suppose that a workpiece coordinate system has been set.



2 Release the tool in X axis direction only, without moving Z axis and stop the spindle.

3 Measure distance β from the zero point in the workpiece coordinate system to surface A.
Set this value as the measured value along the Z–axis for the desired offset number, using the following procedure:

```
OFFSET/GEOMETRY                    O0001 N00000
   NO.          X          Z.          R      T
 G 001        0.000        1.000       0.000   0
 G 002        1.486      -49.561       0.000   0
 G 003        1.486      -49.561       0.000   0
 G 004        1.486        0.000       0.000   0
 G 005        1.486      -49.561       0.000   0
 G 006        1.486      -49.561       0.000   0
 G 007        1.486      -49.561       0.000   0
 G 008        1.486      -49.561       0.000   0
ACTUAL POSITION (RELATIVE)
    U     0.000              W     0.000
    V     0.000              H     0.000

>MZ120._
MDI **** *** ***      16:05:59
[NO,SRH][ MEASUR ][ INP.C. ][ +INPUT ][ INPUT ]
```

3–1 Press the function key OFFSET SETTING or the soft key **[OFFSET]** to display the tool compensation screen. If geometry compensation values and wear compensation values are separately specified, display the screen for either of them.

3–2 Move the cursor to the set offset number using cursor keys.

3–3 Press the address key [Z] to be set.

3–4 Key in the measured value (β).

3–5 Press the soft key **[MESURE]**.
The difference between measured value β and the coordinate is set as the offset value.

- **Setting of X axis offset value**

4 Cut surface B in manual mode.

5 Release the tool in the Z–axis direction without moving the X–axis and stop the spindle.

6 Measure the diameter α of surface B.
Set this value as the measured value along the X–axis for the desired offset number in the same way as when setting the value along the Z–axis.

7 Repeat above procedure the same time as the number of the necessary tools. The offset value is automatically calculated and set.
For example, in case α=69.0 when the coordinate value of surface B in the diagram above is 70.0, set 69.0 **[MEASURE]** at offset No.2.
In this case, 1.0 is set as the X–axis offset value to offset No.2.

Explanations

- **Compensation values for a program created in diameter programming**

Enter diameter values for the compensation values for axes for which diameter programming is used.

- **Tool geometry offset value and tool wear offset value**

If measured values are set on the tool geometry compensation screen, all compensation values become geometry compensation values and all wear compensation values are set to 0. If measured values are set on the tool wear compensation screen, the differences between the measured compensation values and the current wear compensation values become the new compensation values.

- **Retracting along two axes**

If a record button is provided on the machine, the tool can retract along two axes when bit 2 (PRC) of parameter 5005 is set and the record signal is used. Refer to the appropriate manual issued by the machine tool builder.

11.4.3 Direct Input of Tool Offset Measured B

The direct input function B for tool offset measured is used to set tool compensation values and workpiece coordinate system shift values.

Procedure for setting the tool offset value

Tool position offset values can be automatically set by manually moving the tool until it touches the sensor.
Refer to the appropriate manual issued by the machine tool builder for actual operation.

1 Execute manual reference position return.
By executing manual reference position return, a machine coordinate system is established.
The tool offset value is computed on the machine coordinate system.

2 Set the offset writing mode signal GOQSM to HIGH.
(Refer to the appropriate manual issued by the machine tool builder for actual operation.)
The CRT display is automatically changed to the tool offset screen (geometry), and the “OFST” indicator starts blinking in the status indication area in the bottom of the screen, which informs that the offset writing mode is ready.

3 Select a tool to be measured.

4 When the cursor is not coincided with the tool offset number desired to be set, move the cursor to the desired offset number by page key and cursor key.
Besides the cursor can also be coincided with the tool offset number desired to set automatically by the tool offset number input signals (when parameter QNI(No.5005#5)=1).
In this case, the position of the cursor cannot be changed on the tool compensation screen using page keys or cursor keys.

5 Near the tool to the sensor by manual operation.

6 Place the tool edge to a contacting surface of the sensor by manual handle feed.
Bring the tool edge in contact with the sensor. This causes the offset writing signals (+MIT1, –MIT1, +MIT2 or –MIT2) to input to CNC.
The offset writing signal is set to HIGH, and the :

- The axis is interlocked in this direction and its feeding is stopped.
- The tool offset value extracted by the tool offset memory (tool geometry offset value) which corresponds to the offset number shown by the cursor is set up.

7 For both X–axis and Z–axis, their offset value are set by the operations **5** and **6**.

8 Repeat operations **3** to **7** for necessary tools.

9 Set the offset writing signal mode GOQSM to LOW.
The writing mode is canceled and the blinking “OFST” indicator light goes off.

Procedure for setting the work coordinate system shift amount

Tool position offset values can be automatically set by manually moving the tool until it touches the sensor.
Refer to the appropriate manual issued by the machine tool builder for actual operation.

1 The tool compensation values are then calculated based on the machine coordinates of the tool.

2 Execute manual reference position return.
By executing manual reference position return, the machine coordinate system is established.
The workpiece coordinate system shifting amount is computed based on the machine coordinate system of the tool.

3 Set the workpiece coordinate system shifting amount writing signal mode WOQSM to HIGH.
(Refer to the appropriate manual issued by the machine tool builder for actual operation.)
The CRT display is automatically switches to the workpiece shifting screen, the “WFST” indicator starts blinking at the status indicator area in the bottom of the screen, which inform that the workpiece coordinate system shifting amount writing mode is ready.

4 Select a tool to be measured.

5 Check tool offset numbers.
The tool offset number corresponding to the tool required for measurement, shall be set in the parameter (No.5020) in advance.
Besides the tool offset number can be set automatically by setting the tool offset number input signal (with parameter QNI(No.5005#5)=1).
Refer to the appropriate manual issued by the machine tool builder for details.

6 Manually approach the tool to an end face of the workpiece.

7 Place the tool edge to the end face (sensor) of the workpiece by manual handle feed.
The workpiece coordinate system shifting amount on the Z–axis is automatically set.

8 Feed the tool.

9 Set the workpiece coordinate system shifting amount writing signal mode WOQSM to LOW.
The writing mode is canceled and the blinking “WSFT” indicator light goes off.
(Refer to the appropriate manual issued by the machine tool builder for actual operation.)

11.4.4 Counter Input of Offset value

By moving the tool until it reaches the desired reference position, the corresponding tool offset value can be set.

Procedure for counter input of offset value

1 Manually move the reference tool to the reference position.

2 Reset the relative coordinates along the axes to 0 (see subsec. III–11.1.2).

3 Move the tool for which offset values are to be set to the reference position.

4 Select the tool compensation screen. Move the cursor to the offset value to be set using cursor keys.

```
OFFSET/GEOMETRY                    O0001 N00000
   NO.          X          Z.          R      T
 G 001        0.000       1.000       0.000   0
 G 002        1.486     -49.561       0.000   0
 G 003        1.486     -49.561       0.000   0
 G 004        1.486       0.000       0.000   0
 G 005        1.486     -49.561       0.000   0
 G 006        1.486     -49.561       0.000   0
 G 007        1.486     -49.561       0.000   0
 G 008        1.486     -49.561       0.000   0
ACTUAL POSITION (RELATIVE)
    U     0.000              W     0.000
    V     0.000              H     0.000

>X_
HND **** *** ***      16:05:59
[NO,SRH][ MEASUR ][ INP.C. ][ +INPUT ][ INPUT ]
```

5 Press address key [X] (or [Z]) and the soft key **[INP.C.]**.

Explanations

- **Geometry offset and wear offset**

When the above operations are performed on the tool geometry compensation screen, tool geometry compensation values are input and tool wear compensation values do not change.
When the above operations are performed on the tool wear compensation screen, tool wear compensation values are input and tool geometry compensation values do not change.

11.4.5 Setting the Workpiece Coordinate System Shifting Amount

The set coordinate system can be shifted when the coordinate system which has been set by a G50 command (or G92 command for G code system B or C) or automatic coordinate system setting is different from the workpiece coordinate system assumed at programming.

Procedure for setting the workpiece coordinate system shifting amount

1 Press function key [OFFSET SETTING].

2 Press the continuous menu key [▷] several times until the screen with soft key **[WK.SHFT]** is displayed.

```
WORK SHIFT                              O0001 N00000

   (SHIFT VALUE)  (MEASUREMENT)
    X     0.000    X     0.000
    Z     0.000    Z     0.000




 ACTUAL POSITION (RELATIVE)
     U     0.000          W     0.000

> MZ100._                                S   0  T0000
MDI **** *** ***      16:05:59
[      ][ WK.SHFT ][      ][ +INPUT ][ INPUT ]
```

3 Press soft key **[WK.SHFT]**.

4 Move the cursor using cursor keys to the axis along which the coordinate system is to be shifted.

5 Enter the shift value and press soft key **[INPUT]**.



Explanations

- **When shift values become valid**

  Shift values become valid immediately after they are set.

- **Shift values and coordinate system setting command**

  Setting a command (G50 or G92) for setting a coordinate system disables the set shift values.

  Example When G50 X100.0 Z80.0; is specified, the coordinate system is set so that the current tool reference position is X = 100.0, Z = 80.0 regardless of the shift values.

- **Shift values and coordinate system setting**

  If the automatic coordinate system setting is performed by manual reference position return after shift amount setting, the coordinate system is shifted instantly.

- **Diameter or radius value**

  Whether the shift amount on the X axis is diameter or radius value depends on that specified in program.

Examples

When the actual position of the reference point is X = 121.0 (diameter), Z = 69.0 with respect to the workpiece origin but it should be X = 120.0, Z = 70.0, set the following shift values:
X=1.0, Z=–1.0



11.4.6 Y Axis Offset

Tool position offset values along the Y–axis can be set. Counter input of offset values is also possible.
Direct input of tool offset value and direct input function B for tool offset measured are not available for the Y–axis.

Procedure for setting the tool offset value of the Y axis

1 Press function key OFFSET SETTING .

2 Press the continuous menu key ▷ several times until the screen with soft key **[OFST.2]** is displayed.

3 Press soft key **[OFST.2]**.
The Y axis offset screen is displayed.

```
 OFFSET                              O0001 N00000
    NO.       Y
    01     10.000
    02      0.000
    03      0.000
    04     40.000
    05      0.000
    06      0.000
    07      0.000
    08      0.000
 ACTUAL POSITION (RELATIVE)
     U   100.000         W   100.000

>_
 MDI **** *** ***      16:05:59
[ OFST.2 ][ W.SHFT ][      ][       ][ (OPRT) ]
```

3–1 Press soft key **[GEOM]** to display the tool geometry compensation values along the Y–axis.

```
 OFFSET/GEOMETRY                     O0001 N00000
    NO.       Y
  G 01     10.000
  G 02      0.000
  G 03      0.000
  G 04     40.000
  G 05      0.000
  G 06      0.000
  G 07      0.000
  G 08      0.000
 ACTUAL POSITION (RELATIVE)
     U   100.000         W   100.000

>_
 MDI **** *** ***      16:05:59
[  WEAR  ][ GEOM ][      ][       ][ (OPRT) ]
```

3–2 Press soft key **[WEAR]** to display the tool wear compensation values along the Y–axis.



4 Position the cursor at the offset number to be changed by using either of the following methods:

- Move the cursor to the offset number to be changed using page keys and cursor keys.
- Type the offset number and press soft key **[NO.SRH]**.

5 Type the offset value.

6 Press soft key **[WEAR]**. The offset value is set and displayed.



Procedure for counter input of the offset value

To set relative coordinates along the Y–axis as offset values:

1 Move the reference tool to the reference point.

2 Reset relative coordinate Y to 0 (see subsec. III–11.1.2).

3 Move the tool for which offset values are to be set to the reference point.

4 Move the cursor to the value for the offset number to be set, press [Y], then press soft key **[INP.C.]**.
Relative coordinate Y (or V) is now set as the offset value.

11.4.7 Displaying and Entering Setting Data

Data such as the TV check flag and punch code is set on the setting data screen. On this screen, the operator can also enable/disable parameter writing, enable/disable the automatic insertion of sequence numbers in program editing, and perform settings for the sequence number comparison and stop function.
See Chapter III–10 for automatic insertion of sequence numbers.
See subsection III–11.4.8 for the sequence number comparison and stop function. This subsection describes how to set data.

Procedure for setting the setting data

1 Select the **MDI** mode.

2 Press function key [OFFSET SETTING] .

3 Press soft key **[SETING]** to display the setting data screen.
This screen consists of several pages.
Press page key [PAGE ↑] or [PAGE ↓] until the desired screen is displayed.
An example of the setting data screen is shown below.

```
SETTING (HANDY)                    O0001 N00000

  PARAMETER WRITE = 1 (0:DISABLE 1:ENABLE)
  TV CHECK =        0 (0:OFF   1:ON)
  PUNCH CODE =      1 (0:EIA   1:ISO)
  INPUT UNIT =      0 (0:MM    1:INCH)
  I/O CHANNEL =     0 (0–3:CHANNEL NO.)
  SEQUENCE NO. =    0 (0:OFF   1:ON)
  TAPE FORMAT =     0 (0:NO CNV  1:F15)
  SEQUENCE STOP =   0 (PROGRAM NO.)
  SEQUENCE STOP =   0 (SEQUENCE NO.)


> _
MDI **** *** ***      16:05:59
[ OFFSET ][ SETING ][ WORK ][     ][ (OPRT) ]
```

```
SETTING (HANDY)                    O0001 N00000

  MIRROR IMAGE X= 0 (0:OFF   1:ON)
  MIRROR IMAGE Z= 0 (0:OFF   1:ON)









> _
MDI **** *** ***      16:05:59
[ OFFSET ][ SETING ][ WORK ][     ][ (OPRT) ]
```

4 Move the cursor to the item to be changed by pressing cursor keys [↑], [↓], [←], or [→].

5 Enter a new value and press soft key **[INPUT]**.

Contents of settings

- **PARAMETER WRITE**

  Setting whether parameter writing is enabled or disabled.
  0 : Disabled
  1 : Enabled

- **TV CHECK**

  Setting to perform TV check.
  0 : No TV check
  1 : Perform TV check

- **PUNCH CODE**

  Setting code when data is output through reader puncher interface.
  0 : EIA code output
  1 : ISO code output

- **INPUT UNIT**

  Setting a program input unit, inch or metric system
  0 : Metric
  1 : Inch

- **I/O CHANNEL**

  Using channel of reader/puncher interface.
  0 : Channel 0
  1 : Channel 1
  2 : Channel 2
  3 : Channel 3

- **SEQUENCE STOP**

  Setting of whether to perform automatic insertion of the sequence number or not at program edit in the EDIT mode.
  0 : Does not perform automatic sequence number insertion.
  1 : Perform automatic sequence number insertion.

- **TAPE FORMAT**

  Setting the F15 tape format conversion.
  0 : Tape format is not converted.
  1 : Tape format is converted.
  See PROGRAMMING for the F15 tape format.

- **SEQUENCE STOP**

  Setting the sequence number with which the operation stops for the sequence number comparison and stop function and the number of the program to which the sequence number belongs

- **MIRROR IMAGE**

  Setting of mirror image ON/OFF for each axes.
  0 : Mirror image off
  1 : Mirror image on

- **Others**

  Page key [PAGE↑] or [PAGE↓] can also be pressed to display the SETTING (TIMER) screen. See subsection III–11.4.9 for this screen.

11.4.8 Sequence Number Comparison and Stop

If a block containing a specified sequence number appears in the program being executed, operation enters single block mode after the block is executed.

Procedure for sequence number comparison and stop

1 Select the **MDI** mode.

2 Press function key

.

3 Press chapter selection soft key **[SETING]**.

4 Press page key

or

several times until the following screen is displayed.

```
SETTING (HANDY)                    O0001 N00000

  PARAMETER WRITE = 1 (0:DISABLE 1:ENABLE)
  TV CHECK        = 0 (0:OFF   1:ON)
  PUNCH CODE      = 1 (0:EIA   1:ISO)
  INPUT UNIT      = 0 (0:MM    1:INCH)
  I/O CHANNEL     = 0 (0–3:CHANNEL NO.)
  SEQUENCE NO.    = 0 (0:OFF   1:ON)
  TAPE FORMAT     = 0 (0:NO CNV  1:F10/11)
  SEQUENCE STOP   = 0 (PROGRAM NO.)
  SEQUENCE STOP   = 11(SEQUENCE NO.)


> _
MDI **** *** ***      16:05:59
[ OFFSET ][ SETING ][ WORK ][     ][ (OPRT) ]
```

5 Enter in (PROGRAM NO.) for SEQUENCE STOP the number (1 to 9999) of the program containing the sequence number with which operation stops.

6 Enter in (SEQUENCE NO.) for SEQUENCE STOP (with five or less digits) the sequence number with which operation is stopped.

7 When automatic operation is executed, operation enters single block mode at the block containing the sequence number which has been set.

Explanations

- **Sequence number after the program is executed**

After the specified sequence number is found during the execution of the program, the sequence number set for sequence number compensation and stop is decremented by one. When the power is turned on, the setting of the sequence number is 0.

- **Exceptional blocks**

If the predetermined sequence number is found in a block in which all commands are those to be processed within the CNC control unit, the execution does not stop at that block.

Example

```
N1 #1=1 ;
N2 IF [#1 EQ 1] GOTO 08 ;
N3 GOTO 09 ;
N4 M98 P1000 ;
N5 M99 ;
```

In the example shown above, if the predetermined sequence number is found, the execution of the program does not stop.

- **Stop in the canned cycle**

If the predetermined sequence number is found in a block which has a canned–cycle command, the execution of the program stops after the return operation is completed.

- **When the same sequence number is found several times in the program**

If the predetermined sequence number appears twice or more in a program, the execution of the program stops after the block in which the predetermined sequence number is found for the first time is executed.

- **Block to be repeated a specified number of times**

If the predetermined sequence number is found in a block which is to be executed repeatedly, the execution of the program stops after the block is executed specified times.

11.4.9 Displaying and Setting Run Time, Parts Count, and Time

Various run times, the total number of machined parts, number of parts required, and number of machined parts can be displayed. This data can be set by parameters or on this screen (except for the total number of machined parts and the time during which the power is on, which can be set only by parameters).
This screen can also display the clock time. The time can be set on the screen.

Procedure for Displaying and Setting Run Time, Parts Count and Time

1 Select the MDI mode.

2 Press function key [OFFSET SETTING] .

3 Press chapter selection soft key **[SETING]**.

4 Press page key [PAGE ↑] or [PAGE ↓] several times until the following screen is displayed.

```
SETTING (TIMER)                    O0001 N00000

    PARTS TOTAL     =         14
    PARTS REQUIRED  =          0
    PARTS COUNT     =         23

    POWER ON        =      4H 31M
    OPERATING TIME  =      0H  0M  0S
    CUTTING TIME    =      0H 37M  5S
    FREE PURPOSE    =      0H  0M  0S
    CYCLE TIME      =      0H  0M  0S
               DATE =  1993/07/05
               TIME =    11:32:52

> _                                S   0  T0000
MDI **** *** ***       16:05:59
[ OFFSET ][ SETING ][ WORK ][     ][ (OPRT) ]
```

5 To set the number of parts required, move the cursor to PARTS REQUIRED and enter the number of parts to be machined.

6 To set the clock, move the cursor to DATE or TIME, enter a new date or time, then press soft key **[INPUT]**.

Display items

- **PARTS TOTAL**

This value is incremented by one when M02, M30, or an M code specified by parameter 6710 is executed. This value cannot be set on this screen. Set the value in parameter 6712.

- **PARTS REQUIRED**

It is used for setting the number of machined parts required.
When the “0” is set to it, there is no limitation to the number of parts. Also, its setting can be made by the parameter (NO. 6713).

- **PARTS COUNT**

  This value is incremented by one when M02, M30, or an M code specified by parameter 6710 is executed. The value can also be set by parameter 6711. In general, this value is reset when it reaches the number of parts required. Refer to the manual issued by the machine tool builder for details.

- **POWER ON**

  Displays the total time which the power is on. This value cannot be set on this screen but can be preset in parameter 6750.

- **OPERATING TIME**

  Indicates the total run time during automatic operation, excluding the stop and feed hold time.
  This value can be preset in parameter 6751 or 6752.

- **CUTTING TIME**

  Displays the total time taken by cutting that involves cutting feed such as linear interpolation (G01) and circular interpolation (G02 or G03). This value can be preset in parameter 6753 or 6754.

- **FREE PURPOSE**

  This value can be used, for example, as the total time during which coolant flows. Refer to the manual issued by the machine tool builder for details.

- **CYCLE TIME**

  Indicates the run time of one automatic operation, excluding the stop and feed hold time. This is automatically preset to 0 when a cycle start is performed at reset state. It is preset to 0 even when power is removed.

- **DATA and TIME**

  Displays the current date and time. The date and time can be set on this screen.

Explanations

- **Usage**

  When the command of M02 or M30 is executed, the total number of machined parts and the number of machined parts are incremented by one. Therefore, create the program so that M02 or M30 is executed every time the processing of one part is completed. Furthermore, if an M code set to the parameter (NO. 6710) is executed, counting is made in the similar manner. Also, it is possible to disable counting even if M02 or M30 is executed (parameter PCM (No. 6700#0) is set to 1). For details, see the manual issued by machine tool builders.

Restrictions

- **Run time and part count settings**

  Negative value cannot be set. Also, the setting of “M” and “S” of run time is valid from 0 to 59.
  Negative value may not be set to the total number of machined parts.

- **Time settings**

  Neither negative value nor the value exceeding the value in the following table can be set.

Item	Maximum value	Item	Maximum value
Year	2085	Hour	23
Month	12	Minute	59
Day	31	Second	59

11.4.10 Displaying and Setting the Workpiece Origin Offset Value

Displays the workpiece origin offset for each workpiece coordinate system (G54 to G59) and external workpiece origin offset. The workpiece origin offset and external workpiece origin offset can be set on this screen.

Procedure for Displaying and Setting the Workpiece Origin Offset Value

1 Press function key OFFSET SETTING .

2 Press chapter selection soft key **[WORK]**.
The workpiece coordinate system setting screen is displayed.



3 The screen for displaying the workpiece origin offset values consists of two or more pages. Display a desired page in either of the following two ways:

Press the page up PAGE or page down PAGE key.

Enter the workpiece coordinate system number (0: external workpiece origin offset, 1 to 6: workpiece coordinate systems G54 to G59) and press operation selection soft key **[NO.SRH]**.

4 Turn off the data protection key to enable writing.

5 Move the cursor to the workpiece origin offset to be changed.

6 Enter a desired value by pressing numeric keys, then press soft key **[INPUT]**. The entered value is specified in the the workpiece origin offset value. Or, by entering a desired value with numeric keys and pressing soft key **[+INPUT]**, the entered value can be added to the previous offset value.

7 Repeat **5** and **6** to change other offset values.

8 Turn on the data protection key to disable writing.

11.4.11 Direct Input of Measured Workpiece Origin Offsets

This function is used to compensate for the difference between the programmed workpiece coordinate system and the actual workpiece coordinate system. The measured offset for the origin of the workpiece coordinate system can be input on the screen such that the command values match the actual dimensions.
Selecting the new coordinate system matches the programmed coordinate system with the actual coordinate system.

Procedure for Inputting of Measured Workpiece Origin Offsets



1 When the workpiece is shaped as shown above, cut surface A manually.

2 Move the tool along the X axis without changing the Z coordinate then stop the spindle.

3 Measure distance β between surface A and the programmed origin of the workpiece coordinate system as shown above.

4 Press function key OFFSET SETTING .

5 To display the workpiece origin offset setting screen, press the chapter selection soft key **[WORK]**.



6 Position the cursor to the workpiece origin offset value to be set.

7 Press the address key for the axis along which the offset is to be set (Z–axis in this example).

8 Enter the measured value (β) then press the **[MEASUR]** soft key.

9 Cut surface B manually.

10 Move the tool along the Z axis without changing the X coordinate then stop the spindle.

11 Measure the diameter of surface A (α) then enter the diameter at X.

Restrictions

- **Consecutive input**

  Offsets for two or more axes cannot be input at the same time.

- **During program execution**

  This function cannot be used while a program is being executed.

- **Effect from other shift value**

  Any shift specified for the workpiece coordinate system or external offset remains effective when this function is used.

11.4.12 Displaying and Setting Custom Macro Common Variables

Displays common variables (#100 to #149 or #100 to #199, and #500 to #531 or #500 to #999) on the CRT. When the absolute value for a common variable exceeds 99999999, ******** is displayed. The values for variables can be set on this screen. Relative coordinates can also be set to variables.

Procedure for displaying and setting custom macro common variables



1 Press function key [OFFSET SETTING].

2 Press the continuous menu key [▷], then press chapter selection soft key **[MACRO]**.The following screen is displayed:

```
VARIABLE                                O0001 N00000
  NO.      DATA         NO.       DATA
  100    1000.000       108        0.000
  101       0.000       109    40000.000
  102  -50000.000       110    153020.00
  103       0.000       111     0001.000
  104   1238501.0       112        0.000
  105       0.000       113    20000.000
  106       0.000       114        0.000
  107       0.000       115        0.000
 ACTUAL POSITION (RELATIVE)
    U0.000                W 0.000

> _                                 S   0  T0000
MDI **** *** ***       16:05:59
[ NO.SRH ][     ][ INP.C. ][     ][ INPUT ]
```

3 Move the cursor to the variable number to set using either of the following methods:
– Enter the variable number and press soft key **[NO.SRH]**.
– Move the cursor to the variable number to set by pressing page keys [PAGE↑] and/or [PAGE↓] and cursor keys [↑], [↓], [←], and/or [→].

4 Enter data with numeric keys and press soft key **[INPUT]**.

5 To set a relative coordinate in a variable, press address key [X] or [Z], then press soft key **[INP.C.]**.

6 To set a blank in a variable, just press soft key **[INPUT]**. The value field for the variable becomes blank.

11.4.13 Displaying and Setting the Software Operator's Panel

With this function, functions of the switches on the machine operator's panel can be controlled from the MDI panel.
Jog feed can be performed using numeric keys.

Procedure for displaying and setting the software operator's panel



1 Press function key [OFFSET SETTING].

2 Press the continuous menu key [▷], then press chapter selection soft key **[OPR]**.

3 The screen consists of several pages.
Press page key [PAGE ↑] or [PAGE ↓] until the desired screen is displayed.

```
OPERATOR'S PANEL                O0000 N00000

 MODE :  MDI  MEM  EDIT  HND  JOG  REF
 HANDLE AXIS : HX   HZ   HC   HY
 STEP MULTI. : *1   *10  *100
 RAPID OVRD. : 100%  50%   25%  F0
 JOG OVRD    :   2.0%
              **************
 FEED OVRD.  :  100%
              ***
 ACTUAL POSITION (ABSOLUTE)
     X     0.000        Z     0.000

>_
REF **** *** ***       16:05:59
[  MACRO  ][  MEMu  ][ OPR  ][      ][      ]
```

```
OPERATOR'S PANEL                O0000 N00000

BLOCK SKIP :              OFF ■ON
SINGLE BLOCK :           ■OFF   ON
MACHINE LOCK :            OFF ■ON
PROTECT KEY  :           ■PROTECT    RELEASE
FEED HOLD    :           ■OFF

ACTUAL POSITION (ABSOLUTE)
     X     0.000        Z     0.000




MDI **** *** ***       16:05:59
[  MACRO  ][  MENU  ][ OPR  ][      ][      ]
```

4 Move the cursor to the desired switch by pressing cursor key [↑] or [↓].

5 Push the cursor move key ⬅ or ➡ to match the mark ■ to an arbitrary position and set the desired condition.

6 Press one of the following arrow keys to perform jog feed. Press the 5 key together with an arrow key to perform manual continuous rapid traverse.



Explanations

- **Valid operations**

The valid operations on the software operator's panel are shown below. Whether to use the CRT or machine operator's panel for each group of operations can be selected by parameter 7200.

Group1 : Mode selection
Group2 : Selection of jog feed axis, manual continuous rapid traverse
Group3 : Selection of manual pulse generator feed axis, selection of manual pulse magnification x1, x10, x100
Group4 : Jog federate, federate override, rapid traverse override
Group5 : Optional block skip, single block, machine lock, dry run
Group6 : Protect key
Group7 : Feed hold

- **Display**

The groups for which the machine operator's panel is selected by parameter 7200 are not displayed on the software operator's panel.

- **Screens on which jog feed is valid**

When the screen indicates other than the software operator's panel screen and diagnostic screen, jog feed is not conducted even if the arrow key is pushed.

- **Jog feed and arrow keys**

The feed axis and direction corresponding to the arrow keys can be set with parameters (Nos. 7210 to 7217).

- **General purpose switches**

Eight optionally definable switches are added as an extended function of the software operator's panel. The name of these switches can be set by parameters as character strings of max. 8 characters. For the meanings of these switches, refer to the manual issued by machine tool builder.

11.4.14 Displaying and Setting Tool Life Management Data

Tool life data can be displayed to inform the operator of the current state of tool life management. Groups which require tool changes are also displayed. The tool life counter for each group can be preset to an arbitrary value. Tool data (execution data) can be reset or cleared. To register or modify tool life management data, a program must be created and executed. See Explanations in this section for details.

Procedure for display and setting the tool life management data



1 Press function key [OFFSET SETTING] .

2 Press the continuous menu key [▷] to display chapter selection soft key **[TOOLLF]**.

3 Press soft key **[TOOLLF]**.

4 One page displays data on two groups. Pressing page key [PAGE ↓] or [PAGE ↑] successively displays data on the following groups. Up to four group Nos., for which the Tool Change signal is being issued, are displayed at the bottom of each page. An arrow shown in the figure is displayed for five or more groups, if exists.

```
TOOL LIFE DATA  :                O3000 N00060
                      SELECTED GROUP 000
 GROUP  001 : LIFE   0150   COUNT   0000
   0034 0078 0012 0056
   0090 0035 0026 0061
   0000 0000 0000 0000
   0000 0000 0000 0000

 GROUP  002 : LIFE   1400   COUNT   0000
   0062 0024 0044 0074
   0000 0000 0000 0000
   0000 0000 0000 0000
   0000 0000 0000 0000
  TO BE CHANGED  : 003 004 005 006 --->
> _
MEM **** *** ***      16:05:59
[ MACRO ][     ][  OPR  ][ TOOLLF ][ (OPRT) ]
```

5 To display the page containing the data for a group, enter the group number and press soft key **[NO.SRH]**.
The cursor can be moved to an arbitrary group by pressing cursor key [↑] or [↓] .

6 To change the value in the life counter for a group, move the cursor to the group, enter a new value (four digits), and press **[INPUT]**. The life counter for the group indicated by the cursor is preset to the entered value. Other data for the group is not changed.

7 To reset the tool data, move the cursor on the group to reset, then press the **[(OPRT)]**, **[CLEAR]**, and **[EXEC]** soft keys in this order.
All execution data for the group indicated by the cursor is cleared together with the marks (@, #, or *).

Explanations

- **Registering tool life management data**

The tool life management data must be executed to register it in the CNC memory.



(1) Load the program for tool life management in the EDIT mode, as with an ordinary CNC tape.
The program will be registered in the part program memory and will be made ready for display and editing.

(2) Perform a cycle start operation in the MEM mode to run the program. The data will be stored in the tool life data area of the memory; at the same time, the already existing tool life data of all groups will be cancelled and the life counters will be cleared. Data once stored is not erased by turning the power off.

(3) Executing a cycle start operation in the TAPE mode instead of the operation of (1), stores the program contents directly onto the tool life data area. In this case, however, display and editing cannot be done as in (1). TAPE mode is not always prepared according to the machine tool builders.

- **Display contents**

```
TOOL LIFE DATA  :              O3000 N00060
                  SELECTED GROUP 000
 GROUP  001       :  LIFE 0150  COUNT  0007
         *0034   #0078   @0012    0056
          0090    0035    0026    0061
          0000    0000    0000    0000
          0000    0000    0000    0000

  GROUP  002       :  LIFE 1400  COUNT  0000
          0062    0024    0044    0074
          0000    0000    0000    0000
          0000    0000    0000    0000
          0000    0000    0000    0000
  TO BE CHANGED    :   003 004 005 006 --->
> _
MEM **** *** ***      16:05:59
[ MACRO ][      ][  OPR  ][ TOOLLF ][ (OPRT) ]
```

- The first line is the title line.
- In the second line the group number of the current command is displayed.
  When there is no group number of the current command, 0 is displayed.
- In lines 3 to 7 the tool life data of the group is displayed.
  The third line displays group number, life and the count used.
  The life count is chosen by parameter LTM (No. 6800#2) as either minutes(or hours) or number of times used.
  In lines 4 to 7, tool numbers are displayed. In this case, the tool is selected in the order, 0034 → 0078 → 0012 → 056 → 0090 ...
  The meaning of each mark before the tool numbers is :
  * : Shows the life has finished.
  # : Shows that the skip command has been accepted.
  @ : Shows that the tool is currently being used.
  The life counter counts for tool with @.
  "*" is displayed when the next command is issued by the group to which it belongs.
- Lines 8 to 12 are next group life data to the group displayed in lines 3 to 7.
- In the thirteenth line the group number when the tool change signal is being emitted is displayed. The group number display appears in ascending order. When it cannot be completely displayed, "——>" is displayed.

11.4.15 Setting and Displaying B–axis Tool Compensation

Setting and displaying B–axis tool compensation

1 Press the OFFSET SETTING function key.

2 Press the ▷ continuous menu key several times. Then, press the **[OFST.B]** chapter selection key.

- When the option for tool geometry and wear compensation is not provided,



- When the option for tool geometry and wear compensation is provided,



4 Position the cursor to the item to be set or modified, using the cursor keys.

5 Enter the value, then press the INPUT key.

Explanations

The offset can be set to a value in the following valid data ranges.

Offset	Metric input	Inch input
IS–B	–999.999 to 999.999	–99.9999 to 99.9999
IS–C	–999.9999 to 999.9999	–99.99999 to 99.9999

Special B–axis offsets are input or output together with usual offsets.
When the option for tool geometry and wear compensation is provided, wear offsets and geometry offsets can be specified separately. A tool offset consists of both the specified wear offset and geometry offset.
In two–path control, tool offsets can be specified for each tool post or both tool posts, depending on the setting of COF, bit 0 of parameter No. 8242.

11.5 SCREENS DISPLAYED BY FUNCTION KEY SYSTEM

When the CNC and machine are connected, parameters must be set to determine the specifications and functions of the machine in order to fully utilize the characteristics of the servo motor or other parts.
This chapter describes how to set parameters on the MDI panel. Parameters can also be set with external input/output devices such as the Handy File (see Chapter III–9).
In addition, pitch error compensation data used for improving the precision in positioning with the ball screw on the machine can be set or displayed by the operations under function key SYSTEM .

See Chapter III–7 for the diagnostic screens displayed by pressing function key SYSTEM .

11.5.1 Displaying and Setting Parameters

When the CNC and machine are connected, parameters are set to determine the specifications and functions of the machine in order to fully utilize the characteristics of the servo motor. The setting of parameters depends on the machine. Refer to the parameter list prepared by the machine tool builder.
Normally, the user need not change parameter setting.

Procedure for displaying and setting parameters

1 Set 1 for **PARAMETER WRITE** to enable writing. See the procedure for enabling/disabling parameter writing described below.

2 Press function key [SYSTEM] .

3 Press chapter selection soft key **[PARAM]** to display the parameter screen.



4 Move the cursor to the parameter number to be set or displayed in either of the following ways:

- Enter the parameter number and press soft key **[NO.SRH]** .
- Move the cursor to the parameter number using the page keys, [PAGE↑] and [PAGE↓] , and cursor keys, [↑], [↓], [←], and [→] .

5 To set the parameter, enter a new value with numeric keys and press soft key **[INPUT]** in the MDI mode. The parameter is set to the entered value and the value is displayed.

6 Set 0 for **PARAMETER WRITE** to disable writing.

Procedure for enabling/displaying parameter writing

1 Select the **MDI** mode or enter state emergency stop.

2 Press function key [OFFSET SETTING] .

3 Press soft key **[SETING]** to display the setting screen.

```
SETTING (HANDY)                    O0001 N00000

  PARAMETER WRITE = 1 (0:DISABLE 1:ENABLE)
  TV CHECK        = 0 (0:OFF   1:ON)
  PUNCH CODE      = 1 (0:EIA   1:ISO)
  INPUT UNIT      = 0 (0:MM    1:INCH)
  I/O CHANNEL     =  0 (0–3:CHANNEL NO.)
  SEQUENCE NO.    = 0 (0:OFF   1:ON)
  TAPE FORMAT     = 0 (0:NO CNV  1:F10/11)
  SEQUENCE STOP   =     0 (PROGRAM NO.)
  SEQUENCE STOP   =    11 (SEQUENCE NO.)


> _                              S   0  T0000
MDI **** *** ***       16:05:59
[ OFFSET ][ SETING ][ WORK ][     ][ (OPRT) ]
```

4 Move the cursor to **PARAMETER WRITE** using cursor keys.

5 Press soft key **[(OPRT)]**, then press **[1: ON]** to enable parameter writing.
At this time, the CNC enters the P/S alarm state (No. 100).

6 After setting parameters, return to the setting screen. Move the cursor to **PARAMETER WRITE** and press soft key **[(OPRT)]** , then press **[0: OFF]**.

7 Depress the [RESET] key to release the alarm condition. If P/S alarm No. 000 has occurred, however, turn off the power supply and then turn it on, otherwise the P/S alarm is not released.

Explanations

- **Setting parameters with external input/output devices**

  See Chapter 8 for setting parameters with external input/output devices such as the Handy File.

- **Parameters that require turning off the power**

  Some parameters are not effective until the power is turned off and on again after they are set. Setting such parameters causes alarm 000. In this case, turn off the power, then turn it on again.

- **Parameter list**

  Refer to the FANUC Series 21*i*/210*i*–MODEL A Parameter Manual (B–63090EN) for the parameter list.

- **Setting data**

  Some parameters can be set on the setting screen if the parameter list indicates “Setting entry is acceptable”. Setting 1 for **PARAMETER WRITE** is not necessary when three parameters are set on the setting screen.

11.5.2 Displaying and Setting Pitch Error Compensation Data

If pitch error compensation data is specified, pitch errors of each axis can be compensated in detection unit per axis.
Pitch error compensation data is set for each compensation point at the intervals specified for each axis. The origin of compensation is the reference position to which the tool is returned.
The pitch error compensation data is set according to the characteristics of the machine connected to the NC. The content of this data varies according to the machine model. If it is changed, the machine accuracy is reduced.
In principle, the end user must not alter this data.
Pitch error compensation data can be set with external devices such as the Handy File (see Chapter III–9). Compensation data can also be written directly with the MDI panel.
The following parameters must be set for pitch error compensation. Set the pitch error compensation value for each pitch error compensation point number set by these parameters.
In the following example, 33 is set for the pitch error compensation point at the reference position.



Compensation position number	31	32	33	34	35	36	37
Compensation value to be set	+3	–1	–1	+1	+2	–1	–3

- Number of the pitch error compensation point at the reference position (for each axis): Parameter 3620
- Number of the pitch error compensation point having the smallest value (for each axis): Parameter 3621
- Number of the pitch error compensation point having the largest value (for each axis): Parameter 3622
- Pitch error compensation magnification (for each axis): Parameter 3623
- Interval of the pitch error compensation points (for each axis): Parameter 3624

Procedure for displaying and setting the pitch error compensation data

1 Set the following parameters:

- Number of the pitch error compensation point at the reference position (for each axis): Parameter 3620
- Number of the pitch error compensation point having the smallest value (for each axis): Parameter 3621
- Number of the pitch error compensation point having the largest value (for each axis): Parameter 3622
- Pitch error compensation magnification (for each axis): Parameter 3623
- Interval of the pitch error compensation points (for each axis): Parameter 3624

2 Press function key [SYSTEM].



3 Press the continuous menu key [▷], then press chapter selection soft key **[PITCH]**.
The following screen is displayed:

```
 PIT-ERROR SETTING                    O0000 N00000

     NO.DATA      NO.DATA      NO.DATA
     0000 0       0010 0       0020 0
     0001 0       0011 0       0021 0
     0002 0       0012 0       0022 0
     0003 0       0013 0       0023 0
(X)  0004 0       0014 0       0024 0
     0005 0       0015 0       0025 0
     0006 0       0016 0       0026 0
     0007 0       0017 0       0027 0
     0008 0       0018 0       0028 0
     0009 0       0019 0       0029 0
> _
MEM **** *** ***      16:05:59
[ NO.SRH ][ ON:1 ][ OFF:0 ][ +INPUT ][ -INPUT ]
```

4 Move the cursor to the compensation point number to be set in either of the following ways:

- Enter the compensation point number and press the [NO.SRH] soft key.
- Move the cursor to the compensation point number using the page keys, [PAGE↑] and [PAGE↓], and cursor keys, [↑], [↓], [←], and [→].

5 Enter a value with numeric keys and press the **[INPUT]** soft key.

11.6 DISPLAYING THE PROGRAM NUMBER, SEQUENCE NUMBER, AND STATUS, AND WARNING MESSAGES FOR DATA SETTING OR INPUT/OUTPUT OPERATION

The program number, sequence number, and current CNC status are always displayed on the screen except when the power is turned on, a system alarm occurs, or the PMC screen is displayed.
If data setting or the input/output operation is incorrect, the CNC does not accept the operation and displays a warning message.
This section describes the display of the program number, sequence number, and status, and warning messages displayed for incorrect data setting or input/output operation.

11.6.1 Displaying the Program Number and Sequence Number

The program number and sequence number are displayed at the top right on the screen as shown below.



The program number and sequence number displayed depend on the screen and are given below:

On the program screen in the EDIT mode on Background edit screen:
The program No. being edited and the sequence number just prior to the cursor are indicated.

Other than above screens :

The program No. and the sequence No. executed last are indicated.

Immediately after program number search or sequence number search :

Immediately after the program No. search and sequence No. search, the program No. and the sequence No. searched are indicated.

11.6.2 Displaying the Status and Warning for Data Setting or Input/Output Operation

The current mode, automatic operation state, alarm state, and program editing state are displayed on the next to last line on the CRT screen allowing the operator to readily understand the operation condition of the system.
If data setting or the input/output operation is incorrect, the CNC does not accept the operation and a warning message is displayed on the next to last line of the CRT screen. This prevents invalid data setting and input/output errors.

Explanations

- **Description of each display**



Note) Actually, (10) is displayed at the position where (8) is now displayed.

- **(1) Current mode**

MDI : Manual data input, MDI operation
MEM : Automatic operation (Memory operation)
RMT : Automatic operation (DNC operation)
EDIT : Memory editing
HND : Manual handle feed
JOG : Jog feed
TJOG : TEACH IN JOG
THND : TEACH IN HANDLE
INC : Manual incremental feed
REF : Manual reference position return

- **(2) Automatic operation status**

**** : Reset (When the power is turned on or the state in which program execution has terminated and automatic operation has terminated.
STOP : Automatic operation stop (The state in which one block has been executed and automatic operation is stopped.)
HOLD : Feed hold (The state in which execution of one block has been interrupted and automatic operation is stopped.)
STRT : Automatic operation start–up (The state in which the system operates automatically)

- **(3) Axis moving status/dwell status**

MTN : Indicates that the axis is moving.
DWL : Indicates the dwell state.
*** : Indicates a state other than the above.

- **(4) State in which an auxiliary function is being executed**

FIN : Indicates the state in which an auxiliary function is being executed. (Waiting for the complete signal from the PMC)
*** : Indicates a state other than the above.

- **(5) Emergency stop or reset status**

--EMG-- : Indicates emergency stop.(Blinks in reversed display.)
—RESET— : Indicates that the reset signal is being received.

● (6) Alarm status

ALM : Indicates that an alarm is issued. (Blinks in reversed display.)
BAT : Indicates that the battery is low. (Blinks in reversed display.)
Space : Indicates a state other than the above.

● (7) Current time

hh:mm:ss – Hours, minutes, and seconds

● (8) Program editing status

INPUT : Indicates that data is being input.
OUTPUT : Indicates that data is being output.
SRCH : Indicates that a search is being performed.
EDIT : Indicates that another editing operation is being performed (insertion, modification, etc.)
LSK : Indicates that labels are skipped when data is input.
RSTR : Indicates that the program is being restarted
Space : Indicates that no editing operation is being performed.

● (9) Warning for data setting or input/ output operation

When invalid data is entered (wrong format, value out of range, etc.), when input is disabled (wrong mode, write disabled, etc.), or when input/output operation is incorrect (wrong mode, etc.), a warning message is displayed. In this case, the CNC does not accept the setting or input/output operation.
The following are examples of warning messages:

Example 1)
When a parameter is entered

```
> 1
EDIT    WRONG MODE
                    (Display soft keys)
```

Example 2)
When a parameter is entered

```
> 999999999
MDI    TOO MANY DIGITS
                    (Display soft keys)
```

Example 3)
When a parameter is output to an external input/output device

```
> _
MEM    WRONG MODE
                    (Display soft keys)
```

● (10) Tool post name (for the two–path control)

HEAD1 : Tool post 1 is selected.
HEAD2 : Tool post 2 is selected.
Other names can be used depending on the settings of parameters 3141 to 3147.
The tool post name is displayed at the position where (8) is now displayed. While the program is edited, (8) is displayed.

11.7 SCREENS DISPLAYED BY FUNCTION KEY MESSAGE

By pressing the MESSAGE function key, data such as alarms, alarm history data, and external messages can be displayed.
For information relating to alarm display, see Section III.7.1. For information relating to alarm history display, see Section III.7.2.
For information relating to external message display, see the relevant manual supplied by the machine tool builder.

11.7.1 External Operator Message History Display

External operator messages can be preserved as history data.
Preserved history data can be displayed on the external operator message history screen.

Procedure for external operator message history display

Procedure

1 Press the MESSAGE function key.

2 Press the continuous menu key ▷, then press the chapter selection soft key **[MSGHIS]**. The screen shown below appears.



Date and Page number →
Message nuumber →

Display range
(Up to 255 characters)

```
MESSAGE HISTORY                    O0000 N00000
 97/01/01 17:25:00                      PAGE:1
  NO. ****




 MEM STRT MIN FIN ALM 09:36:48
[      ][ MSGHIS ][       ][       ][ (OPRT) ]
```

NOTE
Up to 255 characters can be specified for an external operator message. By setting MS1 and MS0 (bits 7 and 6 of parameter No. 3113), however, the number of characters that can be preserved as external operator message history data can be restricted, and the number of history data items selected.

Explanations

- **Updating external operator message history data**

When an external operator message number is specified, updating of the external operator message history data is started; this updating is continued until a new external operator message number is specified or deletion of the external operator message history data is specified.

- **Clearing external operator message history data**

To clear external operator message history data, press the [CLEAR] soft key. This clears all external operator message history data. (Set MSGCR (bit 0 of parameter No. 3113) to 1.)
Note that when MS1 and MS0 (bits 7 and 6 of parameter No. 3113), used to specify the number of external operator message history data items to be displayed, are changed, all existing external operator message history data is cleared.

Limitations

- **Option**

Before this function can be used, the external data input function or optional external message function must be selected.

11.8 CLEARING THE SCREEN

Displaying the same characters in the same positions on the screen causes a CRT or LCD to degrade relatively quickly. To help prevent this, the screen can be cleared by pressing specific keys. It is also possible to specify the automatic clearing of the screen if no keys are pressed during a period specified with a parameter.

11.8.1 Erase CRT Screen Display

Holding down the CAN key and pressing an arbitrary function key clears the screen.

Procedure for Erase CRT Screen Display

Procedure

- **Clearing the screen**

  Hold down the CAN key and press an arbitrary function key (such as POS and PROG).

- **Restoring the screen**

  Press an arbitrary function key.

11.8.2 Automatic Erase Screen Display

The CNC screen is automatically cleared if no keys are pressed during the period (in minutes) specified with a parameter. The screen is restored by pressing any key.

Procedure for Automatic Erase Screen Display

- **Clearing the screen**

The CNC screen is cleared once the period (minutes) specified with parameter No. 3123 has elapsed, provided the following conditions are satisfied:

Conditions for clearing the CNC screen

- Parameter No. 3123 is set to other than 0.
- None of the following keys have been pressed:
  MDI keys
  Soft keys
  External input keys
- No alarm has been issued.

- **Restoring the screen**

The cleared CNC screen is restored once at least one of the following conditions is satisfied:

Conditions for restoring the CNC screen

- Any of the following keys has been pressed:
  MDI keys
  Soft keys
  Externally input keys
- An alarm has been issued.

Some machines feature a special key for restoring the screen. For an explanation of the location and use of this key, refer to the corresponding manual, supplied by the machine tool builder.

Explanations

- **Clearing the screen using [CAN] + function key**

If parameter No. 3123 is set to 0, clearing of the screen using the [CAN] key and a function key (III–11.8.1) is disabled.

- **Specified period**

The period specified with parameter No. 3123 is valid only for tool post 1.

- **Alarm for another path**

The screen is not cleared if an alarm is issued for tool post 1 or 2 or the loader before the specified period elapses.

CAUTION
Pressing any key while the screen is being cleared restores the screen. In such a case, however, the function assigned to the pressed key is initiated. Do not press the [DELET], [INSERT], or [ALTER] key to restore the screen, therefore.

12 GRAPHICS FUNCTION

The graphic function indicates how the tool moves during automatic operation or manual operation.

12.1 GRAPHICS DISPLAY

It is possible to draw the programmed tool path on the screen, which makes it possible to check the progress of machining, while observing the path on the screen.
In addition, it is also possible to enlarge/reduce the screen.
The drawing coordinates (parameter) and graphic parameters must be set before a tool path can be displayed.
With two–path control, the tool paths of two tool posts are displayed on the same screen, one on the right and the other on the left.

Graphics display procedure

Procedure

Set the drawing coordinates with parameter No.6510 before starting drawing. See “Drawing Coordinate System” for the settings and corresponding coordinates.
For the two–path control, parameter GRL (bit 0 of No. 6500) specifies which tool post is displayed on which side (tool post 1 on the right or tool post 2 on the right).

1 Press function key GRAPH. Press CUSTOM GRAPH for a small MDI unit.
The graphic parameter screen shown below appears. (If this screen does not appear, press soft key **[G.PRM]**.)



2 For the two–path control, determine for which tool post the data is specified, using a tool post select signal.
Specify the PROGRAM STOP (N), AUTO ERASE (A), and GRAPHIC CENTER (X,Y) parameters separately for each tool post. The other parameters are common to both tool posts. It does not matter for which tool post they are specified first.

3 Move the cursor with the cursor keys to a parameter to set.

4 Enter data, then press the INPUT key.

5 Repeat steps 3 and 4 until all required parameters are specified.

6 Press soft key **[GRAPH]**.

7 Automatic or manual operation is started and machine movement is drawn on the screen.



One–path lathe control

- **Magnifying drawings**

Part of a drawing on the screen can be magnified.

8 Press the GRAPH function key, then the **[ZOOM]** soft key to display a magnified drawing. The magnified–drawing screen contains two zoom cursors (■)



A rectangle that has one of its diagonals defined by the two zoom cursors is magnified to the full size of the screen.
For the two–path control, the zoom cursors are indicated for the selected tool post. Use the tool post select switch to select the tool post corresponding to the drawing to be magnified.

9 Using the cursor keys ↓ ↑ → ←, move the zoom cursors to specify a diagonal for the new screen. Pressing the **[HI / LO]** soft key toggles the zoom cursor to be moved.

10 To make the original drawing disappear, press **[EXEC]**.

11 Resume the previous operation. The part of the drawing specified with the zoom cursors will be magnified.



12 To display the original drawing, press the **[NORMAL]** soft key, then start automatic operation.

Explanation

● Setting drawing coordinate systems

Parameter No. 6510 is used to set a drawing coordinate system for using the graphic function. The relationships between setting values and drawing coordinate systems are indicated below. With two–path control, a different drawing coordinate system can be selected for each tool post.



● Graphics parameter

WORK LENGTH (W), WORK DIAMETER (D)

Specify work length and work diameter. The table below lists the input unit and valid data range.



Table 12.1 Unit and Range of Drawing Data

Increment system	Unit		Valid range
	mm input	Inch input	
IS–B	0.001 mm	0.0001 inch	0 to 99999999
IS–C	0.0001 mm	0,00001 inch	

GRAPHIC CENTER (X, Z), SCALE (S)

A screen center coordinate and drawing scale are displayed. A scale screen center coordinate are automatically calculated so that a figure set in WORK LENGTH (a) and WORK DIAMETER (b) can be fully displayed on the screen. So, the user need not set these parameters usually.

A screen center coordinate is defined in the workpiece coordinate system. Table 12. 3. 2 indicates the unit and range. The unit of SCALE is 0.001%.

PROGRAM STOP (N)

Set the sequence number of an end block when part of the program is to be drawn. A value set in this parameter is automatically cancelled (cleared to 0) once a drawing is provided.

AUTO ERASE (A)

If 1 is set, the previous drawing is automatically erased when automatic operation is stated from the reset state. Then, drawing is started.

LIMIT (L)

If 1 is set, the area of stored stroke limit l is drawn with double–dot–and–dash lines.

NOTE
The parameter values for drawing are preserved even if power is turned off.

- **Executing drawing only**

Since the graphic drawing is done when coordinate value is renewed during automatic operation, etc., it is necessary to start the program by automatic operation. To execute drawing without moving the machine, therefore, enter the machine lock state.

- **Deleting the previous drawing**

Pressing the **[REVIEW]** soft key on the graphic screen deletes tool paths on it. Setting the graphic parameter as AUTO ERASE (A) = 1 specifies that when automatic operation is started at reset, program execution begins after the previous drawing is erased automatically (AUTO ERASE = 1).

- **Drawing a part of a program**

When necessary to display a part of a program, search the starting block to be drawn by the sequence number search, and set the sequence number of the end block to the PROGRAM STOP N= of the graphic parameter before starting the program under cycle operation mode.

- **Drawing using dashed lines and solid lines**

The tool path is shown with a dashed line (- - - -) for rapid traverse and with a solid line (——) for cutting feed.

- **Displaying coordinates**

The displayed drawing is indicated with coordinates in a work coordinate system.

- **Displaying the machine zero point**

The machine zero point is indicated with mark.

- **Switching from a drawing screen to another screen**

Even if the screen is switched to a non–drawing screen, drawing continues. When the drawing screen is displayed again, the entire drawing appears (no parts are missing).

13 HELP FUNCTION

The help function displays on the screen detailed information about alarms issued in the CNC and about CNC operations. The following information is displayed.

- **Detailed information of alarms**

When the CNC is operated incorrectly or an erroneous machining program is executed, the CNC enters the alarm state. The help screen displays detailed information about the alarm that has been issued and how to reset it. The detailed information is displayed only for a limited number of P/S alarms. These alarms are often misunderstood and are rather difficult to understand.

- **Operation method**

If you are not sure about a CNC operation, refer to the help screen for information about each operation.

- **Parameter table**

When setting or referring to a system parameter, if you are not sure of the number of the parameter, the help screen displays a list of parameter Nos. for each function.

Help Function Procedure

Procedure

1 Press the HELP key on the MDI. HELP (INITIAL MENU) screen is displayed.

```
HELP (INITIAL MENU)          O1234   N00001

              ***** HELP *****

              1.  ALARM DETAIL
              2.  OPERATION METHOD
              3.  PARAMETER TABLE




                                    S     0 T0000
 MEM **** *** ***        10:12:25
 [ 1 ALM ][ 2 OPR ][ 3 PARA ][       ][       ]
```

Fig.13(a) HELP (INITIAL MENU) Screen

The user cannot switch the screen display from the PMC screen or CUSTOM screen to the help screen. The user can return to the normal CNC screen by pressing the HELP key or another function key.

ALARM DETAIL screen

2 Press soft key **[1 ALAM]** on the HELP (INITIAL MENU) screen to display detailed information about an alarm currently being raised.



Fig.13(b) ALARM DETAIL Screen when P/S Alarm No.27 is issued

Note that only details of the alarm identified at the top of the screen are displayed on the screen.
If the alarms are all reset while the help screen is displayed, the alarm displayed on the ALARM DETAIL screen is deleted, indicating that no alarm is issued.



Fig.13(c) ALARM DETAIL Screen when No Alarm is issued

3 To get details on another alarm number, first enter the alarm number, then press soft key **[SELECT]**. This operation is useful for investigating alarms not currently being raised.

```
>100                              S     0 T0000
MEM **** *** ***          10:12:25
[       ][       ][        ][       ][ SELECT ]
```

Fig.13(d) How to select each ALARM DETAILS

```
HELP (ALARM DETAIL)                O1234 N00001


NUMBER    : 100
M'SAGE    : PARAMETER WRITE ENABLE
FUNCTION  :
ALARM     :

         <<ALARM IS NOT GENERATED>>




>100                              S     0 T0000
MEM **** *** ***          10:12:25
[       ][       ][        ][       ][ SELECT ]
```

Fig.13(e) ALARM DETAIL Screen when P/S alarm No.100 is selected

OPERATION METHOD screen

4 To determine an operating procedure for the CNC, press the soft key **[2 OPR]** key on the HELP (INITIAL MENU) screen. The OPERATION METHOD menu screen is then displayed. (See Fig. 13 (f).)

```
HELP (OPERATION METHOD)          O1234   N00001

1. PROGRAM EDIT
2. SEARCH
3. RESET
4. DATA INPUT WITH MDI
5. DATA INPUT WITH TAPE
6. OUTPUT
7. INPUT WITH FANUC CASSETTE
8. OUTPUT WITH FANUC CASSETTE
9. MEMORY CLEAR


                                  S     0 T0000
 MEM **** *** ***          10:12:25
 [ 1 ALM ][ 2 OPR ][ 3 PARA ][       ][       ]
```

Fig.13(f) OPERATION METHOD Menu Screen

To select an operating procedure, enter an item No. from the keyboard then press the **[SELECT]** key.

```
>1                                S     0 T0000
MEM **** *** ***        10:12:25
[       ][       ][       ][       ][ SELECT ]
```

Fig.13(g) How to select each OPERATION METHOD screen

When “1. PROGRAM EDIT” is selected, for example, the screen in Figure 13 (g) is displayed.
On each OPERATION METHOD screen, it is possible to change the displayed page by pressing the PAGE key. The current page No. is shown at the upper right corner on the screen.



Fig.13(h) Selected OPERATION METHOD screen



5 To return to the OPERATION METHOD menu screen, press the RETURN MENU key to display “**[2 OPR]**” again, and then press the **[2 OPR]** key again.
To directly select another OPERATION METHOD screen on the screen shown in Figure 13 (h), enter an item No. from the keyboard and press the **[SELECT]** key.

```
>3                                S     0 T0000
MEM **** *** ***        10:12:25
[       ][       ][       ][       ][ SELECT ]
```

Fig.13(i) How to select another OPERATION METHOD screen

PARAMETER TABLE screen

6 If you are not sure of the No. of a system parameter to be set, or to refer to a system parameter, press the **[3 PARA]** key on the HELP (INITIAL MENU) screen. A list of parameter Nos. for each function is displayed. (See Figure 13 (j).)
It is possible to change the displayed page on the parameter screen. The current page No. is shown at the upper right corner on the screen.

```
HELP (PARAMETER TABLE)          01234  N00001
                                         1/4

* SETTEING                              (No. 0000~)
* READER/PUNCHER INTERFACE              (No. 0100~)
* AXIS CONTROL
  /SETTING UNIT                         (No. 1000~)
* COORDINATE SYSTEM                     (No. 1200~)
* STROKE LIMIT                          (No. 1300~)
* FEED RATE                             (No. 1400~)
* ACCEL/DECELERATION CTRL               (No. 1600~)
* SERVORELATED                          (No. 1800~)
* DI/DO                                 (No. 3000~)

>_                                    S     0 T0000
MEM **** *** ***          10:12:25
[ 1 ALM ][ 2 OPR ][ 3 PARA ][       ][       ]
```

Fig. 13(j) PARAMETER TABLE screen

7 To exit from the help screen, press the HELP key or another function key.

Explanation

- **Configuration of the Help Screen**



IV. MAINTENANCE

1 METHOD OF REPLACING BATTERY

This chapter describes how to replace the CNC backup battery and absolute pulse coder battery. This chapter consists of the following sections:

1.1 REPLACING THE ALKALINE DRY CELLS (SIZE D)
1.2 USE OF ALKALINE DRY CELLS (SIZE D)
1.3 BATTERY FOR SEPARATE ABSOLUTE PULSE CODERS

Battery for memory backup

Part programs, offset data, and system parameters are stored in CMOS memory in the control unit. The power to the CMOS memory is backed up by a lithium battery mounted on the front panel of the control unit. Therefore, the above data is not lost even if the main battery fails. The backup battery is installed in the control unit prior to being shipped from the factory. This battery can provide backup for the memory contents for about a year.

When the battery voltage falls, alarm message “BAT” blinks on the LCD display and the battery alarm signal is output to the PMC. When this alarm is displayed, replace the battery as soon as possible. In general, the battery can be replaced within one or two weeks of the alarm first being issued. This, however, depends on the system configuration.

If the battery voltage subsequently drops further, backup of memory can no longer be provided. Turning on the power to the control unit in this state causes system alarm 910 (SRAM parity alarm) to be issued because the contents of memory are lost. Replace the battery, clear the entire memory, then reenter the data.
Replace the memory backup battery while the control unit is turned off. The following two kinds of batteries can be used.

- Lithium battery, incorporated into the CNC control unit.
- Two alkaline dry cells (size D) in an external battery case.

NOTE
A lithium battery is installed as standard at the factory.

Replacing the lithium battery

(1) Obtain a new lithium battery (ordering drawing number: A02B–0200–K102).

(2) Turn the Series 21*i*/210*i* on for about 30 seconds.

(3) Turn the Series 21*i*/210*i* off.

(4) Remove the old battery from the top of the CNC control unit.
First, disconnect the battery cable then remove the battery from its case.
The battery case of a control unit with no option slots is located at the top right end of the unit. That of a control unit with 2 slots or 4 slots is located in the central area of the top of the unit (between fans).



(5) Insert a new battery and reconnect the cable.

CAUTION

Complete steps 3 to 5 within 30 minutes (within five minutes for the Series 210*i* with PC functions).
If the battery is left disconnected for any longer, the contents of memory will be lost.
If for some reason, it may prove impossible to complete the battery replacement within 30 minutes, save the entire contents of the CMOS memory to a memory card in advance. The data can thus be easily restored if the contents of memory are lost.
For an explanation of the operating procedure, refer to the maintenance manual.

WARNING

Using other than the recommended battery may result in the battery exploding.
Replace the battery only with the specified type (A02B–0200–K102).

Dispose of used batteries as follows:

(1) Small quantities (less than 10)
Discharge the batteries and dispose of them as ordinary unburnable waste.

(2) Large quantities
Please consult FANUC.

1.1 REPLACING THE ALKALINE DRY CELLS (SIZE D)

(1)Obtain two new alkaline dry cells (size D).
(2) Turn the Series 21*i*/210*i* on.
(3) Remove the battery case cover.
(4) Replace the batteries, paying careful attention to their orientation.
(5) Replace the battery case cover.

NOTE
When replacing the dry cells while the power is off, use the same procedure as that for lithium battery replacement, described above.



1.2 USE OF ALKALINE DRY CELLS (SIZE D)

Connection

Power from external batteries is supplied through the same connector as that to which the lithium battery is connected. The lithium battery, provided as standard, can be replaced with external batteries in a battery case (A02B–0236–C281) according to the battery replacement procedures described above.



NOTE

Install the battery case (A02B–0236–C281: 14–m cable) in a location where the batteries can be replaced even when the control unit power is on.

The battery cable connector is attached to the control unit by means of a simple lock system. To prevent the connector from being disconnected due to the weight or tension of the cable, secure the cable within 50 cm of the connector.

1.3 BATTERY FOR SEPARATE ABSOLUTE PULSE CODERS

One battery unit can maintain the current position data held in an absolute pulse coder for about one year.

When the battery voltage falls, APC alarms 306 to 308 are displayed on the screen. When APC alarm 307 is displayed, replace the battery as soon as possible. In general, the battery should be replaced within one or two weeks of the alarm first appearing. This, however, depends on the number of pulse coders being used.
If the battery voltage drops any further, the current positions for the pulse coders will be lost. Turning on the power to the control unit in this state results in APC alarm 300 (reference position return request alarm) being issued. Return the tool to the reference position after replacing the battery.

See Subsection 7.9.2 for details of connecting the battery to separate absolute pulse coders. The battery for the built–in absolute pulse coder is installed in the servo amplifier. For an explanation of the replacement procedure, refer to the FANUC CONTROL MOTOR AMPLIFIER α Series Maintenance Manual.

APPENDIX

A TAPE CODE LIST

ISO code										EIA code										Remarks		
Character	8	7	6	5	4		3	2	1	Character	8	7	6	5	4		3	2	1		Custom macro B	
																					Not used	Used
0			○	○		●				0			○			●				Number 0		
1	○		○	○		○			○	1						○			○	Number 1		
2	○		○	○		●		○		2						●		○		Number 2		
3			○	○		●		○	○	3				○		●		○	○	Number 3		
4	○		○	○		●	○			4						●	○			Number 4		
5			○	○		●	○		○	5				○		●	○		○	Number 5		
6			○	○		●	○	○		6				○		●	○	○		Number 6		
7	○		○	○		●	○	○	○	7						●	○	○	○	Number 7		
8	○		○	○	○	●				8					○	●				Number 8		
9			○	○	○	●			○	9				○	○	●			○	Number 9		
A		○				●			○	a		○	○			●			○	Address A		
B		○				●		○		b		○	○			●		○		Address B		
C	○	○				●		○	○	c		○	○	○		●		○	○	Address C		
D		○				●	○			d		○	○			●	○			Address D		
E	○	○				●	○		○	e		○	○	○		●	○		○	Address E		
F	○	○				●	○	○		f		○	○	○		●	○	○		Address F		
G		○				●	○	○	○	g		○	○			●	○	○	○	Address G		
H		○			○	●				h		○	○		○	●				Address H		
I	○	○			○	●			○	i		○	○	○	○	●			○	Address I		
J	○	○			○	●		○		j		○		○		●		○	○	Address J		
K		○			○	●		○	○	k		○		○		●		○		Address K		
L	○	○			○	●	○			l		○				●		○	○	Address L		
M		○			○	●	○		○	m		○		○		●	○			Address M		
N		○			○	●	○	○		n		○				●	○		○	Address N		
O	○	○			○	●	○	○	○	o		○				●	○	○		Address O		
P		○		○		●				p		○		○		●	○	○	○	Address P		
Q	○	○		○		●			○	q		○		○	○	●				Address Q		
R	○	○		○		●		○		r		○			○	●			○	Address R		
S		○		○		●		○	○	s			○	○		●		○		Address S		
T	○	○		○		●	○			t			○			●		○	○	Address T		
U		○		○		●	○		○	u			○	○		●	○			Address U		
V		○		○		●	○	○		v			○			●	○		○	Address V		
W	○	○		○		●	○	○	○	w			○			●	○	○		Address W		
X	○	○		○	○	●				x			○	○		●	○	○	○	Address X		
Y		○		○	○	●			○	y			○	○	○	●				Address Y		
Z		○		○	○	●		○		z			○		○	●			○	Address Z		

ISO code										EIA code									Remarks		
Character	8	7	6	5	4		3	2	1	Character	8	7	6	5	4		3	2	1		Custom macro B	
																					Not used	Used
DEL	○	○	○	○	○	○	○	○	○	Del		○	○	○	○	○	○	○	○	Delete (deleting a mispunch)	×	×
NUL						○				Blank						○				No punch. With EIA code, this code cannot be used in a significant information section.	×	×
BS	○				○	○				BS			○		○	○		○		Backspace	×	×
HT					○	○			○	Tab			○	○	○	○	○	○		Tabulator	×	×
LF or NL					○	○		○		CR or EOB	○					○				End of block		
CR	○				○	○	○		○	___										Carriage return	×	×
SP	○		○			○				SP				○		○				Space	□	□
%	○		○			○	○		○	ER					○	○		○	○	Absolute rewind stop		
(			○		○	○				(2–4–5)				○	○	○		○		Control out (start of comment)		
)	○		○		○	○			○	(2–4–7)		○			○	○		○		Control in (end of comment)		
+			○		○	○		○	○	+		○	○	○		○				Plus sign	Δ	
–			○		○	○	○		○	–		○				○				Minus sign		
:			○	○	○	○		○		___										Colon (address O)		
/	○		○		○	○	○	○	○	/			○	○		○			○	Optional block skip		
.			○		○	○	○	○		.		○	○		○	○		○	○	Period (decimal point)		
#	○		○			○		○	○	Parameter (No.6012)										Sharp		
$			○			○	○			___										Dollar sign	×	×
&	○		○			○	○	○		&					○	○	○	○		Ampersand	Δ	○
ヽ			○			○	○	○	○	___										Apostrophe	Δ	Δ
*	○		○		○	○		○		Parameter (No.6010)										Asterisk	Δ	
,	○		○		○	○	○			,			○	○	○	○		○	○	Comma		
;	○		○	○	○	○		○	○	___										Semicolon	×	×
<			○	○	○	○	○			___										Left angle bracket	Δ	Δ
=	○		○	○	○	○	○		○	Parameter (No.6011)										Equal sign	Δ	
>	○		○	○	○	○	○	○		___										Right angle bracket	Δ	Δ
?			○	○	○	○	○	○	○	___										Question mark	Δ	○
@	○	○				○				___										Commercial at mark	Δ	○
”			○					○		___										Quotation mark	Δ	Δ
[	○	○		○	○	○		○	○	Parameter (No.6013)										Left square bracket	Δ	
]	○	○		○	○	○	○		○	Parameter (No.6014)										Right square bracket	Δ	

NOTE

1 The symbols used in the remark column have the following meanings.
(Space) : The character will be registered in memory and has a specific meaning.
If it is used incorrectly in a statement other than a comment, an alarm occurs.
× : The character will not be registered in memory, but will be ignored.
△ : The character will be registered in memmory, but will be ignored during program execution.
○ : The character will be registered in memory. If it is used in a statement other than a comment, an alarm occurs.
□ : If it is used in a statement other than a comment, the character will not be registered in memory. If it is used in a comment, it will be registered in memory.
2 Codes not in this table are ignored if their parity is correct.
3 Codes with incorrect parity cause the TH alarm. But they are ignored without generating the TH alarm when they are in the comment section.
4 A character with all eight holes punched is ignored and does not generate TH alarm in EIA code.

B LIST OF FUNCTIONS AND TAPE FORMAT

Some functions cannot be added as options depending on the model.
In the tables below, IP _:presents a combination of arbitrary axis addresses using X and Z.
x = 1st basic axis (X usually)
z = 2nd basic axis (Z usually)

(1/4)

Functions	Illustration	Tape format
Positioning (G00)		G00 IP_ ;
Linear interpolation (G01)		G01 IP_ F_;
Circular interpolation (G02, G03)		{G02 / G03} X_ Z_ {R_ / I_ K_} F_ ;
Dwell (G04)		G04 {X_ / P_} ;
Cylindrical interpolation		G07.1 IP_ R_ ; Cylindrical interpolation mode G07.1 IP 0; Cylindrical interpolation mode cancel R : Radius of cylindrical
Change of offsetvalue by program (G10)		Tool geometry offset value G10 P_ X_ Z_ R_ Q_ ; P=1000+Geometry offset number Tool wear offset value G10 P_ X_ Z_ R_ Q_ ; P=Wear offset number

(2/4)

Functions	Illustration	Tape format
Polar coordinate interpolation (G12.1, G13.1) (G112, G113)		G12.1 ; Polar coordinate interpolation mode G13.1 ; Polar coordinate interpolation mode cancel
Plane selection (G17, G18, G19)		G17 ; G18 ; G19 ;
Inch/metric conversion (G20, G21)		Inch input : G20 Metric input : G21
Stored stroke check 2, 3 (G22, G23)		G22X_ Z_ I_ K_ ; G23 ;
Spindle speed fluctuation detection (G25, G26)		G25 ; G26 P_ Q_ R_ ;
Reference position return check (G27)		G27 IP_ ;
Reference position return (G28) 2nd, reference position return (G30)		G28 IP_ ; G30 IP_ ;
Cutter compensation (G40, G41, G42)		{G41 / G42} P_ ; P : Tool offset number G40 : Cancel
Skip fubction (G31)		G31 IP_ F_;
Thread cutting (G32)		Equal lead thread cutting G32 IP_ F_;
Variable–lead thread cutting		G34 IP_ F_ K_ ;

(3/4)

Functions	Illustration	Tape format
Automatic tool compensation (G36, G37)		G36 X_xa_ ; G37 Z_za_ ;
Coordinate system setting Spindle speed setting (G50)		G50 X_ Z_ ; Coordinate system setting G50 S_ ; Spindle speed setting
Polygon turning (G50.2, G51.2) (G250, G251)		G51.2 (G251) P_ Q_ ; P, Q : Rotation ratio of spindle and Rotation axis G50.2 (G250) ; Cancel
Workpiece coordinate system preset (G50.3)		G50.3 IP 0 ;
Local coordinate system (G52)		G52 IP_ ;
Selecting machine coordinate system (G53)		G53 IP_ ;
Selecting a workpiece coordinate system (G54 to G59)		{ G54 : G59 } IP_ ;
Custom macro (G65, G66, G67)		One–shot call G65 P_ L_ <argument> ; P : Program number L : Repetition count G66 P_ L_ <argument> ; G67 ; Cancel
Mirror image for double turret (G68, G69)		G68 ; Mirror image for double turret on G69 ; Mirror image cancel

(4/4)

Functions	Illustration	Tape format
Feed per minute (G98) Feed per revolution (G99)	mm/min inch/min mm/rev inch/rev	G98 … F_ ; G99 … F_ ;
Canned cycle for drilling (G80 to G89)	Refer to II.13. FUNCTIONS TO SIMPLIFY PROGRAMMING	G80 ; Cancel G83 X(U)_ C(H)_ Z(W)_ R_ Q_ P_ F_ M_ K_ ; G84 X(U)_ C(H)_ Z(W)_ R_ P_ F_ M_ K_ ; G85 X(U)_ C(H)_ Z(W)_ R_ P_ F_ M_ K_ ; G87 Z(W)_ C(H)_ X(U)_ R_ Q_ P_ F_ M_ K_ ; G88 Z(W)_ C(H)_ X(U)_ R_ P_ F_ M_ K_ ; G89 Z(W)_ C(H)_ X(U)_ R_ P_ F_ M_ K_ ;
Constant surface speed control (G96/G97)	m/min or feet/min 	G96 S_ ; G97 ; Cancel
Chamfering, Corner R		X_ ; { C ± k / R_ } P_ ; Z_ ; { C ± i / R_ } P_ ;
Canned cycle (G71 to G76) (G90, G92, G94)	Refer to II.13. FUNCTIONS TO SIMPLIFY PROGRAMMING	N_ G70 P_ Q_ ; G71 U_ R_ ; G71 P_ Q_ U_ W_ F_ S_ T_ ; G72 W_ R_ ; G72 P_ Q_ U_ W_ F_ S_ T_ ; G73 U_ W_ R_ ; G73 P_ Q_ U_ W_ F_ S_ T_ ; G74 R_ ; G74 X(u)_ Z(w)_ P_ Q_ R_ F_ ; G75 R_ ; G75 X(u)_ Z(w)_ P_ Q_ R_ F_ ; G76 P_ Q_ R_ ; G76 X(u)_ Z(w)_ P_ Q_ R_ F_ ; { G90 / G92 } X_ Z_ I_ F_ ; G94 X_ Z_ K_ F_ ;
Absolute/incremental programming (G90/G91) (during G code system B, C)		G90_ ; Absolute programming G91_ ; Incremental programming G90_ G91_ ; Used together
(G98/G99) (during G code system B, C)		G98_ ; G99_ ;

C RANGE OF COMMAND VALUE

Linear axis

- **In case of millimeter input, feed screw is millimeter**

	Increment system	
	IS–B	**IS–C**
Least input increment	0.001 mm	0.0001 mm
Least command increment	X : 0.0005 mm Y : 0.001 mm	X : 0.00005 mm Y : 0.0001 mm
Max. programmable dimension	±99999.999 mm	±9999.9999 mm
Max. rapid traverse ***1**	240000 mm/min	100000 mm/min
Feedrate range ***1**	Feed per minute : 1 to 240000 mm/min Feed per revolution 0.0001 to 500.0000 mm/rev	Feed per minute : 1 to 100000 mm/min Feed per revolution 0.0001 to 500.0000 mm/rev
Incremental feed	0.001, 0.01, 0.1, 1mm/step	0.0001, 0.001, 0.01, 0.1 mm/step
Tool compensation	0 to ±999.999 mm	0 to ±999.9999 mm
Backlash compensation	0 to ±0.255 mm	0 to ±0.255 mm
Dwell time	0 to 99999.999 sec	0 to 99999.999 sec

- **In case of inch input, feed screw is millimeter**

	Increment system	
	IS–B	**IS–C**
Least input increment	0.0001 inch	0.00001 inch
Least command increment	X : 0.00005 inch Y : 0.0001 inch	X : 0.000005 inch Y : 0.00001 inch
Max. programmable dimension	±9999.9999 inch	±393.70078 inch
Max. rapid traverse ***1**	240000 mm/min	100000 mm/min
Feedrate range ***1**	Feed per minute : 0.01 to 9600 inch/min Feed per revolution 0.000001 to 9.999999 inch/rev	Feed per minute : 0.01 to 4000 inch/min Feed per revolution 0.000001 to 9.999999 inch/rev
Incremental feed	0.0001, 0.001, 0.01, 0.1 inch/step	0.00001, 0.0001, 0.001, 0.01 inch/step
Tool compensation	0 to ±99.9999 inch	0 to ±99.9999 inch
Backlash compensation	0 to ±0.255 mm	0 to ±0.255 mm
Dwell time	0 to 99999.999 sec	0 to 9999.9999 sec

- **In case of inch input, feed screw is inch**

	Increment system	
	IS–B	**IS–C**
Least input increment	0.0001 inch	0.00001 inch
Least command increment	X : 0.00005 inch Y : 0.0001 inch	X : 0.000005 inch Y : 0.00001 inch
Max. programmable dimension	±9999.9999 inch	±999.99999 inch
Max. rapid traverse ***1**	9600 inch/min	4000 inch/min
Feedrate range ***1**	Feed per minute : 0.01 to 9600 inch/min Feed per revolution 0.000001 to 9.999999 inch/rev	Feed per minute : 0.01 to 4000 inch/min Feed per revolution 0.000001 to 9.999999 inch/rev
Incremental feed	0.0001, 0.001, 0.01, 0.1 inch/step	0.00001, 0.0001, 0.001, 0.01 inch/step
Tool compensation	0 to ±99.9999 inch	0 to ±99.9999 inch
Backlash compensation	0 to ±0.0255 inch	0 to ±0.0255 inch
Dwell time	0 to 99999.999 sec	0 to 9999.9999 sec

- **In case of millimeter input, feed screw is inch**

	Increment system	
	IS–B	**IS–C**
Least input increment	0.001 mm	0.0001 mm
Least command increment	X : 0.00005 inch Y : 0.0001 inch	X : 0.000005 inch Y : 0.00001 inch
Max. programmable dimension	±99999.999 mm	±9999.9999 mm
Max. rapid traverse ***1**	9600 inch/min	960 inch/min
Feedrate range ***1**	Feed per minute : 1 to 240000 mm/min Feed per revolution 0.0001 to 500.0000 mm/rev	Feed per minute : 1 to 100000 mm/min Feed per revolution 0.0001 to 500.0000 mm/rev
Incremental feed	0.001, 0.01, 0.1, 1mm/ step	0.0001, 0.001, 0.01, 0.1 mm/step
Tool compensation	0 to ±999.999 mm	0 to ±999.9999 mm
Backlash compensation	0 to ±0.0255 inch	0 to ±0.0255 inch
Dwell time	0 to 99999.999 sec	0 to 9999.9999 sec

Rotation axis

	Increment system	
	IS–B	**IS–C**
Least input increment	0.001 deg	0.0001 deg
Least command increment	±0.001 deg	±0.0001 deg
Max. programmable dimension	±99999.999 deg	±9999.9999 deg
Max. rapid traverse ***1**	240000 deg/min	100000 deg/min
Feedrate range ***1**	1 to 240000 deg/min	1 to 100000 deg/min
Incremental feed	0.001, 0.01, 0.1, 1 deg/step	0.0001, 0.001, 0.01, 0.1 deg/step
Tool compensation	0 to ±999.999 mm	0 to ±999.9999 mm
Backlash compensation	0 to ±0.255 deg	0 to ±0.255 deg

NOTE

*1 The feedrate range shown above are limitations depending on CNC interpolation capacity.
As a whole system, limitations depending on servo system must also be considered.

D NOMOGRAPHS

D.1 INCORRECT THREADED LENGTH

The leads of a thread are generally incorrect in δ_1 and δ_2, as shown in Fig. D.1 (a), due to automatic acceleration and deceleration.
Thus distance allowances must be made to the extent of δ_1 and δ_2 in the program.



Fig.D.1(a) Incorrect thread position

Explanations

- **How to determine δ_2**

$$\delta_2 = T_1 V \text{ (mm)} \quad \ldots\ldots\ldots \text{(1)}$$

$$V = \frac{1}{60} RL$$

T_1 : Time constant of servo system (sec)
V : Cutting speed (mm/sec)
R : Spindle speed (rpm)
L : Thread feed (mm)

Time constant T_1 (sec) of the servo system: Usually 0.033 s.

- **How to determine δ_1**

$$\delta_1 = \{t - T_1 + T_1 \exp(-\frac{t}{T_1})\} V \quad \ldots\ldots\ldots \text{(2)}$$

$$a = \exp(-\frac{t}{T_1}) \quad \ldots\ldots\ldots \text{(3)}$$

T_1 : Time constant of servo system (sec)
V : Cutting speed (mm/sec)

Time constant T_1 (sec) of the servo system: Usually 0.033 s.

The lead at the beginning of thread cutting is shorter than the specified lead L, and the allowable lead error is ΔL. Then as follows.

$$a = \frac{\Delta L}{L}$$

When the value of HαI is determined, the time lapse until the thread accuracy is attained. The time HtI is substituted in (2) to determine δ_1: Constants V and T_1 are determined in the same way as for δ_2. Since the calculation of δ_1 is rather complex, a nomography is provided on the following pages.

- **How to use nomograph**

First specify the class and the lead of a thread. The thread accuracy, α, will be obtained at (1), and depending on the time constant of cutting feed acceleration/ deceleration, the δ_1 value when V = 10mm / s will be obtained at (2). Then, depending on the speed of thread cutting, δ_1 for speed other than 10mm/ s can be obtained at (3).



Fig.D.1(b) Nomograph

NOTE
The equations for δ_1, and δ_2 are for when the acceleration/deceleration time constant for cutting feed is 0.

D.2 SIMPLE CALCULATION OF INCORRECT THREAD LENGTH



Fig. D.2 (a) Incorrect threaded portion

Explanations

- **How to determine δ_2**

$$\delta_2 = \frac{LR}{1800\ *} \text{ (mm)}$$

R : Spindle speed (rpm)
L : Thread lead (mm)

* When time constant T of the servo system is 0.033 s.

- **How to determine δ_1**

$$\delta_1 = \frac{LR}{1800\ *}(-1-lna) \text{ (mm)}$$
$$= \delta_2(-1-lna) \text{ (mm)}$$

R : Spindle speed (rpm)
L : Thread lead (mm)

* When time constant T of the servo system is 0.033 s.

Following a is a permitted value of thread.

a	–1–lna
0.005	4.298
0.01	3.605
0.015	3.200
0.02	2.912

Examples

R=350rpm
L=1mm
a=0.01 then

$$\delta_2 = \frac{350 \times 1}{1800} = 0.194 \text{ (mm)}$$

$$\delta_1 = \delta_2 \times 3.605 = 0.701 \text{ (mm)}$$

- **Reference**



Nomograph for obtaining approach distance δ_1

D.3 TOOL PATH AT CORNER

When servo system delay (by exponential acceleration/deceleration at cutting or caused by the positioning system when a servo motor is used) is accompanied by cornering, a slight deviation is produced between the tool path (tool center path) and the programmed path as shown in Fig. D.3 (a).
Time constant T_1 of the exponential acceleration/deceleration is fixed to 0.



Fig. D.3 (a) Slight deviation between the tool path and the programmed path

This tool path is determined by the following parameters:
· Feedrate (V_1, V_2)
· Corner angle (θ)
· Exponential acceleration / deceleration time constant (T_1) at cutting ($T_1 = 0$)
· Presence or absence of buffer register.
The above parameters are used to theoretically analyze the tool path and above tool path is drawn with the parameter which is set as an example. When actually programming, the above items must be considered and programming must be performed carefully so that the shape of the workpiece is within the desired precision.
In other words, when the shape of the workpiece is not within the theoretical precision, the commands of the next block must not be read until the specified feedrate becomes zero. The dwell function is then used to stop the machine for the appropriate period.

Analysis

The tool path shown in Fig. D.3 (b) is analyzed based on the following conditions:
Feedrate is constant at both blocks before and after cornering.
The controller has a buffer register. (The error differs with the reading speed of the tape reader, number of characters of the next block, etc.)



Fig. D.3(b) Example of tool path

• Description of conditions and symbols

$$V_{X1} = V\cos\phi_1$$

$$V_{Y1} = V\sin\phi_1$$

$$V_{X2} = V\cos\phi_2$$

$$V_{Y2} = V\sin\phi_2$$

V : Feedrate at both blocks before and after cornering
V_{X1} : X–axis component of feedrate of preceding block
V_{Y1} : Y–axis component of feedrate of preceding block
V_{X2} : X–axis component of feedrate of following block
V_{Y2} : Y–axis component of feedrate of following block
θ : Corner angle
ϕ_1 : Angle formed by specified path direction of preceding block and X–axis
ϕ_2 : Angle formed by specified path direction of following block and X–axis

- **Initial value calculation**



Fig. D.3(c) Initial value

The initial value when cornering begins, that is, the X and Y coordinates at the end of command distribution by the controller, is determined by the feedrate and the positioning system time constant of the servo motor.

$$X_0 = V_{X1}(T_1 + T_2)$$

$$Y_0 = V_{Y1}(T_1 + T_2)$$

T_1:Exponential acceleration / deceleration time constant. (T=0)
T_2:Time constant of positioning system (Inverse of position loop gain)

- **Analysis of corner tool path**

The equations below represent the feedrate for the corner section in X–axis direction and Y–axis direction.

$$V_X(t) = (V_{X2}-V_{X1})[1-\frac{V_{X1}}{T_1-T_2}\{T_1\exp(-\frac{t}{T_1})-T_2\exp(-\frac{t}{T_2})\} + V_{X1}]$$
$$= V_{X2}[1-\frac{V_{X1}}{T_1-T_2}\{T_1\exp(-\frac{t}{T_1})-T_2\exp(-\frac{t}{T_2})\}]$$

$$V_Y(t) = \frac{V_{Y1}-V_{Y2}}{T_1-T_2}\{T_1\exp(-\frac{t}{T_1})-T_2\exp(-\frac{t}{T_2})\} + V_{Y2}$$

Therefore, the coordinates of the tool path at time t are calculated from the following equations:

$$X(t) = \int_0^t V_X(t)dt - X_0$$
$$= \frac{V_{X2}-V_{X1}}{T_1-T_2}\{{T_1}^2\exp(-\frac{t}{T_1})-{T_2}^2\exp(-\frac{t}{T_2})\}-V_{X2}(T_1 + T_2-t)$$

$$Y(t) = \int_0^t V_Y(t)dt - Y_0$$
$$= \frac{V_{Y2}-V_{Y1}}{T_1-T_2}\{{T_1}^2\exp(-\frac{t}{T_1})-{T_2}^2\exp(-\frac{t}{T_2})\}-V_{Y2}(T_1 + T_2-t)$$

D.4 RADIUS DIRECTION ERROR AT CIRCLE CUTTING

When a servo motor is used, the positioning system causes an error between input commands and output results. Since the tool advances along the specified segment, an error is not produced in linear interpolation. In circular interpolation, however, radial errors may be produced, specially for circular cutting at high speeds.
This error can be obtained as follows:



$$\Delta r = \frac{1}{2}(T_1^{\,2} + T_2^{\,2})\frac{V^2}{r} \quad \cdots\cdots\cdots (1)$$

Δr : Maximum radius error (mm)
v : Feedrate (mm/s)
r : Circle radius (mm)
T_1 : Exponential acceleration/deceleration time constant (sec) at cutting (T=0)
T_2 : Time constant of positoning system (sec). (Inverse of positon loop gain)

In the case of bell–shaped acceleration/deceleration and linear acceleration/deceleration after cutting feed interpolation, an approximation of this radius error can be obtained with the following expression:

$$\Delta r = (\frac{1}{24}T_1^{\,2} + \frac{1}{2}T_2^{\,2})\frac{V^2}{r}$$

Thus, the radius error in the case of bell–shaped acceleration/deceleration and linear acceleration/deceleration after interpolation is smaller than in case of exponential acceleration/deceleration by a factor of 12, excluding any error caused by a servo loop time constant.

Fig. D.4(a) Radius direction error of circular cutting

Since the machining radius r (mm) and allowable errorΔr (mm) of the workpiece is given in actual machining, the allowable limit feedrate v (mm /sec) is determined by equation (1).
Since the acceleration/deceleration time constant at cutting which is set by this equipment varies with the machine tool, refer to the manual issued by the machine tool builder.

E STATUS WHEN TURNING POWER ON, WHEN CLEAR AND WHEN RESET

Parameter 3402 (CLR) is used to select whether resetting the CNC places it in the cleared state or in the reset state (0: reset state/1: cleared state). The symbols in the tables below mean the following :
○:The status is not changed or the movement is continued.
×:The status is cancelled or the movement is interrupted.

Item		When turning power on	Cleared	Reset
Setting data	Offset value	○	○	○
	Data set by the MDI setting operation	○	○	○
	Parameter	○	○	○
Various data	Programs in memory	○	○	○
	Contents in the buffer storage	×	×	○ : MDI mode × : Other mode
	Display of sequence number	○	○ (Note 1)	○ (Note 1)
	One shot G code	×	×	×
	Modal G code	Initial G codes. (The G20 and G21 codes return to the same state they were in when the power was last turned off.)	Initial G codes. (G20/G21 are not changed.)	○
	F	Zero	Zero	○
	S, T, M	×	○	○
	K (Number of repeats)	×	×	×
Work coordinate value		Zero	○	○

Item		When turning power on	Cleared	Reset
Action in operation	Movement	×	×	×
	Dwell	×	×	×
	Issuance of M, S and T codes	×	×	×
	Tool offset	×	Depending on parameter LVK(No.5003#6)	○ : MDI mode Other modes depend on parameter LVK(No.5003#6).
	Tool nose radius compensation	×	×	○ : MDI mode × : Other modes
	Storing called subprogram number	×	× (Note 2)	○ : MDI mode × : Other modes (Note 2)
Output signals	CNC alarm signal AL	Extinguish if there is no cause for the alarm	Extinguish if there is no cause for the alarm	Extinguish if there is no cause for the alarm
	Reference position return completion LED	×	○ (× : Emergency stop)	○ (× : Emergency stop)
	S, T and B codes	×	○	○
	M code	×	×	×
	M, S and T strobe signals	×	×	×
	Spindle revolution signal (S analog signal)	×	○	○
	CNC ready signal MA	ON	○	○
	Servo ready signal SA	ON (When other than servo alarm)	ON (When other than servo alarm)	ON (When other than servo alarm)
	Cycle start LED (STL)	×	×	×
	Feed hold LED (SPL)	×	×	×

NOTE
1 When heading is performed, the main program number is displayed.
2 When a reset is performed during execution of a subprogram, control returns the main program. Execution cannot be started from the middle of the subprogram.

F CHARACTER–TO–CODES CORRESPONDENCE TABLE

Character	Code	Comment	Character	Code	Comment
A	065		6	054	
B	066		7	055	
C	067		8	056	
D	068		9	057	
E	069			032	Space
F	070		!	033	Exclamation mark
G	071		”	034	Quotation mark
H	072		#	035	Hash sign
I	073		$	036	Dollar sign
J	074		%	037	Percent
K	075		&	038	Ampersand
L	076		’	039	Apostrophe
M	077		(	040	Left parenthesis
N	078		)	041	Right parenthesis
O	079		*	042	Asterisk
P	080		+	043	Plus sign
Q	081		,	044	Comma
R	082		–	045	Minus sign
S	083		.	046	Period
T	084		/	047	Slash
U	085		:	058	Colon
V	086		;	059	Semicolon
W	087		<	060	Left angle bracket
X	088		=	061	Equal sign
Y	089		>	062	Right angle bracket
Z	090		?	063	Question mark
0	048		@	064	HAtI mark
1	049		[	091	Left square bracket
2	050		^	092	
3	051		¥	093	Yen sign
4	052		]	094	Right square bracket
5	053		_	095	Underscore

G ALARM LIST

1) Program errors (P/S alarm)

Number	Message	Contents
000	PLEASE TURN OFF POWER	A parameter which requires the power off was input, turn off power.
001	TH PARITY ALARM	TH alarm (A character with incorrect parity was input). Correct the tape.
002	TV PARITY ALARM	TV alarm (The number of characters in a block is odd). This alarm will be generated only when the TV check is effective.
003	TOO MANY DIGITS	Data exceeding the maximum allowable number of digits was input. (Refer to the item of max. programmable dimensions.)
004	ADDRESS NOT FOUND	A numeral or the sign " – " was input without an address at the beginning of a block. Modify the program .
005	NO DATA AFTER ADDRESS	The address was not followed by the appropriate data but was followed by another address or EOB code. Modify the program.
006	ILLEGAL USE OF NEGATIVE SIGN	Sign " – " input error (Sign " – " was input after an address with which it cannot be used. Or two or more " – " signs were input.) Modify the program.
007	ILLEGAL USE OF DECIMAL POINT	Decimal point " . " input error (A decimal point was input after an address with which it can not be used. Or two decimal points were input.) Modify the program.
009	ILLEGAL ADDRESS INPUT	Unusable character was input in significant area. Modify the program.
010	IMPROPER G–CODE	An unusable G code or G code corresponding to the function not provided is specified. Modify the program.
011	NO FEEDRATE COMMANDED	Feedrate was not commanded to a cutting feed or the feedrate was inadequate. Modify the program.
014	ILLEGAL LEAD COMMAND	In variable lead threading, the lead incremental and decremental outputted by address K exceed the maximum command value or a command such that the lead becomes a negative value is given. Modify the program.
015	TOO MANY AXES COMMANDED	An attempt has been made to move the tool along more than the maximum number of simultaneously controlled axes. Alternatively, no axis movement command or an axis movement command for two or more axes has been specified in the block containing the command for skip using the torque limit signal (G31 P99/98). The command must be accompanied with an axis movement command for a single axis, in the same block.
020	OVER TOLERANCE OF RADIUS	In circular interpolation (G02 or G03), difference of the distance between the start point and the center of an arc and that between the end point and the center of the arc exceeded the value specified in parameter No. 3410.
021	ILLEGAL PLANE AXIS COMMANDED	An axis not included in the selected plane (by using G17, G18, G19) was commanded in circular interpolation. Modify the program.
022	CIRCULAR INTERPOLATION	In circular interpolation, radius R, or the distance between the start point and the center of the arc, I, J, or K, has not been specified.
020	G NO CIRCLE RADIUS	When circular interpolation is specified, neither R (specifying an arc radius), nor I, J, and K (specifying the distance from a start point to the center) is specified.

Number	Message	Contents
021	ILLEGAL PLANE AXIS COMMANDED	An axis not included in the selected plane (by using G17, G18, G19) was commanded in circular interpolation. Modify the program.
022	NO CIRCLE RADIUS	The command for circular interpolation lacks arc radius R or coordinate I, J, or K of the distance between the start point to the center of the arc.
023	ILLEGAL RADIUS COMMAND	In circular interpolation by radius designation, negative value was commanded for address R. Modify the program.
028	ILLEGAL PLANE SELECT	In the plane selection command, two or more axes in the same direction are commanded. Modify the program.
029	ILLEGAL OFFSET VALUE	The offset values specified by T code is too large. Modify the program.
030	ILLEGAL OFFSET NUMBER	The offset number in T function specified for tool offset is too large. Modify the program.
031	ILLEGAL P COMMAND IN G10	In setting an offset amount by G10, the offset number following address P was excessive or it was not specified. Modify the program.
032	ILLEGAL OFFSET VALUE IN G10	In setting an offset amount by G10 or in writing an offset amount by system variables, the offset amount was excessive.
033	NO SOLUTION AT NRC	A point of intersection cannot be determined for tool nose radius compensation. Modify the program.
034	NO CIRC ALLOWED IN ST–UP /EXT BLK	The start up or cancel was going to be performed in the G02 or G03 mode in tool nose radius compensation. Modify the program.
035	CAN NOT COMMANDED G31	Skip cutting (G31) was specified in tool nose radius compensation mode. Modify the program.
037	CAN NOT CHANGE PLANE IN NRC	The offset plane is switched in tool nose radius compensation. Modify the program.
038	INTERFERENCE IN CIRCULAR BLOCK	Overcutting will occur in tool nose radius compensation because the arc start point or end point coincides with the arc center. Modify the program.
039	CHF/CNR NOT ALLOWED IN NRC	Chamfering or corner R was specified with a start–up, a cancel, or switching between G41 and G42 in tool nose radius compensation. The program may cause overcutting to occur in chamfering or corner R. Modify the program.
040	INTERFERENCE IN G90/G94 BLOCK	Overcutting will occur in tool nose radius compensation in canned cycle G90 or G94. Modify the program.
041	INTERFERENCE IN NRC	Overcutting will occur in tool nose radius compensation. Modify the program.
046	ILLEGAL REFERENCE RETURN COMMAND	Other than P2, P3 and P4 are commanded for 2nd, 3rd and 4th reference position return command.
050	CHF/CNR NOT ALLOWED IN THRD BLK	Chamfering or corner R is commanded in the thread cutting block. Modify the program.
051	MISSING MOVE AFTER CHF/CNR	Improper movement or the move distance was specified in the block next to the chamfering or corner R block. Modify the program.
052	CODE IS NOT G01 AFTER CHF/CNR	The block next to the chamfering or corner R block is not G01. Modify the program.
053	TOO MANY ADDRESS COMMANDS	In the chamfering and corner R commands, two or more of I, K and R are specified. Otherwise, the character after a comma(“,”) is not C or R in direct drawing dimensions programming. Modify the program.
054	NO TAPER ALLOWED AFTER CHF/CNR	A block in which chamfering in the specified angle or the corner R was specified includes a taper command. Modify the program.

Number	Message	Contents
055	MISSING MOVE VALUE IN CHF/CNR	In chamfering or corner R block, the move distance is less than chamfer or corner R amount.
056	NO END POINT & ANGLE IN CHF/CNR	Neither the end point nor angle is specified in the command for the block next to that for which only the angle is specified (A). In the chamfering common, I(K) is commanded for the X(Z) axis.
057	NO SOLUTION OF BLOCK END	Block end point is not calculated correctly in direct dimension drawing programming.
058	END POINT NOT FOUND	Block end point is not found in direct dimension drawing programming.
059	PROGRAM NUMBER NOT FOUND	In an external program number search or external workpiece number search, a specified program number was not found. Otherwise, a program specified for searching is being edited in background processing. Check the program number and external signal. Or discontinue the background editing.
060	SEQUENCE NUMBER NOT FOUND	Commanded sequence number was not found in the sequence number search. Check the sequence number.
061	ADDRESS P/Q NOT FOUND IN G70–G73	Address P or Q is not specified in G70, G71, G72, or G73 command. Modify the program.
062	ILLEGAL COMMAND IN G71–G76	1 The depth of cut in G71 or G72 is zero or negative value. 2 The repetitive count in G73 is zero or negative value. 3 The negative value is specified to Δi or Δk is zero in G74 or G75. 4 A value other than zero is specified to address U or W, though Δi or Δk is zero in G74 or G75. 5 A negative value is specified to Δd, though the relief direction in G74 or G75 is determined. 6 Zero or a negative value is specified to the height of thread or depth of cut of first time in G76. 7 The specified minimum depth of cut in G76 is greater than the height of thread. 8 An unusable angle of tool tip is specified in G76. Modify the program.
063	SEQUENCE NUMBER NOT FOUND	The sequence number specified by address P in G70, G71, G72, or G73 command cannot be searched. Modify the program.
064	SHAPE PROGRAM NOT MONOTONOUSLY	A target shape which is not monotonous increase or decrease was specified in a repetitive canned cycle (G71 or G72).
065	ILLEGAL COMMAND IN G71–G73	1 G00 or G01 is not commanded at the block with the sequence number which is specified by address P in G71, G72, or G73 command. 2 Address Z(W) or X(U) was commanded in the block with a sequence number which is specified by address P in G71 or G72, respectively. Modify the program.
066	IMPROPER G–CODE IN G71–G73	An unallowable G code was commanded between two blocks specified by address P in G71, G72, or G73. Modify the program.
067	CAN NOT OPERATE IN MDI MODE	G70, G71, G72, or G73 command with address P and Q was specified. Modify the program.
069	FORMAT ERROR IN G70–G73	The final move command in the blocks specified by P and Q of G70, G71, G72, or G73 ended with chamfering or corner R.
070	NO PROGRAM SPACE IN MEMORY	The memory area is insufficient. Delete any unnecessary programs, then retry.
071	DATA NOT FOUND	The address to be searched was not found. Or the program with specified program number was not found in program number search. Check the data.

Number	Message	Contents
072	TOO MANY PROGRAMS	The number of programs to be stored exceeded 63 (basic), 125 (option), 200 (option), 400 (option), or 1000 (option). Delete unnecessary programs and execute program registration again.
073	PROGRAM NUMBER ALREADY IN USE	The commanded program number has already been used. Change the program number or delete unnecessary programs and execute program registration again.
074	ILLEGAL PROGRAM NUMBER	The program number is other than 1 to 9999. Modify the program number.
075	PROTECT	An attempt was made to register a program whose number was protected.
076	ADDRESS P NOT DEFINED	Address P (program number) was not commanded in the block which includes an M98, G65, or G66 command. Modify the program.
077	SUB PROGRAM NESTING ERROR	The subprogram was called in five folds. Modify the program.
078	NUMBER NOT FOUND	A program number or a sequence number which was specified by address P in the block which includes an M98, M99, M65 or G66 was not found. The sequence number specified by a GOTO statement was not found. Otherwise, a called program is being edited in background processing. Correct the program, or discontinue the background editing.
079	PROGRAM VERIFY ERROR	In memory or program collation,a program in memory does not agree with that read from an external I/O device. Check both the programs in memory and those from the external device.
080	G37 ARRIVAL SIGNAL NOT ASSERTED	In the automatic tool compensation function (G36, G37), the measurement position reach signal (XAE or ZAE) is not turned on within an area specified in parameter 6254 (value ε). This is due to a setting or operator error.
081	OFFSET NUMBER NOT FOUND IN G37	Automatic tool compensation (G36, G37) was specified without a T code. (Automatic tool compensation function) Modify the program.
082	T–CODE NOT ALLOWED IN G37	T code and automatic tool compensation (G36, G37) were specified in the same block. (Automatic tool compensation function) Modify the program.
083	ILLEGAL AXIS COMMAND IN G37	In automatic tool compensation (G36, G37), an invalid axis was specified or the command is incremental. Modify the program.
085	COMMUNICATION ERROR	When entering data in the memory by using Reader / Puncher interface, an overrun, parity or framing error was generated. The number of bits of input data or setting of baud rate or specification No. of I/O unit is incorrect.
086	DR SIGNAL OFF	When entering data in the memory by using Reader / Puncher interface, the ready signal (DR) of reader / puncher was turned off. Power supply of I/O unit is off or cable is not connected or a P.C.B. is defective.
087	BUFFER OVERFLOW	When entering data in the memory by using Reader / Puncher interface, though the read terminate command is specified, input is not interrupted after 10 characters read. I/O unit or P.C.B. is defective.
090	REFERENCE RETURN INCOMPLETE	The reference position return cannot be performed normally because the reference position return start point is too close to the reference position or the speed is too slow. Separate the start point far enough from the reference position, or specify a sufficiently fast speed for reference position return. Check the program contents.
091	REFERENCE RETURN INCOMPLETE	In the automatic operation halt state, manual reference position return cannot be performed.
092	AXES NOT ON THE REFERENCE POINT	The commanded axis by G27 (Reference position return check) did not return to the reference position.

Number	Message	Contents
094	P TYPE NOT ALLOWED (COORD CHG)	P type cannot be specified when the program is restarted. (After the automatic operation was interrupted, the coordinate system setting operation was performed.) Perform the correct operation according to th operator's manual.
095	P TYPE NOT ALLOWED (EXT OFS CHG)	P type cannot be specified when the program is restarted. (After the automatic operation was interrupted, the external workpiece offset amount changed.) Perform the correct operation according to th operator's manual.
096	P TYPE NOT ALLOWED (WRK OFS CHG)	P type cannot be specified when the program is restarted. (After the automatic operation was interrupted, the workpiece offset amount changed.) Perform the correct operation according to th operator's manual.
097	P TYPE NOT ALLOWED (AUTO EXEC)	P type cannot be directed when the program is restarted. (After power ON, after emergency stop or P/S alarm 94 to 97 were reset, no automatic operation was performed.) Perform automatic operation.
098	G28 FOUND IN SEQUENCE RETURN	A command of the program restart was specified without the reference position return operation after power ON or emergency stop, and G28 was found during search. Perform the reference position return.
099	MDI EXEC NOT ALLOWED AFT. SEARCH	After completion of search in program restart, a move command is given with MDI.
100	PARAMETER WRITE ENABLE	On the PARAMETER(SETTING) screen, PWE(parameter writing enabled) is set to 1. Set it to 0, then reset the system.
101	PLEASE CLEAR MEMORY	The power turned off while rewriting the memory by program edit operation. If this alarm has occurred, press <RESET> while pressing <PROG>, and only the program being edited will be deleted. Register the deleted program.
109	P/S ALARM	A value other than 0 or 1 was specified after P in the G08 code, or no value was specified.
111	CALCULATED DATA OVERFLOW	The result of calculation is out of the allowable range (-10^{47} to -10^{-29}, 0, and 10^{-29} to 10^{47}).
112	DIVIDED BY ZERO	Division by zero was specified. (including tan 90°) Modify the program.
113	IMPROPER COMMAND	A function which cannot be used in custom macro is commanded. Modify the program.
114	FORMAT ERROR IN MACRO	There is an error in other formats than <Formula>. Modify the program.
115	ILLEGAL VARIABLE NUMBER	A value not defined as a variable number is designated in the custom macro or in high–speed cycle cutting. Modify the program.
116	WRITE PROTECTED VARIABLE	The left side of substitution statement is a variable whose substitution is inhibited. Modify the program.
118	PARENTHESIS NESTING ERROR	The nesting of bracket exceeds the upper limit (quintuple). Modify the program.
119	ILLEGAL ARGUMENT	The SQRT argument is negative, BCD argument is negative, or other values than 0 to 9 are present on each line of BIN argument. Modify the program.
122	QUADRUPLE MACRO MODAL–CALL	A total of four macro calls and macro modal calls are nested. Modify the program.
123	CAN NOT USE MACRO COMMAND IN DNC	Macro control command is used during DNC operation. Modify the program.
124	MISSING END STATEMENT	DO – END does not correspond to 1 : 1. Modify the program.

Number	Message	Contents
125	FORMAT ERROR IN MACRO	<Formula> format is erroneous. Modify the program.
126	ILLEGAL LOOP NUMBER	In DOn, 1≦ n ≦3 is not established. Modify the program.
127	NC, MACRO STATEMENT IN SAME BLOCK	NC and custom macro commands coexist. Modify the program.
128	ILLEGAL MACRO SEQUENCE NUMBER	The sequence number specified in the branch command was not 0 to 9999. Or, it cannot be searched. Modify the program.
129	ILLEGAL ARGUMENT ADDRESS	An address which is not allowed in <Argument Designation > is used. Modify the program.
130	ILLEGAL AXIS OPERATION	An axis control command was given by PMC to an axis controlled by CNC. Or an axis control command was given by CNC to an axis controlled by PMC. Modify the program.
131	TOO MANY EXTERNAL ALARM MESSAGES	Five or more alarms have generated in external alarm message. Consult the PMC ladder diagram to find the cause.
132	ALARM NUMBER NOT FOUND	No alarm No. concerned exists in external alarm message clear. Check the PMC ladder diagram.
133	ILLEGAL DATA IN EXT. ALARM MSG	Small section data is erroneous in external alarm message or external operator message. Check the PMC ladder diagram.
135	SPINDLE ORIENTATION PLEASE	Without any spindle orientation , an attempt was made for spindle indexing. Perform spindle orientation.
136	C/H–CODE & MOVE CMD IN SAME BLK.	A move command of other axes was specified to the same block as spindle indexing addresses C, H. Modify the program.
137	M–CODE & MOVE CMD IN SAME BLK.	A move command of other axes was specified to the same block as M–code related to spindle indexing. Modify the program.
138	G SUPERIMPOSED DATA OVERFLOW	In PMC axis control, the increment for pulse distribution on the CNC and PMC side are too large when the superimposed control extended function is used.
139	CAN NOT CHANGE PMC CONTROL AXIS	An axis is selected in commanding by PMC axis control. Modify the program.
145	ILLEGAL COMMAND G112/G113	The conditions are incorrect when the polar coordinate interpolation starts or it is canceled. 1) In modes other than G40, G12.1/G13.1 was specified. 2) An error is found in the plane selection. Parameters No. 5460 and No. 5461 are incorrectly specified. Modify the value of program or parameter.
146	IMPROPER G CODE	G codes which cannot be specified in the polar coordinate interpolation mode was specified. See section II–4.4 and modify the program.
150	ILLEGAL TOOL GROUP NUMBER	Tool Group No. exceeds the maximum allowable value. Modify the program.
151	TOOL GROUP NUMBER NOT FOUND	The tool group commanded in the machining program is not set. Modify the value of program or parameter.
152	NO SPACE FOR TOOL ENTRY	The number of tools within one group exceeds the maximum value registrable. Modify the number of tools.
153	T–CODE NOT FOUND	In tool life data registration, a T code was not specified where one should be. Correct the program.
155	ILLEGAL T–CODE IN M06	In the machining program, M06 and T code in the same block do not correspond to the group in use. Correct the program.
156	P/L COMMAND NOT FOUND	P and L commands are missing at the head of program in which the tool group is set. Correct the program.
157	TOO MANY TOOL GROUPS	The number of tool groups to be set exceeds the maximum allowable value. (See parameter No. 6800 bit 0 and 1) Modify the program.
158	ILLEGAL TOOL LIFE DATA	The tool life to be set is too excessive. Modify the setting value.

Number	Message	Contents
159	TOOL DATA SETTING INCOMPLETE	During executing a life data setting program, power was turned off. Set again.
175	ILLEGAL G107 COMMAND	Conditions when performing circular interpolation start or cancel not correct. To change the mode to the cylindrical interpolation mode, specify the command in a format of “G07.1 rotation–axis name radius of cylinder.”
176	IMPROPER G–CODE IN G107	Any of the following G codes which cannot be specified in the cylindrical interpolation mode was specified. 1) G codes for positioning, such as G28, G76, G81 – G89, including the codes specifying the rapid traverse cycle 2) G codes for setting a coordinate system: G50, G52 3) G code for selecting coordinate system: G53 G54–G59 Modify the program.
177	CHECK SUM ERROR (G05 MODE)	Check sum error Modify the program.
178	G05 NOT ALLOWED IN G41/G42 MODE	G05 was commanded in the G41/G42 mode. Correct the program.
179	PARAM. (NO. 7510) SETTING ERROR	The number of controlled axes set by the parameter 7510 exceeds the maximum number. Modify the parameter setting value.
180	COMMUNICATION ERROR (REMOTE BUF)	Remote buffer connection alarm has generated. Confirm the number of cables, parameters and I/O device.
190	ILLEGAL AXIS SELECT	In the constant surface speed control, the axis specification is wrong. (See parameter No. 3770.) The specified axis command (P) contains an illegal value. Correct the program.
194	SPINDLE COMMAND IN SYNCHRO–MODE	A contour control mode, spindle positioning (Cs–axis control) mode, or rigid tapping mode was specified during the serial spindle synchronous control mode. Correct the program so that the serial spindle synchronous control mode is released in advance.
197	C–AXIS COMMANDED IN SPINDLE MODE	The program specified a movement along the Cf–axis when the signal CON(DGN=G027#7) was off. Correct the program, or consult the PMC ladder diagram to find the reason the signal is not turned on.
199	MACRO WORD UNDEFINED	Undefined macro word was used. Modify the custom macro.
200	ILLEGAL S CODE COMMAND	In the rigid tapping, an S value is out of the range or is not specified. The maximum values for S which can be specified in rigid tapping is set in parameters 5241 to 5243. Change the setting in the parameter or modify the program.
201	FEEDRATE NOT FOUND IN RIGID TAP	In the rigid tapping, no F value is specified. Correct the program.
202	POSITION LSI OVERFLOW	In the rigid tapping, spindle distribution value is too large.
203	PROGRAM MISS AT RIGID TAPPING	In the rigid tapping, position for a rigid M code (M29) or an S command is incorrect. Modify the program.
204	ILLEGAL AXIS OPERATION	In the rigid tapping, an axis movement is specified between the rigid M code (M29) block and G84 (G88) block. Modify the program.
205	RIGID MODE DI SIGNAL OFF	Rigid tapping signal (DGNG061 #1) is not 1 when G84 (G88) is executed though the rigid M code (M29) is specified. Consult the PMC ladder diagram to find the reason the signal is not turned on.
210	CAN NOT COMAND M198/M099	1 M198 and M199 are executed in the schedule operation. Or M198 is executed in the DNC operation. Modify the program. 2 In a multiple repetitive pocketing canned cycle, an interrupt macro was specified, and M99 was executed.
211	G31 (HIGH) NOT ALLOWED IN G99	G31 is commanded in the per revolution command when the high–speed skip option is provided. Modify the program.

Number	Message	Contents
212	ILLEGAL PLANE SELECT	The direct drawing dimensions programming is commanded for the plane other than the Z–X plane. Correct the program.
213	ILLEGAL COMMAND IN SYNCHRO–MODE	Movement is commanded for the axis to be synchronously controlled.
214	ILLEGAL COMMAND IN SYNCHRO–MODE	Coordinate system is set or tool compensation of the shift type is executed in the synchronous control. Correct the program.
217	DUPLICATE G251 (COMMANDS)	G51.2 or G251 is further commanded in the polygon machining mode. Modify the program.
218	NOT FOUND P/Q COMMAND IN G251	P or Q is not commanded in the G251 block, or the command value is out of the range. Modify the program.
219	COMMAND G250/G251 INDEPENDENTLY	G251 and G250 are not independent blocks.
220	ILLEGAL COMMAND IN SYNCHR–MODE	In the synchronous operation, movement is commanded by the NC program or PMC axis control interface for the synchronous axis.
221	ILLEGAL COMMAND IN SYNCHR–MODE	Polygon machining synchronous operation and axis control or balance cutting are executed at a time. Modify the program.
224	RETURN TO REFERENCE POINT	Not returned to reference point before cycle start.
231	FORMAT ERROR IN G10 OR L50	Any of the following errors occurred in the specified format at the programmable–parameter input. 1 Address N or R was not entered. 2 A number not specified for a parameter was entered. 3 The axis number was too large. 4 An axis number was not specified in the axis–type parameter. 5 An axis number was specified in the parameter which is not an axis type. 6 An attempt was made to reset bit 4 of parameter 3202 (NE9) or change parameter 3210 (PSSWD) when they are protected by a password. Correct the program.
232	ILLEGAL AXIS COMMAND IN HELICAL	Three or more axes were specified as helical axes in the helical interpolation mode.
233	DEVICE BUSY	When an attempt was made to use a unit such as that connected via the RS–232–C interface, other users were using it.
239	BP/S ALARM	While punching was being performed with the function for controlling external I/O units ,background editing was performed.
240	BP/S ALARM	Background editing was performed during MDI operation.
244	P/S ALARM	In the skip function activated by the torque limit signal, the number of accumulated erroneous pulses exceed 32767 before the signal was input. Therefore, the pulses cannot be corrected with one distribution. Change the conditions, such as federates along axes and torque limit, and try again.
245	T–CODE NOT ALOWED IN THIS BLOCK	One of the G codes, G50, G10, and G04, which cannot be specified in the same block as a T code, was specified with a T code.
5010	END OF RECORD	The end of record (%) was specified.
5020	PARAMETER OF RESTART ERROR	An erroneous parameter was specified for restarting a program.
5030	ILLEGAL COMMAND (G100)	The end command (G110) was specified before the registration start command (G101, G102, or G103) was specified for the B–axis.
5031	ILLEGAL COMMAND (G100, G102, G103)	While a registration start command (G101, G102, or G103) was being executed, another registration start command was specified for the B–axis.
5032	NEW PRG REGISTERED IN B–AXS MOVE	While the machine was moving about the B–axis, at attempt was made to register another move command.

Number	Message	Contents
5033	NO PROG SPACE IN MEMORY B–AXIS	Commands for movement about the B–axis were not registered because of insufficient program memory.
5034	PLURAL COMMAND IN G110	Multiple movements were specified with the G110 code for the B–axis.
5035	NO FEEDRATE COMMANDED B–AXIS	A feedrate was not specified for cutting feed about the B–axis.
5036	ADDRESS R NOT DEFINED IN G81–G86	Point R was not specified for the canned cycle for the B–axis.
5037	ADDRESS Q NOT DEFINED IN G83	Depth of cut Q was not specified for the G83 code (peck drilling cycle). Alternatively, 0 was specified in Q for teh B–axis.
5038	TOO MANY START M–CODE COMMAND	More than six M codes for starting movement about the B–axis were specified.
5039	START UNREGISTERED B–AXIS PROG	An attempt was made to execute a program for the B–axis which had not been registered.
5040	CAN NOT COMMANDED B–AXIS MOVE	The machine could not move about the B–axis because parameter No.8250 was incorrectly specified, or because the PMC axis system could not be used.
5041	CAN NOT COMMANDED G110 BLOCK	Blocks containing the G110 codes were successively specified in tool–tip radius compensation for the B–axis.
5046	ILLEGAL PARAMETER (ST.COMP)	Parameters related to straightness compensation have been erroneously specified. Possible causes are as follows : 1 Invalid axis numbers have been assigned to move or compensation axes. 2 The number of pitcherror compensation points between the maximum positive and maximum negative points exceeds 128. 3 Straightness compensation point numbers have been assigned in other than ascending order. 4 Straightness compensation points could not belocated between the maximum positive and maximum negative pitch error compensation points. 5 The amount of compensation per compensation point is too large or too small.
5073	NO DECIMAL POINT	A decimal point is not specified for a command for which a decimal point must be specified.
5074	ADDRESS DUPLICATION ERROR	The same address appears more than once in a block. Alternatively, a block contains two or more G codes belonging to the same group.
5134	FSSB : OPEN READY TIME OUT	Initialization did not place FSSB in the open ready state.
5135	FSSB : ERROR MODE	FSSB has entered error mode.
5136	FSSB : NUMBER OF AMPS IS SMALL	In comparison with the number of controlled axes, the number of amplifiers recognized by FSSB is not enough.
5137	FSSB : CONFIGURATION ERROR	FSSB detected a configuration error.
5138	FSSB : AXIS SETTING NOT COMPLETE	In automatic setting mode, axis setting has not been made yet. Perform axis setting on the FSSB setting screen.
5197	FSSB : OPEN TIME OUT	The CNC permitted FSSB to open, but FSSB was not opened.
5198	FSSB : ID DATA NOT READ	Temporary assignment failed, so amplifier initial ID information could not be read.

2) Background edit alarm

Number	Message	Contents
070 to 074 085 to 087	BP/S alarm	BP/S alarm occurs in the same number as the P/S alarm that occurs in ordinary program edit.
140	BP/S alarm	It was attempted to select or delete in the background a program being selected in the foreground. **(Note)** Use background editing correctly.

NOTE

Alarm in background edit is displayed in the key input line of the background edit screen instead of the ordinary alarm screen and is resettable by any of the MDI key operation.

3) Absolute pulse coder (APC) alarm

Number	Message	Contents
300	n AXIS NEED ZRN	Manual reference position return is required for the nth–axis (n=1 – 4).
301	APC ALARM:n AXIS COMMUNICATION	nth–axis (n=1 – 4) APC communication error. Failure in data transmission Possible causes include a faulty APC, cable, or servo interface module.
302	APC ALARM:n AXIS OVER TIME	nth–axis (n=1 – 4) APC overtime error. Failure in data transmission. Possible causes include a faulty APC, cable, or servo interface module.
303	APC ALARM:n AXIS FRAMING	nth–axis (n=1 – 4) APC framing error. Failure in data transmission. Possible causes include a faulty APC, cable, or servo interface module.
304	APC ALARM:n AXIS PARITY	nth–axis (n=1 – 4) APC parity error. Failure in data transmission. Possible causes include a faulty APC, cable, or servo interface module.
305	APC ALARM:n AXIS PULSE MISS	nth–axis (n=1 – 4) APC pulse error alarm. APC alarm. APC or cable may be faulty.
306	APC ALARM:n AXIS BATTERY ZERO	nth–axis (n=1 – 4) APC battery voltage has decreased to a low level so that the data cannot be held. APC alarm. Battery or cable may be faulty.
307	APC ALARM:n AXIS BATTERY DOWN 1	nth–axis (n=1 – 4) axis APC battery voltage reaches a level where the battery must be renewed. APC alarm. Replace the battery.
308	APC ALARM:n AXIS BATTERY DOWN 2	nth–axis (n=1 – 4) APC battery voltage has reached a level where the battery must be renewed (including when power is OFF). APC alarm .Replace battery.
309	APC ALARM:n AXIS ZRN IMPOSSIBLE	An attempt was made to perform reference position return without rotating the motor through one or more turns. Rotate the motor through one or more turns, turn off the power then on again, then perform reference position return.

4) Serial pulse coder (SPC) alarms

Number	Message	Contents
360	n AXIS : ABNORMAL CHECKSUM (INT)	A checksum error occurred in the built–in pulse coder.
361	n AXIS : ABNORMAL PHASE DATA (INT)	A phase data error occurred in the built–in pulse coder.
362	n AXIS : ABNORMAL REV.DATA (INT)	A rotation speed count error occurred in the built–in pulse coder.
363	n AXIS : ABNORMAL CLOCK (INT)	A clock error occurred in the built–in pulse coder.
364	n AXIS : SOFT PHASE ALARM (INT)	A software phase data error occurred in the built–in pulse coder.
365	n AXIS : BROKEN LED (INT)	An LED error occurred in the built–in pulse coder.
366	n AXIS : PULSE MISS (INT)	A feedback error occurred in the built–in pulse coder.
367	n AXIS : COUNT MISS (INT)	A count error occurred in the built–in pulse coder.
368	n AXIS : SERIAL DATA ERROR (INT)	A data error occurred in the built–in pulse coder.
369	n AXIS : DATA TRANS. ERROR (INT)	A CRC or stop bit error occurred in the built–in pulse coder.
380	n AXIS : BROKEN LED (EXT)	An LED error occurred in the separate pulse coder.
381	n AXIS : ABNORMAL PHASE (EXT LIN)	A phase data error occurred in the separate linear scale.
382	n AXIS : COUNT MISS (EXT)	A count error occurred in the separate pulse coder.
383	n AXIS : PULSE MISS (EXT)	A feedback error occurred in the separate pulse coder.
384	n AXIS : SOFT PHASE ALARM (EXT)	A software phase data error occurred in the separate pulse coder.
385	n AXIS : SERIAL DATA ERROR (EXT)	A data error occurred in the separate pulse coder.
386	n AXIS : DATA TRANS. ERROR (EXT)	A CRC or stop bit error occurred in the separate pulse coder.

- **The details of serial pulse coder alarm No.350**

The details of serial pulse coder alarm No. 350 (pulse coder alarm) are displayed in the diagnosis display (No. 202) as shown below.

	#7	#6	#5	#4	#3	#2	#1	#0
202		CSA	BLA	PHA	RCA	BZA	CKA	SPH

CSA : The serial pulse coder is defective. Replace it.
BLA : The battery voltage is low. Replace the batteries. This alarm has nothing to do with alarm 350 (serial pulse coder alarm).
PHA : The serial pulse coder or feedback cable is defective. Replace the serial pulse coder or cable.
RCA : The serial pulse coder is defective. Replace it.
BZA : The pulse coder was supplied with power for the first time. Make sure that the batteries are connected.
Turn the power off, then turn it on again and perform a reference position return. This alarm has nothing to do with alarm 350 (serial pulse coder alarm).
CKA : The serial pulse coder is defective. Replace it.
SPH : The serial pulse coder or feedback cable is defective. Replace the serial pulse coder or cable.

- **The details of serial pulse coder alarm No.351**

The details of serial pulse coder alarm No. 351 (communication alarm) are displayed in the diagnosis display (No. 203) as shown below.

	#7	#6	#5	#4	#3	#2	#1	#0
203	DTE	CRC	STB	PRM				

DTE : The serial pulse coder encountered a communication error. The pulse coder, feedback cable, or feedback receiver circuit is defective. Replace the pulse coder, feedback cable, or NC–axis board

CRC : The serial pulse coder encountered a communication error. The pulse coder, feedback cable, or feedback receiver circuit is defective. Replace the pulse coder, feedback cable, or NC–axis board.

STB : The serial pulse coder encountered a communication error. The pulse coder, feedback cable, or feedback receiver circuit is defective.
Replace the pulse coder, feedback cable, or NC–axis board.

PRM: An invalid parameter was found. Alarm 417 (invalid servo parameter) is also issued.

5) Servo alarms

Number	Message	Contents
401	SERVO ALARM: n AXIS VRDY OFF	The n–th axis (axis 1–4) servo amplifier READY signal (DRDY) went off.
404	SERVO ALARM: n AXIS VRDY ON	Even though the n–th axis (axis 1–4) READY signal (MCON) went off, the servo amplifier READY signal (DRDY) is still on. Or, when the power was turned on, DRDY went on even though MCON was off. Check that the servo interface module and servo amp are connected.
405	SERVO ALARM: (WRONG ZRN)	Position control system fault. Due to an NC or servo system fault in the reference position return, there is the possibility that reference position return could not be executed correctly. Try again from the manual reference position return.
407	SERVO ALARM: EXCESS ERR	The difference in synchronous axis position deviation exceeded the set value.
409	SERVO ALARM:EXCESS ERROR	An abnormal load on the servo motor was detected. Alternatively, an abnormal load on the spindle motor was detected in Cs mode.
410	SERVO ALARM: n AXIS EXCESS ERR	The position deviation value when the n–th axis (axis 1–4) stops is larger than the set value. Note) Limit value must be set to parameter No.1829 for each axis.
411	SERVO ALARM: n AXIS EXCESS ERR	The position deviation value when the n–th axis (axis 1–4) moves is larger than the set value. Note) Limit value must be set to parameter No.1828 for each axis.
413	SERVO ALARM: n AXIS LSI OVER	The contents of the error register for the n–th axis (axis 1–4) are beyond of the range of -2^{31} to 2^{31}. This error usually occurs as the result of an improperly set parameters.
415	SERVO ALARM: n AXIS MOTION OVER	A speed higher than 511875 units/s was attempted to be set in the n–th axis (axis 1–4). This error occurs as the result of improperly set CMR.

Number	Message	Contents
417	SERVO ALARM: n AXIS DGTL PARAM	This alarm occurs when the n–th axis (axis 1–4) is in one of the conditions listed below. (Digital servo system alarm) 1) The value set in Parameter No. 2020 (motor form) is out of the specified limit. 2) A proper value (111 or –111) is not set in parameter No.2022 (motor revolution direction). 3) Illegal data (a value below 0, etc.) was set in parameter No. 2023 (number of speed feedback pulses per motor revolution). 4) Illegal data (a value below 0, etc.) was set in parameter No. 2024 (number of position feedback pulses per motor revolution). 5) Parameters No. 2084 and No. 2085 (flexible field gear rate) have not been set. 6) A value outside the limit of {1 to the number of control axes} or a non–continuous value (Parameter 1023 (servo axis number) contains a value out of the range from 1 to the number of axes,or an isolated value (for example, 4 not prceded by 3).was set in parameter No. 1023 (servo axisnumber).
421	SERVO ALARN : n AXIS EXCESS ER (D)	While the dual position feedback function is being applied, an excessive difference was detected between a semi–closed loop error and closed loop error. Check the dual position conversion factor set in parameter Nos. 2078 and 2079.
422	SERVO ALARN : n AXIS EXCESS ER (D)	The specified maximum allowable speed was exceeded during torque control for a PMC–controlled axis.
423	SERVO ALARN : n AXIS EXCESS ER (D)	The maximum allowable accumulated amount of travel, specified with a parameter, was exceeded during torque control for a PMC–controlled axis.
430	n AXIS : SV MOTOR OVERHEAT	The servo motor overheated.
431	n AXIS : CNV. OVERLOAD	The servo amplifier overheated.
432	n AXIS : CONV. LOWVOLT CON. /POWFAULT	A low voltage was detected in the converter controller.
433	n AXIS : CNV. LOW VOLT DC LINK	A low voltage was detected in the converter DC link.
434	n AXIS : INV. LOW VOLT CONTROL	A low voltage was detected in the inverter controller.
435	n AXIS : INV. LOW VOLT DC LINK	A low voltage was detected in the inverter DC link.
436	n AXIS : SOFTTHERMAL (OVC)	An overcurrent was detected.
437	n AXIS : CNV. OVERCURRENT POWER	An abnormal current was detected in the converter.
438	n AXIS : INV. ABNORMAL CURRENT	An abnormal current was detected in the inverter.
439	n AXIS : CNV. OVERVOLT POWER	An overvoltage was detected.
440	n AXIS : CNV. EX DECELERATION POW.	A regenerative discharge circuit error occurred.
441	n AXIS : ABNORMAL CURRENT OFFSET	A/D conversion of the digital servo current failed.
442	n AXIS : CNV. CHARGE FAULT/INV. DB	The contacts of the servo amplifier magnetic contactor have welded together.
443	n AXIS : CNV. COOLING FAN FAILURE	Converter cooling fan error
444	n AXIS : INV. COOLING FAN FAILURE	Inverter cooling fan error
445	n AXIS : SOFT DISCONNECT ALARM	Pulse coder disconnection (software)
446	n AXIS : HARD DISCONNECT ALARM	Built–in pulse coder disconnection (hardware)

Number	Message	Contents
447	n AXIS : HARD DISCONNECT (EXT)	Separate pulse coder disconnection (hardware)
448	n AXIS : UNMATCHED FEEDBACK ALARM	Feedback error
449	n AXIS : INV. IPM ALARM	An IPM error occurred in the inverter.
460	n AXIS : FSSB DISCONNECT	Communication through FSSB was abruptly disconnected. The most likely causes are: 1. The communication cable for FSSB was disconnected or other wise failed. 2. The power to the amplifier was inadvertently turned off. 3. The voltage supplied to the amplifier has dropped.
461	n AXIS : ILLEGAL AMP INTERFACE	Both axes of the two–axis amplifier are assigned to the Fast–type interface.
462	n AXIS : SEND CNC DATA FAILED	An FSSB communication error disabled correct data reception by the slave.
463	n AXIS : SEND SLAVE DATA FAILED	An FSSB communication error disabled correct data reception by the servo.
464	n AXIS : WRITE ID DATA FAILED	An attempt to write maintenance information on the amplifier maintenance screen failed.
465	n AXIS : READ ID DATA FAILED	Upon power–on, an attempt to read the initial ID information for the amplifier failed.
466	n AXIS : MOTOR/AMP COMBINATION	The maximum current for the amplifier differs from that for the motor.
467	n AXIS : ILLEGAL SETTING OF AXIS	Although two exclusive axes are set on the axis setting screen, any of the following servo functions is not enabled: 1. Learning control (bit 5 of parameter No. 2008 = 1) 2. High–speed current loop (bit 0 of parameter No. 2004 = 1) 3. High–speed interface axis (bit 4 of parameter No. 2005 = 1)

- **Details of servo alarm No.414**

The details of servo alarm No. 414 are displayed in the diagnosis display (No. 200 and No.204) as shown below.

	#7	#6	#5	#4	#3	#2	#1	#0
200	OVL	LV	OVC	HCA	HVA	DCA	FBA	OFA

OVL : An overload alarm is being generated.
(This bit causes servo alarm No. 400. The details are indicated in diagnostic data No.201).

LV : A low voltage alarm is being generated in servo amp.
Check LED.

OVC : A overcurrent alarm is being generated inside of digital servo.

HCA : An abnormal current alarm is being generated in servo amp.
Check LED.

HVA : An overvoltage alarm is being generated in servo amp.
Check LED.

DCA : A regenerative discharge circuit alarm is being generated in servo amp.
Check LED.

FBA : A disconnection alarm is being generated.
(This bit causes servo alarm No.416.The details are indicated in diagnostic data No. 201)

OFA : An overflow alarm is being generated inside of digital servo.

	#7	#6	#5	#4	#3	#2	#1	#0
201	ALD			EXP				

When OVL equal 1 in diagnostic data No.200 (servo alarm No. 400 is being generated):

ALD 0 : Motor overheating
1 : Amplifier overheating

When FBAL equal 1 in diagnostic data No.200 (servo alarm No. 416 is being generated):

ALD	EXP	Alarm details
1	0	Built–in pulse coder disconnection (hardware)
1	1	Separately installed pulse coder disconnection (hardware)
0	0	Pulse coder is not connected due to software.

	#7	#6	#5	#4	#3	#2	#1	#0
204		OFS	MCC	LDA	PMS			

OFS : A current conversion error has occurred in the digital servo.
MCC : A magnetic contactor contact in the servo amplifier has welded.
LDA : The LED indicates that serial pulse coder C is defective
PMS : A feedback pulse error has occurred because the feedback cable is defective.

6) Over travel alarms

Number	Message	Contents
500	OVER TRAVEL : +n	Exceeded the n–th axis + side stored stroke limit I. (Parameter No.1320 or 1326 **Notes**)
501	OVER TRAVEL : –n	Exceeded the n–th axis – side stored stroke limit I. (Parameter No.1321 or 1327 **Notes**)
502	OVER TRAVEL : +n	Exceeded the n–th axis + side stored stroke limit II. (Parameter No.1322)
503	OVER TRAVEL : –n	Exceeded the n–th axis – side stored stroke limit II. (Parameter No.1323)
504	OVER TRAVEL : +n	Exceeded the n–th axis + side stored stroke limit III. (Parameter No.1324)
505	OVER TRAVEL : –n	Exceeded the n–th axis – side stored stroke limit III. (Parameter No.1325)
506	OVER TRAVEL : +n	Exceeded the n–th axis + side hardware OT.
507	OVER TRAVEL : –n	Exceeded the n–th axis – side hardware OT.
508	INTERFERENCE : +n	When n–axis is moving in the positive direction, it interferes with the order tool post (only with two–path control)
509	INTERFERENCE : –n	When n–axis is moving in the negative direction, it interferes with the order tool post (only with two–path control)
510	OVER TRAVEL : +n	A stroke limit check, made before starting movement, found that the end point of a block falls within the plus (+) side inhibited area along the n–axis defined by a stroke limit. Correct the program.
511	OVER TRAVEL : –n	A stroke limit check, made before starting movement, found that the end point of a block falls within the minus (–) side inhibited area along the N–axis defined by a stroke limit. Correct the program.

NOTE
Over travel alarms No. 504 and No. 505 are provided only with the T series.
Parameters 1326 and 1327 are effective when EXLM(stroke limit switch signal) is on.

7) Overheat alarms

Number	Message	Contents
700	OVERHEAT: CONTROL UNIT	Control unit overheat Check that the fan motor operates normally, and clean the air filter.
701	OVERHEAT: FAN MOTOR	The fan motor on the top of the cabinet for the control unit is overheated. Check the operation of the fan motor and replace the motor if necessary.
704	OVERHEAT: SPINDLE	Spindle overheat in the spindle fluctuation detection (1)If the cutting load is heavy, relieve the cutting condition. (2)Check whether the cutting tool is share. (3)Another possible cause is a faulty spindle amp.

8) Rigid tapping alarm

Number	Message	Contents
740	RIGID TAP ALARM : EXCESS ERROR	During rigid tapping, the position deviation of the spindle in the stop state exceeded the setting.
741	RIGID TAP ALARM : EXCESS ERROR	During rigid tapping, the position deviation of the spindle in the stop state exceeded the setting.
742	RIGID TAP ALARM : LSI OVER FLOW	During rigid tapping, an LSI overflow occurred on the spindle side.

9) Serial spindle alarms

Number	Message	Contents
749	S–SPINDLE LSI ERROR	A communication error occurred for the serial spindle. The cause may be the disconnection of an optical cable or the interruption of the power to the spindle amplifier. (Note) Unlike alarm No. 750, this alarm occurs when a serial communication alarm is detected after the spindle amplifier is normally activated.
750	SPINDLE SERIAL LINK ERROR	This alarm is generated when the spindle control unit is not ready for starting correctly when the power is turned on in the system with the serial spindle. The four reasons can be considered as follows: 1) An improperly connected optic cable, or the spindle control unit's power is OFF. 2) When the NC power was turned on under alarm conditions other than SU–01 or AL–24 which are shown on the LED display of the spindle control unit. In this case, turn the spindle amplifier power off once and perform startup again. 3) Other reasons (improper combination of hardware) This alarm does not occur after the system including the spindle control unit is activated. 4) The second spindle (when SP2, bit 4 of parameter No. 3701, is 1) is in one of the above conditions 1) to 3). See diagnostic display No. 409 for details.
751	SPINDLE–1 ALARM DETECT (AL–XX)	This alarm indicates in the NC that an alarm is generated in the spindle unit of the system with the serial spindle. The alarm is displayed in form AL–XX (XX is a number). Refer to **(11) Alarms displayed on spindle servo unit** .The alarm number XX is the number indicated on the spindle amplifier. The CNC holds this number and displays on the screen.

Number	Message	Contents
752	SPINDLE–1 MODE CHANGE ERROR	This alarm is generated if the system does not properly terminate a mode change. The modes include the Cs contouring, spindle positioning, rigid tapping, and spindle control modes. The alarm is activated if the spindle control unit does not respond correctly to the mode change command issued by the NC.
754	SPINDLE–1 ABNORMAL TORQUE ALM	An abnormal load on the first spindle motor was detected.
761	SPINDLE–2 ALARM DETECT (AL–XX)	Refer to spindle alarm No. 751. (For 2nd axis)
762	SPINDLE–2 MODE CHANGE ERROR	Refer to spindle alarm No. 752.(For 2nd axis)
764	SPINDLE–2 ABNORMAL TORQUE ALM	Same as for alarm No. 754 (for the second spindle)

- **The details of spindle alarm No.750**

The details of spindle alarm No. 750 are displayed in the diagnosis display (No. 409) as shown below.

	#7	#6	#5	#4	#3	#2	#1	#0
409					SPE	S2E	S1E	SHE

SPE **0** : In the spindle serial control, the serial spindle parameters fulfill the spindle unit startup conditions.
1 : In the spindle serial control, the serial spindle parameters do not fulfill the spindle unit startup conditions.

S2E **0** : The second spindle is normal during the spindle serial control startup.
1 : The second spindle was detected to have a fault during the spindle serial control startup.

S1E **0** : The first spindle is normal during the spindle serial control startup.
1 : The first spindle was detected to have a fault during the spindle axis serial control startup.

SHE **0** : The serial communications module in the CNC is normal.
1 : The serial communications module in the CNC was detected to have a fault.

10) System alarms

(These alarms cannot be reset with reset key.)

Number	Message	Contents
900	ROM PARITY	ROM parity error (CNC/OMM/Servo) Replace the number of ROM.
910	SRAM PARITY : (BYTE 0)	RAM parity error in the tape memory RAM module. Clear the memory or replace the module. After this operation, reset all data including the parameters.
911	SRAM PARITY: (BYTE 1)	RAM parity error in the tape memory RAM module. Clear the memory or replace the module. After this operation, reset all data including the parameters.
912	DRAM PARITY : (BYTE 0)	RAM parity error in the DRAM module. Replace the DRAM module.
913	DRAM PARITY : (BYTE 1)	
914	DRAM PARITY : (BYTE 2)	
915	DRAM PARITY : (BYTE 3)	
916	DRAM PARITY : (BYTE 4)	
917	DRAM PARITY : (BYTE 5)	
918	DRAM PARITY : (BYTE 6)	
919	DRAM PARITY : (BYTE 7)	
920	SERVO ALARM (1 to 4 AXIS)	Servo alarm (1st to 4th axis). A watchdog alarm or a RAM parity error in the servo module occurred. Replace the servo control module on the main CPU board.
926	FSSB ALARM	FSSB alarm. Replace the servo control module on the main CPU board.
930	CPU INTERRUPUT	CPU error (abnormal interrupt) The main CPU board is faulty.
950	PMC SYSTEM ALARM	Fault occurred in the PMC. The PMC control module on the main CPU board or option board may be faulty.
951	PMC–RC WATCH DOG ALARM	Fault occurred in the PMC–RC (watchdog alarm).Option board may be faulty.
972	NMI OCCURRED IN OTHER MODULE	NMI occurred in a board other than the main CPU board.
973	NON MASK INTERRUPT	NMI occurred for an unknown reason.
974	F–BUS ERROR	BUS error of FANUC BUS. The main CPU board or option boards may be faulty.
975	BUS ERROR (MAIN)	Main CPU board bus error. The main CPU board may be faulty.
976	L–BUS ERROR	Bus error of Local Bus. The main CPU board may be faulty.

11) Alarms Displayed on spindle Servo Unit

No.	Message	Alarm No.	Meaning	Description	Remedy
		"A" display	Program ROM abnormality (not installed)	Detects that control program is not started (due to program ROM not installed, etc.)	Install normal program ROM
7n01	SPN_n_ : MOTOR OVERHEAT	AL–01	Motor overheat	Detects motor speed exceeding specified speed excessively.	Check load status. Cool motor then reset alarm.
7n02	SPN_n_ : EX SPEED ERROR	AL–02	Excessive speed deviation	Detects motor speed exceeding specified speed excessively.	Check load status. Reset alarm.
7n03	SPN_n_ : FUSE ON DC LINK BLOWN	AL–03	DC link section fuse blown	Detects that fuse F4 in DC link section is blown (models 30S and 40S).	Check power transistors, and so forth. Replace fuse.
7n04	SPN_n_ : INPUT FUSE/ POWER FAULT	AL–04	Input fuse blown. Input power open phase.	Detects blown fuse (F1 to F3), open phase or momentary failure of power (models 30S and 40S).	Replace fuse. Check open phase and power supply regenerative circuit operation.
7n05	SPN_n_ : POWER SUPPLY FUSE BLOWN	AL–05	Control power supply fuse blown	Detects that control power supply fuse AF2 or AF3 is blown (models 30S and 40S).	Check for control power supply short circuit . Replace fuse.
7n07	SPN_n_ : OVERSPEED	AL–07	Excessive speed	Detects that motor rotation has exceeded 115% of its rated speed.	Reset alarm.
7n08	SPN_n_ : HIGH VOLT INPUT POWER	AL–08	High input voltage	Detects that switch is flipped to 200 VAC when input voltage is 230 VAC or higher (models 30S and 40S).	Flip switch to 230 VAC.
7n09	SPN_n_ : OVERHEAT MAIN CIRCUIT	AL–09	Excessive load on main circuit section	Detects abnormal temperature rise of power transistor radiator.	Cool radiator then reset alarm.
7n10	SPN_n_ : LOW VOLT INPUT POWER	AL–10	Low input voltage	Detects drop in input power supply voltage.	Remove cause, then reset alarm.
7n11	SPN_n_ : OVERVOLT POW CIRCUIT	AL–11	Overvoltage in DC link section	Detects abnormally high direct current power supply voltage in power circuit section.	Remove cause, then reset alarm.
7n12	SPN_n_ : OVERCURRENT POW CIRCUIT	AL–12	Overcurrent in DC link section	Detects flow of abnormally large current in direct current section of power cirtcuit	Remove cause, then reset alarm.
7n13	SPN_n_ : DATA MEMORY FAULT CPU	AL–13	CPU internal data memory abnormality	Detects abnormality in CPU internal data memory. This check is made only when power is turned on.	Remove cause, then reset alarm.
7n15	SPN_n_ : SP SWITCH CONTROL ALARM	AL–15	Spindle switch/output switch alarm	Detects incorrect switch sequence in spindle switch/output switch operation.	Check sequence.
7n16	SPN_n_ : RAM FAULT	AL–16	RAM abnormality	Detects abnormality in RAM for external data. This check is made only when power is turned on.	Remove cause, then reset alarm.
7n18	SPN_n_ : SUMCHECK ERROR PGM DATA	AL–18	Program ROM sum check error	Detects program ROM data error.This check is made only when power is turned on.	Remove cause, then reset alarm.

No.	Message	Alarm No.	Meaning	Description	Remedy
7n19	SPN_n_ : EX OFFSET CURRENT U	AL–19	Excessive U phase current detection circuit offset	Detects excessive U phase current detection ciucuit offset. This check is made only when power is turned on.	Remove cause, then reset alarm.
7n20	SPN_n_ : EX OFFSET CURRENT V	AL–20	Excessive V phase current detection circuit offset	Detects excessive V phase current detection circuit offset. This check is made only when power is turned on.	Remove cause, then reset alarm.
7n24	SPN_n_ : SERIAL TRANSFER ERROR	AL–24	Serial transfer data error	Detects serial transfer data error (such as NC power supply turned off, etc.)	Remove cause, then reset alarm.
7n25	SPN_n_ : SERIAL TRANSFER STOP	AL–25	Serial data transfer stopped	Detects that serial data transfer has stopped.	Remove cause, then reset alarm.
7n26	SPN_n_ : DISCONNECT C–VELO DETECT	AL–26	Disconnection of speed detection signal for Cs contouring control	Detects abnormality in position coder signal(such as unconnected cable and parameter setting error).	Remove cause, then reset alarm.
7n27	SPN_n_ : DISCONNECT POS–CODER	AL–27	Position coder signal disconnection	Detects abnormality in position coder signal (such as unconnected cable and adjustment error).	Remove cause, then reset alarm.
7n28	SPN_n_ : DISCONNECT C–POS DETECT	AL–28	Disconnection of position detection signal for Cs contouring control	Detects abnormality in position detection signal for Cs contouring control (such as unconnected cable and adjustment error).	Remove cause, then reset alarm.
7n29	SPN_n_ : SHORTTIME OVERLOAD	AL–29	Short–time overload	Detects that overload has been continuously applied for some period of time (such as restraining motor shaft in positioning).	Remove cause, then reset alarm.
7n30	SPN_n_ : OVERCURRENT POW CIRCUIT	AL–30	Input circuit overcurrent	Detects overcurrent flowing in input circuit.	Remove cause, then reset alarm.
7n31	SPN_n_ : MOTOR LOCK OR V–SIG LOS	AL–31	Speed detection signal disconnection motor restraint alarm or motor is clamped.	Detects that motor cannot rotate at specified speed or it is detected that the motor is clamped. (but rotates at very slow speed or has stopped). (This includes checking of speed detection signal cable.)	Remove cause, then reset alarm.
7n32	SPN_n_ : RAM FAULT SERIAL LSI	AL–32	Abnormality in RAM inside the LSI used for serial data transfer. This check is made only when power is turned on.	Detects abnormality in RAM inside the LSI used for serial data transfer. This check is made only when power is turned on.	Remove cause, then reset alarm.

No.	Message	Alarm No.	Meaning	Description	Remedy
7n33	SPN_n_ : SHORTAGE POWER CHARGE	AL–33	Insufficient DC link section charging	Detects insufficient charging of direct current power supply voltage in power circuit section when magnetic contactor in amplifier is turned on (such as open phase and defectifve charging resistor).	Remove cause, then reset alarm.
7n34	SPN_n_ : PARAMETER SETTING ERROR	AL–34	Parameter data setting beyond allowable range of values	Detects parameter data set beyond allowable range of values.	Set correct data.
7n35	SPN_n_ : EX SETTING GEAR RATIO	AL–35	Excessive gear ratio data setting	Detects gear ratio data set beyond allowable range of values.	Set correct data.
7n36	SPN_n_ : OVERFLOW ERROR COUNTER	AL–36	Error counter overflow	Detects error counter overflow.	Correct cause, then reset alarm.
7n37	SPN_n_ : SPEED DETECT PAR. ERROR	AL–37	Speed detector parameter setting error	Detects incorrect setting of parameter for number of speed detection pulses.	Set correct data.
7n39	SPN_n_ : 1–ROT Cs SIGNAL ERROR	AL–39	Alarm for indicating failure in detecting 1–rotation signal for Cs contouring control	Detects 1–rotaion signal detection failure in Cs contouring contorl.	Make 1–rotaion signal adjustment. Check cable shield status.
7n40	SPN_n_ : NO 1–ROT Cs SIGNAL DETECT	AL–40	Alarm for indicating 1–rotation signal for Cs contouring control not detected	Detects that 1–rotation signal has not occurred in Cs contouring control.	Make 1–rotaion signal adjustment.
7n41	SPN_n_ : 1–ROT POS–CODER ERROR	AL–41	Alarm for indicating failure in detecting position coder 1–rotaion signal.	Detects failure in detecting position coder 1–rotation signal.	Make signal adjustment for signal conversion circuit. Check cable shield status.
7n42	SPN_n_ : NO 1–ROT. POS–CODER DETECT	AL–42	Alarm for indicating position coder 1–rotation signal not detected	Detects that position coder 1–rotation signal has not issued.	Make 1–rotation signal adjustment for signal conversion circuit.
7n43	SPN_n_ : DISCON. PC FOR DIF. SP. MOD.	AL–43	Alarm for indicating disconnection of position coder signal for differential speed mode	Detects that main spindle position coder signal used for differential speed mode is not connected yet (or is disconnected).	Check that main spindle position coder signal is connected to connector CN12.
7n44	SPN_n_ : CONTROL CIRCUIT(AD) ERROR	AL–44			

No.	Message	Alarm No.	Meaning	Description	Remedy
7n46	SPN_n_ : SCREW 1–ROT POS–COD. ALARM	AL–46	Alarm for indicating failure in detecting position coder 1–rotation signal in thread cutting operation.	Detects failure in detecting position coder 1–rotation signasl in thread cutting operation.	Make 1–rotation signal adjustment for signal conversion circuit. Check cable shield status.
7n47	SPN_n_ : POS–CODER SIGNAL ABNORMAL	AL–47	Position coder signal abnormality	Detects incorrect position coder signal count operation.	Make signal adjustment for signal conversion circuit. Check cable shield status.
7n49	SPN_n_ : HIGH CONV. DIF. SPEED	AL–49	The converted differential speed is too high.	Detects that speed of other spindle converted to speed of local spindle has exceeded allowable limit in differential mode.	Calculate differential speed by multiplying speed of other spindle by gear ratio. Check if calculated value is not greater than maximum speed of motor.
7n50	SPN_n_ : SPNDL CONTROL OVERSPEED	AL–50	Excessive speed command calculation value in spindle synchronization control	Detects that speed command calculation value exceeded allowable range in spindle synchronization control.	Calculate motor speed by multiplying specified spindle speed by gear ratio. Check if calculated value is not greater than maximum speed of motor.
7n51	SPN_n_ : LOW VOLT DC LINK	AL–51	Undervoltage at DC link section	Detects that DC power supply voltage of power circuit has dropped (due to momentary power failure or loose contact of magnetic contactor).	Remove cause, then reset alarm.
7n52	SPN_n_ : ITP SIGNAL ABNORMAL I	AL–52	ITP signal abnormality I	Detects abnormality in synchronization signal (ITP signal) used in software.	Replace servo amp. PCB.
7n53	SPN_n_ : ITP SIGNAL ABNORMAL II	AL–53	ITP signal abnormality II	Detects abnormality in synchronization signal (ITP signal) used in hardware.	Replace servo amp. PCB.
7n56	SPN_n_ : INNER COOLING FAN STOP	AL–56	The cooling fan in the unit stopped.	The cooling fan in the control circuit section stopped.	Check the turning state of the cooling fan. Replace the cooling fan.
7n57	SPN_n_ : EX DECELERATION POWER	AL–57	Deceleration power is too high.	Abnormal current flowed through the regenerative resistor.	Check the selection of the regenerative resistor. Alternatively, check whether the cooling fan motor is rotating.
7n58	SPN_n_ : OVERLOAD IN PSM	AL–58	Overload on the PSM main circuit	The temperature of the radiator of the main circuit has increased abnormally. (Cooling fan failure, dirt in the cooling fan, overload operation, etc.)	Eliminate the cause, then reset the alarm.
7n59	SPN_n_ : COOLING FAN STOP IN PSM	AL–59	The PSM cooling fan stopped.	The cooling fan of the control circuit section stopped.	Check the turning state of the cooling fan. Replace the cooling fan.

H OPERATION OF PORTABLE TAPE READER

Portable tape reader is the device which inputs the NC program and the data on the paper tape to CNC.

- **Names and descriptions of each section**



Table 1 Description of Each Section

No.	Name	Descriptions
1	Light Sources	An LED (Light emitting diode) is mounted for each channel and for the feed hole (9 diodes in total). A built–in Stop Shoe functions to decelerate the tape. The light source is attracted to the optical reader by a magnet so that the tape will be held in the correct position. This unit can be opened upward, by turning the tape reader control switch to the RELEASE position (this turns off the magnet).
2	Optical Reader	Reads data punched on the tape, through a glass window. Dust or scratches on the glass window can result in reading errors. Keep this window clean.
3	Capstan Roller	Controls the feeding of tape as specified by the control unit.
4	Tape Reader Control Switch	A 3–position switch used to control the Tape Reader. **RELEASE** ----- The tape is allowed to be free, or used to open the lightsource. When loading or unloading the tape, select this position. **AUTO** -------- The tape is set to fixed position by the Stop Shoe. The feed and stop of the tape is controlled by the CNC. To input data from tape, the Light Source must be closed and this position must be selected. **MANUAL** ----- The tape can be fed in the forward reading direction. if another position is selected, the tape feed is stopped.
5	Tape Box	A Tape Box is located below the Tape Reader. A belt used to draw out a paper tape is located inside the box. The paper tape can easily be pulled out using this belt. The tape box accomodates 15 meters of tape.
6	Handle	Used to carry the tape reader.
7	Winder	Used to advance or rewind the tape.
8	Metal A	
9	Cover lock	Be sure to use the lock for fastening the cover before carrying the tape reader.

No.	Name	Descriptions
10	Lowering lock lever	When the tape reader is raised, the latch mechanism is activated to fix the tape reader. Thus, the tape reader is not lowered. The latch is locked with the lowering lock lever. The latch is therefore not unlocked even when the tape reader is raised with the handle. When the latch is locked, the lever is horizontal. To store the tape reader in the box, push the lever to release the lock, then raise the tape reader with the handle to unlock the latch. When the latch is unlocked, the tape reader can be stored in the box. When storing the tape reader, secure it with the cover lock.
11	Cable storage	Used to store rolled power and signal cables. The cable length is 1.5 m.
12	Photoamplifier	For the tape reader
13	Reader/punch interface adapter	200 VAC input and 5 VDC output power and reader/punch interface adapter PCB

Procedure for Operating the Portable Tape Reader

Preparations

1 Unlock the cover locks **9**. Raise the tape reader with the handle **6** until it clicks, then lower the tape reader. The tape reader then appears and is secured. Check that the lowering lock levers **10** are horizontal.

2 Take out the signal and power cables from the cable storage **11** and connect the signal cable with the CNC reader/punch interface port and the power cable with the power supply.

Setting the tape

3 Turn the control switch to the RELEASE position.

4 Lift the Light Source Unit, and insert an NC tape between the gap. The tape must be positioned as shown in the figure, when viewed looking downward.



5 Pull the tape until the top of the tape goes past the Capstan roller.

6 Check that the NC tape is correctly positioned by the Tape Guide.

7 Lower the Light Source.

8 Turn the switch to the AUTO position.

9 Suspend the top and rear–end of the tape in the Tape Box.

Removing the tape

10 Turn the switch to the RELEASE position.

11 Lift the Light Source and remove the tape.

12 Lower the Light Source

Storage

13 Store the cables in the cable storage **11**.

14 Push the lowering lock lever **10** at both sides down.

15 Raise the tape reader with the handle **6** to unlock the latch, then gently lower it.

16 Lock the cover lock **9** and carry the tape reader with the handle **6**.

CAUTION

1 SETTING OF A TAPE

When the NC tape is loaded, the Label Skip function activates to read but skip data until first End of Block code (CR in EIA code or LF in ISO code) is read. When loading an NC tape, the location within the tape, from which data reading should be started must properly be selected and the NC tape should be set as shown in the figure below.



2 DISCONNECTION AND CONNECTION OF A PORTABLE TAPE READER CONNECTION CABLE

Don’t disconnect or connect CNC tape reader connection cable (signal cable) without turning off the CNC power supply, otherwise the PCB of the tape reader and master PCB of CNC controller may be broken.Turn off the CNC power supply before disconnecting or connecting the connection cable, accordingly.

≪A≫

Absolute and incremental programming (G90, G91), 88
Actual feedrate display, 600
Address and specifiable value range for Series 10/11 tape format, 305
Alarm and self–diagnosis functions, 480
Alarm display, 368, 481
Alarm history display, 483
Alarm list, 707
Altering a word, 558
Angular axis control / arbitrary angular axis control, 339
Arithmetic and logic operation, 260
Automatic erase screen display, 662
Automatic inserting of sequence numbers, 582
Automatic operation, 359, 424
Automatic tool offset (G36, G37), 246
Auxiliary function, 111
Auxiliary function (M function), 112
Axis control function, 320

≪B≫

B–axis control (G100, G101, G102, G103, G110), 329
Background editing, 577
Battery for separate absolute pulse coders, 682
Branch and repetition, 266

≪C≫

Canceling spindle positioning, 103
Canned cycle, 308
Canned cycle (G90, G92, G94), 130
Canned cycle for drilling (G80 – G89), 157
Canned cycle for drilling cancel (G80), 166
Canned drilling cycle formats, 311
Chamfering and corner R, 168
Change of words or addresses, 574
Changing of tool offset value (programmable data input) (G10), 245
Changing workpiece coordinate system, 79
Character–to–codes correspondence table, 706
Characters and codes to be used for the pattern data input function, 350
Check by running the machine, 361
Checked by self–diagnostic screen, 484
Chuck and tailstock barriers, 473
Circular interpolation (G02, G03), 40
Clearing the screen, 661
CNC control unit with 7.2″/8.4″ LCD, 374
CNC control unit with 9.5″/10.4″ LCD, 374
Command for machine operations – miscellaneous function, 22
Compensation function, 26, 181
Conditional branch (IF statement), 267
Constant lead threading (G32), 51
Constant surface speed control (G96, G97), 94
Continuous thread cutting, 56
Controlled axes, 28, 29
Coordinate system, 74
Coordinate system on part drawing and coordinate system specified by CNC – coordinate system, 16
Coordinate value and dimension, 87
Copying an entire program, 568
Copying part of a program, 569
Correction in chamfering and corner arcs, 230
Counter input of offset value, 628
Counting a tool life, 109
Creating programs, 580
Creating programs in teach in mode (playback), 584
Creating programs using the MDI panel, 581
Current block display screen, 607
Current position display, 368
Custom macro, 249
Cutting feed, 67
Cutting speed – spindle speed function, 21
Cylindrical interpolation (G07.1), 48

≪D≫

Data input/output, 487
Data input/output on the ALL IO screen, 515
Data input/output using a memory card, 540
Data output, 371
Decimal point programming, 90
Deleting a block, 560
Deleting a word, 559
Deleting all programs, 565
Deleting blocks, 560
Deleting files, 512
Deleting more than one program by specifying a range, 566
Deleting multiple blocks, 561
Deleting one program, 565
Deleting programs, 565
Details of functions, 294
Details of tool nose radius compensation, 204
Diameter and radius programming, 91
Direct drawing dimensions programming, 172
Direct input of measured workpiece origin offsets, 641
Direct input of tool offset measured B, 626
Direct input of tool offset value, 624
Direction of imaginary tool nose, 193
Display, 367
Display of run time and parts count, 602

Displaying a program list for a specified group, 617
Displaying and entering setting data, 634
Displaying and setting custom macro common variables, 643
Displaying and setting data, 364
Displaying and setting parameters, 652
Displaying and setting pitch error compensation data, 654
Displaying and setting run time, parts count, and time, 638
Displaying and setting the software operator’s panel, 644
Displaying and setting the workpiece origin offset value, 640
Displaying and setting tool life management data, 646
Displaying directory of floppy disk, 506
Displaying memory used and a list of programs, 614
Displaying the B–axis operation state, 612
Displaying the directory, 507
Displaying the pattern menu, 342
Displaying the program number and sequence number, 656
Displaying the program number, sequence number, and status, and warning messages for data setting or input/output operation, 656
Displaying the status and warning for data setting or input/output operation, 657
Distribution processing termination monitoring function for the high–speed machining command (G05), 319
DNC operation, 454
Dry run, 462
Dwell (G04), 69

≪E≫

Editing a part program, 363
Editing of custom macros, 576
Editing programs, 552
Emergency stop, 467
End face peck drilling cycle (G74), 150
End face turning cycle (G94), 135
Equal–lead threading, 306
Erase CRT screen display, 661
Explanation of the keyboard, 379
Extended part program editing function, 567
External I/O devices, 402
External output commands, 288

≪F≫

FANUC FA Card, 405
FANUC Floppy Cassette, 404
FANUC Handy File, 404
FANUC PPR, 405
Feed functions, 64
Feed–feed function, 14
Feedrate override, 460
File deletion, 492
File search, 490
Files, 488
Finishing cycle (G70), 146
Front boring cycle (G85) / side boring cycle (G89), 165
Front drilling cycle (G83) / side drilling cycle (G87), 160
Front tapping cycle (G84) / side tapping cycle (G88), 163
Function keys, 382
Function keys and soft keys, 381
Function to simplify programming, 129
Functions for high speed cutting, 315

≪G≫

General flow of operation of CNC machine tool, 5
General precautions for offset operations, 233
General screen operations, 381
Graphic display, 370
Graphics display, 664
Graphics function, 663

≪H≫

Heading a program, 556
Help function, 669
High–speed remote buffer A (G05), 317
How to indicate command dimensions for moving the tool – absolute, incremental commands, 19
How to use canned cycles (G90, G92, G94), 138
How to view the position display change without running the machine, 362

≪I≫

Imaginary tool nose, 191
Inch/metric conversion (G20, G21), 89
Incorrect threaded length, 696
Increment system, 30
Incremental feed, 415
Input command from MDI, 232
Inputting a program, 493
Inputting and outputting offset data, 523
Inputting and outputting parameters, 521
Inputting and outputting parameters and pitch error compensation data, 500
Inputting and outputting programs, 517
Inputting custom macro common variables, 504
Inputting offset data, 498
Inputting parameters, 500
Inputting pitch error compensation data, 502
Inputting/outputting custom macro common variables, 504

Inserting a word, 557
Inserting, altering and deleting a word, 553
Interference check, 224
Interpolation functions, 36
Interruption type custom macro, 292

≪J≫

Jog feed, 413

≪K≫

Key input and input buffer, 399

≪L≫

Linear interpolation (G01), 39
List of functions and tape format, 688
Local coordinate system, 84

≪M≫

Machine coordinate system, 75
Machine lock and auxiliary function lock, 458
Macro call, 271
Macro call using an M code, 279
Macro call using G code, 278
Macro statements and NC statements, 265
Manual absolute on and off, 419
Manual handle feed, 416
Manual handle interruption, 447
Manual intervention and return, 452
Manual operation, 356, 410
Manual reference position return, 411
Maximum strokes, 31
MDI operation, 428
Memory card input/output, 531
Memory operation, 425
Memory operation by Series 10/11 tape format, 304
Merging a program, 571
Method of replacing battery, 677
Mirror image, 450
Mirror image for double turret (G68, G69), 171
Modal call (G66), 276
Moving part of a program, 570
Multiple M commands in a single block, 113
Multiple repetitive canned turning cycle, 309
Multiple repetitive cycle (G70 – G76), 140
Multiple thread cutting cycle (G76), 152
Multiple–thread cutting, 57
Multistage skip, 61

≪N≫

Name of axes, 29
Next block display screen, 608
Nomographs, 695
Notes on multiple repetitive cycle (G70 – G76), 156
Notes on reading this manual, 7
Notes on tool nose radius compensation, 201

≪O≫

Offset, 184
Offset data input and output, 498
Offset number, 183
Offset number and offset value, 194
Operating monitor display, 603
Operation of portable tape reader, 729
Operational devices, 372
Outer diameter / internal diameter cutting cycle (G90), 130
Outer diameter / internal diameter drilling cycle (G75), 151
Outputting a program, 496
Outputting a program list for a specified group, 514
Outputting custom macro common variable, 505
Outputting custom macro common variables, 525, 526
Outputting offset data, 499
Outputting parameters, 501
Outputting pitch error compensation data, 503
Outputting programs, 511
Overall position display, 598
Overcutting by tool nose radius compensation, 229
Overtravel, 468
Overview of tool nose radius compensation, 191

≪P≫

Part drawing and tool movement, 15
Parts count display, run time display, 369
Password function, 578
Pattern data display, 346
Pattern data input function, 341
Pattern repeating (G73), 145
Plane selection, 86
Polar coordinate interpolation (G12.1, G13.1), 44
Polygonal turning, 321
Portable tape reader, 406
Position display in the relative coordinate system, 596
Position display in the workpiece coordinate system, 595

Positioning (G00), 37
Power disconnection, 409
Power on/off, 407
Precautions to be taken by operator, 167
Preparatory function (G function), 32
Presetting the workpiece coordinate system, 599
Processing macro statements, 284
Program check screen, 609
Program components other than program sections, 117
Program configuration, 23, 115
Program contents display, 606
Program display, 367
Program input/output, 493
Program number search, 562
Program of tool life data, 106
Program restart, 432
Program screen for MDI operation, 611
Program section configuration, 120
Programmable parameter entry (G10), 301

≪R≫

Radius direction error at circle cutting, 703
Range of command value, 692
Rapid traverse, 66
Rapid traverse override, 461
Reading files, 510
Reference position, 70
Reference position (machine–specific position), 15
Reference position return, 71
Registering custom macro programs, 286
Remote buffer, 316
Removing the tape, 731
Repetition (WHILE statement), 268
Replacing the alkaline dry cells (size D), 680
Rigid tapping, 177
Rotary axis roll–over, 326

≪S≫

Safety functions, 466
Sample program, 282
Scheduling function, 440
Screen displayed at power–on, 408
Screens displayed by function key [MESSAGE], 659
Screens displayed by function key [OFFSET SETTING], 620
Screens displayed by function key [POS], 595
Screens displayed by function key [PROG] (in memory mode or MDI mode), 605
Screens displayed by function key [PROG] (in the EDIT mode), 613
Screens displayed by function key [SYSTEM], 651
Selecting a workpiece coordinate system, 78
Selection of tool used for various machining – tool function, 22
Separate–type small MDI unit, 375
Separate–type standard MDI unit (horizontal type), 376
Separate–type standard MDI unit (vertical type), 377
Separate–type standard MDI unit (vertical type) (for 210*i*), 378
Sequence number comparison and stop, 636
Sequence number search, 563
Setting a workpiece coordinate system, 76
Setting and display units, 373
Setting and displaying B–axis tool compensation, 649
Setting and displaying data, 587
Setting and displaying the tool offset value, 621
Setting input/output–related parameters, 516
Setting the workpiece coordinate system shifting amount, 629
Simple calculation of incorrect thread length, 698
Simple call (G65), 272
Simple synchronization control, 327
Single block, 463
Skip function (G31), 59
Soft key configuration, 401
Soft keys, 383
Specification method, 293
Specifying a tool group in a machining program, 110
Specifying the spindle speed value directly (S5–digit command), 93
Specifying the spindle speed with a code, 93
Spindle orientation, 101
Spindle positioning, 101
Spindle positioning function, 101
Spindle speed fluctuation detection function (G25, G26), 98
Spindle speed function, 92
Status when turning power on, when clear and when reset, 704
Stock removal in facing (G72), 144
Stock removal in turning (G71), 140
Stroke check, 469
Subprogram (M98, M99), 126
Subprogram call function (M198), 445
Subprogram call using an M code, 280
Subprogram calling, 307
Subprogram calls using a T code, 281
Supplementary explanation for copying, moving and merging, 572
System variables, 254

≪T≫

T code for tool offset, 183
Tape code list, 685
Test operation, 457
Testing a program, 361
The second auxiliary functions (B codes), 114
Thread cutting cycle (G92), 132
Tool compensation and number of tool compensation, 243
Tool compensation values, number of compensation value, and entering values from the program (G10), 243
Tool function (T function), 104
Tool geometry offset and tool wear offset, 182
Tool life management, 106
Tool movement along workpiece parts figure–interpolation, 12
Tool movement by programming – automatic operation, 358
Tool movement in offset mode, 208
Tool movement in offset mode cancel, 221
Tool movement in start–up, 206
Tool movement range – stroke, 27
Tool offset, 182
Tool path at corner, 700
Tool selection, 105, 183
Torque limit skip (G31 P99), 62
Turning on the power, 407

≪U≫

Unconditional branch (GOTO statement), 266
Use of alkaline dry cells (size D), 681

≪V≫

Variable–lead thread cutting (G34), 55
Variables, 250

≪W≫

Warning messages, 400
Word search, 554
Work position and move command, 196
Workpiece coordinate system, 76
Workpiece coordinate system preset (G92.1), 81
Workpiece coordinate system shift, 83

≪Y≫

Y axis offset, 631

Revision Record

FANUC Series 21*i*/210*i*–TA OPERATOR'S MANUAL (B–63084EN)

Edition	Date	Contents	Edition	Date	Contents
01	Apr., '97				

- *No part of this manual may be reproduced in any form.*
- *All specifications and designs are subject to change without notice.*